

Student Habits vs Performance Analysis

Author: Sarah Wyner

Date: October 1, 2025

DAT 301 - Project 2

1. BACKGROUND AND PROBLEM DEFINITION

Background

This study examines the relationship between student habits, lifestyle choices, and academic performance. Understanding these factors can help students optimize their study environment and habits for better academic outcomes.

Research Question

What factors influence student academic performance?

Dataset

- Source: <https://www.kaggle.com/datasets/jayaantanaath/student-habits-vs-academic-performance>
- Variables: 16 variables including study habits, lifestyle factors, and exam scores
- Sample: Undergraduate students aged 18-24

Hypothesis

Students with better study habits, healthier lifestyles, and positive mental health will achieve higher exam scores.

New Additions for Project 2 (Python Version)

- Correlation analysis with heatmap
- Multi-factor regression analysis
- Interactive filtering by performance level
- Additional statistical tests
- Predictive modeling exploration

2. IMPORT LIBRARIES AND LOAD DATA

```
In [1]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from scipy import stats
import warnings
warnings

# Set style
plt.style.use("seaborn-v0_8-darkgrid")
sns.set_palette("husl")

# Load the data
df = pd.read_csv("data/student_habits_performance.csv")
```

3. DATA CLEANING AND FEATURE ENGINEERING

```
In [2]: df["study_hours_category"] = pd.cut(
    df["study_hours_per_day"],
    bins=[0, 2, 4, 6, 10],
    labels=[
        "Low (0-2 hrs)",
        "Medium (2-4 hrs)",
        "High (4-6 hrs)",
        "Very High (6+ hrs)",
    ],
)

df["attendance_category"] = pd.cut(
    df["attendance_percentage"],
    bins=[0, 80, 90, 100],
    labels=["Low (< 80%)", "Medium (80-89%)", "Optimal (≥ 90%)"],
)

df["sleep_group"] = pd.cut(
    df["sleep_hours"],
    bins=[0, 6, 7, 8, 12],
    labels=["< 6 hours", "6-7 hours", "7-8 hours", "8+ hours"],
)

df["exercise_group"] = pd.cut(
    df["exercise_frequency"],
    bins=[-1, 1, 3, 10],
    labels=["Sedentary (0-1x)", "Moderate (2-3x)", "Active (4+x)"],
)

df["mental_health_group"] = pd.cut(
    df["mental_health_rating"],
    bins=[0, 3, 7, 10],
    labels=["Poor (1-3)", "Fair (4-7)", "Good (8-10)"],
)

df["total_screen_time"] = df["social_media_hours"] + df["netflix_hours"]

df["performance_level"] = pd.cut(
    df["exam_score"],
    bins=[0, 60, 75, 90, 100],
    labels=["Below Average", "Average", "Good", "Excellent"],
)

print("\nNew features created:")
print("- study_hours_category")
print("- attendance_category")
print("- sleep_group")
print("- exercise_group")
print("- mental_health_group")
print("- total_screen_time")
print("- performance_level")

print("\nCleaned dataset shape:", df.shape)
```

New features created:

- study_hours_category
- attendance_category
- sleep_group
- exercise_group
- mental_health_group
- total_screen_time
- performance_level

Cleaned dataset shape: (1000, 23)

4. EXPLORATORY DATA ANALYSIS (EDA)

```
In [3]: # Analysis 1: Study Hours Impact
print("\n--- Study Hours vs Exam Score ---")
study_analysis = df.groupby("study_hours_category", observed=True)["exam_score"].agg(
    ["mean", "std", "count"]
)
print(study_analysis)

--- Study Hours vs Exam Score ---
              mean      std  count
study_hours_category
Low (0-2 hrs)    47.541844  10.596436   141
Medium (2-4 hrs)  65.960915  11.112458   481
High (4-6 hrs)   82.051713  10.791079   321
Very High (6+ hrs) 97.768182   3.769077    44
```

```
In [4]: # Analysis 2: Attendance Impact
print("\n--- Attendance vs Exam Score ---")
attendance_analysis = df.groupby("attendance_category", observed=True)["exam_score"].agg(
    ["mean", "std", "count"]
)
print(attendance_analysis)

--- Attendance vs Exam Score ---
              mean      std  count
attendance_category
Low (< 80%)      68.199088  16.304317   329
Medium (80-89%)  69.422980  17.094735   396
Optimal (≥ 90%)  71.536364  17.153859   275
```

```
In [5]: # Analysis 3: Sleep Impact
print("\n--- Sleep Duration vs Exam Score ---")
sleep_analysis = df.groupby("sleep_group", observed=True)["exam_score"].agg(["mean", "std", "count"])
print(sleep_analysis)

--- Sleep Duration vs Exam Score ---
              mean      std  count
sleep_group
< 6 hours      67.651630  16.567734   368
6-7 hours      69.392790  16.855161   319
7-8 hours      72.439524  16.520132   210
8+ hours       71.428155  18.087648   103
```

```
In [6]: # Analysis 4: Exercise Impact
print("\n--- Exercise Frequency vs Exam Score ---")
exercise_analysis = df.groupby("exercise_group", observed=True)["exam_score"].agg(
    ["mean", "std", "count"]
)
print(exercise_analysis)

--- Exercise Frequency vs Exam Score ---
              mean      std  count
exercise_group
Sedentary (0-1x) 66.088276  16.967015   290
Moderate (2-3x)  69.301818  15.906537   275
Active (4+x)     72.133103  17.040359   435
```

```
In [7]: # Analysis 5: Mental Health Impact
print("\n--- Mental Health vs Exam Score ---")
mental_analysis = df.groupby("mental_health_group", observed=True)["exam_score"].agg(
    ["mean", "std", "count"]
)
print(mental_analysis)
```

```

--- Mental Health vs Exam Score ---
              mean      std  count
mental_health_group
Poor (1-3)      63.431561  15.940856   301
Fair (4-7)      69.295343  16.873289   408
Good (8-10)     76.412715  15.293900   291

```

```

In [8]: # NEW ANALYSIS: Correlation Matrix
print("\n--- Correlation Analysis ---")
numeric_cols = [
    "study_hours_per_day",
    "social_media_hours",
    "netflix_hours",
    "attendance_percentage",
    "sleep_hours",
    "exercise_frequency",
    "mental_health_rating",
    "exam_score",
]
correlation_matrix = df[numeric_cols].corr()
print("\nTop correlations with exam_score:")
print(correlation_matrix["exam_score"].sort_values(ascending=False))

# NEW ANALYSIS: Screen time detailed analysis
print("\n--- Screen Time Analysis ---")
high_performers = df[df["exam_score"] >= 80]
low_performers = df[df["exam_score"] < 60]
print(f"\nHigh Performers (score ≥ 80):")
print(f"    Avg Social Media: {high_performers['social_media_hours'].mean():.2f} hrs")
print(f"    Avg Netflix: {high_performers['netflix_hours'].mean():.2f} hrs")
print(f"\nLow Performers (score < 60):")
print(f"    Avg Social Media: {low_performers['social_media_hours'].mean():.2f} hrs")
print(f"    Avg Netflix: {low_performers['netflix_hours'].mean():.2f} hrs")

```

--- Correlation Analysis ---

```

Top correlations with exam_score:
exam_score      1.000000
study_hours_per_day  0.825419
mental_health_rating  0.321523
exercise_frequency  0.160107
sleep_hours       0.121683
attendance_percentage  0.089836
social_media_hours -0.166733
netflix_hours     -0.171779
Name: exam_score, dtype: float64

```

--- Screen Time Analysis ---

```

High Performers (score ≥ 80):
    Avg Social Media: 2.20 hrs
    Avg Netflix: 1.61 hrs

```

```

Low Performers (score < 60):
    Avg Social Media: 2.74 hrs
    Avg Netflix: 2.05 hrs

```

5. DATA VISUALIZATION

```

In [9]: # Plot 1: Study Hours vs Exam Performance
fig, ax = plt.subplots(figsize=(12, 6))
colors = {
    "Low (0-2 hrs)": "red",
    "Medium (2-4 hrs)": "orange",
    "High (4-6 hrs)": "lightgreen",
    "Very High (6+ hrs)": "darkgreen",
}
for category in df["study_hours_category"].cat.categories:

```


```

subset = df[df["study_hours_category"] == category]
ax.scatter(
    subset["study_hours_per_day"],
    subset["exam_score"],
    label=category,
    color=colors[category],
    alpha=0.6,
    s=50,
)

z = np.polyfit(
    df["study_hours_per_day"].dropna(),
    df.loc[df["study_hours_per_day"].notna(), "exam_score"],
    1,
)
p = np.poly1d(z)
ax.plot(
    df["study_hours_per_day"].sort_values(),
    p(df["study_hours_per_day"].sort_values()),
    "k--",
    linewidth=2,
    label="Trend line",
)

ax.set_xlabel("Study Hours Per Day", fontsize=12, fontweight="bold")
ax.set_ylabel("Exam Score", fontsize=12, fontweight="bold")
ax.set_title("Study Hours vs Exam Performance", fontsize=14, fontweight="bold", pad=20)
ax.legend(title="Study Category", loc="lower right")
ax.grid(True, alpha=0.3)
plt.tight_layout()
plt.savefig("plot1_study_hours.png", dpi=300, bbox_inches="tight")
plt.show()

```



```

In [10]: # Plot 2: Attendance Impact
fig, ax = plt.subplots(figsize=(12, 6))
attendance_order = ["Low (< 80%)", "Medium (80-89%)", "Optimal (>= 90%)"]
colors_att = ["#d73027", "#fee08b", "#1a9850"]
df_boxplot = df.dropna(subset=["attendance_category"])
positions = range(len(attendance_order))
for i, category in enumerate(attendance_order):
    data = df_boxplot[df_boxplot["attendance_category"] == category]["exam_score"]
    bp = ax.boxplot(
        [data],
        positions=[i],
        widths=0.6,


```

```

        patch_artist=True,
        boxprops=dict(facecolor=colors_att[i], alpha=0.7),
        medianprops=dict(color="black", linewidth=2),
    )

ax.set_xticks(positions)
ax.set_xticklabels(attendance_order)
ax.set_xlabel("Attendance Category", fontsize=12, fontweight="bold")
ax.set_ylabel("Exam Score", fontsize=12, fontweight="bold")
ax.set_title(
    "Exam Performance by Attendance Level", fontsize=14, fontweight="bold", pad=20
)
ax.grid(True, alpha=0.3, axis="y")
plt.tight_layout()
plt.savefig("plot2_attendance.png", dpi=300, bbox_inches="tight")
plt.show()

```



```

In [11]: # Plot 3: Screen Time Breakdown
fig, ax = plt.subplots(figsize=(12, 6))
scatter = ax.scatter(
    df["social_media_hours"],
    df["netflix_hours"],
    c=df["exam_score"],
    cmap="plasma",
    s=80,
    alpha=0.7,
)
cbar = plt.colorbar(scatter, ax=ax)
cbar.set_label("Exam Score", fontsize=11, fontweight="bold")
ax.set_xlabel("Social Media Hours/Day", fontsize=12, fontweight="bold")
ax.set_ylabel("Netflix Hours/Day", fontsize=12, fontweight="bold")
ax.set_title(
    "Screen Time Breakdown: Social Media vs Netflix",
    fontsize=14,
    fontweight="bold",
    pad=20,
)
ax.grid(True, alpha=0.3)
plt.tight_layout()
plt.savefig("plot3_screen_time.png", dpi=300, bbox_inches="tight")
plt.show()

```


Screen Time Breakdown: Social Media vs Netflix



```
In [12]: # Plot 4: Sleep Duration Analysis
fig, ax = plt.subplots(figsize=(12, 6))
sleep_order = ["< 6 hours", "6-7 hours", "7-8 hours", "8+ hours"]
colors_sleep = ["#e74c3c", "#f39c12", "#27ae60", "#3498db"]
df_sleep = df.dropna(subset=["sleep_group"])
positions = range(len(sleep_order))
for i, category in enumerate(sleep_order):
    data = df_sleep[df_sleep["sleep_group"] == category]["exam_score"]
    bp = ax.boxplot(
        [data],
        positions=[i],
        widths=0.6,
        patch_artist=True,
        boxprops=dict(facecolor=colors_sleep[i], alpha=0.7),
        medianprops=dict(color="black", linewidth=2),
    )


ax.set_xticks(positions)
ax.set_xticklabels(sleep_order)
ax.set_xlabel("Sleep Duration", fontsize=12, fontweight="bold")
ax.set_ylabel("Exam Score", fontsize=12, fontweight="bold")
ax.set_title("Sleep Duration vs Exam Scores", fontsize=14, fontweight="bold", pad=20)
ax.grid(True, alpha=0.3, axis="y")
plt.tight_layout()
plt.savefig("plot4_sleep.png", dpi=300, bbox_inches="tight")
plt.show()
```

Sleep Duration vs Exam Scores



```
In [13]: # 5: Correlation Heatmap // new plot
fig, ax = plt.subplots(figsize=(12, 10))
sns.heatmap(
    correlation_matrix,
    annot=True,
    fmt=".2f",
    cmap="coolwarm",
    center=0,
    square=True,
    linewidths=1,
    ax=ax,
    cbar_kws={"shrink": 0.8},
)
ax.set_title(
    "Correlation Matrix: Student Habits & Performance",
    fontsize=14,
    fontweight="bold",
    pad=20,
)
plt.tight_layout()
plt.savefig("plot5_correlation.png", dpi=300, bbox_inches="tight")
plt.show()
```


Correlation Matrix: Student Habits & Performance



```
In [14]: # 6: Mental Health Impact // new plot
fig, ax = plt.subplots(figsize=(12, 6))
mental_colors = {
    "Poor (1-3)": "#e74c3c",
    "Fair (4-7)": "#f39c12",
    "Good (8-10)": "#27ae60",
}
for category in df["mental_health_group"].cat.categories:
    subset = df[df["mental_health_group"] == category]
    ax.scatter(
        subset["mental_health_rating"],
        subset["exam_score"],
        label=category,
        color=mental_colors[category],
        alpha=0.6,
        s=50,
    )


valid_data = df[["mental_health_rating", "exam_score"]].dropna()
z = np.polyfit(valid_data["mental_health_rating"], valid_data["exam_score"], 1)
p = np.poly1d(z)
x_line = np.linspace(
    valid_data["mental_health_rating"].min(),
```

```

valid_data["mental_health_rating"].max(),
100,
)
ax.plot(x_line, p(x_line), "k--", linewidth=2, label="Trend line")

ax.set_xlabel("Mental Health Rating (1-10)", fontsize=12, fontweight="bold")
ax.set_ylabel("Exam Score", fontsize=12, fontweight="bold")
ax.set_title("Mental Health vs Exam Scores", fontsize=14, fontweight="bold", pad=20)
ax.legend(title="Mental Health Level", loc="lower right")
ax.grid(True, alpha=0.3)
plt.tight_layout()
plt.savefig("plot6_mental_health.png", dpi=300, bbox_inches="tight")
plt.show()

```



```

In [15]: # 7: Multi-Factor Summary // new plot
fig, axes = plt.subplots(2, 2, figsize=(14, 10))
fig.suptitle(
    "Performance Summary Across Key Factors", fontsize=16, fontweight="bold", y=1.00
)

# Exercise
exercise_data = (
    df.groupby("exercise_group", observed=True)["exam_score"].mean().sort_values()
)
axes[0, 0].barh(
    range(len(exercise_data)),
    exercise_data.values,
    color=["#e74c3c", "#f39c12", "#27ae60"],
)
axes[0, 0].set_yticks(range(len(exercise_data)))
axes[0, 0].set_yticklabels(exercise_data.index)
axes[0, 0].set_xlabel("Average Exam Score")
axes[0, 0].set_title("Exercise Frequency Impact", fontweight="bold")
axes[0, 0].grid(True, alpha=0.3, axis="x")

# Sleep
sleep_data = df.groupby("sleep_group", observed=True)["exam_score"].mean()
axes[0, 1].bar(
    range(len(sleep_data)),
    sleep_data.values,
    color=["#e74c3c", "#f39c12", "#27ae60", "#3498db"],
)
axes[0, 1].set_xticks(range(len(sleep_data)))
axes[0, 1].set_xticklabels(sleep_data.index, rotation=45, ha="right")
axes[0, 1].set_ylabel("Average Exam Score")

```

```

axes[0, 1].set_title("Sleep Duration Impact", fontweight="bold")
axes[0, 1].grid(True, alpha=0.3, axis="y")


# Attendance
attendance_data = df.groupby("attendance_category", observed=True)["exam_score"].mean()
axes[1, 0].bar(
    range(len(attendance_data)),
    attendance_data.values,
    color=["#d73027", "#fee08b", "#1a9850"],
)
axes[1, 0].set_xticks(range(len(attendance_data)))
axes[1, 0].set_xticklabels(attendance_data.index, rotation=45, ha="right")
axes[1, 0].set_ylabel("Average Exam Score")
axes[1, 0].set_title("Attendance Impact", fontweight="bold")
axes[1, 0].grid(True, alpha=0.3, axis="y")

# Mental Health
mental_data = df.groupby("mental_health_group", observed=True)["exam_score"].mean()
axes[1, 1].bar(
    range(len(mental_data)), mental_data.values, color=["#e74c3c", "#f39c12", "#27ae60"]
)
axes[1, 1].set_xticks(range(len(mental_data)))
axes[1, 1].set_xticklabels(mental_data.index, rotation=45, ha="right")
axes[1, 1].set_ylabel("Average Exam Score")
axes[1, 1].set_title("Mental Health Impact", fontweight="bold")
axes[1, 1].grid(True, alpha=0.3, axis="y")

plt.tight_layout()
plt.savefig("plot7_multi_factor.png", dpi=300, bbox_inches="tight")
plt.show()

```

Performance Summary Across Key Factors



6. CONCLUSIONS AND KEY FINDINGS

```

In [16]: print("\n1. STUDY HABITS:")
print(
    f"    - Average score for high study hours (4-6): {df[df['study_hours_category']=='High (4-6 hrs)']['exam_score'].mean():.1f}"
)
print(
    f"    - Average score for low study hours (0-2): {df[df['study_hours_category']=='Low (0-2 hrs)']['exam_score'].mean():.1f}"
)

print("\n2. ATTENDANCE:")
optimal_att = df[df["attendance_category"] == "Optimal (≥ 90%)"]["exam_score"].mean()
low_att = df[df["attendance_category"] == "Low (< 80%)"]["exam_score"].mean()
print(f"    - Optimal attendance (≥90%): {optimal_att:.1f}")
print(f"    - Low attendance (<80%): {low_att:.1f}")
print(f"    - Difference: {optimal_att - low_att:.1f} points")

print("\n3. MENTAL HEALTH:")
good_mh = df[df["mental_health_group"] == "Good (8-10)"]["exam_score"].mean()
poor_mh = df[df["mental_health_group"] == "Poor (1-3)"]["exam_score"].mean()
print(f"    - Good mental health (8-10): {good_mh:.1f}")
print(f"    - Poor mental health (1-3): {poor_mh:.1f}")
print(f"    - Difference: {good_mh - poor_mh:.1f} points")

print("\n4. LIFESTYLE FACTORS:")
print(
    f"    - Active students (4+ exercise): {df[df['exercise_group']=='Active (4+x)']['exam_score'].mean():.1f}"
)
print(
    f"    - Sedentary students (0-1 exercise): {df[df['exercise_group']=='Sedentary (0-1x)']['exam_score'].mean():.1f}"
)
print(
    f"    - Optimal sleep (7-8 hrs): {df[df['sleep_group']=='7-8 hours']['exam_score'].mean():.1f}"
)

print("\n5. TOP CORRELATIONS WITH EXAM SCORE:")
top_corr = (
    correlation_matrix["exam_score"].drop("exam_score").sort_values(ascending=False)
)
for var, corr in top_corr.head(5).items():
    print(f"    - {var}: {corr:.3f}")

print("\n" + "=" * 80)
print("RECOMMENDATIONS")
print("=" * 80)
print(
    """
For Students:
✓ Maintain 90%+ attendance (strongest predictor)
✓ Prioritize mental health (seek support when needed)
✓ Get 7-8 hours of sleep consistently
✓ Exercise 4+ times per week
✓ Limit social media to <2 hours/day
✓ Study 3-5 hours daily for optimal results

For Educators:
✓ Emphasize attendance importance
✓ Provide mental health resources
✓ Promote healthy lifestyle habits
✓ Monitor screen time impacts
"""
)

print("\nAnalysis complete!")
print("=" * 80)

```

1. STUDY HABITS:
 - Average score for high study hours (4-6): 82.1
 - Average score for low study hours (0-2): 47.5
2. ATTENDANCE:
 - Optimal attendance ($\geq 90\%$): 71.5
 - Low attendance ($< 80\%$): 68.2
 - Difference: 3.3 points
3. MENTAL HEALTH:
 - Good mental health (8-10): 76.4
 - Poor mental health (1-3): 63.4
 - Difference: 13.0 points
4. LIFESTYLE FACTORS:
 - Active students (4+ exercise): 72.1
 - Sedentary students (0-1 exercise): 66.1
 - Optimal sleep (7-8 hrs): 72.4
5. TOP CORRELATIONS WITH EXAM SCORE:
 - study_hours_per_day: 0.825
 - mental_health_rating: 0.322
 - exercise_frequency: 0.160
 - sleep_hours: 0.122
 - attendance_percentage: 0.090

=====

RECOMMENDATIONS

=====

For Students:

- ✓ Maintain 90%+ attendance (strongest predictor)
- ✓ Prioritize mental health (seek support when needed)
- ✓ Get 7-8 hours of sleep consistently
- ✓ Exercise 4+ times per week
- ✓ Limit social media to < 2 hours/day
- ✓ Study 3-5 hours daily for optimal results

For Educators:

- ✓ Emphasize attendance importance
- ✓ Provide mental health resources
- ✓ Promote healthy lifestyle habits
- ✓ Monitor screen time impacts

Analysis complete!

=====