Can LLMs Build Better Annotators? Self-Improving Harnesses for Ontology-Guided Annotation

Anonymous ACL submission

Abstract

Annotating text with a rich ontology, such as UMR graphs, TimeML or a policy codebook, is still done by trained people following long guidelines. LLMs follow instructions, but a scheme's conventions are external knowledge, and the harness that turns an LLM into an annotator (per-step instructions, tools, the chain of calls) is built by hand through error analysis. We ask whether an LLM can build that harness itself from a few gold documents. ANNOFORGE traces every step of a harness, attributes each divergence from gold to the responsible step and scheme category, applies typed edits to that step only, and admits new tools and steps only through tests and a reviewer, with a guard against copying gold. We evaluate test-then-train and pair each score with the seed harness on the same unseen document. On Chinese UMR, the learned harness gains 9.0 sentence F on unseen documents (95% CI 5.5–12.5; 8 of 9 documents) [and beats in-context learning and guideline-only refinement with the same documents]. The gain is scheme convention written into the generator's instructions, not better semantic judgment; a verification step adds 0.5 F, and no proposed tool is admitted. The loop almost never deletes, the harness grows 39-fold while the gain stops growing, and a 9B builder makes the annotator worse. [TimeML and manifesto coding.]

1 Introduction

Many language-processing projects begin by committing to an ontology, a scheme of labels, relations and conventions, and annotating data with it: Uniform Meaning Representation (UMR) graphs for cross-lingual semantics (Van Gysel et al., 2021; Bonn et al., 2024), TimeML for temporal structure (Pustejovsky et al., 2003), codebooks for political text (Lehmann et al., 2026). People are trained on the guideline for weeks, and one document can take hours; for Chinese UMR, even revising GPT-4 drafts saved about two thirds of the time (Sun et al., 2024).

LLMs recover who did what to whom without training. What they lack is the scheme: its labels, its conventions where it departs from intuition, the resources it points to. Supplying this is the job of the *harness* around the model: the instructions of each step, the tools a step can call, the chain of calls, and deterministic code that keeps the output well formed. Harnesses are built the way guidelines are: a person annotates a document with the current harness, compares it with gold, decides which component is at fault, edits it, and repeats. This loop decides how good the annotator is, and it is the expensive part.

We ask whether the model can run the loop itself: *given a few gold documents and a seed harness that a person could write in an afternoon, can an LLM build a better annotator?* Earlier work has LLMs revise annotation guidelines against gold for biomedical entity recognition (Kim et al., 2026); it starts from a detailed human guideline, targets one error pattern per iteration, rewrites the guideline text, and has no place for tools or steps. Self-improving agents optimize prompts, workflows and code against task rewards on agentic and reasoning benchmarks (Zhang et al., 2026a; Hu et al., 2025). Annotation offers a richer signal than either: gold is a structure that can be aligned with the prediction, so each divergence can be traced to a place in the harness. The difficulties are credit assignment over hundreds of divergences per document, knowledge that belongs in code or lookups rather than prose, a builder that runs its own code and can copy gold, and honest measurement when every annotated document is precious.

We present ANNOFORGE (Figure 1). After annotating a gold document it records a trace of every step, attributes each divergence to the responsible skill and scheme category, applies typed edits (modify, add, delete) to that skill only, admits new tools

and steps only through machine checks and a reviewer, and rejects edits that copy gold text. We measure it test-then-train: each document is annotated by the harness built from the documents before it, and the seed harness annotating the same document is the paired control.

On Chinese UMR (11 documents, 415 sentences):

- The learned harness gains 9.0 sentence F on unseen documents (95% CI 5.5–12.5; 8 of 9 documents) and 10.1 on the comprehensive score with document-level relations (9 of 9). [Comparison with in-context learning, guideline-only refinement and a hand-designed procedural harness.]
- What transfers is *convention, not competence*: checks on peripheral roles, abstract rolesets, modal strength and pronoun attributes gain 12–25 points; sense, aspect and core arguments do not move. It sits in the generator's instructions; a checking step adds 0.5 F.
- The loop is append-only (1 delete in 1060 edits); the harness grows from 11.2 to 434 KB while the gain stops growing; no proposed tool passes review. The builder's 130 out-of-scope requests mostly concern inconsistent gold and missing code.
- With Qwen3.5-9B as builder and annotator, unseen-document F changes by −1.4. [TimeML and manifesto coding.]

Our contributions are the formulation and protocol, the loop, and an account of what an LLM builder learns, what it does not, and how it fails, with all harness versions and per-round records.

2 Related Work

LLMs as annotators. LLMs match or replace crowd workers on many labeling tasks (Gilardi et al., 2023; He et al., 2024; Ziems et al., 2024; Tan et al., 2024) but follow a scheme's conventions poorly out of the box: as AMR analyzers (Ettinger et al., 2023), with concept guidelines (Fonseca and Cohen, 2024), and with real codebooks (Halterman and Keith, 2026). Automatic UMR parsers build on AMR parsers (Chun and Xue, 2024; Markle et al., 2026).

Guidelines as input and as learnable objects. Guidelines help when models are trained to follow them (Sainz et al., 2024; Srivastava et al., 2025) or replace examples in context (Huang et al., 2025); Guideline Learning synthesizes rules from errors for in-context extraction (Pang et al., 2023), a modern form of error-driven rule learning (Brill, 1995). Earlier work lets LLMs improve annotation guidelines against gold (Bibal et al., 2025; Kim et al., 2025, 2026): for biomedical NER, a moderator picks the most frequent error pattern, writes one principle, re-emits the whole guideline, and keeps it if development F1 improves (Kim et al., 2026). Codebook work revises coding instructions from model disagreement or expert feedback (He et al., 2026; Yuan et al., 2026). In all of these the object that changes is instruction text, edited as one document; we change a harness and attribute each error to a component before editing it.

Prompt and context optimization. Instructions can be searched (Zhou et al., 2023; Yang et al., 2024), edited along textual "gradients" (Pryzant et al., 2023; Yuksekgonul et al., 2025), compiled with demonstrations (Khattab et al., 2024; Opsahl-Ong et al., 2024), evolved by reflection (Agrawal et al., 2026), or grown as playbooks and memories (Zhang et al., 2026c; Suzgun et al., 2026). They optimize a scalar metric over a training set, and with little data can lose to fixed prompts (Singh, 2026); our setting has one document per step but a full gold structure per document.

Self-improving agents and harnesses. Self-feedback rarely helps without an external signal (Madaan et al., 2023; Shinn et al., 2023; Huang et al., 2024; Kamoi et al., 2024). Agents learn skills (Wang et al., 2024; Zheng et al., 2025), make tools (Cai et al., 2024; Qian et al., 2023; Wölflein et al., 2025), and search over workflows and their own code (Hu et al., 2025; Zhang et al., 2025, 2026b). Recent work optimizes the harness itself (Lee et al., 2026; Zhang et al., 2026a; Lin et al., 2026a; Xia et al., 2026), admitting edits through regression tests, verified predictions or critics; gains compound only with regression control (Wang et al., 2026), and writing useful updates and benefiting from them dissociate across model tiers (Lin et al., 2026b). These target coding, terminal and web agents with pass/fail rewards; to our knowledge none targets annotation, where gold locates the error. Our test-then-train protocol follows stream learning (Dawid, 1984; Gama et al., 2013).




Figure 1: ANNOFORGE. A harness is a chain of skills (instruction text with optional examples), shared tools and deterministic rule steps. One round annotates a gold document, attributes each divergence from gold to the responsible skill and scheme category, and edits those skills (orange borders). The next document is annotated by the new harness before it is used to improve it.

3 Building an Annotator

Schemes, evaluators, harnesses. A scheme fixes the labels, structures and conventions of an annotation; for UMR, concepts with PropBank senses (Palmer et al., 2005), roles, attributes such as aspect and modal strength, named-entity structures, and document-level temporal, modal and coreference relations (Van Gysel et al., 2021). An evaluator compares an annotation with gold and returns, besides a score, *units*: per-check verdicts with the aligned gold and predicted elements. For UMR we use AnCast++ (Sun and Xue, 2024; Sun et al., 2025) for score and alignment and a judge that sorts aligned elements into 25 checks in 11 groups named after parts of the scheme (Appendix A). An annotator is an LLM inside a harness $H = (S, T, G, R)$: *skills* S (an instruction, optional examples and an output schema, run as one model call), *tools* T any skill may call, a *chain* G saying which skill runs on whose output, and *rule steps* R, deterministic code. Running H on a document x yields an annotation $A_H(x)$ and a trace of every step.

The building task. A builder receives a seed harness H_0, written by a person in an afternoon (what the output contains, its format, the checks the evaluator makes, no examples), and gold documents $(x_1, y_1), \ldots, (x_n, y_n)$, and returns H_n. The only signal is gold; no person edits the harness (one disclosed exception, §4.1). A_{H_n} should score well on unseen documents at a known cost, and H_n should stay readable for annotators to audit.

Sequential evaluation. With a few dozen gold documents there is no room for a large development set, and a document used for improving cannot also measure. We evaluate test-then-train, as for stream learners (Dawid, 1984; Gama et al., 2013): for $i = 1, \ldots, n$, annotate x_i with H_{i-1} and score it, then improve H_{i-1} into H_i with (x_i, y_i). Every score is on an unseen document, and documents differ in difficulty, so each score is paired with H_0 on the same document. A held-out set never used for building compares the final harness with baselines that receive the same gold.

4 ANNOFORGE

4.1 Harness representation

Every part of a harness is a file that a builder can read, edit and diff. A skill is a Markdown instruction whose last section holds the per-call input, so the part above it is identical across calls and cached; it may have worked examples in a separate file read through the shared `get_example` tool. Tools are typed Python functions with a docstring. A registry declares skills, output schemas and the chain; rule steps are Python functions that call no model. Versions are directories never edited after their round: round y on document x produces R_{xy}, and $H_n = R_{n3}$ is the version after document n.

The UMR harness. Per sentence, three model calls (Figure 1). `generate` writes the whole sentence graph from a 2 KB description of what a UMR graph contains and how it is written, with no examples. `critique` checks the draft one evalua-

tor group at a time (nodes, senses, attributes, arguments, role labels, names, reentrancy); each group says what the evaluator checks and lists *common errors*, a few generic ones in the seed. It returns findings and a corrected graph. A rule step repairs the last parseable graph (duplicate or undefined variables, self-loops, disconnected parts).[1] `document` sees the graph and the five before it and writes the sentence's temporal, modal and coreference relations. All skills can call `propbank_lookup` and `get_example`. The seed has 11.2 KB of instructions.

4.2 One improvement round

1. Annotate and trace. The current harness annotates the gold document; the trace holds each sentence's draft, each later step's findings and the triples it added or removed, the rule repairs, and the document-level calls.

2. Align. The evaluator aligns prediction and gold and lists the units it did not count as correct.

3. Find. For every sentence with an error, the builder model sees the sentence, both graphs, the alignment, the incorrect units, both sides' document-level relations, and the trace. It lists every divergence, merging those with one cause, and labels each with its kind, its evaluator check, the step it came from, the skill whose instructions *should change*, its cause, and, if gold follows a convention, that convention in general terms. The prompt gives the rule for blame: what `critique` should catch in its group is `critique`'s; a draft no check can repair, or a misleading instruction of `generate`, is `generate`'s; document-level errors are `document`'s.

4. Plan. One call reads up to 250 problems (taken in turn from each sentence), grouped by responsible skill and, for `critique`, by evaluator group, together with every skill's full text. It returns edits, each naming a skill, a file, an action, an anchor, a text and the problems it addresses: *modify* replaces an instruction, common error or example that is wrong or too narrow; *add* inserts a missing rule, example or common error after an anchor; *delete* removes text that causes an error or contradicts gold. Edits must be general and checkable, one edit should fix many problems, and one-offs and gold errors get no edit; changes outside the instructions go to a list of suggestions the loop does not apply.

5. Admit and apply. An edit applies only if its anchor occurs exactly once, and is rejected if it shares eight consecutive characters with any sentence of the corpus, training or held-out. A round may also propose one tool (a Python function every skill can call) and one step (a skill inserted in the chain). A proposal must pass machine checks (the registry loads; a tool imports only whitelisted modules, touches no files, has one typed public function, and passes at least three tests of its own in an isolated process) and then a reviewer, a separate builder call that approves only if six criteria clearly hold: the problem recurs and is costly, no edit could fix it as well, the part has one narrow responsibility, it is worth its cost, it is correct, and it leaks nothing (Appendix C). Edits that depend on a rejected proposal are dropped.

Schedule. Documents are processed in order, three rounds each; each round re-annotates the document with the previous round's version. H_n then annotates document $n{+}1$, unchanged; that is its test score.

Attribution (step 3) and typed, anchored edits (step 4) are our answer to credit assignment and auditability: each edit touches one place and leaves a diff, instead of a rewritten guideline. Tools and steps are gated because they persist across documents. In this version the loop does not test an edit before keeping it, and nothing prompts it to consolidate; §6 shows the consequences. For TimeML and manifesto coding the harness has the same shape (Appendix F).

5 Experimental Setup

Data. Chinese UMR (Bonn et al., 2024), 31 documents with sentence graphs and document-level relations, in a cleaned version of the gold [cite the cleanup]. The sequential run takes documents 0001–0011 in numerical order (415 sentences, 10–82 per document) and stopped after the first round on 0011, so 9 documents (0002–0010) have both a learned and a seed annotation. The other 20 documents (297 sentences) were never shown to a builder and form the held-out set.

Models and metrics. Claude Sonnet 5.5 annotates and Claude Opus 5.5 builds (find, plan, re-

[1] When R_{12} annotated document 0001, one sentence lost all credit to a missing bracket, and we added bracket balancing to this rule from R_{13} on: the only change a person made to any harness during the run.

view), with adaptive thinking at default effort; §6.6 varies them. AnCast++ (Sun et al., 2025) aligns each predicted sentence graph with gold and gives F over sentence graphs (F) and a comprehensive score that adds document-level modal, temporal and coreference relations (C). For analysis we use the judge's per-check scores and per-sentence Smatch.

Baselines. Each sees the same gold documents as the builder, or none. **Zero-shot prompt**: one call per sentence naming the language and the scheme and pointing to its guidelines; sentence graphs only. **Seed harness** H_0. **Few-shot** [to run]: H_0 with the gold graphs of the k most similar training sentences (character TF-IDF) in `generate`, $k \in \{10, 30\}$. **Guideline-only refinement** [to run]: the closest analogue of earlier work (Kim et al., 2026), with the same builder and gold, but a single guideline prompt rewritten in full each round from the dominant error pattern and kept only if the training document improves. **Procedural harness**: a hand-designed harness that follows the human annotation procedure (Anonymous, 2026), with dozens of narrow decisions per sentence, improved by the same builder with edits confined to the skill that made each decision.

Statistics. We report the mean paired difference over documents with a bootstrap 95% interval (20,000 resamples), the exact Wilcoxon signed-rank test, and the number of documents that improve; sentence-level intervals resample documents, then sentences. Each configuration was run once [G-var].

6 Results

6.1 The learned harness is better on unseen documents

On the documents that also have the zero-shot prompt (0002–0007; Table 1), the systems form a ladder: 30.9 F for one call per sentence, 46.9 for the seed harness, 58.5 for the learned harness. Over the 9 documents with a seed control, the learned harness gains 9.0 F (95% CI 5.5–12.5; Wilcoxon $p = 0.008$) and improves 8 of them; on the comprehensive score it gains 10.1 (7.0–13.0) and improves all 9 ($p = 0.004$). Of 337 paired sentences, 77.2% get higher Smatch and 18.4% lower (mean +9.5, 6.2–12.5). The one document that does not improve, 0008 (-0.8), has ten sentences.

Training fit is not generalization. Three rounds on a document raise its own F by 26.6 points, to 84.2 on average and up to 99.2, against 9.0 on the next, unseen document (Figure 2a). The leakage guard stops copying, not learning one document's particular conventions. Evaluated on its training documents, the same loop would look three times better.

6.2 Against baselines with the same gold

The held-out comparison is pending (Table 2). One matched comparison exists: trained on 0001–0004 with the same models, the learned harness scores 58.5 F on document 0005 and the procedural harness 55.7; the procedural seed starts higher there (51.1 vs. 48.0), so the learned gains are +10.5 and +4.6 (one document; the procedural harness had 10 rounds, ours 12; Appendix Table 11).

6.3 Where the gains come from

The generator, not the checker. Scoring the graph after each step (Appendix Table 9) shows that the learned `generate` alone is 9.6 F better than the seed's on unseen documents, and `critique` adds 0.5 on top (-0.4 to +1.4), less than the 1.0 it adds to the seed's draft; on the document it was trained on it adds 1.7. The common-error lists learn to fix their own document; what transfers is in the generator's instructions. A variant with five specialized checks shows this more sharply: the checks add +8.9 to +9.3 on their training documents and 0.5 on unseen ones (Appendix Table 10). At annotation time a checker has no gold, only what it was told, as self-correction studies would predict (Huang et al., 2024; Kamoi et al., 2024).

Convention, not competence. By judge check (Figure 3), the largest gains are on the scheme's conventions: pronoun person and number (+24.8 points), the author's modal strength (+18.9), non-core role labels (+18.3), arguments of abstract rolesets such as `have-org-role-91` (+13.2), non-core arguments of events (+12.4), entity concepts (+10.7). Checks that need a semantic judgment the model already makes as well as it can do not move: PropBank sense (+0.2), aspect (+0.4), core arguments of events (+0.3). Coreference (+5.1) gains little and polarity falls (-10.9, few units). The builder mostly teaches the annotator how the scheme writes things down, which is what a guideline is for.

Doc	Sent.	Annotated by	Zero-shot prompt F	Seed H_0 F	Learned F	Δ F	Seed C	Learned C	Δ C	Trained on it, F
0001	51	H_0	31.0	45.1	–	–	40.5	–	–	77.5
0002	60	H_1	31.1	49.4	61.1	+11.8	44.1	56.2	+12.1	77.3
0003	31	H_2	32.3	45.3	57.2	+11.9	41.3	55.4	+14.1	84.4
0004	59	H_3	33.5	42.9	52.4	+9.5	39.3	49.7	+10.4	72.4
0005	40	H_4	32.3	48.0	58.5	+10.5	44.4	57.1	+12.7	79.7
0006	35	H_5	23.6	49.3	56.1	+6.8	40.4	49.2	+8.8	81.0
0007	82	H_6	32.6	46.4	65.5	+19.1	42.3	59.6	+17.3	85.4
0008	10	H_7	TBD	57.1	56.4	−0.8	52.5	53.7	+1.2	92.7
0009	10	H_8	TBD	59.7	68.0	+8.3	55.2	65.3	+10.1	99.2
0010	12	H_9	TBD	51.2	55.2	+4.0	45.7	50.2	+4.5	92.5
0011	25	H_{10}	TBD	TBD	53.4	TBD	TBD	48.5	TBD	–
Mean, 9 paired documents			–	49.9	58.9	+9.0	45.0	55.2	+10.1	
Mean, 0002–0007			30.9	46.9	58.5	+11.6				

Table 1: Sequential (test-then-train) evaluation on Chinese UMR. Document n is annotated by the harness built from documents $1..n-1$ ("Learned"), then used to improve it. "Seed" is H_0 on the same document, the paired control. "Zero-shot prompt" is one call per sentence with no harness (sentence graph only, so only F is comparable). F = AnCast++ sentence F; C = comprehensive score (sentence graphs plus document-level relations). The last column is the harness trained on the document itself (training fit, not generalization). Document 0001 has no earlier harness; 0011 has no seed run yet; zero-shot is missing for 0008–0011.




Figure 2: (a) Sentence F per document in training order: seed harness, learned harness that has not seen the document, and the harness after three rounds on it. (b) Gain of the learned harness over the seed per unseen document (bars; dotted: mean) and the size of the harness that annotated it (line).

System (gold: 0001–0004)	F	C	Calls/sent.
Zero-shot prompt	TBD	–	1
Few-shot, k=30	TBD	TBD	3
Guideline-only refinement	TBD	TBD	1
Procedural harness	TBD	TBD	dozens
Seed harness H_0	TBD	TBD	3
Learned H_4 (and H_1, H_{10})	TBD	TBD	3

Table 2: Held-out set (20 documents no builder saw), same gold budget for all trained systems. [G1–G4]

6.4 Tools are proposed rarely and admitted never

In 31 rounds the builder proposed 3 tools and no steps; the reviewer rejected all three. `check_umr_graph` checked attribute values, entity types and role names; the reviewer kept the purely mechanical checks (colon-prefixed or misspelled closed-list values, parse failures, duplicate variables) and judged the rest to be missing conventions that belong in the instructions. `check_umr_form` flagged bare constants and aspect on discourse role-sets; the second part contradicted the builder's own earlier rule. `check_doc_relations` checked coreference on name nodes and double temporal parents, but one test contradicted a convention of `document`. Each time a sound core was lost, because rejected proposals are not revised. Without the reviewer (the TimeML and manifesto runs), the builder changes tools or rules in most rounds [G7: does admitting




Figure 3: Judge score per check on unseen documents: seed (grey) and learned harness (blue; orange where lower), mean over 9 documents.

them help?].

6.5 More documents, more text, the same gain

The gain does not grow with the number of documents behind it (Figure 2b): +10.1 on average for documents 2–6, +7.7 for 7–10 (Spearman $\rho = -0.62$, $p = 0.077$). The harness grows from 11.2 to 434 KB (200 in `generate`, 152 in `critique`, 81 in `document`), 13.6 KB per round. Of 1060 applied edits, 663 modify, 396 add and 1 delete (Appendix Table 7): nothing rewards a shorter harness. Whether the plateau comes from what one document can teach, from interference among accumulated rules, or from length is open; held-out scores of H_1 to H_{10} and a consolidation pass under a size budget would separate these [G5, G6].

6.6 The builder must be capable

The gain holds for the procedural harness with the same models and for DeepSeek building and annotating without thinking (Table 3). With Qwen3.5-9B building and annotating over 13 documents, the learned harness is worse than the seed (−1.4 F on average; better on 3 documents), and the decline deepens (+0.6 in the first half, −3.0 in the second); two independent seed runs differ by 2.3 F per document, so single documents are within noise, the trend is not. On agentic tasks, by contrast, a 9B

Builder / annotator	Harness	n	Seed	Learned	Δ
Opus / Sonnet 5.5	ours^s	9	49.9	58.9	+9.0
Opus / Sonnet 5.5	proc.	2	45.5	52.9	+7.4
DeepSeek (no thinking)	proc.	5	32.5	37.6	+5.2
Qwen3.5-9B	proc.^{s}	13	17.6	16.3	−1.4
Qwen3.5-27B	proc.^{s}	TBD	TBD	TBD	TBD
Opus / small model	ours	TBD	TBD	TBD	TBD
Small model / Sonnet	ours^s	TBD	TBD	TBD	TBD

Table 3: Seed vs. learned harness on unseen documents, sentence F. One name: the same model builds and annotates. proc.: procedural harness. ^{s}sequential protocol; otherwise a few training documents and separate test documents. DeepSeek's seed reaches 49.1 F with thinking on vs. 35.9 off (document 0002).

Variant	ΔF seq.	ΔF held-out	KB
AnnoForge	+9.0	TBD	434
no attribution (one list)	TBD	TBD	TBD
whole-skill rewrites	TBD	TBD	TBD
`generate` only	TBD	TBD	TBD
no reviewer	TBD	TBD	TBD
+ test edits on held-in docs	TBD	TBD	TBD
+ consolidation	TBD	TBD	TBD
other document orders	TBD	TBD	TBD

Table 4: Ablations: sequential gain on 0002–0005 and gain on the held-out set. [G9]

model's harness updates were as useful as a frontier model's (Lin et al., 2026b). Whether builder or annotator matters more here is not yet separated [G8].

6.7 Ablations of the loop

Table 4 lists the ablations that test the design: whether attribution to a skill matters (one undivided problem list), whether typed edits matter (each round rewrites a skill in full, as guideline refinement does), whether the checking step is needed, whether the reviewer helps or only blocks, whether testing each edit before keeping it (Zhang et al., 2026a; Kim et al., 2026) closes the training-fit gap, whether consolidation lifts the plateau, and how much document order matters [G9: to run].

6.8 Beyond UMR

The same loop builds a TimeML annotator for TempEval-3 (UzZaman et al., 2013) and a coder that assigns manifesto sentences one of the eight policy domains of the Manifesto Project scheme (Lehmann et al., 2026), with the same protocol (Appendix F; finished baselines in Tables 12 and 13). On both test sets the seed harness is below the zero-shot prompt (TimeML event F1 74.5 vs. 80.7;

manifesto accuracy 63.8 vs. 65.0), so the learned harness must first make up for its own seed. [G10, G11: learned harness on both test sets; sequential gains.]

7 Analysis

What the builder writes. In its first round the builder found 752 divergences in document 0001, read 250 of them (the cap), and sorted them into six patterns: form (colon-prefixed or capitalized values, abbreviated modal strengths, AMR role names such as `:time` for UMR's `:temporal`); named-entity types and tokens; discourse relations written as reified rolesets (`have-reason-91`) rather than edges; reported speech; Chinese granularity (which compounds split, which adverbs, demonstratives and classifiers keep a node); and document-level defaults for dates and temporal relations. These are the topics a human guideline spends its pages on, and they match the checks that improve on unseen documents (Appendix D shows edits verbatim).

What the builder asks for and cannot do. Each round may also list changes outside the instructions, which the loop does not apply. We coded all 130 (Appendix E). 78 concern the gold: conventions that differ between documents or annotators (the argument order of the concession roleset, whether title marks belong to a name, how names are split into tokens, which person type is used), usually with a decision not to learn from them yet, and outright errors such as undefined variables or an unbalanced bracket. 27 ask for deterministic code, such as normalizing attribute values or validating document-level relations against the graphs; one is the bracket fix we made by hand. 14 ask for more input to a skill (a running list of coreference chains, the genre) and 10 for evaluator changes. A builder with gold is thus also an auditor of gold, the moderation step of a human project; and by its own diagnosis much of what remains needs code and context, which the admission gate of §6.4 blocked every time.

How the harness goes wrong. Beyond the training-fit gap and unbounded growth, three failure modes recur. *Contradictions*: in round 2 the builder proposed a check forbidding aspect on discourse rolesets while its own round-1 rule and example required it; the reviewer caught this because it came as a tool, but edits to prose pass no such check. *Following the latest document*: after 0001 the instructions said a negated event is full-negative *without* `:polarity -`; the first round on 0002, whose gold marks polarity, made it require both. By R_{111}, disagreements between documents have become rules conditioned on genre ("in a biography only", "in a plot summary"). *Local regressions*: since no edit is tested before it is kept, a regression surfaces only on the next document. Testing edits on held-in documents (Zhang et al., 2026a; Wang et al., 2026) and sending gold conflicts to people would address the last two [G9].

Cost. The seed harness costs about $0.08 per sentence at API list prices (three calls, cached prefixes). The learned harness reads up to 434 KB of instructions per sentence, mostly cached; building costs one call per sentence with an error and one planning call per round. [G12: cost and latency of H_1, H_4, H_{10}; cost of building; time to write the seed.]

8 Conclusion

Can LLMs build better annotators? On Chinese UMR, in a specific sense, yes: from a few gold documents an LLM builder writes the scheme's conventions into a harness, and the annotator gains 9.0 F on documents it has not seen. It does not get better at the judgments that make semantic annotation hard; its rules accumulate, follow the latest document when annotators disagree, and stop paying off after the first few documents; and the builder must be strong. Its own suggestions say what comes next: code, context and consistent gold rather than more prose. A loop that tests edits before keeping them, admits code under tests, consolidates, and returns gold conflicts to people is the next step, and a sequential protocol with a paired seed is how to tell whether it works.

Limitations

Scale and variance. The complete results are on one scheme and language, Chinese UMR, with 11 documents and 415 sentences in the sequential run; three documents have only 10–12 sentences. Each configuration was run once, in one document order; we report paired tests over documents and a sentence-level bootstrap, but not run-to-run variance of building or annotating [G-var].

No test before keeping an edit. AnnoForge keeps every edit that applies cleanly; its quality is measured only on the next document. Methods that test edits on held-in data may avoid some of the

failure modes we report, and we have not compared them [G9].

Human influence. The seed harness, the judge's checks and the builder's prompts were written by the authors, and one rule step was changed by hand during the run (§4.1). The suggestions in §7 were coded by one person.

Models. The main run uses one closed model family for both annotating and building. Results with other models (Table 3) use a different harness and fewer documents, and DeepSeek ran without thinking.

Data. The leakage guard blocks verbatim copying of eight characters or more, not paraphrase or document-specific knowledge. The source texts of the documents may appear in pretraining data; [state whether the Chinese UMR gold is public]. Gold conventions differ between documents (§7), which bounds what any learner can reach.

Ethics Statement

Automating annotation can reduce the paid work available to annotators. We see the learned harness as a way to produce drafts and to audit gold, with people deciding conventions; its suggestions about inconsistent gold are addressed to them. All model calls were made through commercial APIs or open-weight models under their terms of use; the UMR documents are used for research under their release terms.

References

Lakshya A Agrawal, Shangyin Tan, Dilara Soylu, Noah Ziems, Rishi Khare, Krista Opsahl-Ong, Arnav Singhvi, Herumb Shandilya, Michael J Ryan, Meng Jiang, Christopher Potts, Koushik Sen, Alexandros G. Dimakis, Ion Stoica, Dan Klein, Matei Zaharia, and Omar Khattab. 2026. GEPA: Reflective prompt evolution can outperform reinforcement learning. In *The Fourteenth International Conference on Learning Representations (ICLR)*.

Anonymous. 2026. Decision orchestration: Learning annotation procedures from a handful of gold documents. Under review.

Adrien Bibal, Nathaniel Gerlek, Goran Muric, Elizabeth Boschee, Steven C. Fincke, Mike Ross, and Steven N. Minton. 2025. Automating annotation guideline improvements using LLMs: A case study. In *Proceedings of Context and Meaning: Navigating Disagreements in NLP Annotation*, pages 129–144, Abu Dhabi, UAE. International Committee on Computational Linguistics.

Julia Bonn, Matthew Buchholz, Jayeol Chun, Andrew Cowell, William Croft, Lukas Denk, Sijia Ge, Jan Hajič, Kenneth Lai, James H. Martin, Skatje Myers, Alexis Palmer, Martha Palmer, Claire Benét Post, James Pustejovsky, Kristine Stenzel, Haibo Sun, Zdeňka Urešová, Rosa Vallejos, and 4 others. 2024. Building a broad infrastructure for uniform meaning representations. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 2537–2547, Torino, Italia. ELRA and ICCL.

Eric Brill. 1995. Transformation-based error-driven learning and natural language processing: A case study in part-of-speech tagging. *Computational Linguistics*, 21(4):543–565.

Tianle Cai, Xuezhi Wang, Tengyu Ma, Xinyun Chen, and Denny Zhou. 2024. Large language models as tool makers. In *The Twelfth International Conference on Learning Representations (ICLR)*.

Jayeol Chun and Nianwen Xue. 2024. Uniform meaning representation parsing as a pipelined approach. In *Proceedings of TextGraphs-17: Graph-based Methods for Natural Language Processing*, pages 40–52.

A. P. Dawid. 1984. Present position and potential developments: Some personal views: Statistical theory: The prequential approach. *Journal of the Royal Statistical Society. Series A (General)*, 147(2):278.

Allyson Ettinger, Jena Hwang, Valentina Pyatkin, Chandra Bhagavatula, and Yejin Choi. 2023. "you are an expert linguistic annotator": Limits of LLMs as analyzers of abstract meaning representation. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 8250–8263.

Marcio Fonseca and Shay B. Cohen. 2024. Can large language models follow concept annotation guidelines? a case study on scientific and financial domains. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 8027–8042.

João Gama, Raquel Sebastião, and Pedro Pereira Rodrigues. 2013. On evaluating stream learning algorithms. *Machine Learning*, 90(3):317–346.

Fabrizio Gilardi, Meysam Alizadeh, and Maël Kubli. 2023. ChatGPT outperforms crowd workers for text-annotation tasks. *Proceedings of the National Academy of Sciences*, 120(30):e2305016120.

Andrew Halterman and Katherine A. Keith. 2026. Codebook LLMs: Evaluating LLMs as measurement tools for political science concepts. *Political Analysis*, 34(2):188–204.

Xingwei He, Zhenghao Lin, Yeyun Gong, A-Long Jin, Hang Zhang, Chen Lin, Jian Jiao, Siu Ming Yiu, Nan Duan, and Weizhu Chen. 2024. AnnoLLM: Making large language models to be better crowdsourced annotators. In *Proceedings of the 2024 Conference of the North American Chapter of the Association*

for Computational Linguistics: Human Language Technologies (Volume 6: Industry Track), pages 165–190.

Zeyu He, Zhuqian Zhou, Kirk Vanacore, Rene F. Kizilcec, and Ting-Hao 'Kenneth' Huang. 2026. Experts rise where LLMs disagree: Using cross-model disagreement to target expert effort in LLM codebook revision for large-scale annotation. arXiv:2609.26926. *Preprint*, arXiv:2609.26926.

Shengran Hu, Cong Lu, and Jeff Clune. 2025. Automated design of agentic systems. In *The Thirteenth International Conference on Learning Representations (ICLR)*.

Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. 2024. Large language models cannot self-correct reasoning yet. In *The Twelfth International Conference on Learning Representations (ICLR)*.

Shizhou Huang, Bo Xu, Yang Yu, Changqun Li, and Xin Alex Lin. 2025. GuideNER: Annotation guidelines are better than examples for in-context named entity recognition. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 24159–24166.

Ryo Kamoi, Yusen Zhang, Nan Zhang, Jiawei Han, and Rui Zhang. 2024. When can LLMs actually correct their own mistakes? a critical survey of self-correction of LLMs. *Transactions of the Association for Computational Linguistics*, 12:1417–1440.

Omar Khattab, Arnav Singhvi, Paridhi Maheshwari, Zhiyuan Zhang, Keshav Santhanam, Sri Vardhamanan, Saiful Haq, Ashutosh Sharma, Thomas T. Joshi, Hanna Moazam, Heather Miller, Matei Zaharia, and Christopher Potts. 2024. DSPy: Compiling declarative language model calls into state-of-the-art pipelines. In *The Twelfth International Conference on Learning Representations (ICLR)*.

Kon Woo Kim, Rezarta Islamaj, Jin-Dong Kim, Florian Boudin, and Akiko Aizawa. 2025. Repurposing annotation guidelines to instruct LLM annotators: A case study. In *International Conference on Applications of Natural Language to Information Systems (NLDB 2025), Springer LNCS*, pages 140–151.

Kon Woo Kim, Jin-Dong Kim, and Akiko Aizawa. 2026. Refining and reusing annotation guidelines for LLM annotation. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 37951–37964, San Diego, California, United States. Association for Computational Linguistics.

Yoonho Lee, Roshen Nair, Qizheng Zhang, Kangwook Lee, Omar Khattab, and Chelsea Finn. 2026. Meta-harness: End-to-end optimization of model harnesses. arXiv:2603.28052. *Preprint*, arXiv:2603.28052.

Pola Lehmann, Simon Franzmann, Denise Al-Gaddooa, Christoph Ivanusch, Jirka Lewandowski, Felicia Riethmüller, Svenja Samstag, and Lisa Zehnter. 2026. Manifesto corpus. version 2026-1.

Jiahang Lin, Shichun Liu, Chengjun Pan, Lizhi Lin, Shihan Dou, Zhiheng Xi, Xuanjing Huang, Hang Yan, Zhenhua Han, Tao Gui, and Yu-Gang Jiang. 2026a. Agentic harness engineering: Observability-driven automatic evolution of coding-agent harnesses. arXiv:2604.25850. *Preprint*, arXiv:2604.25850.

Minhua Lin, Juncheng Wu, Zijun Wang, Zhan Shi, Yisi Sang, Bing He, Zewen Liu, Tianxin Wei, Zongyu Wu, Zhiwei Zhang, Dakuo Wang, Xiang Zhang, Benoit Dumoulin, Cihang Xie, Yuyin Zhou, Suhang Wang, and Hanqing Lu. 2026b. Harness updating is not harness benefit: Disentangling evolution capabilities in self-evolving LLM agents. arXiv:2605.30621. *Preprint*, arXiv:2605.30621.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. 2023. Self-refine: Iterative refinement with self-feedback. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023)*.

Emma Markle, Javier Gutierrez Bach, and Shira Wein. 2026. SETUP: Sentence-level english-to-uniform meaning representation parser. In *Proceedings of LREC 2026*.

Krista Opsahl-Ong, Michael J Ryan, Josh Purtell, David Broman, Christopher Potts, Matei Zaharia, and Omar Khattab. 2024. Optimizing instructions and demonstrations for multi-stage language model programs. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 9340–9366.

Martha Palmer, Daniel Gildea, and Paul Kingsbury. 2005. The proposition bank: An annotated corpus of semantic roles. *Computational Linguistics*, 31(1):71–106.

Chaoxu Pang, Yixuan Cao, Qiang Ding, and Ping Luo. 2023. Guideline learning for in-context information extraction. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 15372–15389, Singapore. Association for Computational Linguistics.

Reid Pryzant, Dan Iter, Jerry Li, Yin Lee, Chenguang Zhu, and Michael Zeng. 2023. Automatic prompt optimization with "gradient descent" and beam search. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 7957–7968.

James Pustejovsky, José Castaño, Robert Ingria, Roser Saurí, Robert Gaizauskas, Andrea Setzer, Graham Katz, and Dragomir Radev. 2003. TimeML: Robust

specification of event and temporal expressions in text. In *AAAI Spring Symposium 2003 (AAAI Technical Report SS-03-07)*.

Cheng Qian, Chi Han, Yi Fung, Yujia Qin, Zhiyuan Liu, and Heng Ji. 2023. CREATOR: Tool creation for disentangling abstract and concrete reasoning of large language models. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 6922–6939.

Oscar Sainz, Iker García-Ferrero, Rodrigo Agerri, Oier Lopez de Lacalle, German Rigau, and Eneko Agirre. 2024. GoLLIE: Annotation guidelines improve zero-shot information-extraction. In *The Twelfth International Conference on Learning Representations (ICLR)*.

Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023)*.

Prateek Singh. 2026. MAGE: Understanding stability-performance trade-offs in multi-component prompt optimization. arXiv:2607.11944. *Preprint*, arXiv:2607.11944.

Saurabh Srivastava, Sweta Pati, and Ziyu Yao. 2025. Instruction-tuning LLMs for event extraction with annotation guidelines. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 13055–13071.

Haibo Sun, Jayeol Chun, and Nianwen Xue. 2025. AnCast++: Document-level evaluation of graph-based meaning representations. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 19642–19654.

Haibo Sun and Nianwen Xue. 2024. Anchor and broadcast: An efficient concept alignment approach for evaluation of semantic graphs. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 1052–1062, Torino, Italia. ELRA and ICCL.

Haibo Sun, Nianwen Xue, Jin Zhao, Liulu Yue, Yao Sun, Keer Xu, and Jiawei Wu. 2024. Chinese UMR annotation: Can LLMs help? In *Proceedings of the Fifth International Workshop on Designing Meaning Representations @ LREC-COLING 2024*, pages 131–139, Torino, Italia. ELRA and ICCL.

Mirac Suzgun, Mert Yuksekgonul, Federico Bianchi, Dan Jurafsky, and James Zou. 2026. Dynamic cheatsheet: Test-time learning with adaptive memory. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7080–7106.

Zhen Tan, Dawei Li, Song Wang, Alimohammad Beigi, Bohan Jiang, Amrita Bhattacharjee, Mansooreh Karami, Jundong Li, Lu Cheng, and Huan Liu. 2024. Large language models for data annotation and synthesis: A survey. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 930–957.

Naushad UzZaman, Hector Llorens, Leon Derczynski, James Allen, Marc Verhagen, and James Pustejovsky. 2013. SemEval-2013 task 1: TempEval-3: Evaluating time expressions, events, and temporal relations. In *Second Joint Conference on Lexical and Computational Semantics (*SEM), Volume 2: Proceedings of the Seventh International Workshop on Semantic Evaluation (SemEval 2013)*, pages 1–9, Atlanta, Georgia, USA. Association for Computational Linguistics.

Jens E. L. Van Gysel, Meagan Vigus, Jayeol Chun, Kenneth Lai, Sarah Moeller, Jiarui Yao, Tim O'Gorman, Andrew Cowell, William Croft, Chu-Ren Huang, Jan Hajič, James H. Martin, Stephan Oepen, Martha Palmer, James Pustejovsky, Rosa Vallejos, and Nianwen Xue. 2021. Designing a uniform meaning representation for natural language processing. *KI - Künstliche Intelligenz*, 35(3–4):343–360.

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. 2024. Voyager: An open-ended embodied agent with large language models. *Transactions on Machine Learning Research*.

Wenxiao Wang, Priyatham Kattakinda, and Soheil Feizi. 2026. Do agent optimizers compound? a continual-learning evaluation on terminal-bench 2.0. arXiv:2607.14004. *Preprint*, arXiv:2607.14004.

Georg Wölflein, Dyke Ferber, Daniel Truhn, Ognjen Arandjelović, and Jakob Nikolas Kather. 2025. LLM agents making agent tools. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 26092–26130.

Peng Xia, Rujun Han, Zifeng Wang, Yanfei Chen, Yufan Zhuang, Yoonho Lee, Chengsong Huang, Han Yu, Zhongying CuiZhu, Yifei Ming, Huaxiu Yao, Burak Gokturk, Tomas Pfister, and Chen-Yu Lee. 2026. RRSI: Regularized recursive self-improvement of agent harnesses. arXiv:2609.24972. *Preprint*, arXiv:2609.24972.

Chengrun Yang, Xuezhi Wang, Yifeng Lu, Hanxiao Liu, Quoc V. Le, Denny Zhou, and Xinyun Chen. 2024. Large language models as optimizers. In *The Twelfth International Conference on Learning Representations (ICLR)*.

Boqin Yuan, Xiaoyi Gu, Fiona Li, Chang Wan, Angel Hsing-Chi Hwang, and Jieyu Zhao. 2026. CALICO: A human-centered, codebook-aligned system for annotation. arXiv:2609.14726. *Preprint*, arXiv:2609.14726.

Mert Yuksekgonul, Federico Bianchi, Joseph Boen, Sheng Liu, Pan Lu, Zhi Huang, Carlos Guestrin, and James Zou. 2025. Optimizing generative AI by

backpropagating language model feedback. *Nature*, 639(8055):609–616.

Hangfan Zhang, Shao Zhang, Kangcong Li, Chen Zhang, Yang Chen, Yiqun Zhang, Lei Bai, and Shuyue Hu. 2026a. Self-harness: Harnesses that improve themselves. arXiv:2606.09498. *Preprint*, arXiv:2606.09498.

Jenny Zhang, Shengran Hu, Cong Lu, Robert Lange, and Jeff Clune. 2026b. Darwin Gödel machine: Open-ended evolution of self-improving agents. In *The Fourteenth International Conference on Learning Representations (ICLR)*.

Jiayi Zhang, Jinyu Xiang, Zhaoyang Yu, Fengwei Teng, Xionghui Chen, Jiaqi Chen, Mingchen Zhuge, Xin Cheng, Sirui Hong, Jinlin Wang, Bingnan Zheng, Bang Liu, Yuyu Luo, and Chenglin Wu. 2025. AFlow: Automating agentic workflow generation. In *The Thirteenth International Conference on Learning Representations (ICLR)*.

Qizheng Zhang, Changran Hu, Shubhangi Upasani, Boyuan Ma, Fenglu Hong, Vamsidhar Kamanuru, Jay Rainton, Chen Wu, Mengmeng Ji, Hanchen Li, Urmish Thakker, James Zou, and Kunle Olukotun. 2026c. Agentic context engineering: Evolving contexts for self-improving language models. In *The Fourteenth International Conference on Learning Representations (ICLR)*.

Boyuan Zheng, Michael Y. Fatemi, Xiaolong Jin, Zora Zhiruo Wang, Apurva Gandhi, Yueqi Song, Yu Gu, Jayanth Srinivasa, Gaowen Liu, Graham Neubig, and Yu Su. 2025. SkillWeaver: Web agents can self-improve by discovering and honing skills. arXiv:2504.07079. *Preprint*, arXiv:2504.07079.

Yongchao Zhou, Andrei Ioan Muresanu, Ziwen Han, Keiran Paster, Silviu Pitis, Harris Chan, and Jimmy Ba. 2023. Large language models are human-level prompt engineers. In *The Eleventh International Conference on Learning Representations (ICLR)*.

Caleb Ziems, William Held, Omar Shaikh, Jiaao Chen, Zhehao Zhang, and Diyi Yang. 2024. Can large language models transform computational social science? *Computational Linguistics*, 50(1):237–291.

A The Judge

AnCast++ aligns each predicted node to at most one gold node. The judge then scores 25 checks in 11 groups over the aligned graphs; each check yields units with a verdict (correct, partial, wrong, missing, extra) and a credit, and reports F over its units. Three checks never fire on this corpus (granularity, the modal-strength attribute, which is moved to the document level, and Wikipedia links).

Group	Checks
a nodes	`event_found`, `event_concept`, `entity_found`, `entity_concept`, `granularity`
b senses	`event_sense`
c attributes	`aspect`, `modstr`, `polarity`, `refer`, `other_attributes`
d arguments	`core_args_event`, `core_args_abstract`, `peripheral_event`, `peripheral_entity`
e role labels	`core_labels`, `peripheral_labels`
f names	`name_tokens`, `wiki`
g reentrancy	`reentrancy`
h–k document	`temporal`, `modal`, `coref_chain`, `coref_subset`, `doc_format`

Table 5: The judge's checks.

Round	Probl.	D-lvl	Gen.	Crit.	Doc.	Rej.	Proposal
R_{11}	752	187	3	8	6	3	check_umr_graph (rej.)
R_{12}	610	183	18	15	5	4	check_umr_form (rej.)
R_{13}	516	175	31	18	3	0	–
R_{21}	775	254	26	18	4	0	–
R_{22}	693	262	34	24	6	1	–
R_{23}	623	266	14	14	7	0	–
R_{31}	407	114	16	9	4	0	–
R_{32}	314	105	34	27	2	0	–
R_{33}	250	111	17	14	5	1	check_doc_relations (rej.)
R_{41}	780	237	13	11	2	0	–
R_{42}	698	245	24	13	3	2	–
R_{43}	625	231	17	11	3	1	–
R_{51}	463	144	16	12	4	0	–
R_{52}	404	151	25	24	7	1	–
R_{53}	343	117	36	27	4	1	–
R_{61}	440	123	24	18	2	0	–
R_{62}	379	149	20	12	4	1	–
R_{63}	311	122	12	12	3	0	–
R_{71}	692	273	11	7	2	0	–
R_{72}	548	251	11	13	7	0	–
R_{73}	524	256	15	18	5	1	–
R_{81}	132	40	14	7	4	1	–
R_{82}	96	33	17	7	5	0	–
R_{83}	73	28	3	8	5	0	–
R_{91}	109	39	15	9	4	0	–
R_{92}	67	33	12	12	9	1	–
R_{93}	43	29	5	7	7	1	–
R_{101}	188	62	2	7	2	0	–
R_{102}	92	42	12	8	10	0	–
R_{103}	67	36	10	13	9	0	–
R_{111}	258	80	2	3	2	0	–

Table 6: Every improvement round of the sequential run: divergences found (of them document-level), edits applied per skill, edits rejected, and tool or step proposals.

B Records of the Sequential Run

Table 6 lists every round, Table 7 the applied edits by skill and action, Table 8 the per-check scores behind Figure 3, Table 9 what the checking step adds, Table 10 the variant with five checking steps, and Table 11 the matched comparison with the procedural harness.

C Admission of Tools and Steps

Machine checks. A new step must load in the registry, attach after an existing step of the right chain, and keep its instruction prefix constant across calls. A new tool may import only `re`, `json`, `math`, `itertools`, `collections`, `functools`, `unicodedata`, `string` and `penman`;

Skill	Modify	Add	Delete	Total
`generate`	333	176	0	509
`critique`	255	151	0	406
`document`	75	69	1	145
All	663	396	1	1060

Table 7: Applied edits over 31 improvement rounds (19 further edits were rejected: anchor not found, copied document text, or depending on a rejected tool).

Check	Seed	Learned	Δ	Docs ↑
`c_refer`	0.53	0.78	+0.25	5/6
`i_modal`	0.40	0.59	+0.19	9/9
`e_peripheral_labels`	0.67	0.86	+0.18	9/9
`d_core_args_abstract`	0.30	0.43	+0.13	7/9
`d_peripheral_entity`	0.43	0.56	+0.13	8/9
`d_peripheral_event`	0.35	0.47	+0.12	8/9
`a_entity_concept`	0.71	0.82	+0.11	8/9
`h_temporal`	0.29	0.39	+0.09	6/9
`k_doc_format`	0.91	0.98	+0.08	9/9
`g_reentrancy`	0.41	0.48	+0.07	8/9
`j_coref_chain`	0.26	0.32	+0.05	6/9
`f_name_tokens`	0.55	0.59	+0.04	5/9
`a_event_concept`	0.81	0.85	+0.04	6/9
`a_entity_found`	0.92	0.95	+0.03	9/9
`e_core_labels`	0.84	0.87	+0.02	5/9
`a_event_found`	0.95	0.97	+0.02	6/9
`c_other_attributes`	0.70	0.71	+0.02	5/9
`c_aspect`	0.68	0.68	+0.00	6/9
`d_core_args_event`	0.65	0.65	+0.00	5/9
`b_event_sense`	0.90	0.90	+0.00	4/9
`c_polarity`	0.68	0.57	−0.11	3/8

Table 8: Judge score per check on unseen documents, seed vs. learned harness (mean over the paired documents; "Docs ↑" counts documents where the learned harness is higher).

an AST check rejects `open`, `eval`, `exec`, `getattr` and access to underscored attributes, and requires exactly one public function with type annotations and a docstring. The proposal brings at least three tests, run in an isolated subprocess, all of which must pass. Nothing in a proposal may share eight characters with a corpus sentence.

Reviewer. A separate call of the builder model receives the pipeline, the proposal, the machine-check results, the problems it addresses, all problem counts, the judge scores and the current skills. It approves only if all six criteria clearly hold and rejects when in doubt: (1) the problems are many, costly and will recur; (2) an edit to the skill that owns the aspect could not do as well; (3) one narrow responsibility that no skill has, in the right place, not fighting another skill; (4) worth its cost: a step is one more call per sentence and a new chance to break a correct graph, a tool must do

Annotated by	Mean	Docs > 0	Range
Seed H_0	+1.0	8/10	−0.1 to +2.3
Learned, unseen doc.	+0.5	8/10	−0.4 to +1.4
Trained on the doc.	+1.7	10/10	+0.3 to +4.4

Table 9: What the `critique` step adds to the `generate` draft (AnCast++ sentence F, sentence graphs only, before the document layer).

	Doc	Version	`generate`	+5 checks	Δ
trained	0001	R_{13}	65.8	75.0	+9.3
	0002	R_{23}	67.0	75.9	+8.9
unseen	0002	R_{13}	57.3	59.7	+2.4
	0004	R_{13}	49.1	50.0	+0.9
	0005	R_{13}	58.9	57.6	−1.3
	0004	R_{23}	50.4	51.9	+1.5
	0005	R_{23}	58.6	57.5	−1.1

Table 10: A variant with five checking steps after `generate` (concepts, arguments, attributes, entities, reentrancy), improved by the same loop. Sentence F after `generate` and after the five checks, on the document the version was trained on and on documents it had not seen.

what a model cannot do reliably (an exact lookup, a computation, a well-formedness check); (5) correct and safe, consistent with the other skills, with real tests; (6) no leakage.

D Edits, Verbatim

Two edits from the first round on document 0001, as applied (line breaks and some list items omitted). Each was written in general terms; the guard rejects any text sharing eight characters with a corpus sentence.

Added to `critique`, group e (role labels).

```
- AMR labels: ‘:time‘ must be
‘:temporal‘ and ‘:poss‘ must be
‘:possessor‘; - have-org-role-91
numbered the AMR way. In UMR, :ARG1 is
the holder, :ARG2 the organization or
country and :ARG3 the title;
have-rel-role-91 is numbered the same
way. identity-91 has :ARG1 and :ARG2
and no :ARG0. have-org-role-92 and
have-role-91 are wrong;
```

Reason given: P8 (`:poss` vs. `:possessor`), P15, P188, P192, P194, P203–P205, P208, P212–P220, P173, P177, P239.

Replacing a rule of `document`.

```
- an absolute date in the past (a
date-entity with a year: *in 1979*) is
‘document-creation-time‘ ‘before‘ it; a
relative or vague time expression
(*today*, *last week*, *next year*) is
```

Held-out doc	Procedural	Ours	Few-shot
0005	55.7	58.5	TBD
0006	49.5	TBD	TBD
0007	62.0	TBD	TBD

Table 11: Trained on documents 0001–0004 with the same models, tested on 0005–0007, sentence F. The procedural harness (R_{42}) has had 10 rounds (two on each of 0003 and 0004), ours (H_4) 12.

> ‘document-creation-time‘ ‘depends-on‘ it; - an event with an explicit time expression is ‘overlap‘ that expression’s node (the date is the source, the event the target); - between two events, use ‘before‘ or ‘after‘ only when the text marks an order (then, later, as a result). [. . .]
> *Reason given:* P245 (absolute past date → before), P246 (date overlap event), P248 (overlap by default), P250 (no temporal parent for role predicates).

A reversal. R_{13}, `generate`: “A negated event (未经 + a procedure, 从不 V, 没有V) is full-negative, with no :polarity -.” R_{21}, after the first round on 0002: “A negated event (未经 + a procedure, 从不 V, 没有V) is full-negative, together with :polarity -.”

E The Builder’s Suggestions

Each round’s plan may list changes the loop cannot apply. We coded all 130 (file `data/umr/suggestions_coded.csv`) into five codes: *gold* (78): a convention that differs between documents or annotators, or an error in gold, usually with a decision not to learn from it; *rule code* (27): a deterministic change to a rule step, the output handler or a validator; *context* (14): more input to a skill, such as earlier sentences, a running list of coreference chains, or the document’s genre; *evaluator* (10): a change to scoring, for instance normalizing equivalent quantity forms; *other* (1). Examples, verbatim: “Check the gold argument order of but-91 for concessives [. . .] The prompts follow the majority” (gold, round 1); “Make final_graph (or the output handler) normalise attribute values before choosing a graph” (rule code, round 1); “Give the document step a running list of coreference chains for the whole document so far” (context, document 0006); “Have the scorer report AnCast node-matching cascades separately from real concept errors” (evaluator, document 0003). [G13: a second coder and agreement.]

	TIMEX3			EVENT		TLINK
System	strict	relaxed	value	F1	class	F1
HeidelTime (2013)	81.3	90.3	77.6	–	–	–
ClearTK (2013)	82.7	90.2	64.7	77.3	65.4	29.8
TIPSem (2013)	81.6	84.9	65.3	82.9	75.6	42.4
Zero-shot prompt	85.4	92.9	84.6	80.7	65.5	39.8
Few-shot (10 docs)	TBD	TBD	TBD	TBD	TBD	TBD
Seed H_0	81.1	90.2	79.0	74.5	61.9	37.9
Learned harness	TBD	TBD	TBD	TBD	TBD	TBD

Table 12: TempEval-3 platinum test (20 documents), official scorer. 2013 systems rescored from their released outputs (UzZaman et al., 2013); “–”: the system does not produce this layer.

System	Acc.	Macro-F1
Majority class	33.4	6.3
TF-IDF + LR, same 1,200 sentences	42.9	22.9
TF-IDF + LR, 33k sentences	62.5	50.3
ManifestoBERTa*	72.1	59.2
Zero-shot prompt	65.0	56.0
Few-shot, 30 retrieved examples	67.8	58.5
Seed harness H_0	63.8	54.5
Learned harness	TBD	TBD

Table 13: Manifesto coding into eight policy domains, 800 test sentences. *Trained on the Manifesto Corpus, which these sentences come from: a reference, not a fair comparison.

F Other Schemes and Models

TimeML. Test: the 20 TempEval-3 platinum documents with the official scorer (UzZaman et al., 2013); training documents in a fixed order from TimeBank and AQUAINT (TBAQ-cleaned). The harness marks time expressions and events per sentence (`mark`, with a normalization tool for values, then `critique`), then writes TLINKs per document (`link`, `link_critique`, with a link-checking tool). The 2013 systems are rescored from their released outputs with the same scorer, which reproduces their published numbers. Zero-shot: the seed’s instructions and the whole document in one call; few-shot: the same with the ten training documents and their gold as examples.

Manifesto coding. English sentences of electoral programs with one of eight domains of the Manifesto Project coding scheme (dataset `siacus/manifesto` on HuggingFace). The dataset has no document identifiers, so a “document” is a random batch of 120 sentences: ten training batches and one test set of 800 sentences. The harness is `classify` with a codebook lookup tool,

then `critique`. Few-shot uses the 30 training sentences most similar to the input (TF-IDF).

Admission in these runs. Both use machine checks only, without the reviewer, and also allow the builder to rewrite rule code, add or remove steps, and change the registry; a change that fails its checks is dropped.

Qwen3.5-9B. Served with vLLM, thinking on, as both annotator and builder, on the procedural harness, sequentially over documents 0008–0035. Its anchors are often inexact (with strict matching, 1 of its first 15 edits applied), so its runs use fuzzy anchors (a unique line with similarity at least 0.85). Two independent runs of the seed estimate annotation noise.

DeepSeek. The same model annotates and builds, on the procedural harness: two rounds each on documents 0001 and 0004, test on 0002, 0003 and 0005–0007; thinking was off in these runs.