InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	1/29
Document No.		Issue date	2009/05/08	Revision	01

IVO Product Information

To:

Product Name: M236MWF1   R1

Document Issue Date: 2009/05/08

Customer	InfoVision Optoelectronics
SIGNATURE	**SIGNATURE**
	QA
	PREPARED BY FAE
Please return 1 copy for your confirmation with your signature and comments.	

Note: 1. Please contact InforVision Company. Before designing your product based on this product.
   2. The information contained herein is presented merely to indicate the characteristics and performance of our products. No responsibility is assumed by IVO for any intellectual property claims or other problems that may result from application based on the module described herein.

FQ-7-30-0-009-03D

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	2/29
Document No.		Issue date	2009/05/08 Revision	01

Revision	Date	Page	Old Description	New Description	Remark
00	2009/5/4	all		first issued.	
01	2009/5/8	10	Inverter Ignition Voltage 1210　Ta=25[deg C] 1540　Ta=0[deg C]	Inverter Ignition Voltage 1500　Ta=25[deg C] 1900　Ta=0[deg C]	
		15,20	Clock Frequency 57.8	Clock Frequency 63.5	

NO.1 Long Teng Road, KunShan City, JiangSu, China
InfoVision Optoelectronics (Kunshan) Co., LTD

Tel:0512-57278888
Fax:0512-57278900

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	3/29
Document No.		Issue date	2009/05/08	Revision	01

Contents

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 3 of 29

IVO InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	4/29
Document No.		Issue date	2009/05/08	Revision	01

1.0 General Descriptions

1.1 Introduction

The M236MWF1 R1 is a color active matrix thin film transistor (TFT) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching device. It is composed of a TFT LCD panel, a timing controller, voltage reference, common voltage, driver DC-DC converter, column driver, and row driver circuit. This TFT LCD has a 23.6inch diagonally measured active display area with FHD resolution (1920 vertical by 1080 horizontal pixel array).

1.2 Features

- 23.6"FHD TFT LCD Panel
- 2 CCFLs Backlight System
- Supported FHD(V:1920 lines, H:1080pixels) resolution
- Compatible with RoHS Standard

1.3 Product Summary

| Items	Specifications	Unit
Screen Diagonal	23.6	Inch
Active Area	521.28 (H) x 293.22 (V)	mm
Pixels H x V	1, 920(x3) x 1080	
Pixel Pitch	0.2715 (per one triad) x 0.2715	mm
Pixel Arrangement	R.G.B. Vertical Stripe	
Display Mode	Normally White	
White Luminance	180 typical	cd/m^2
Contrast Ratio	500 : 1 typical	
Color Saturation	72%	NTSC
Response Time	5 typical	msec
Input Voltage	+ 5.0 typical	V
Logic Power Consumption	4.5 typical (Black pattern, 60Hz)	Watt
Backlight Power Consumption	12.6 max(CCFL current 7.0mA)	Watt
Weight	2900 typical	g
Outline Dimension	544.8(W) x 320.5(H) x 18.38(T) typical	mm
Electrical Interface (Logic)	6bit+Hi-FRC , dual LVDS	
Support Color	16.7M	
Lamp Life Time	50,000	Hours
Luminance Uniformity	70% min(@9 points)	
Optimum Viewing Direction	6 o'clock	
Surface Treatment	AG/3H	
Screw torque value	5 max	Kgf-cm

Note: Lamp Life Time is 50,000h(Ta=25+/-3degC and ICCFL=7.0mA, brightness becomes lower than 50% of initial value)

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 4 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	5/29
Document No.		Issue date 2009/05/08	Revision	01

1.4 Functional Block Diagram

.

Figure 1 shows the functional block diagram of the LCD module.

Figure 1 Block Diagram

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 5 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	6/29
Document No.		Issue date 2009/05/08	Revision	01

2.0   Absolute Maximum Ratings

Table 1

Item	Symbol	Min	Max	Unit	Conditions
Supply Voltage	VDD	-0.3	+6.0	V	--
Input Signal	--	-0.3	+2.7	V	LVDS signals
Operating Temperature	TOP	0	+50	Deg. C	(Note)
Operating Humidity	HOP	10	80	%RH	(Note)
Storage Temperature	TST	-20	+60	Deg. C	(Note)
Storage Humidity	HST	10	90	%RH	(Note)
Vibration	--	--	1.5 （10-500-10）	G Hz	30min for X, Y, Z axis
Shock	--	--	50 11	G ms	Half sign wave

Note： (1) Storage /Operating temperature. Maximum Wet-Bulb should be 39 degree C.

No condensation.

Figure 2

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	7/29
Document No.		Issue date	2009/05/08	Revision	01

3.0 Pixel Format Image

Figure shows the relationship of the input signals and LCD pixel format image.

Figure 3 Pixel Format

IVO InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	8/29
Document No.		Issue date 2009/05/08	Revision	01

4.0 Optical Characteristics

The optical characteristics are measured under stable conditions as following notes

Table 2 Optical Characteristics

Item	Conditions	Specification			
		Min	Typ	Max	Note
Viewing Angle [degrees] K=Contrast Ratio>10	Horizontal	35	45	--	A, B
		35	45		
	Vertical	10	20	--	
		35	45		
Contrast ratio		350	500	--	A, C
Response Time [ms]	Rising + Falling	--	5	8	A, D
Color Chromaticity (CIE1931)	Red x	-0.03	0.641	+0.03	A,
	Red y		0.335		A,
	Green x		0.280		A,
	Green y		0.599		A,
	Blue x		0.145		A,
	Blue y		0.068		A,
	White x		0.313		A,
	White y		0.329		A,
White Luminance [cd/m^2]	ICCFL=7.0mA	150	180	--	Center A, E
Luminance Uniformity	ICCFL=7.0mA, 9points	70%	--	--	A, F

Note:

A. Measurement Setup:

The LCD module should be stabilized at given temperature for 20 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting backlight for 20 minutes in a windless room.

Figure 4 Measurement Setup

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 8 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	9/29
Document No.		Issue date	2009/05/08 Revision	01

B. Definition of Viewing Angle

Figure 5 Definition of Viewing Angle

C. Definition of Contrast Ratio (CR)

The contrast ratio can be calculated by the following expression

Contrast Ratio (CR) = L255 / L0

L255: Luminance of gray level 255,

L0: Luminance of gray level 0

D. Definition of Response Time (T_R, T_F)

Figure 6 Definition of Response Time

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 9 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

| Document Title	M236MWF1 Product Specification		Page No.	10/29
Document No.		Issue date	2009/05/08	Revision	01

E. Definition of Luminance White

Measure the luminance of gray level 255 at center point

F. Definition of Luminance Uniformity(Variation)

Measure the luminance of gray level 255 at 9 points.

$$\text{UNF(9pts)} = \frac{\min(L1, L2, \cdots L9)}{\max(L1, L2, \cdots L9)}$$

Figure 7 Measurement Locations of 9 Points

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 10 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	11/29
Document No.		Issue date 2009/05/08	Revision	01

5.0 Backlight Characteristics

5.1 CCFL Connector

Table 3 Connector Name / Designation

Manufacturer	Yeonho
Type / Part Number	35001HS-02L

Table 4 Signal Assignment

Pin #	Signal Name
1	Lamp High Voltage
2	Lamp Low Voltage

5.2 Parameter Guideline for CCFL Inverter

Table 5 Parameter Guideline For CCFL Inverter

Symbol	Parameter	Min	Design Point	Max	Units	Condition
ICCFL	CCFL current	3	7.0	8	[mA]	Ta=25[deg C] **(Note A)**
FCCFL	CCFL Frequency	40	--	80	[kHz]	Ta=25[deg C] **(Note B)**
VCCFLi	Inverter Ignition Voltage	1500	--	--	[Vrms]	Ta=25[deg C] **(Note C)**
		1900	--	--	[Vrms]	Ta=0[deg C] **(Note C)**
VCCFL	CCFL Voltage	792	880	968	[Vrms]	@ ICCFL=7.0mA Ta=25[deg C]

Note:

A. If it exceeds MIN/MAX values, then "CCFL Life", "ON/OFF Cycle", and "SAFETY" will not be guaranteed.

B. CCFL Frequency should be carefully determined to avoid interference between inverter and TFT LCD.

C. The voltage over specified value (VCCFLi) should be applied to the lamp more than 1 second after startup. Otherwise, the lamp may not be turned on. The used lamp current is the lamp typical current. The inverter should be able to give out a power that has a generating capacity of over 1900 voltage.Lamp units need to over 1900 voltage for ignition.

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 11 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

| Document Title	M236MWF1 Product Specification		Page No.	12/29
Document No.		Issue date	2009/05/08	Revision	01

D. The distortion tae of the waveform should be within $\sqrt{2}\pm10\%$

The inverter output waveform should be better similar to the ideal sine wave.

Asymmetry rate = $|I_p-I_{-p}|$ / I_{rms} x 100%

Distortion rate = I_p (or I_{-p}) / I_{rms}

Figure 8 Recommendation of Lighting Waveform

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 12 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	13/29
Document No.		Issue date 2009/05/08	Revision	01

6.0 Electrical Characteristics

6.1 Interface Connector

Table 6 Connector Name / Designation

Manufacturer	JAE (or equivalent)
Type / Part Number	UJU IS100-L30B-C23
Mating Receptacle/Part Number	JAE FI-X30H(L), JAE FI-X30C*(L), JAE FI-X30M*

Table 7 Signal Pin Assignment

Pin #	Signal Name	Description	Remarks
1	RXinO0-	LVDS differential data input	
2	RXinO0+	LVDS differential data input	
3	RXinO1-	LVDS differential data input	
4	RXinO1+	LVDS differential data input	
5	RXinO2-	LVDS differential data input	
6	RXinO2+	LVDS differential data input	
7	GND	Ground	
8	RXOC-	LVDS differential data input	
9	RXOC+	LVDS differential data input	
10	RXinO3-	LVDS differential data input	
11	RXinO3+	LVDS differential data input	
12	RXinE0-	LVDS differential data input	
13	RXinE0+	LVDS differential data input	
14	GND	Ground	
15	RXinE1-	LVDS differential data input	
16	RXinE1+	LVDS differential data input	
17	GND	Ground	
18	RXinE2-	LVDS differential data input	
19	RXinE2+	LVDS differential data input	
20	RXEC-	LVDS differential data input	
21	RXEC+	LVDS differential data input	
22	RXinE3-	LVDS differential data input	
23	RXinE3+	LVDS differential data input	
24	GND	Ground	
25	GND	Ground	
26	NC	Reserved for LCD manufacturer.	
27	GND	Ground	
28	VDD	Power Supply	

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 13 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	14/29
Document No.		Issue date	2009/05/08	Revision	01

29	VDD	Power Supply	
30	VDD	Power Supply	

All input signals shall be low or Hi-Z state when VDD is off.

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification			Page No.	15/29
Document No.		Issue date	2009/05/08	Revision	01

6.2 LVDS Receiver

6.2.1 Signal Electrical Characteristics for LVDS Receiver

The built-in LVDS receiver is compatible with ANSI/TIA/TIA-644 standard.

Table 8 LVDS Receiver Electrical Characteristics

Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Differential Input High Threshold	Vth	--	--	+100	mV	Vcm=+1.2V
Differential Input Low Threshold	Vtl	-100	--	--	mV	Vcm=+1.2V
Magnitude Differential Input Voltage	|Vid|	100	--	600	mV	--
Common Mode Voltage	Vcm	1.0	1.2	1.4	V	Vth - Vtl = 200mV
Common Mode Voltage Offset	ΔVcm	-50	--	+50	mV	Vth - Vtl = 200mV

Note:

A. Input signals shall be low or Hi-Z state when VDD is off.

B. All electrical characteristics for LVDS signal are defined and shall be measured at the interface connector of LCD.

Table 9 Timing Requirements

Parameter	Symbol	Min	Typ	Max	Unit	Conditions	Note
Clock Frequency	Fc	63.5	73.3	96.7	MHz	--	--
Input Data Skew Margin	Trskm	-850	--	+850	ps	Fc=73.26MHz, |Vth-Vtl| = 400mV Vcm = 1.2V, ΔVcm = 0	(Figure 9)

Note: All values are at VDD=5.0V, Ta=25 degree C.

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 15 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	16/29
Document No.		Issue date	2009/05/08	Revision	01

Figure 9 Voltage Definitions

Figure 10 Measurement System

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	17/29
Document No.		Issue date	2009/05/08	Revision	01

Figure 3 Data Mapping

RX(O/E)C										
RXinO0			OG0	OR5	OR4	OR3	OR2	OR1	OR0	
RXinO1			OB1	OB0	OG5	OG4	OG3	OG2	OG1	
RXinO2			DE	VS	HS	OB5	OB4	OB3	OB2	
RXinO3			RSVD	OB7	OB6	OG7	OG6	OR7	OR6	
RXinE0			EG0	ER5	ER4	ER3	ER2	ER1	ER0	
RXinE1			EB1	EB0	EG5	EG4	EG3	EG2	EG1	
RXinE2			DE	VS	HS	EB5	EB4	EB3	EB2	
RXinE3			RSVD	EB7	EB6	EG7	EG6	ER7	ER6	

Current cycle

InfoVision Optoelectronics (Kunshan) Co.,LTD.

| Document Title	M236MWF1 Product Specification		Page No.	18/29
Document No.		Issue date	2009/05/08	Revision	01

Figure 12 Timing Definition

Detail A

Note: Tsu and Thd is internal data sampling window of receiver. Trskm is the system skew margin; i.e., the sum of cable skew, source clock jitter, and other inter-symbol interference, shall be less than Trskm.

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 18 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	19/29
Document No.		Issue date	2009/05/08	Revision	01

6.2.2 LVDS Receiver Internal Circuit

Figure 4 LVDS Receiver Internal Circuit shows the internal block diagram of the LVDS receiver. This LCD module equips termination resistors for LVDS link.

Figure 4 LVDS Receiver Internal Circuit

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 19 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	20/29
Document No.		Issue date	2009/05/08	Revision	01

7.0 Interface Timings

7.1 Timing Characteristics

Table 10 Interface Timings

Parameter	Symbol	Unit	min	Typ	Max
LVDS Clock Frequency(dual)	Fdck	MHz	63.5	73.3	96.7
H Total Time	Htotal	clocks	1050	1100	1150
H Active Time	Hac	clocks	960	960	960
V Total Time	Vtotal	lines	1100	1110	1121
V Active Time	Vac	lines	1080	1080	1080
Frame Rate	Vsync	Hz	55	60	75

Figure 14 Timing Characteristics

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	21/29
Document No.		Issue date 2009/05/08	Revision	01

8.0 Power Consumption

Input power specifications are as follows.

Table 11 Power Consumption

Symbol L	Parameter	Min	Typ	Max	Units	Condition
VDD	Logic/LCD Drive Voltage	4.5	5.0	5.5	[V]	
IDD	VDD Current	--	0.85	1.02	[A]	All black pattern, 60Hz
		--	0.9	1.08	[A]	Max pattern, 60Hz
PDD	VDD Power	--	4.5	--	[W]	All black pattern, 60Hz
Irush	Rush Current	--	--	2.5	[A]	VDD rise time over 0.5ms. Oscilloscope Sampling over 2ms
VDDrp	Allowable Logic/ LCD Drive Ripple Voltage	--	--	300	[mVp-p]	

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 21 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	22/29
Document No.		Issue date 2009/05/08	Revision	01

9.0 Power ON/OFF sequence

VDD power, interface signals, and lamp on/off sequence are shown in
Figure .Signals shall be Hi-Z state or low level when VDD is off.

Figure 15 Power Sequence

Table 12 Power Sequencing Requirements

Parameter	Symbol	Unit	Min	Typ	Max
VDD Rise Time	T1	ms	0.5	--	10
VDD Good to Signal Valid	T2	ms	0	--	50
Signal Valid to Backlight On	T3	ms	200	--	--
Backlight Off to Signal Disable	T4	ms	90	--	--
Signal Disable to Power Down	T5	ms	0	--	50
VDD Fall Time	T6	ms	0	--	100
Power Off	T7	ms	500	--	--

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	23/29
Document No.		Issue date	2009/05/08	Revision	01

10.0 Mechanical Characteristics

Figure 16 Reference Outline Drawing (Front side)

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	24/29
Document No.		Issue date	2009/05/08	Revision	01

Figure 17 Reference Outline Drawing (Back side)

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 24 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	25/29
Document No.		Issue date	2009/05/08	Revision	01

10.1 Dimension Specification

Table 13 Module Dimension Specifications

Width [mm]			544.8 ± 0.5
Height [mm]			320.5 ± 0.5
Thickness [mm]			18.38± 0.5
Bezel Opening [mm]		X	525.22± 0.5
		Y	297.22± 0.5
Mounting Hole [mm]		UR	65.25±0.3
		LR	65.25±0.3
		UL	36.25±0.3
		LL	36.25±0.3
Connector position from screen center [mm]		X	148.6±5
		Y	272±5
CCFL harness length [mm]			170± 10
Weight [g]			2850 typ, 2900 max
BM : │a-b│ & │c-d│			≤1.0 mm

Figure 18

Active

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	26/29
Document No.		Issue date 2009/05/08	Revision	01

11.0 Package Specification.

Figure 19

InfoVision Optoelectronics (Kunshan) Co.,LTD.

12.0 Lot Mark.

12.1 Lot Mark

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20

code 1,2,3,6,7,8,9,10,11: IVO internal flow control code.
code 5: production location.
code 12: production year.
code 13: production month.
code 16,17,18,19,20: serial number.

Note (1) Production Year

Year	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015
Mark	6	7	8	9	A	B	C	D	F	G

Note (2) Production Month

Month	Jan.	Feb.	Mar.	Apr.	May.	Jun.	Jul.	Aug.	Sep.	Oct	Nov.	Dec.
Mark	1	2	3	4	5	6	7	8	9	A	B	C

12.2 23 product barcode

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23

code 1,2: MD Mindtech Display.
code 3,4,5,6,7: IVO internal module name.
code 8,9,10,13,16: IVO internal flow control code.
code 11,12: Cell location Suzhou defined as "SZ".
code 14 ,15: Module line kunshan defined as" KS".
code 17,18,19 : Year, Month, Day Refer to MTDis barcode Note(1),Note(2).
code 20~23 : Serial Number.

NO.1 Long Teng Road, KunShan City, JiangSu, China
InfoVision Optoelectronics (Kunshan) Co., LTD

Tel:0512-57278888
Fax:0512-57278900

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	28/29
Document No.		Issue date	2009/05/08	Revision	01

13.0   General Precaution

13.1 Use Restriction

This product is not authorized for use in life supporting systems, aircraft navigation control systems, military systems and any other application where performance failure could be life-threatening or otherwise catastrophic.

13.2   Disassembling or Modification

Do not disassemble or modify the module. It may damage sensitive parts inside LCD module, and may cause scratches or dust on the display. MTD does not warrant the module, if customers disassemble or modify the module.

13.3   Breakage of LCD Panel

13.3.1 If LCD panel is broken and liquid crystal spills out, do not ingest or inhale liquid Crystal, and do not contact liquid crystal with skin.

13.3.2 If liquid crystal contacts mouth or eyes, rinse out with water immediately.

13.3.3 If liquid crystal contacts skin or cloths, wash it off immediately with alcohol and Rinse thoroughly with water.

13.3.4 Handle carefully with chips of glass that may cause injury, when the glass is Broken

13.4   Electric Shock

13.4.1 Disconnect power supply before handling LCD module.

13.4.2 Do not pull or fold the CCFL cable.

13.4.3 Do not touch the parts inside LCD modules and the fluorescent lamp's connector

Or cables in order to prevent electric shock

13.5 Absolute Maximum Ratings and Power Protection Circuit

13.5.1 Do not exceed the absolute maximum rating values, such as the supply voltage variation, input voltage variation, variation in parts' parameters, environmental temperature; etc otherwise LCD module may be damaged.

13.5.2 Please do not leave LCD module in the environment of high humidity and high temperature for a long time.

13.5.3 It's recommended employing protection circuit for power supply.

13.6 Operation

13.6.1 Do not touch, push or rub the polarizer with anything harder than HB pencil lead.

Use fingerstalls of soft gloves in order to keep clean display quality, when Persons handle the LCD module for incoming inspection or assembly.

13.6.2 When the surface is dusty, please wipe gently with absorbent cotton or other soft

Material

13.6.3 Wipe off saliva or water drops as soon as possible. If saliva or water drops Contact with polarizer for a long time, they may causes deformation or color Fading

13.6.4 When cleaning the adhesives, please use absorbent cotton wetted with a little Petroleum benzene or other adequate solvent

13.7 Mechanism

Please mount LCD module by using mounting holes arranged in four corners tightly.

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 28 of 29

InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M236MWF1 Product Specification		Page No.	29/29
Document No.		Issue date	2009/05/08	Revision	01

13.8 Static Electricity

13.8.1 Protection film must remove very slowly from the surface of LCD module to Prevent from electrostatic occurrence.

13.8.2 Because LCD module uses CMOS-IC on circuit board and TFT-LCD panel, it is Very weak to electrostatic discharge, Please be careful with electrostatic Discharge

13.8.3 Persons who handle the module should be grounded through adequate methods.

13.9 Strong Light Exposure

The module shall not be exposed under strong light such as direct sunlight. Otherwise, Display characteristics may be changed.

13.10 Disposal

When disposing LCD module, obey the local environmental regulations.

NO.1 Long Teng Road, KunShan City, JiangSu, China   Tel:0512-57278888
InfoVision Optoelectronics (Kunshan) Co., LTD   Fax:0512-57278900

Page 29 of 29