

APRIL 4, 2023 / #PENETRATION TESTING

# Google Dorking for Penetration Testers — A Practical Tutorial



Manish Shivanandhan



Every day, Google processes over 8.5 billion searches. We know how much we use Google daily.

With the crawling capabilities of Google, it can also be a powerful tool for pen testers. Google can help us find exposed files, scripts and other critical resources in web applications.

Google Dorks are special search terms that help locate information which is not found through regular web searches.

In this article, we will look at what Google Dorks are and how they can help us in penetration testing.

# What are Google Dorks?

A Google Dork is a special search term. These terms, when used with regular search keywords, can help us discover hidden resources crawled by Google.

These resources include sensitive information such as usernames, passwords, credit card numbers, email addresses, shell scripts, user accounts, and so on.

These Dorks are not limited to Google. We can also use them with search engines like Bing and Yahoo. The results might vary, but they still serve the same purpose.

To harness the full potential of Google Dorking, we'll need to master some specialized search operators. These operators will fine-tune our search results and help us find exactly what we are looking for.


Let's try a few Google dorks.

## Common Google Dorks

Some of the common query operators in Google Dorking include search modifiers. These search modifiers allow us to find specific information that may not be accessible through traditional search methods.

# Intitle operator

The “**intitle**” operator searches for web pages with specific words or phrases in the title tag. For instance, if you’re looking for pages that contain the phrase “password” and have “index of” in the title, you would use the search term: `intitle:"index of" password`.




In title. Image by the author.

# Inurl operator

The “**inurl**” operator searches for web pages that contain specific words or phrases in the URL. For example, if you’re looking for pages that contain “admin.php” in the URL, you would use the search term: `inurl:admin.php`.

## Learn to code — free 3,000-hour curriculum




In url. Image by the author.

## Site operator

The “**site**” operator allows you to search within a specific website or domain. For instance, if you’re looking for pages on the example.com domain that contain the word “Steganography”, you would use the search term: `site:yeahhub.com “Steganography”`


Learn to code — free 3,000-hour curriculum



In site. Image by the author.

## Filetype operator

The “**filetype**” operator allows you to search for specific file types, such as PDFs or Word documents. For example, if you’re looking for PDF files that contain the phrase “confidential report”, you would use the search term: `filetype:pdf "Advanced Network Security"`




Filetype. Image by the author.

Learn to code — free 3,000-hour curriculum

## intext operator

The “**intext**” operator searches for pages that contain specific words or phrases within the body of the page. For instance, if you’re looking for pages that contain both the words “login” and “password” within the body of the page, you would use the search term: `intext:"about" contact`.




In text. Image by the author.

## Link operator

The “**link**” operator searches for web pages that link to a specific URL. For example, if you’re looking for web pages that link to the example.com domain, you would use the search term: `link:"example.com"`

Learn to code — free 3,000-hour curriculum



Link operator. Image by the author.

## Cache operator

The “cache” operator is used to retrieve the cached version of a web page. When you search for a website using Google, Google creates a cached version of that page in its system. This version can be useful if the original website is temporarily down or if you want to view an older version of the website.

Here is the syntax to find the cached version of  
yahoo.com.cache:https://www.yahoo.com



Learn to code — free 3,000-hour curriculum

LIVE UPDATES:  
Trump to surrender for arraignment on criminal charges in NYC

Top stories




Cached version of yahoo.com. Image by author.

## Related operator

The “related” operator is used to find web pages that are related to a specific URL. Here is the syntax to use the “related” operator to find sites similar to yahoo.com.



## Learn to code — free 3,000-hour curriculum



Related operator. Image by author.

By combining these operators in creative ways, you can find specific types of information on the web that can be useful for penetration testing and other purposes.

# Structure of Query Operators

Google Dorking query operators have a structure similar to regular Google search query operators. This technique involves using advanced operators and search queries to uncover information that is not typically available through regular searches.

The general structure of query operators in Google Dorking includes three elements:

1. **Operator:** A specific keyword or symbol that instructs Google what to search for. For instance, the “**inurl**” operator searches for pages that contain a particular keyword in their URL.

3. **Modifier:** An additional search parameter that you can use to further refine your search. For example, the “**filetype**” modifier searches for a specific file type, such as a PDF.

Here’s an example of a query operator structure in Google Dorking: `intitle: “index of” site:example.com password filetype:pdf`

This query uses the “**intitle**” operator to search for pages with “index of” in their title, the “**site**” operator to search within the `example.com` domain, the keyword “password,” and the “**filetype**” modifier to search for PDF files.

By utilizing query operators in Google Dorking, we can find useful and often vulnerable information that might not be accessible through regular searches.

# Google Hacking Database (GHDB)

The Google Hacking Database (GHDB) is a compilation of search queries and query operators that help us in Google Dorking.

## Learn to code — free 3,000-hour curriculum

2023-03-29	BroadBand Device Webserver	Files Containing Juicy Info	Shx
2023-03-29	allintitle:"ResolutionMD Login"	Pages Containing Login Portals	Heverin Hacker
2023-03-29	intitle:"index of "application.yml"	Files Containing Juicy Info	Suman Das
2023-03-29	intitle:"index of "conf.json"	Files Containing Juicy Info	Suman Das
2023-03-29	allintitle:"Synapse Mobility Login"	Pages Containing Login Portals	Heverin Hacker
2023-03-29	intitle:index of django/admin site:.*	Files Containing Juicy Info	Md rofikul
2023-03-29	allintitle:"MobileIron User Portal: Sign In"	Pages Containing Login Portals	Heverin Hacker
2023-03-24	inurl:adminpanel site:.in	Pages Containing Login Portals	Md rofikul
2023-03-24	allintitle:"VidyoRouter Configuration"	Files Containing Juicy Info	Heverin Hacker
2023-03-21	intitle:"index of" site:.bd	Files Containing Juicy Info	Soriful Islam
2023-03-21	intitle:"index of" inurl:admin/php	Files Containing Juicy Info	Md Hasib
2023-03-16	inurl:ssh intitle:index of /files	Files Containing Juicy Info	PRINCY M JOSE
2023-03-16	inurl:guest/auth_login.php	Pages Containing Login Portals	Javier Bernardo
2023-03-16	inurl:login/login	Files Containing Juicy Info	Javier Bernardo

Showing 1 to 15 of 7,632 entries

FIRST PREVIOUS 1 2 3 4 5 ... 509 NEXT LAST

Google hacking database. Image generated by author.

Johnny Long, a well-known security researcher and author, established the GHDB. It has since become a valuable resource for security engineers like you and me.

The GHDB has several search queries and operators that can uncover numerous sensitive files, vulnerable web servers, and applications. It can also discover default login pages and credentials, as well as network and security devices that may be prone to attack.

GHDB is arranged into categories such as “Files containing passwords” “Vulnerable servers” “Footholds” and “Error Messages”. Each category contains several search queries and operators crafted to reveal specific information about a target.

Please note that search queries and operators in the GHDB might produce false positives or outdated information. Always verify the information obtained through these search operators.

## A Dorking Scenario

Let’s assume you have to conduct a pentesting audit for a client. Here is a sample dorking scenario.