A Survey on Energy-Efficient and Sustainable Large Language Models for Edge and Resource-Constrained Environments

Abstract

Large Language Models (LLMs) have achieved remarkable performance across various natural language processing tasks. However, their growing size and computational demands raise serious concerns regarding energy consumption, deployment cost, and environmental impact. This survey reviews recent research focused on improving the efficiency and sustainability of language models, particularly for edge and resource-constrained environments. The analyzed works explore techniques such as model compression, quantization, pruning, adaptive training strategies, hardware acceleration, and energy-aware benchmarking. Overall, the findings show that significant reductions in energy usage and latency can be achieved without substantial loss in performance. However, trade-offs between efficiency, accuracy, and scalability remain a key challenge. This survey highlights current progress, identifies research gaps, and outlines future directions toward developing sustainable and resource-efficient language modeling systems.

Index Terms

Large Language Models, Energy Efficiency, Model Compression, Quantization, Edge Computing, Sustainable AI, Hardware Acceleration, Green AI.

CONTENTS

I Introduction 2

II Methods and Approaches in the Sources 2
- II-A Model Compression and Quantization . . . 2
- II-B Architectural Innovation and Context Management . . . 2
- II-C Adaptive Training and Fine-Tuning . . . 2
- II-D Hardware-Aware Optimization and Acceleration . . . 3
- II-E Benchmarking and Environmental Impact Assessment . . . 3

III Findings and Comparative Analysis 3
- III-A Summary of Optimization Strategies . . . 3
- III-B Quantitative Performance Metrics . . . 3

IV Technical and Algorithmic Discussion 4
- IV-A Complexity Reduction in Attention Mechanisms . . . 4
- IV-B Mathematical Foundations of Quantization . . . 4
- IV-C Optimization through Sparsity . . . 4
- IV-D Adaptive Backpropagation and Fine-Tuning . . . 4
- IV-E Knowledge Distillation for Model Shrinkage . . . 5
- IV-F Retrieval-Augmented Generation (RAG) at the Edge . . . 5

V Limitations of the Evidence 5

VI Research Gaps and Future Directions 5

VII Conclusion 5

References 6

I. Introduction

The rapid proliferation of Large Language Models (LLMs) has transformed the field of natural language processing, enabling capabilities that range from sophisticated text generation to complex reasoning. Models like GPT-4, Llama, and PaLM have demonstrated unprecedented performance in diverse domains. However, the sheer scale of these models, often comprising hundreds of billions of parameters, presents a significant challenge for deployment. The computational power required for both training and inference is immense, leading to substantial energy consumption and a significant environmental footprint.

The concept of "Green AI" has emerged as a critical research direction, focusing on making AI systems more sustainable and energy-efficient. This is particularly vital for edge and resource-constrained environments, such as mobile devices, Internet of Things (IoT) sensors, and embedded systems. These environments typically lack the massive computational resources, high-speed memory, and stable power supplies available in centralized data centers. Consequently, deploying LLMs at the edge requires innovative strategies to reduce their resource demands while maintaining acceptable levels of performance.

This survey provides a comprehensive review of recent advancements in energy-efficient LLMs. We categorize and analyze various optimization techniques, ranging from model-level compression (quantization, pruning) to training-level adaptations (adaptive backpropagation) and hardware-level accelerations. We also examine the emerging field of sustainability benchmarking, which aims to provide standardized metrics for evaluating the environmental impact of AI models. By synthesizing the findings from several key research works, this paper identifies current trends, highlights existing limitations, and proposes future directions for achieving sustainable and resource-aware language modeling.

II. Methods and Approaches in the Sources

The research analyzed in this survey employs a variety of methodologies to tackle the challenges of energy efficiency in LLMs. These can be broadly classified into the following categories:

A. Model Compression and Quantization

Quantization is a fundamental technique used to reduce the memory footprint and computational requirements of LLMs. By representing model weights and activations with lower-precision numerical formats (e.g., 4-bit or 8-bit integers instead of 32-bit floating-point numbers), significant reductions in size can be achieved. For instance, Erik Johannes Husom et al. [2] evaluated 28 quantized LLMs on a Raspberry Pi 4, demonstrating the feasibility of running these models on low-power hardware. Similarly, S. Pujari et al. [3] utilized sparse ternary quantization, which restricts weights to just three values (-1, 0, +1), achieving a 5.8× reduction in model size. This method significantly reduces memory and multiplication cost.

B. Architectural Innovation and Context Management

Efficient architectural designs are crucial for edge deployment. The Dolphin framework, proposed by Wei Chen et al. [1], addresses the quadratic complexity of long-context processing in transformers. It introduces a dual-decoder mechanism that separates context compression from generation. A lightweight model compresses long context into compact memory tokens before passing them to a larger decoder for response generation. This results in a 10× improvement in energy efficiency and 5× faster inference. Other works, such as the Super Tiny Language Models (STLMs) by R. Hillier et al. [7], focus on extreme parameter reduction through architectural simplifications to create models that can operate on devices with highly limited storage and processing power.

C. Adaptive Training and Fine-Tuning

To reduce the environmental cost of the training phase, researchers have proposed adaptive mechanisms. M. Huang et al. [5] introduced adaptive backpropagation, which selectively updates only the most significant parameters during fine-tuning. This approach minimizes unnecessary gradient computations and lowers GPU utilization, thereby reducing the energy consumption and training cost without significantly affecting model performance.

TABLE I
COMPARATIVE ANALYSIS OF ENERGY-EFFICIENT LLM RESEARCH

Ref	Main Focus	Technique	Advantages	Drawbacks
[1]	Long-context edge efficiency	Dual-decoder mechanism	10× energy improvement	High training complexity
[2]	Edge LLM sustainability	Low-bit quantization (INT8/4)	Real-world edge evaluation	Hardware-specific results
[3]	TinyML for edge devices	Sparse ternary quantization	5.8× size reduction	Accuracy loss in complex tasks
[4]	Sustainability metrics	Compression & Benchmarking	Balanced trade-off analysis	No architectural novelty
[5]	Green AI fine-tuning	Adaptive backpropagation	Reduced GPU training cost	Requires parameter tuning
[6]	Scaling and efficiency	Pruning and acceleration	Improved scalability	Limited hardware focus
[7]	Ultra-compact models	Architectural simplification	Extremely low memory footprint	Limited reasoning capability
[8]	Hardware acceleration	FPGA/ASIC/GPU survey	High throughput/efficiency	High development cost
[9]	Multi-agent RAG for edge	Pruning and vLLM	Efficient edge retrieval	Coordination complexity
[10]	Sustainability benchmarking	SLM-Bench framework	Environmental transparency	Hardware-dependent metrics

D. Hardware-Aware Optimization and Acceleration

The synergy between software and hardware is a key driver of efficiency. C. Kachris [8] analyzed the role of specialized hardware accelerators, including GPUs, TPUs, FPGAs, and ASICs, which are designed to handle the high computational and memory demands of LLMs more efficiently than general-purpose CPUs. Parallel matrix multiplication and systolic array computation are core technologies used in these accelerators. Furthermore, hardware-aware optimization techniques ensure that model architectures are tailored to the specific constraints of the target deployment platform, such as the memory bandwidth and cache sizes of microcontrollers [3].

E. Benchmarking and Environmental Impact Assessment

Standardized evaluation is essential for progress in Green AI. T. Pham et al. [10] developed the SLM-Bench framework, which goes beyond traditional performance metrics (like accuracy) to measure energy consumption and carbon emissions. This allows for a transparent comparison of the environmental impact of different models and optimization strategies, assessment across diverse hardware platforms, and lifecycle-based carbon assessment methodologies.

III. FINDINGS AND COMPARATIVE ANALYSIS

The comparative evaluation of the surveyed works reveals significant progress in achieving energy-aware AI. This section provides a detailed analysis based on system-level and performance-centric metrics.

A. Summary of Optimization Strategies

Table I provides a high-level summary of the core focus, techniques, and trade-offs identified in the literature.

B. Quantitative Performance Metrics

The impact of these optimization techniques on energy consumption, latency, and throughput is summarized in Table II.

The findings indicate that:

- **Energy Efficiency:** Significant reductions in energy usage, often exceeding 10× [1], can be achieved through specialized architectures and quantization.
- **Latency:** Model compression and pruning significantly reduce inference latency, making real-time applications feasible on edge devices [1, 6, 7].
- **Trade-offs:** While efficiency is improved, there is often a trade-off with model accuracy, particularly for complex reasoning tasks [3, 7].

TABLE II
COMPARISON OF ENERGY AND PERFORMANCE METRICS

Ref	Approach	Energy Usage	Inference Latency	Throughput
[1]	Dolphin	Very Low	Very Low	High
[2]	Quantized LLMs	Low	Moderate	Moderate
[3]	TinyML Sparse SLM	Very Low	Low	Moderate
[4]	Optimization Study	Reduced	Improved	Improved
[5]	Adaptive Backprop	Reduced	Reduced	N/A
[6]	Pruned Large LMs	Reduced	Low	High
[7]	Super Tiny LMs	Extremely Low	Very Low	Moderate
[8]	Hardware Accel.	Optimized	Very Low	Very High
[9]	Multi-Agent RAG	Low	Low	High
[10]	SLM-Bench	Varies	Varies	Varies

IV. TECHNICAL AND ALGORITHMIC DISCUSSION

The effectiveness of the surveyed approaches stems from their underlying mathematical and algorithmic innovations.

A. Complexity Reduction in Attention Mechanisms

The standard self-attention mechanism in transformers has a quadratic complexity of $O(n^2)$ relative to the sequence length n. The Dolphin framework [1] utilizes a context compression function $C(x) \to m$ that reduces the number of effective tokens, effectively lowering the computational burden of processing long contexts.

B. Mathematical Foundations of Quantization

Quantization maps high-precision values to a discrete set of low-precision levels. The uniform quantization function $Q(x)$ is typically expressed as:

$$Q(x) = \text{round}(x/s) \cdot s \tag{1}$$

where $Q(x)$ is the quantized value, x is the original floating-point weight, and s is the scaling factor. In sparse ternary quantization [3], weights w are restricted to the set:

$$w \in \{-1, 0, +1\} \tag{2}$$

This restriction eliminates the need for complex floating-point multiplications, replacing them with simple additions and shifts.

C. Optimization through Sparsity

Sparsity is achieved by penalizing non-zero weights during training using L1 regularization:

$$L = L_0 + \lambda ||W||_1 \tag{3}$$

where L_0 is the task-specific loss and λ is the regularization coefficient that promotes sparsity (sum of absolute weights). This allows for the pruning of insignificant connections, reducing both memory usage and FLOPs.

D. Adaptive Backpropagation and Fine-Tuning

In the fine-tuning phase, adaptive backpropagation [5] modifies the gradient update step:

$$\theta_{t+1} = \theta_t - \eta \cdot g_{\text{selected}} \tag{4}$$

where θ represents model parameters, η is the learning rate, and g_{selected} denotes the gradients for selected important parameters. This selectively updates parameters, reducing computational overhead and GPU utilization during the adaptation of large models.

E. Knowledge Distillation for Model Shrinkage

Knowledge distillation [7] trains a small "student" model to mimic the behavior of a large "teacher" model. The objective function combines the cross-entropy loss with a distillation loss:

$$L = \alpha L_{\text{CE}} + \beta L_{\text{KD}} \tag{5}$$

where L_{CE} is cross-entropy loss and L_{KD} is knowledge distillation loss, with α and β as balancing coefficients. This allows the student model to inherit the knowledge of the teacher while maintaining a fraction of its size.

F. Retrieval-Augmented Generation (RAG) at the Edge

The energy-aware multi-agent RAG planner [9] optimizes task planning, retrieval $R(q)$, and generation $G(R(q))$ for a query q. Pruning is applied to the generator model to reduce memory footprint, and agents coordinate to ensure energy-efficient execution on edge hardware.

V. Limitations of the Evidence

Despite the promising results, several limitations persist in the current body of research:

- **Generalizability:** Many studies focus on specific hardware (e.g., Raspberry Pi 4 [2] or specific microcontrollers like Cortex-M7 and ESP32 [3]), making it difficult to generalize the findings across different edge platforms.
- **Accuracy vs. Efficiency:** There is often a noticeable accuracy loss in complex tasks when aggressive compression or quantization is applied [3, 7]. The research primarily relies on comparative evaluation rather than establishing a universal Pareto-optimal boundary.
- **Hardware Measurement Gaps:** Some studies mainly focus on performance optimization (computational complexity, training time) and do not deeply address energy measurement at the hardware level [6].
- **Standardization:** Current benchmarks like SLM-Bench [10] are sensitive to hardware-specific measurements and rapidly evolving model architectures, making fair comparison across diverse systems challenging.
- **Training Complexity:** While inference efficiency is a major focus, the additional training complexity introduced by multi-stage learning [1] or adaptive backpropagation [5] can be significant.

VI. Research Gaps and Future Directions

Future research should aim to address the identified limitations and explore new frontiers in sustainable AI:

- **Universal Compression Techniques:** Researching adaptive pruning and quantization strategies that can dynamically adjust based on task complexity and hardware availability for larger models.
- **Hardware-Software Co-Optimization:** Designing more adaptable, energy-aware accelerator architectures (GPUs, FPGAs, ASICs) and improving co-design strategies with large language models [8].
- **Standardized Sustainability Benchmarks:** Developing comprehensive, lifecycle-based carbon assessment methodologies and standardized benchmarks that integrate energy-aware evaluation metrics into industrial applications [4, 10].
- **Enhanced Reasoning in Compact Models:** Improving the reasoning capability of Super Tiny Language Models (STLMs) while maintaining their ultra-low memory usage [7].
- **Privacy-Preserving Mechanisms:** Integrating stronger privacy-preserving mechanisms into on-device NLP processing frameworks [3].

VII. Conclusion

This survey has reviewed recent research on energy-efficient and performance-optimized language models, particularly those designed for edge and resource-constrained environments. The analyzed works explored multiple directions, including model compression, quantization, pruning, adaptive training strategies, hardware acceleration, and sustainability benchmarking. We have demonstrated that achieving truly sustainable language modeling will require a balanced approach that integrates efficiency, scalability, and environmental responsibility. The insights provided in this survey offer a foundational guide for future research toward achieving high-performance yet energy-aware language model deployment.

References

[1] W. Chen et al., "Dolphin: Long Context as a New Modality for Energy-Efficient On-Device LMs," 2024.
[2] E. J. Husom et al., "Sustainable LLM Inference for Edge AI," 2024.
[3] S. Pujari et al., "Efficient TinyML Architectures for On-Device SLMs," 2024.
[4] A. Khan et al., "Optimizing Large Language Models: Metrics & Energy Efficiency," 2024.
[5] M. Huang et al., "Towards Green AI via Adaptive Backpropagation," 2024.
[6] Y. Mei et al., "Efficiency Optimization of Large-Scale LMs," 2024.
[7] R. Hillier et al., "Super Tiny Language Models," 2024.
[8] C. Kachris, "Survey on Hardware Accelerators for LLMs," 2024.
[9] R. Bhatia et al., "Energy-Aware Multi-Agent RAG Planner," 2024.
[10] T. Pham et al., "SLM-Bench: Environmental Benchmark for SLMs," 2024.

Acknowledgement
Author thanks all the authors whoes papers has been refere in this paper.

Copyright Notice:
© 2026 Author syeda. All rights reserved. This survey paper may not be copied, reproduced, or distributed without permission from the author.

Acknowledgment

The author would like to thank all researchers whose works have been cited in this survey. Their valuable contributions have greatly supported the understanding and development of energy■efficient and sustainable large language models.

Copyright Notice

© 2026 Author. This survey paper is the original work of the author. Any use, reproduction, or distribution of this material should be properly cited.