
MGM250-31-10-16

MINI THERMOELECTRIC GENERATOR MODULE





Features

- Compact structure (no moving parts)
- Reliable performance
- Maintenance-free
- Noise-free operation
- Low-carbon, green technology
- Epoxy sealed - suitable for use in high humidity conditions
- High temperature

Geometric Dimensions

A	[mm]	15
B	[mm]	15
H	[mm]	approx. 3.2


CHARACTERISTICS


Parameters correct at temp.	[°C]	Hot side: 250 Cold side: 30	Hot side: 100 Cold side: 30
Matched load output power	[W]	0.76	0.10
Matched load resistance	[Ω]	1.9 ± 15%	1.5 ± 15%
Open circuit voltage	[V]	2.5	0.8
Matched load output	[A]	0.6	0.3
Matched load output voltage	[V]	1.2	0.4
Heat flow through module	[W]	15	4.5
Maximum compress (non-destructive)	[MPa]	-	1
Maximum operation temperature	[°C]	Hot side: 250 Cold side: 175	


Adaptive is a registered trademark of European Thermodynamics Limited.
Web: www.etdyn.com | Tel: +44(0)116 279 6899
E-mail: info@etdyn.com


MGM250-31-10-16


GRAPHS











Adaptive is a registered trademark of European Thermodynamics Limited.
Web: www.etdyn.com | Tel: +44(0)116 279 6899
E-mail: info@etdyn.com