Task 1

Problem: **Company Employee Access System**

Build a small employee access model for a company, applying encapsulation and inheritance.

1. Create class **Employee** with private fields:
    - **employeeId (int)** — auto-generated using a private static int counter that increments whenever a new Employee is created. Do not provide a setter for employeeId.
    - **name (String)**
    - **dailyAccessHours (int)** — default value 8.
    - Provide a **constructor that takes only name**. The employeeId must be generated automatically.
    - Provide **getters for all fields**.
    - Add a method **describe()** that prints the employee's ID, name, and allowed daily access hours.
    - If the provided name is blank or empty, the constructor should:
        - Print an error message.
        - Set the employee's name to "Unknown Employee".
2. Create subclass **Manager** extends Employee with an additional private field:
    - **teamSize (int)**
    - Its constructor takes **name** and **teamSize**.
      Override **getDailyAccessHours()** so that a manager receives:
      8 + (teamSize ~/ 5) hours
      For example, a manager with a team size of 12 receives 8 + 2 = 10 hours.
      Override **describe()** to also display the manager's team size.
3. Create subclass **Intern** extends Employee with an additional private field:
    - **month (int)**
    - Its constructor takes **name** and **month**.
      **Override getDailyAccessHours(**):
        - Months 1–3 → 4 hours
        - Months 4–6 → 6 hours
4. In **Main**:
    - Create one plain Employee.
    - Create one Manager.
    - Create one Intern.
    - Call describe() for each object.
    - Print getDailyAccessHours() for each object.
    - Create another Employee with a blank name to demonstrate constructor validation.