

```
syed123@localhost:~  
[syed123@localhost ~]$ rtouch fork_program.c  
[syed123@localhost ~]$ ls  
Desktop  emp.awk      hello-1.0  Music      rpmbuild    Videos  
Documents emp.dat      marks.awk  Pictures   shell_script  
Downloads fork_program.c marks.dat  Public     Templates  
[syed123@localhost ~]$ vi fork_program.c  
[syed123@localhost ~]$ gcc fork_program.c -o fork_program  
[syed123@localhost ~]$ ./fork_program  
  
--- PARENT PROCESS ---  
Parent Process ID: 3477  
Parent's Parent Process ID: 2547  
IT CAN BE EXECUTED TWICE  
THIS LINE EXECUTED TWICE  
  
--- CHILD PROCESS ---  
Child Process ID: 3478  
Parent Process ID: 1934  
IT CAN BE EXECUTED TWICE  
[syed123@localhost ~]$
```



```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>

int main()
{
    int pid;

    // Create a new process
    pid = fork();

    printf("THIS LINE EXECUTED TWICE\n");

    // Check if fork failed
    if (pid == -1)
    {
        printf("CHILD PROCESS NOT CREATED\n");
        exit(0);
    }

    // Child process
    if (pid == 0)
    {
```



```
    printf("CHILD PROCESS NOT CREATED\n");
    exit(0);
}

// Child process
if (pid == 0)
{
    printf("\n--- CHILD PROCESS ---\n");
    printf("Child Process ID: %d\n", getpid());
    printf("Parent Process ID: %d\n", getppid());
}
// Parent process
else
{
    printf("\n--- PARENT PROCESS ---\n");
    printf("Parent Process ID: %d\n", getpid());
    printf("Parent's Parent Process ID: %d\n", getppid());
}

printf("IT CAN BE EXECUTED TWICE\n");

return 0;
```