

Rajalakshmi Engineering College

Name: syed mohammed hussain
Email: 241801288@rajalakshmi.edu.in
Roll no: 241801288
Phone: 9363281289
Branch: REC
Department: I AI & DS FD
Batch: 2028
Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Your task is to create a program to manage a playlist of items. Each item is represented as a character, and you need to implement the following operations on the playlist.

Here are the main functionalities of the program:

Insert Item: The program should allow users to add items to the front and end of the playlist. Items are represented as characters. Display Playlist: The program should display the playlist containing the items that were added.

To implement this program, a doubly linked list data structure should be used, where each node contains an item character.

Input Format

The input consists of a sequence of space-separated characters, representing the items to be inserted into the doubly linked list.

The input is terminated by entering - (hyphen).

Output Format

The first line of output prints "Forward Playlist: " followed by the linked list after inserting the items at the end.

The second line prints "Backward Playlist: " followed by the linked list after inserting the items at the front.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: a b c -

Output: Forward Playlist: a b c

Backward Playlist: c b a

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    char item;  
    struct Node* next;  
    struct Node* prev;  
};
```

```
void insertAtEnd(struct Node** head, char item) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->item = item;  
    newNode->next = NULL;  
    newNode->prev = NULL;  
    if(*head == NULL)  
    {  
        *head = newNode;  
        return;  
    }  
}
```

```
    struct Node* temp = *head;
    while(temp -> next != NULL)
    {
        temp = temp -> next;
    }
    temp -> next = newNode;
    newNode -> prev = temp;
}
void displayForward(struct Node* head) {
    struct Node* temp = head;
    while(temp != NULL)
    {
        printf("%c ",temp -> item);
        temp = temp -> next;
    }
    printf("\n");
}
```

```
void displayBackward(struct Node* tail) {
    struct Node* temp = tail;
    while(temp != NULL)
    {
        printf("%c ",temp -> item);
        temp = temp -> prev;
    }
    printf("\n");
}
```

```
void freePlaylist(struct Node* head) {
    struct Node* temp = head;
    while(temp != NULL)
    {
        struct Node* nextNode = temp -> next;
        free(temp);
        temp = nextNode;
    }
    head = NULL;
}
```

```
int main() {
    struct Node* playlist = NULL;
    char item;
```

```
while (1) {
    scanf(" %c", &item);
    if (item == '-') {
        break;
    }
    insertAtEnd(&playlist, item);
}

struct Node* tail = playlist;
while (tail->next != NULL) {
    tail = tail->next;
}

printf("Forward Playlist: ");
displayForward(playlist);

printf("Backward Playlist: ");
displayBackward(tail);

freePlaylist(playlist);

return 0;
}
```

Status : Correct

Marks : 10/10