

Maharaja Agrasen Institute of Technology
ETCS 211
Computer Graphics & Multimedia
UNIT 3
Shading

Objective

Why Shade?

illumination Vs. Shading

Global Illumination

Local illumination

Q & A

MAIT/CSE/COM/UNIT-3/SHADING

1

MAIT/CSE/COM/UNIT-3/SHADING

2

Why Shade?

Human vision uses shading as a cue to form, position, and depth

- Total handling of light is very expensive
- Shading models can give us a good approximation of what would "really" happen, much less expensively
- Average and approximate



MAIT/CSE/COM/UNIT-3/SHADING

3

MAIT/CSE/COM/UNIT-3/SHADING

4

illumination Vs. Shading

- Illumination (lighting) model: determine the color of a surface point by simulating some light attributes.
- Shading model: applies the illumination models at a set of points and colors the whole image.

Illumination (Lighting) Model

To model the interaction of light with surfaces to determine the final color & brightness of the surface


- Global illumination
- Local illumination

MAIT/CSE/COM/UNIT-3/SHADING

5

Global Illumination

Global Illumination models: take into account the interaction of light from all the surfaces in the scene. (will cover under the Radiosity section)




MAIT/CSE/COM/UNIT-3/SHADING

6

Local illumination

Only consider the light, the observer position, and the object material properties



MAIT.CSE.COM, UNIT-3 SHADING

7

Basic Illumination Model

Simple and fast method for calculating surface intensity at a given point

Lighting calculation are based on:

- The background lighting conditions
- The light source specification: color, position
- Optical properties of surfaces:
 - Glossy OR matte
 - Opaque OR transparent (control refraction and absorption)

MAIT.CSE.COM, UNIT-3 SHADING

8

Ambient light (background light)

The light that is the result from the light reflecting off other surfaces in the environment

A general level of brightness for a scene that is independent of the light positions or surface directions
-> ambient light

Has no direction

Each light source has an ambient light contribution, I_a

For a given surface, we can specify how much ambient light the surface can reflect using an ambient reflection coefficient: K_a ($0 < K_a < 1$)

MAIT.CSE.COM, UNIT-3 SHADING

9

Ambient Light

So the amount of light that the surface reflect is therefore

$$I_{amb} = K_a * I_a$$

MAIT.CSE.COM, UNIT-3 SHADING

10

Diffuse Light

The illumination that a surface receives from a light source and reflects equally in all directions

This type of reflection is called Lambertian Reflection (thus, Lambertian surfaces)

The brightness of the surface is independent of the observer position (since the light is reflected in all direction equally)

MAIT.CSE.COM, UNIT-3 SHADING

11


Lambert's Law

How much light the surface receives from a light source depends on the angle between its angle and the vector from the surface point to the light (light vector)

Lambert's law: the radiant energy ' I_d ' from a small surface d_a for a given light source is:

$$I_d = I_L * \cos(\theta)$$

I_L : the intensity of the light source
 θ is the angle between the surface normal (N) and light vector (L)



MAIT.CSE.COM, UNIT-3 SHADING

The Diffuse Component

Surface's material property: assuming that the surface can reflect K_d ($0 < K_d < 1$), diffuse reflection coefficient) amount of diffuse light:

$$I_{diff} = K_d * I_L * \cos(\theta)$$

If N and L are normalized, $\cos(\theta) = N \cdot L$

$$I_{diff} = K_d * I_L * (N \cdot L)$$

The total diffuse reflection = ambient + diffuse

$$I_{diff} = K_a * I_a + K_d * I_L * (N \cdot L)$$

Examples



Sphere diffusely lit from various angles !

MAIT.CSE.COM, UNIT-3 SHADING


13

MAIT.CSE.COM, UNIT-3 SHADING

14

Specular Light

- These are the bright spots on objects (such as polished metal, apple ...)
- Light reflected from the surface unequally to all directions.
- The result of near total reflection of the incident light in a concentrated region around the specular reflection angle



MAIT.CSE.COM, UNIT-3 SHADING


15

Phong's Model for Specular

How much reflection light you can see depends on where you are

Specular light :

Phong's model $I_s = K_s * I_s * \cos^n(\theta)$




MAIT.CSE.COM, UNIT-3 SHADING

16

Phong Illumination Curves

Specular exponents are much larger than 1;
Values of 100 are not uncommon.

n : glossiness, rate of falloff



MAIT.CSE.COM, UNIT-3 SHADING

17

Specular Highlights

- Shiny surfaces change appearance when viewpoint is changed
- Specularities are caused by microscopically smooth surfaces.
- A mirror is a perfect specular reflector

MAIT.CSE.COM, UNIT-3 SHADING


18

Reflected Ray

How to calculate R?

$$R + L = 2(N \cdot L) N$$

$$R = 2(N \cdot L) N - L$$



MAIT.CSE.COM, UNIT 3 SHADING


19

Half Vector

An alternative way of computing phong lighting is: $I_s = k_s * I_s * (N \cdot H)^n$

H (halfway vector): halfway between V and L: $(V+L)/2$


Fuzzier highlight




MAIT.CSE.COM, UNIT 3 SHADING

20

Phong Illumination



Moving Light



Change n

MAIT.CSE.COM, UNIT 3 SHADING

21

Putting It All Together

Single Light (white light source)

$$I = \text{Ambient} + \text{Diffuse} + \text{Specular} =$$

$$K_a * I_a + K_d * \frac{I_L * (N \cdot L)}{I_d} + K_s * \frac{I_L * (R \cdot V)}{I_s}^n$$

MAIT.CSE.COM, UNIT 3 SHADING

22

Multiple Light Source

I_L : light intensity

$$I = K_a * I_a + \sum_i (K_d * I_L * (N \cdot L) + K_s * I_L * (R \cdot V)^n)$$

For multiple light sources

- Repeat the diffuse and specular calculations for each light source
- Add the components from all light sources
- The ambient term contributes only once

The different reflectance coefficients can differ.

- Simple "metal": k_s and k_d share material color,
- Simple plastic: k_s is white

Remember, when cosine is negative lighting term is zero!

MAIT.CSE.COM, UNIT 3 SHADING

23

Constant Shading

Compute illumination only at one point on the surface


Okay to use if all of the following are true

- The object is not a curved (smooth) surface (e.g. a polyhedron object)
- The light source is very far away (so $N \cdot L$ does not change much across a polygon)
- The eye is very far away (so $V \cdot R$ does not change much across a polygon)
- The surface is quite small (close to pixel size)

MAIT.CSE.COM, UNIT 3 SHADING

24


Un-lit



MAIT.CSE.COM.UINT-3 SHADING

25


Flat Shading



MAIT.CSE.COM.UINT-3 SHADING

26

Mach Band ?



MAIT.CSE.COM.UINT-3 SHADING

27

Smooth Shading

Need to have per-vertex normals

Gouraud Shading

- Interpolate color across triangles
- Fast, supported by most of the graphics accelerator cards

Phong Shading

- Interpolate normals across triangles
- More accurate, but slow. Not widely supported by hardware

MAIT.CSE.COM.UINT-3 SHADING


28

Gouraud Shading

Normals are computed at the polygon vertices

If we only have per-face normals, the normal at each vertex is the average of the normals of its adjacent faces

Intensity interpolation: linearly interpolate the pixel intensity (color) across a polygon surface



MAIT.CSE.COM.UINT-3 SHADING


29

Linear Interpolation

Calculate the value of a point based on the distances to the point's two neighbor points

If $v1$ and $v2$ are known, then

$$x = b/(a+b) * v1 + a/(a+b) * v2$$



MAIT.CSE.COM.UINT-3 SHADING

30

Linear Interpolation in a Triangle


To determine the intensity (color) of point P in the triangle,

we will do:

determine the intensity of 4 by linearly interpolating between 1 and 2

determine the intensity of 5 by linearly interpolating between 2 and 3


determine the intensity of P by linear interpolating between 4 and 5



MAIT.CSE.COM, UNIT-3 SHADING

31

Mach Band ?



MAIT.CSE.COM, UNIT-3 SHADING

32

Image




MAIT.CSE.COM, UNIT-3 SHADING

33

Phong Shading Model

Gouraud shading does not properly handle specular highlights, specially when the n parameter is large (small highlight).



• **Reason:** colors are interpolated.

• **Solution:** (Phong Shading Model)


- 1. Compute averaged normal at vertices.
- 2. Interpolate *normals* along edges and scan-lines. (component by component)
- 3. Compute *per-pixel* illumination.

MAIT.CSE.COM, UNIT-3 SHADING

34


Gouraud

Phong





MAIT.CSE.COM, UNIT-3 SHADING

35



MAIT.CSE.COM, UNIT-3 SHADING

36




Interpolated Shading - Problems

- Polygonal silhouette – edge is always polygonal. Solution ?
- Perspective distortion – interpolation is in screen space and hence for-shortening takes place. Solution ?
- In both cases finer polygons can help !


Interpolated Shading - Problems

- Orientation dependence - small rotations cause problems



Interpolated Shading - Problems

- Problems at shared vertices – shared by right polygons and not by one on left and hence discontinuity
- Incorrect Vertex normals – no variation in shade



Light Sources


Point light source
 Directional light source: e.g. sun light
 Spot light

Spot Light


To restrict a light's effects to a limited area of the scene

Flap: confine the effects of the light to a designed range in x, y, and z world coordinate

Cone: restrict the effects of the light using a cone with a generating angle δ



Example



Light Source Attenuation

Takes into account the distance of the light from the surface

$$I'_L = I_L * fatt(d)$$

I'_L : the received light after attenuation

I_L : the original light strength

fatt: the attenuation factor

d: the distance between the light source and the surface point

$$fatt = \max \left(\frac{1}{c_1 + c_2*d + c_3*d^2}, 1 \right)$$

C_1, C_2, C_3 are user defined constants associated with each light source

MAIT/CSE/COM/UNIT-3/SHADING

43

MAIT/CSE/COM/UNIT-3/SHADING

44

More on Homogeneous Coordinates

To 4D: $(x,y,z) \rightarrow (x,y,z,1)$

Back to 3D: $(x,y,z,w) \rightarrow (x/w, y/w, z/w)$

A point is on a plane if the point satisfies $0 == A*x + B*y + C*z + D$

Point P: $(x,y,z,1)$.

Representing a plane $N = (A,B,C,D)$. Point P is on the plane, if $P \cdot N == 0$

MAIT/CSE/COM/UNIT-3/SHADING

45

MAIT/CSE/COM/UNIT-3/SHADING

46

Q & A

Q1. A surface rendering algorithm

- is used to calculate the intensity of light that we should see at a given point on the surface of an object
- uses the intensity calculations to determine the light intensity
- scattered light from a rough surface
- light source creating highlights on bright spots

Q2. Diffuse reflection is

- is used to calculate the intensity of light that we should see at a given point on the surface of an object
- uses the intensity calculations to determine the light intensity
- scattered light from a rough surface
- light source creating highlights on bright spots

Q & A

Q3. A shading Model

- is used to calculate the intensity of light that we should see at a given point on the surface of an object
- uses the intensity calculations to determine the light intensity
- scattered light from a rough surface
- light source creating highlights on bright spots

Q4. In the Clip Art task pane, the standard extension of an "event" sound such as a door closing sound is

- .mp3
- .wav
- .midi
- .ram

MAIT/CSE/COM/UNIT-3/SHADING

47

MAIT/CSE/COM/UNIT-3/SHADING

48

Q & A

Q5. Wave front is

- intermediate frames between the key frame
- positioning of objects + it sources
- layout of motion paths for the object and camera
- an animation package