EXPERIMENT - 6

Computer Networks Lab

Aim

Write a program in NS3 to implement Bus Topology.

Syeda Reeha Quasar
14114802719
6C7

EXPERIMENT – 6

Aim:

Write a program in NS3 to implement Bus Topology.

Source Code:

```
#include "ns3/core-module.h"
#include "ns3/network-module.h"
#include "ns3/csma-module.h"
#include "ns3/internet-module.h"
#include "ns3/point-to-point-module.h"
#include "ns3/applications-module.h"
#include "ns3/ipv4-global-routing-helper.h"

// Default Network Topology
//
//       10.1.1.0
// n0 -------------- n1   n2   n3   n4
//    point-to-point  |    |    |    |
//                    ================
//                      LAN 10.1.2.0


using namespace ns3;

NS_LOG_COMPONENT_DEFINE ("SecondScriptExample");

int
main (int argc, char *argv[])
{
  bool verbose = true;
  uint32_t nCsma = 3;

  CommandLine cmd (__FILE__);
  cmd.AddValue ("nCsma", "Number of \"extra\" CSMA nodes/devices", nCsma);
  cmd.AddValue ("verbose", "Tell echo applications to log if true", verbose);

  cmd.Parse (argc,argv);

  if (verbose)
    {
```

```
    LogComponentEnable ("UdpEchoClientApplication", LOG_LEVEL_INFO);
    LogComponentEnable ("UdpEchoServerApplication", LOG_LEVEL_INFO);
  }

nCsma = nCsma == 0 ? 1 : nCsma;

NodeContainer p2pNodes;
p2pNodes.Create (2);

NodeContainer csmaNodes;
csmaNodes.Add (p2pNodes.Get (1));
csmaNodes.Create (nCsma);

PointToPointHelper pointToPoint;
pointToPoint.SetDeviceAttribute ("DataRate", StringValue ("5Mbps"));
pointToPoint.SetChannelAttribute ("Delay", StringValue ("2ms"));

NetDeviceContainer p2pDevices;
p2pDevices = pointToPoint.Install (p2pNodes);

CsmaHelper csma;
csma.SetChannelAttribute ("DataRate", StringValue ("100Mbps"));
csma.SetChannelAttribute ("Delay", TimeValue (NanoSeconds (6560)));

NetDeviceContainer csmaDevices;
csmaDevices = csma.Install (csmaNodes);

InternetStackHelper stack;
stack.Install (p2pNodes.Get (0));
stack.Install (csmaNodes);

Ipv4AddressHelper address;
address.SetBase ("10.1.1.0", "255.255.255.0");
Ipv4InterfaceContainer p2pInterfaces;
p2pInterfaces = address.Assign (p2pDevices);

address.SetBase ("10.1.2.0", "255.255.255.0");
Ipv4InterfaceContainer csmaInterfaces;
csmaInterfaces = address.Assign (csmaDevices);

UdpEchoServerHelper echoServer (9);

ApplicationContainer serverApps = echoServer.Install (csmaNodes.Get (nCsma));
serverApps.Start (Seconds (1.0));
serverApps.Stop (Seconds (10.0));
```

```
  UdpEchoClientHelper echoClient (csmaInterfaces.GetAddress (nCsma), 9);
  echoClient.SetAttribute ("MaxPackets", UintegerValue (1));
  echoClient.SetAttribute ("Interval", TimeValue (Seconds (1.0)));
  echoClient.SetAttribute ("PacketSize", UintegerValue (1024));

  ApplicationContainer clientApps = echoClient.Install (p2pNodes.Get (0));
  clientApps.Start (Seconds (2.0));
  clientApps.Stop (Seconds (10.0));

  Ipv4GlobalRoutingHelper::PopulateRoutingTables ();

  pointToPoint.EnablePcapAll ("second");
  csma.EnablePcap ("second", csmaDevices.Get (1), true);

  Simulator::Run ();
  Simulator::Destroy ();
  return 0;
}
```

Output:

```
reeha@Reeha:~/networkEng/ns-allinone-3.35/ns-3.35$ ./waf --run second.cc
Waf: Entering directory `/home/reeha/networkEng/ns-allinone-3.35/ns-3.35/build'
Waf: Leaving directory `/home/reeha/networkEng/ns-allinone-3.35/ns-3.35/build'
Build commands will be stored in build/compile_commands.json
'build' finished successfully (1.113s)
At time +2s client sent 1024 bytes to 10.1.2.4 port 9
At time +2.0078s server received 1024 bytes from 10.1.1.1 port 49153
At time +2.0078s server sent 1024 bytes to 10.1.1.1 port 49153
At time +2.01761s client received 1024 bytes from 10.1.2.4 port 9
reeha@Reeha:~/networkEng/ns-allinone-3.35/ns-3.35$
```