

INDEX

S.No.	Program Name	Date	Marks	Signature	Remarks
1.	Write a program to find whether a number is prime or not.	18-03-2021			
2.	Write a program to take name, address as character string, age as int, salary as float and contains inline function to set the values and display it.	18-03-2021			
3.	Using the concept of function overloading, write function for calculating area of triangle, circle and rectangle.	18-03-2021			
4.	Create a class Student, which have data members as name, branch, roll no., age, sex, five subjects. Display the name of student & his percentage who has more than 70%.	18-03-2021			
5.	Write a program for multiplication of two matrices using OOP.	18-03-2021			
6.	To create a class TIME with members hours, minutes and seconds. Take input, add two-time objects and passing objects to function and display the result.	25-03-2021			
7.	To create a function power to raise a number m to a power n. The function takes double value for m and integer value for n. Use default value for n to make the function. Calculate the squares when this argument is omitted.	25-03-2021			
8.	Write a program to find the greatest of two given numbers in two different classes using friend function.	08-04-2021			
9.	Write a program to find the biggest of three number using Friend Function.	08-04-2021			
10.	Write a program to find the sum of two numbers declared in a class and display the numbers and sum using friend class.	08-04-2021			
11.	Write a program to demonstrate the use of friend function with Inline assignment.	08-04-2021			

[illegible]



EXPERIMENT - 1

Object Oriented Programming Lab

Aim

Write a program to find whether a number is prime or not.

Syeda Reeha Quasar

14114802719

4C7

EXPERIMENT – 1

Aim:

Write a program to find whether a number is prime or not.

Source Code:

```
#include <iostream>
#include <math.h>
using namespace std;

bool isPrime(int n){
    if (n < 2) return false;
    for (int i = 2; i < n; ++i) {
        if ((n % i) == 0) return false;
    }
    return true;
}

bool isPrime1(int n){
    if (n < 2) return false;
    if (n % 2 == 0) return false;
    for (int i = 2; i < sqrt(n); ++i) {
        if ((n % i) == 0) return false;
    }
    return true;
}

int main() {
    cout << "Enter the number you wan to check whether prime or not";
    int n;
    cin >> n;
    cout << "result = " << isPrime(n);
    cout << "result = " << isPrime1(n);
    return 0;
}
```

Output:

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ isPrime.cpp -o isPrime } ; if ($?) { .\isPrime }
Enter the number you wan to check whether prime or not 23
result = 1
result = 1
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ isPrime.cpp -o isPrime } ; if ($?) { .\isPrime }
Enter the number you wan to check whether prime or not 18
result = 0
result = 0
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ isPrime.cpp -o isPrime } ; if ($?) { .\isPrime }
Enter the number you wan to check whether prime or not 101
result = 1
result = 1
PS D:\sem 4\cpp\oops> █
```



EXPERIMENT - 2

Object Oriented Programming Lab

Aim

Write a program to take name, address as character string, age as int, salary as float and contains inline function to set the values and display them.

Syeda Reeha Quasar

14114802719

4C7

EXPERIMENT – 2

Aim:

Write a program to take name, address as character string, age as int, salary as float and contains inline function to set the values and display them.

Source Code:

```
#include <iostream>
#include <string>
using namespace std;

class details{
public:
    string name;
    string address;
    int age;
    float salary;

    void getData() {
        cout << "Enter name" << endl;
        getline(cin, name);
        cout << "Enter address" << endl;
        getline(cin, address);
        cout << "Enter age" << endl;
        cin >> age;
        cout << "Enter salary" << endl;
        cin >> salary;
    }

    void showdata();
};

void details :: showdata(){
    cout << "details of employee \n";
    cout << "name: " << name << endl;
    cout << "address: " << address << endl;
    cout << "age: " << age << endl;
    cout << "salary: " << salary << endl;
}
```



```
int main(){
    details d;
    d.getData();
    d.showdata();
    return 0;
}
```

Output:

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ employeeDetails.cpp -o employeeDetails } ; if ($?) { .\employeeDetails }
Enter name
Syeda Reeha Quasar
Enter address
Rohini, New Delhi - 110089
Enter age
20
Enter salary
700000
details of employee
name: Syeda Reeha Quasar
address: Rohini, New Delhi - 110089
age: 20
salary: 700000
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ employeeDetails.cpp -o employeeDetails } ; if ($?) { .\employeeDetails }
Enter name
reeha
Enter address
Rohini, Delhi
Enter age
20
Enter salary
900000
details of employee
name: reeha
address: Rohini, Delhi
age: 20
salary: 900000
PS D:\sem 4\cpp\oops> |
```



EXPERIMENT - 3

Object Oriented Programming Lab

Aim

Using concept of function overloading, write function for calculating area of triangle, circle and rectangle.

Syeda Reeha Quasar

14114802719

4C7

EXPERIMENT – 3

Aim:

Using concept of function overloading, write function for calculating area of triangle, circle and rectangle.

Source Code:

```
#include <iostream>
using namespace std;

int area(int l, int b){
    return l * b;
}

float area(float r){
    return 3.14 * r * r;
}

float area(float b, float h){
    return (b * h)/2;
}

int main(){
    int l, b;
    float r, ba, he;
    cout << "Enter length and breadth of rectangle" << endl;
    cin >> l >> b;
    cout << "Area of rectangle is: " << area(l, b) << endl;
    cout << "Enter radius for circle"<<endl;
    cin >> r;
    cout << "Area of circle is: " << area(r) << endl;
    cout << "Enter base and height of triangle" << endl;
    cin >> ba >> he;
    cout << "Area of triangle is: " << area(ba, he) << endl;
    return 0;
}
```

Output:

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ Areas.cpp -o Areas } ; if ($?) { .\Areas }
Enter length and breadth of rectangle
2 3
Area of rectangle is: 6
Enter radius for circle
2
Area of circle is: 12.56
Enter base and height of triangle
12 3
Area of triangle is: 18
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ Areas.cpp -o Areas } ; if ($?) { .\Areas }
Enter length and breadth of rectangle
3 12
Area of rectangle is: 36
Enter radius for circle
5
Area of circle is: 78.5
Enter base and height of triangle
4 12
Area of triangle is: 24
PS D:\sem 4\cpp\oops> █
```



EXPERIMENT - 4

Object Oriented Programming Lab

Aim

Create a class student which have data members as name, branch, roll no., age, sex, five subjects. Display the name of the student and his percentage who has more than 70%.

Syeda Reeha Quasar

14114802719

4C7

EXPERIMENT – 4

Aim:

Create a class student which have data members as name, branch, roll no., age, sex and marks in five subjects. Display the name of the student and his percentage who has more than 70%.

Source Code:

```
#include <iostream>
#include <string>

using namespace std;

class studentRecord{
    private:
        string name;
        string branch;
        int rollNo;
        int age;
        char sex[15];
        float marks;

    public:
        void getDetails();
        void check();
        void showDetails();
        void details();
};

void studentRecord::getDetails(){
    cout << "Enter name" << endl;
    cin >> name;
    cout << "Enter branch" << endl;
    cin >> branch;
    cout << "Enter Roll no. " << endl;
    cin >> rollNo;
    cout << "Enter age" << endl;
    cin >> age;
    cout << "Enter sexuality" << endl;
    cin >> sex;
    cout << "Enter total marks scored in 5 subjects" << endl;
```

```

        cin >> marks;
    }

void studentRecord::showDetails(){
    cout << "Name: " << name << endl;
    cout << "Percentage: " << (marks/5) << "%" << endl;
}

void studentRecord::check(){
    if (((marks/5)) > 70) {
        showDetails();
    }
}

void studentRecord::details(){
    cout << "name: " << name << ", branch: " << branch << ", roll no.: " << rollNo << ", age: " << age << ", sex: " << sex << ", marks: " << marks << endl;
}

int main(int argc, char const *argv[]){
    int students;
    cout << "Enter the no. of students: ";
    cin >> students;
    studentRecord studentsArr[students];
    for (int i = 0; i < students; ++i) {
        cout << "For student " << i + 1 << " : " << endl;
        studentsArr[i].getDetails();
    }


    cout << "\nYou have entered:" << endl;
    for (int i = 0; i < students; i++) {
        studentsArr[i].details();
    }

    cout << "\n\n\n" << endl;

    cout << "Students having marks greater than 70% are: " << endl;
    for (int i = 0; i < students; i++) {
        studentsArr[i].check();
    }
}

```


Output:



```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ studentRecord.cpp -o studentRecord } ; if ($?) { .\studentRecord }
Enter the no. of students: 5
For student1 :
Enter name
reeha
Enter branch
cse
Enter Roll no.
1
Enter age
19
Enter sexuality
F
Enter total marks scored in 5 subjects
498
For student2 :
Enter name
saba
Enter branch
cse
Enter Roll no.
2
Enter age
18
Enter sexuality
F
Enter total marks scored in 5 subjects
498
For student3 :
Enter name
manav
Enter branch
mae
Enter Roll no.
3
Enter age
19
Enter sexuality
M
Enter total marks scored in 5 subjects
350
For student4 :
Enter name
shruti
Enter branch
eee
Enter Roll no.
4
Enter age
20
Enter sexuality
F
Enter total marks scored in 5 subjects
400
For student5 :
Enter name
rohan
Enter branch
ece
Enter Roll no.
5
Enter age
20
Enter sexuality
M
Enter total marks scored in 5 subjects
300

You have entered:
name: reeha, branch: cse, roll no.: 1, age: 19, sex: F, marks: 498
name: saba, branch: cse, roll no.: 2, age: 18, sex: F, marks: 498
name: manav, branch: mae, roll no.: 3, age: 19, sex: M, marks: 350
name: shruti, branch: eee, roll no.: 4, age: 20, sex: F, marks: 400
```

You have entered:

name: reeha, branch: cse, roll no.: 1, age: 19, sex: F, marks: 490

name: saba, branch: cse, roll no.: 2, age: 18, sex: F, marks: 498

name: manav, branch: mae, roll no.: 3, age: 19, sex: M, marks: 350

name: shruti, branch: eee, roll no.: 4, age: 20, sex: F, marks: 400

name: rohan, branch: ece, roll no.: 5, age: 20, sex: M, marks: 300

Students having marks greater than 70% are:

Name: reeha

Percentage: 98%

Name: saba

Percentage: 99.6%

Name: shruti

Percentage: 80%

PS D:\sem 4\cpp\oops> █



EXPERIMENT - 5

Object Oriented Programming Lab

Aim

Write a program for multiplication of two matrices using OOP.

Syeda Reeha Quasar

14114802719

4C7

EXPERIMENT – 5

Aim:

Write a program for multiplication of two matrices using OOP.

Source Code:

```
#include <iostream>

using namespace std;

class MatrixMultiplication{
public:
    int a[3][3];
    int b[3][3];
    int c[3][3];

    void InputMatrix();
    void multiply();
    void result();
};

void MatrixMultiplication::InputMatrix(){
    cout << "Enter the values for the first 3 x 3 matrix row wise" << endl;
    for (int i = 0; i < 3; i++) {
        for (int j = 0; j < 3; j++)
        {
            cin >> a[i][j];
        }
    }
    cout << "Enter the values for the second 3 x 3 matrix row wise" << endl;
    for (int i = 0; i < 3; i++) {
        for (int j = 0; j < 3; j++) {
            cin >> b[i][j];
        }
    }
}

void MatrixMultiplication::multiply(){
    for (int i = 0; i < 3; i++) {
        for (int j = 0; j < 3; j++) {
            c[i][j]=0;
        }
    }
}
```

```

        for (int k = 0; k < 3; k++) {
            c[i][j] += a[i][k] * b[k][j];
        }
    }
}

void MatrixMultiplication::result(){
    cout << "The Resultant Matrix is: \n";
    for (int i = 0; i < 3; i++) {
        for (int j = 0; j < 3; j++) {
            cout << " " << c[i][j];
        }
        cout << endl;
    }
}

int main(){
    MatrixMultiplication x;
    cout << "Program to multiply 2 3X3 matrices: " << endl;
    x.InputMatrix();
    x.multiply();
    x.result();
    return 0;
}

```

Output:

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ matrixMultiplications.cpp -o matrixMultiplications } ; if ($?) { .\matrixMultiplications }
Program to multiply 2 3X3 matrices:
Enter the values for the first 3 x 3 matrix row wise
1 2 3
4 5 6
7 8 9
Enter the values for the second 3 x 3 matrix row wise
2 2 2
2 2 2
2 2 2
The Resultant Matrix is:
12 12 12
30 30 30
48 48 48
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ matrixMultiplications.cpp -o matrixMultiplications } ; if ($?) { .\matrixMultiplications }
Program to multiply 2 3X3 matrices:
Enter the values for the first 3 x 3 matrix row wise
1 2 3
4 5 6
7 8 9
Enter the values for the second 3 x 3 matrix row wise
1 2 3
4 5 6
7 8 9
The Resultant Matrix is:
30 36 42
66 81 96
102 126 150
PS D:\sem 4\cpp\oops> 
```

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ matrixMultiplications.cpp -o matrixMultiplications } ; if ($?) { .\matrixMultiplications }
Program to multiply 2 3X3 matrices:
Enter the values for the first 3 x 3 matrix row wise
1 2 3
4 5 6
7 8 9
Enter the values for the second 3 x 3 matrix row wise
1 1 1
1 1 1
1 1 1
The Resultant Matrix is:
6 6 6
15 15 15
24 24 24
PS D:\sem 4\cpp\oops> 
```



EXPERIMENT - 6

Object Oriented Programming Lab

Aim

To create a class TIME with members hours, minutes and seconds. Take input, add two-time objects and passing objects to function and display the result.

Syeda Reeha Quasar

14114802719

4C7

EXPERIMENT – 6

Aim:

To create a class TIME with members hours, minutes and seconds. Take input, add two-time objects and passing objects to function and display the result.

Source Code:

```
#include <iostream>
using namespace std;
class times{
    int seconds, minutes, hours;

public:
    void getTime(int h, int m, int s){
        hours = h;
        minutes = m;
        seconds = s;
    }

    void putTime(){
        cout << "The time is " << hours << " hours " << minutes << " minutes
" << seconds << " seconds\n";
    }

    void sum(times, times);
};

void times::sum(times t1, times t2){
    seconds = t1.seconds + t2.seconds;
    minutes = seconds / 60;
```



```

        seconds %= 60;
        minutes += t1.minutes + t2.minutes;
        hours = minutes / 60;
        minutes %= 60;
        hours += t1.hours + t2.hours;
    }

int main(){
    times t1, t2, t3;
    t1.getTime(1, 2, 30);
    t2.getTime(4, 5, 55);
    t3.sum(t1, t2);
    t1.putTime();
    t2.putTime();
    t3.putTime();
    int hour1, minute1, second1, hour2, minute2, second2;
    cout << "Time - 1 \n Enter Hour, minute and second " << endl;
    cin >> hour1 >> minute1 >> second1;
    cout << "Time - 2 \n Enter Hour, minute and second " << endl;
    cin >> hour2 >> minute2 >> second2;
    t1.getTime(hour1, minute1, second1);
    t2.getTime(hour2, minute2, second2);
    t3.sum(t1, t2);
    t1.putTime();
    t2.putTime();
    t3.putTime();
    return 0;
}

```

Output:

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ time.cpp -o time } ; if ($?) { .\time }
The time is 1 hours 2 minutes 30 seconds
The time is 4 hours 5 minutes 55 seconds
The time is 5 hours 8 minutes 25 seconds
PS D:\sem 4\cpp\oops> █
```

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ time.cpp -o time } ; if ($?) { .\time }
The time is 4 hours 5 minutes 55 seconds
The time is 5 hours 8 minutes 25 seconds
Time - 1
  Enter Hour, minute and second
6 25 30
Time - 2
  Enter Hour, minute and second
7 30 50
The time is 6 hours 25 minutes 30 seconds
The time is 7 hours 30 minutes 50 seconds
The time is 13 hours 56 minutes 20 seconds
PS D:\sem 4\cpp\oops> █
```



EXPERIMENT - 7

Object Oriented Programming Lab

Aim

To create a function power to raise a number m to a power n . The function takes double value for m and integer value for n . Use default value for n to make the function. Calculate the squares when this argument is omitted.

Syeda Reeha Quasar

14114802719

4C7

EXPERIMENT – 7

Aim:

To create a function power to raise a number m to a power n. The function takes double value for m and integer value for n. Use default value for n to make the function. Calculate the squares when this argument is omitted.

Source Code:

```
#include <iostream>

using namespace std;

float power(double base, int powr = 0){
    if (powr == 0) {
        return base * base;
    }
    float res = 1;
    for (int i = 0; i < powr; ++i) {
        res *= base;
    }
    return res;
}

int main(){
    int powr;
    double base;
    cout << "Enter the number whose power you want to calculate:- " << endl;
    cin >> base;
    cout << "Enter the power of the base:- " << endl;
    cin >> powr;
```

```
    cout << "The result of " << base << " to the power " << powr << " is " << pow  
er(base, powr) << endl;  
    return 0;  
}
```

Output:

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ power.cpp -o power } ; if ($?) { .\power }
Enter the number whose power you want to calculate:-
2
Enter the power of the base:-
18
The result of 2 to the power 18 is 262144
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ power.cpp -o power } ; if ($?) { .\power }
Enter the number whose power you want to calculate:-
12
Enter the power of the base:-
12
The result of 12 to the power 12 is 8.9161e+12
PS D:\sem 4\cpp\oops> █
```



EXPERIMENT - 8

Object Oriented Programming Lab

Aim

Write a program to find the greatest of two given numbers in two different classes using friend function.

Syeda Reeha Quasar

14114802719

4C7

EXPERIMENT – 8

Aim:

Write a program to find the greatest of two given numbers in two different classes using friend function.

Source Code:

```
#include <iostream>
using namespace std;

class ClassB;

class ClassA {
    private:
        int numA;
        friend int greatest(ClassA, ClassB);

    public:
        void input() {
            cout << "Enter number for class A:";
            cin >> numA;
        }
};

class ClassB {
    private:
        int numB;
        friend int greatest(ClassA, ClassB);

    public:
```



```
        void input() {
            cout << "Enter number for class B:";
            cin >> numB;
        }
};

int greatest(ClassA objectA, ClassB objectB) {
    return max(objectA.numA, objectB.numB);
}

int main() {
    ClassA objectA;
    ClassB objectB;
    objectA.input();
    objectB.input();
    cout << "Greatest: " << greatest(objectA, objectB);
    return 0;
}
```

Output:

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ greatest.cpp -o greatest } ; if ($?) { .\greatest }
Enter number for class A: 23
Enter number for class B: 13
Greatest: 23
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ greatest.cpp -o greatest } ; if ($?) { .\greatest }
Enter number for class A: 22
Enter number for class B: 10
Greatest: 22
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ greatest.cpp -o greatest } ; if ($?) { .\greatest }
Enter number for class A: 02
Enter number for class B: 20
Greatest: 20
PS D:\sem 4\cpp\oops> █
```

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ greatest.cpp -o greatest } ; if ($?) { .\greatest }
Enter number for class A: 23
Enter number for class B: 13
Greatest: 23
```



EXPERIMENT - 9

Object Oriented Programming Lab

Aim

Write a program to find the biggest of three number using Friend Function.

Syeda Reeha Quasar

14114802719

4C7

EXPERIMENT – 9

Aim:

Write a program to find the biggest of three number using Friend Function.

Source Code:

```
#include <iostream>
using namespace std;

class threeNumbers{
    private:
        int x, y, z;

    public:
        void input(){
            cout << "Enter three numbers: ";
            cin >> x >> y >> z;
        }

        friend void findLargest(threeNumbers t);
};

void findLargest(threeNumbers t){
    if (t.x > t.y && t.x > t.z) {
        cout << "Largest is:" << t.x;
    }
    else if (t.y > t.z) {
        cout << "Largest is:" << t.y;
    }
}
```

```
    else {  
        cout << "Largest is:" << t.z;  
    }  
}
```

```
int main(){  
    threeNumbers t;  
    t.input();  
    findLargest(t);  
    return 0;  
}
```

Output:

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ largestFriend.cpp -o largestFriend } ; if ($?) { .\largestFriend }
Enter three numbers: 12 23 10
Largest is:23
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ largestFriend.cpp -o largestFriend } ; if ($?) { .\largestFriend }
Enter three numbers:
10
20
30
Largest is:30
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ largestFriend.cpp -o largestFriend } ; if ($?) { .\largestFriend }
Enter three numbers: 220 234 890
Largest is:890
PS D:\sem 4\cpp\oops> |
```

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ largestFriend.cpp -o largestFriend } ; if ($?) { .\largestFriend }
Enter three numbers:
10
23
45
Largest is:45
```



EXPERIMENT - 10

Object Oriented Programming Lab

Aim

Write a program to find the sum of two numbers declared in a class and display the numbers and sum using friend class.

Syeda Reeha Quasar

14114802719

4C7

EXPERIMENT – 10

Aim:

Write a program to find the sum of two numbers declared in a class and display the numbers and sum using friend class.

Source Code:

```
#include <iostream>
using namespace std;

class twoNum{
    private:
        int a, b;

    public:
        void input(){
            cout << "Enter 2 numbers: ";
            cin >> a >> b;
        }

        friend void sum(twoNum t);
};

void sum(twoNum t){
    cout << "First number is: " << t.a << endl;
    cout << "Second number is: " << t.b << endl;
    cout << "Sum of these numbers is " << t.a + t.b << endl;
}

int main(){
```



```
    twoNum t;  
    t.input();  
    sum(t);  
    return 0;  
}
```

Output:

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ friendSum.cpp -o friendSum } ; if ($?) { .\friendSum }
Enter 2 numbers: 12 8
First number is: 12
Second number is: 8
Sum of these numbers is 20
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ friendSum.cpp -o friendSum } ; if ($?) { .\friendSum }
Enter 2 numbers: 23 16
First number is: 23
Second number is: 16
Sum of these numbers is 39
PS D:\sem 4\cpp\oops> █
```

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ friendSum.cpp -o friendSum } ; if ($?) { .\friendSum }
Enter 2 numbers:
13
23
First number is: 13
Second number is: 23
Sum of these numbers is 36
PS D:\sem 4\cpp\oops> █
```



EXPERIMENT - 11

Object Oriented Programming Lab

Aim

Write a program to demonstrate the use of friend function with Inline assignment.

Syeda Reeha Quasar

14114802719

4C7

EXPERIMENT – 11

Aim:

Write a program to demonstrate the use of friend function with Inline assignment.

Source Code:

```
#include <iostream>
using namespace std;

class threeNumbers{
    private:
        int x, y, z;

    public:
        void input(){
            cout << "Enter three numbers: ";
            cin >> x >> y >> z;
        }

        friend inline void findLargest(threeNumbers t);
};

inline void findLargest(threeNumbers t){
    if (t.x > t.y && t.x > t.z) {
        cout << "Largest is:" << t.x;
    }
    else if (t.y > t.z) {
        cout << "Largest is:" << t.y;
    }
}
```

```
    else {  
        cout << "Largest is:" << t.z;  
    }  
}
```

```
int main(){  
    threeNumbers t;  
    t.input();  
    findLargest(t);  
    return 0;  
}
```

Output:

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ inlineFriend.cpp -o inlineFriend } ; if ($?) { .\inlineFriend }
Enter three numbers: 23 45 32
Largest is:45
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ inlineFriend.cpp -o inlineFriend } ; if ($?) { .\inlineFriend }
Enter three numbers: 23 45 34
Largest is:45
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ inlineFriend.cpp -o inlineFriend } ; if ($?) { .\inlineFriend }
Enter three numbers:
12
4
23
Largest is:23
PS D:\sem 4\cpp\oops> 
```

```
PS D:\sem 4\cpp\oops> cd "d:\sem 4\cpp\oops\" ; if ($?) { g++ inlineFriend.cpp -o inlineFriend } ; if ($?) { .\inlineFriend }
Enter three numbers: 2 4 5
Largest is:5
```