

# STUDENT REPORT

# DETAILS

#### Name

SYEDA SAFIA

#### **Roll Number**

TEMPBTech-CSE079

## **EXPERIMENT**

# Title

CANDIES

#### **Description**

Let's consider a scenario where there are K candies to be distributed among N children, each uniquely numbered from 1 to N. The distribution commences with Child A, followed by a sequential allocation to the subsequent children in the order: A, A+1, A+2,..., N. The query at hand is to identify which child will be the last recipient of a candy.

In more explicit terms, after Child x (where  $1 \le x \le N$ ) receives a candy, the subsequent candy is granted to Child x+1. Upon Child N receiving a candy, the distribution cycle restarts. and Child 1 becomes the next recipient.

The primary objective is to ascertain the identity of the child who will receive the last candy in this cyclic distribution.

Note: Each child receives only 1 candy.

### **Input Format:**

The first line of input contains 3 space seperated integers N, K and A.

## **Output Format:**

Print the friend who will be the final recipient of the candy.

#### **Constraints:**

#### 1<=N<=K<=10^8

Sample Input:

5 2 1

Sample Output:

2

#### Source Code:

```
def last_candy_recipient(N, K, A):
    last_child = (A - 1 + K - 1) % N + 1
    return last_child

# Example usage:
N, K, A = map(int, input().strip().split())
print(last_candy_recipient(N, K, A))
```

**RESULT** 

Je NBB,

Lec'l Blo

BIENY

Let Y