

FRIDA SETUP ON ROOTED PHONE – COMPLETE GUIDE

Rooted phone par Frida Server setup karne ke liye kuch steps follow karne hote hain. Sab se important baat yeh hai ke Frida Server ko root permissions ke saath chalana hota hai, aur PC aur phone par Frida ki versions match honi chahiye .

Prerequisites

Shuru karne se pehle, yeh ensure karein:

- **Rooted Android Device:** Phone root hona chahiye (Magisk recommended) .
- **USB Debugging Enabled:** Developer options mein USB Debugging ON karein .
- **ADB Installed:** Computer par Android SDK Platform Tools (ADB) install hona chahiye .
- **Python & pip:** Computer par Python aur pip install hona chahiye, kyunke Frida tools Python package hain .

Step-by-Step Setup Guide

1. **Computer par Frida Tools Install Karein** Sab se pehle, computer par Frida command-line tools install karein. Version number (16.x.x) yaad rakhein, kyunke Server ka bhi wahi version hona chahiye .

```
pip install frida-tools
```

Version check karne ke liye:

```
frida --version
```

2. **Device Architecture Check Karein** Phone ki CPU architecture pata karein, taake sahi Frida Server binary download ho .

```
adb shell getprop ro.product.cpu.abi
```

Output ke hisaab se binary choose karein :

- a. arm64-v8a → android-arm64
- b. armeabi-v7a → android-arm
- c. x86_64 → android-x86_64
- d. x86 → android-x86

3. **Frida Server Download Karein**

- a. [Frida Releases Page](#) par jayein .

b. Computer par install kiye gaye Frida version ke hisaab se file download karein.

c. Example: Agar version 16.1.17 hai, toh frida-server-16.1.17-android-arm64.xz download karein .

4. Frida Server Phone Par Push Karein Download ki gayi compressed file (xz) ko extract karein. Phir ADB ke zariye phone par push karein .

```
# Extract karein
```

```
unxz frida-server-16.1.17-android-arm64.xz
```

```
# Push karein
```

```
adb push frida-server-16.1.17-android-arm64  
/data/local/tmp/frida-server
```

5. Permissions Set Karein aur Server Start Karein (as Root) Phone mein ADB shell mein jayein, root banen, aur file ko executable banayein. Phir server start karein

.

```
adb shell
```

```
su
```

```
cd /data/local/tmp
```

```
chmod 755 frida-server
```

```
./frida-server &
```

Tip: Frida Server ko background mein run karne ke liye command ke end mein & use karein .

6. **Port Forwarding Set Karein** Computer aur phone ke beech communication establish karne ke liye port forward karein .

```
adb forward tcp:27042 tcp:27042
```

```
adb forward tcp:27043 tcp:27043
```

7. **Setup Verify Karein** Check karein ke sab kuch sahi se kaam kar raha hai. Phone par running processes ki list aani chahiye .

```
frida-ps -U
```

Important Points

- **Version Mismatch:** PC aur phone par Frida versions ka mismatch hona sab se common error hai. Hamesha ensure karein ke dono par same version ho .
- **Root Access:** Frida Server ko root privileges ke saath chalana zaroori hai. su command ke baad hi start karein .
- **Avoid Detection:** Kuch apps specific file names ya default ports (27042) ko detect kar sakti hain. Server binary ka naam change kar ke (jaise fs) aur custom port

par (-l 0.0.0.0:8888) start kar ke isko bypass kar sakte hain .

- **Automation:** Agar baar baar manual setup karna mushkil lag raha hai, toh F-for-Frida jaise tools hain jo version management aur installation process ko automate kar sakte hain.

 **Educational Purpose Only:** Yeh guide sirf educational aur authorized security testing ke liye hai. Kisi doosre ke app mein bina permission ke dynamic analysis karna applicable cyber laws ke under punishable hai .

Setup complete ho jaane ke baad, Frida dynamic analysis aur hooking ke liye ready ho jata hai. Agar koi specific error aata hai toh batao, main help kar sakta hoon.

MADE BY:
SYED GHOU
