

Objection – Runtime Mobile Exploration

Objection ek powerful runtime mobile exploration toolkit hai jo Frida ke upar based hai. Isko sensepost ne develop kiya hai aur yeh mobile applications ki security assessment ko bohot easy banata hai.

🔗 Objection Kya Hai?

Objection ek runtime mobile exploration toolkit hai jo **Frida** ko power karta hai . Iska sab se bada feature yeh hai ke yeh **without jailbreak/root** bhi kaam kar sakta hai . Objection ka naam approach ko explain karta hai – runtime mein specific objects ko running process mein inject kiya jata hai .

Objection Frida ke upar ek **user-friendly layer** provide karta hai. Aapko complex JavaScript scripts likhne ki zaroorat nahi, ready-made commands available hain .

🔑 Key Features

SSL Pinning Bypass – Built-in commands se SSL pinning disable kar sakte hain

Root/Jailbreak Detection Bypass – android root disable aur ios jailbreak disable commands se detection bypass

Memory Dumping & Patching – Process memory dump kar sakte hain aur patch bhi

Filesystem Interaction – App ke container filesystem mein browse, upload, download

Class & Method Discovery – Loaded classes aur unke methods list kar sakte hain

Method Hooking – Methods ko watch kar sakte hain aur return values change

SQLite Database Interaction – Bina file download kiye database interact

Custom Frida Scripts – Apni custom scripts bhi import kar sakte hain

Installation

Objection install karna bohot simple hai:

```
pip3 install objection
```

Update karne ke liye:

```
pip3 install --upgrade objection
```

Installation ke baad objection command available ho jati hai .

Setup – Rooted/Non-Rooted

Rooted Device (Android) ke liye:

Frida server setup karein aur run karein :

```
adb shell
su
cd /data/local/tmp
./frida-server &
```

Phir Objection attach karein:

```
objection -g "com.example.app" explore
```

Non-Rooted Device ke liye:

APK patch karna hota hai Frida gadget embed karne ke liye :

```
objection patchapk --source app.apk
```

Patched APK install karein aur explore command run karein.

🔗 Basic Commands

Environment info:

```
env
```

App ke data storage locations aur file paths dikhata hai .

Activities list:

```
android hooking list activities
```

App ki saari activities list hoti hain .

Services list:

```
android hooking list services
```

Current Activity:

```
android hooking get current_activity
```

Classes search:

```
android hooking search classes packageName
```

Methods list:

```
android hooking list methods packageName.ClassName
```

Har method ke parameters ke saath .

Method hook with details:

```
android hooking watch class_method packageName.methodName --dump-args --dump-return --dump-backtrace
```

Method call hote hi arguments, return value, aur backtrace dikhega .

Security Bypass Commands

SSL Pinning Bypass:

```
android sslpinning disable
```

Root Detection Bypass:

```
android root disable
```

Return Value Override:

```
android hooking set return_value packageName.ClassName.methodName true
```

Example: PIN verification method ko hamesha true return karne ke liye .

Memory Commands

Loaded Modules:

```
memory list modules
```

App ke saare loaded libraries/modules list .

Module Exports:

```
memory list exports moduleName
```

Memory Dump:

```
memory dump all memory_dump.bin
```

Poori process memory dump .

vs Objection vs Frida – Kab Kaunsa Use Karein

Objection use karein jab:

- Quick aur easy exploration karna ho
- Common bypasses (SSL, root detection) quickly karni hon
- Ready-made commands se kaam ho
- Frida scripts likhne ka time nahi hai

Frida use karein jab:

- Complex aur custom instrumentation chahiye
- Specific behaviour ko deep analyze karna ho
- Custom hooks aur scripts likhni ho
- Advanced control chahiye

🔑 Real-World Example – PIN Bypass

Maan lijiye app PIN check karti hai :

1. App Attach Karein:

```
objection -g com.example.bankapp explore
```

2. PIN Check Method Override Karein:

android hooking set return_value com.example.bankapp.CheckPin
checkPin true

3. **Koi bhi PIN enter karein** – app access de dega kyunke method ab hamesha true return karega .

Important Notes

Frida Version Match: Objection aur Frida server ki versions match honi chahiye .

Root Detection Apps: Kuch security apps Objection attach hone ko detect kar sakti hain .

Permissions: AndroidManifest.xml mein INTERNET permission chahiye root detection bypass ke liye.

Production Use: Objection ko production apps par authorized testing ke alawa use karna illegal hai.

 **Educational Purpose Only:** Objection ka istemal sirf apne own apps aur authorized testing environments mein karein. Kisi doosre ke app mein bina permission ke runtime exploration karna applicable cyber laws ke under punishable hai.

MADE BY:
SYED GHOUS
