

# Module: Donation

[pawguard/modules/donation](#) — API prefix: `/donations`

PawGuard Backend | FastAPI 3.13 + PostgreSQL 17 + Redis/ARQ + S3 | Generated from repo @ commit 99a8430 (2026-08-12)

## 1. Purpose

Donor management, one-off and recurring pledges, payment/receipt handling, and donation-to-ledger posting.

## 2. Position in the Layered Architecture

[Client](#) → [Router \(auth+validate\)](#) → [Service \(business logic\)](#) → [Repository \(data access\)](#) → [PostgreSQL](#)

Like every module in this codebase, business rules live only in the Service layer; Routers authenticate/authorize/validate and Repositories perform data access with no business decisions (see [AGENTS.md](#) — the project's engineering constitution).

## 3. Data Model — Owned Tables

| Model Class    | Table Name       |
|----------------|------------------|
| DonorProfile   | donor_profiles   |
| DogSponsorship | dog_sponsorships |
| Donation       | donations        |

## 4. API Endpoints (30 total)

| Method | Path                                            | Permission Required |
|--------|-------------------------------------------------|---------------------|
| POST   | /donations/register                             | —                   |
| PUT    | /donations/donors/{donor_id}                    | donation:update     |
| DELETE | /donations/donors/{donor_id}                    | donation:update     |
| POST   | /donations                                      | donation:manage     |
| POST   | /donations/checkout                             | —                   |
| POST   | /donations/verify                               | —                   |
| POST   | /donations/webhook/razorpay                     | —                   |
| GET    | /donations/history                              | —                   |
| GET    | /donations                                      | donation:read       |
| GET    | /donations/donors                               | donation:read       |
| GET    | /donations/{donation_id}/receipt                | —                   |
| PATCH  | /donations/{donation_id}/status                 | donation:update     |
| POST   | /donations/{donation_id}/reconcile              | finance:create      |
| POST   | /donations/bulk/status-update                   | donation:update     |
| POST   | /donations/donors/bulk/delete                   | donation:update     |
| POST   | /donations/sponsorships                         | —                   |
| PATCH  | /donations/sponsorships/{sponsorship_id}/status | —                   |
| GET    | /donations/sponsorships/my                      | —                   |
| GET    | /donations/sponsorships                         | donation:read       |
| GET    | /donations/sponsorships/{sponsorship_id}        | —                   |

+10 additional endpoints not shown — see *openapi.json* for the full list.

**Distinct permission codes used:** donation:update, donation:manage, donation:read, finance:create

## 5. Key Service-Layer Operations

- bulk\_soft\_delete
- bulk\_update\_status
- cancel\_recurring\_subscription
- cancel\_sponsorship
- charge\_due\_recurring\_subscriptions
- create\_campaign
- create\_recurring\_subscription
- create\_sponsorship
- get\_campaign
- get\_donation
- get\_or\_create\_donor
- get\_sponsorship
- handle\_gateway\_webhook
- initiate\_online\_donation

+16 additional service methods.

## 6. Notable Implementation Details

- Successful donations auto-post to the finance ledger and count toward the finance summary.
- Reconciliation and webhook verification endpoints are idempotent against duplicate provider callbacks.

---

*Auto-extracted from pawguard/modules/donation/ (models.py, router(s), service.py) at repo commit 99a8430, 2026-08-12.*