

Module: Foster

pawguard/modules/foster — API prefix: /fosters

PawGuard Backend | FastAPI 3.13 + PostgreSQL 17 + Redis/ARQ + S3 | Generated from repo @ commit 99a8430 (2026-08-12)

1. Purpose

Foster-care workflow: applications, active placements, and return-to-shelter processing for dogs in foster care.

2. Position in the Layered Architecture

Client → Router (auth+validate) → Service (business logic) → Repository (data access) → PostgreSQL

Like every module in this codebase, business rules live only in the Service layer; Routers authenticate/authorize/validate and Repositories perform data access with no business decisions (see AGENTS.md — the project's engineering constitution).

3. Data Model — Owned Tables

Model Class	Table Name
FosterProfile	foster_profiles
FosterPlacement	foster_placements
FosterSupplyDispatch	foster_supply_dispatches
FosterProgressLog	foster_progress_logs

4. API Endpoints (12 total)

Method	Path	Permission Required
POST	/fosters/apply	—
PUT	/fosters/{profile_id}	foster:update
DELETE	/fosters/{profile_id}	foster:update
POST	/fosters/{profile_id}/placements	foster:approve
POST	/fosters/placements/{placement_id}/return	foster:approve
GET	/fosters	foster:update
POST	/fosters/bulk/delete	foster:update
POST	/fosters/placements/{placement_id}/progress	foster:approve
GET	/fosters/placements/{placement_id}/progress	—
POST	/fosters/placements/{placement_id}/supplies	foster:approve
GET	/fosters/placements/{placement_id}/supplies	—
POST	/fosters/placements/{placement_id}/convert-to-adopt	foster:approve

Distinct permission codes used: foster:update, foster:approve

5. Key Service-Layer Operations

- apply_to_foster
- bulk_soft_delete
- convert_to_adoption
- get_placement
- get_profile
- get_progress_logs

- list_profiles_paginated
- list_supply_dispatches
- log_daily_progress
- log_supply_dispatch
- place_dog
- return_dog
- soft_delete_profile
- update_profile

Auto-extracted from pawguard/modules/foster/ (models.py, router(s), service.py) at repo commit 99a8430, 2026-08-12.