

Module: Shelter

[pawguard/modules/shelter](#) — API prefix: `/shelter`

PawGuard Backend | FastAPI 3.13 + PostgreSQL 17 + Redis/ARQ + S3 | Generated from repo @ commit 99a8430 (2026-08-12)

1. Purpose

Shelter facility management: capacity, room/kennel assignments, and facility status — the data model `rescue_centre` builds its directory view on.

2. Position in the Layered Architecture

[Client](#) → [Router \(auth+validate\)](#) → [Service \(business logic\)](#) → [Repository \(data access\)](#) → [PostgreSQL](#)

Like every module in this codebase, business rules live only in the Service layer; Routers authenticate/authorize/validate and Repositories perform data access with no business decisions (see [AGENTS.md](#) — the project's engineering constitution).

3. Data Model — Owned Tables

Model Class	Table Name
ShelterFacility	shelter_facilities
ShelterSection	shelter_sections
Kennel	kennels
FacilityTransfer	facility_transfers
DailyCareLog	daily_care_logs
KennelCleaningLog	kennel_cleaning_logs

4. API Endpoints (23 total)

Method	Path	Permission Required
POST	<code>/shelter/facilities</code>	<code>shelter:update</code>
GET	<code>/shelter/facilities</code>	<code>shelter:read</code>
GET	<code>/shelter/facilities/{facility_id}</code>	<code>shelter:read</code>
PUT	<code>/shelter/facilities/{facility_id}</code>	<code>shelter:update</code>
POST	<code>/shelter/facilities/{facility_id}/sections</code>	<code>shelter:update</code>
GET	<code>/shelter/facilities/{facility_id}/sections</code>	<code>shelter:read</code>
POST	<code>/shelter/sections/{section_id}/kennels</code>	<code>shelter:update</code>
GET	<code>/shelter/sections/{section_id}/kennels</code>	<code>shelter:read</code>
POST	<code>/shelter/kennels/{kennel_id}/assign/{dog_id}</code>	<code>shelter:update</code>
PUT	<code>/shelter/kennels/{kennel_id}/sanitation</code>	<code>shelter:update</code>
POST	<code>/shelter/kennels/{kennel_id}/cleaning-logs</code>	<code>shelter:update</code>
GET	<code>/shelter/kennels/{kennel_id}/cleaning-logs</code>	<code>shelter:read</code>
POST	<code>/shelter/transfers</code>	<code>shelter:update</code>
GET	<code>/shelter/transfers</code>	<code>shelter:read</code>
GET	<code>/shelter/transfers/{transfer_id}</code>	<code>shelter:read</code>
POST	<code>/shelter/transfers/{transfer_id}/confirm-sender</code>	<code>shelter:update</code>
POST	<code>/shelter/transfers/{transfer_id}/confirm-receiver</code>	<code>shelter:update</code>

Method	Path	Permission Required
POST	/shelter/care-logs	shelter:update
GET	/shelter/dogs/{dog_id}/care-logs	shelter:read
DELETE	/shelter/facilities/{facility_id}	shelter:update

+3 additional endpoints not shown — see *openapi.json* for the full list.

Distinct permission codes used: shelter:update, shelter:read

5. Key Service-Layer Operations

- assign_dog_to_kennel
- bulk_delete_facilities
- bulk_update_facility_status
- confirm_transfer_receiver
- confirm_transfer_sender
- create_facility
- create_kennel
- create_section
- get_facility
- get_transfer
- list_care_logs
- list_cleaning_logs_paginated
- list_facilities
- list_facilities_paginated

+12 additional service methods.

Auto-extracted from pawguard/modules/shelter/ (models.py, router(s), service.py) at repo commit 99a8430, 2026-08-12.