

Module: Storage

pawguard/modules/storage — API prefix: /storage

PawGuard Backend | FastAPI 3.13 + PostgreSQL 17 + Redis/ARQ + S3 | Generated from repo @ commit 99a8430 (2026-08-12)

1. Purpose

Centralized file-upload handling: issues presigned S3 upload URLs and confirms/finalizes uploaded objects for every module that accepts media or documents.

2. Position in the Layered Architecture

Client → Router (auth+validate) → Service (business logic) → Repository (data access) → PostgreSQL

Like every module in this codebase, business rules live only in the Service layer; Routers authenticate/authorize/validate and Repositories perform data access with no business decisions (see AGENTS.md — the project's engineering constitution).

3. Data Model — Owned Tables

Model Class	Table Name
StoredFile	stored_files

4. API Endpoints (8 total)

Method	Path	Permission Required
POST	/storage/upload-url	—
PUT	/storage/{file_id}/confirm	—
GET	/storage/{file_id}/download-url	—
GET	/storage/{file_id}	—
GET	/storage	—
DELETE	/storage/{file_id}	—
POST	/storage/bulk/delete	—
GET	/storage/entity/{entity_type}/{entity_id}	—

5. Key Service-Layer Operations

- bulk_delete_files
- confirm_upload
- delete_file
- get_download_url
- get_download_url_for_object
- get_file
- is_admin_user
- list_by_entity
- list_files_paginated
- request_upload_url

6. Notable Implementation Details

- Presigned-URL pattern: files are uploaded directly to S3, never proxied through the API server.
- Confirm step re-checks object existence in S3 before the owning module creates its DB record.

