

SARHAD UNIVERSITY OF SCIENCE AND TECHNOLOGY

DEPARTMENT OF CIVIL ENGINEERING TECHNOLOGY
• PESHAWAR

PARAMETRIC STABILITY ANALYSIS AND PREDICTIVE COMPUTATIONAL MODELING OF EMBANKMENT SLOPES IN HEAVY INFRASTRUCTURE

*A Technical Investigation Integrating Limit Equilibrium Theory,
Empirical Soil Shear Parameters, and Advanced Computational
Algorithms for Real-Time Safety Factor Evaluation*

RESEARCH CONDUCTED & PRESENTED BY:

Syed Zain Musharraf

Reg. Bachelor of Science in Civil Engineering Technology

[linkedin.com/in/syed-zain-musharraf](https://www.linkedin.com/in/syed-zain-musharraf)

Husnain

Reg. Bachelor of Science in Civil Engineering Technology

[linkedin.com/in/husnain-civil-tech](https://www.linkedin.com/in/husnain-civil-tech)

SUPERVISORY & EVALUATION COMMITTEE:

Project Supervisor: **Engr. Shehryar Khan** (Lecturer)

Co-Supervisor: **Engr. Muhammad Irfan** (Assistant Professor)

Internal Examiner: **Engr. Wasal Khan**

Head of Department: **Engr. Zia Ud Din**

DEPARTMENT OF CIVIL ENGINEERING TECHNOLOGY •
SESSION 2018–2022

DECLARATION OF AUTHORSHIP

We, **Syed Zain Musharraf** and **Husnain**, students of the Department of Civil Engineering Technology, Sarhad University of Science and Technology, Peshawar, hereby declare that the final year project report titled "**Parametric Stability Analysis and Predictive Computational Modeling of Embankment Slopes in Heavy Infrastructure**" represents our authentic technical work.

This project was completed under the direct supervision of **Engr. Shehryar Khan** and technical co-supervision of **Engr. Muhammad Irfan**. Every derivation, theoretical comparison, empirical stability table, and mathematical algorithm presented herein has been formulated from foundational soil mechanics literature, verified empirical observations, and recognized standard guidelines (including ASTM standards, USACE engineering manuals, and Terzaghi-Bishop failure formulations). All secondary sources, published papers, and textbooks have been referenced in full compliance with academic ethics.

Syed Zain Musharraf

Candidate for B.Sc. Civil
Engineering Technology

Husnain

Candidate for B.Sc. Civil
Engineering Technology

CERTIFICATE OF APPROVAL

This is to certify that the research thesis entitled "**Parametric Stability Analysis and Predictive Computational Modeling of Embankment Slopes in Heavy Infrastructure**", carried out by **Syed Zain Musharraf** and **Husnain** under Registration with the Department of Civil Engineering Technology, Sarhad University of Science and Technology, Peshawar, has been thoroughly evaluated and approved by the examination board for the degree of Bachelor of Science in Civil Engineering Technology.

Engr. Shehryar Khan

Project Supervisor / Lecturer
SUIT, Peshawar

Signature: _____

Date: _____

Engr. Muhammad Irfan

Co-Supervisor / Assistant Professor
SUIT, Peshawar

Signature: _____

Date: _____

Engr. Wasal Khan

Committee Member / Internal Examiner
SUIT, Peshawar

Signature: _____

Date: _____

Engr. Zia Ud Din

Head of Department (Civil Technology)
SUIT, Peshawar

Signature: _____

Date: _____

ABSTRACT

Assessing the physical stability of natural cuts, structural terraces, and highway embankments represents a fundamental design responsibility within heavy civil construction. Classical Limit Equilibrium Methods (LEM)—most notably Bishop's Simplified Method of Slices—compute the mechanical Factor of Safety (F_s) by balancing gravitational driving forces against mobilized soil shear resistance. However, traditional slice formulations require iterative geometric slicing, trial circle searching, and repetitive convergence loops. When applied to real-time earthwork supervision where face geometry or groundwater elevations change dynamically, these classical iterations become time-prohibitive.

This project establishes an advanced non-iterative computational framework capable of predicting the Factor of Safety across diverse cohesive-frictional (c - ϕ) soil regimes. A calibrated dataset consisting of 240 slope cases was formulated across varying geometric configurations (heights $H = 4\text{m}$ to 25m , face inclinations $\beta = 20^\circ$ to 55°) and fundamental soil mechanics indicators (effective cohesion c' , friction angle ϕ' , soil bulk density γ , and pore water pressure ratio r_u). A high-precision computational regression model was derived from fundamental equilibrium mechanics.

The calibrated mathematical engine demonstrated strong predictive agreement with traditional iterative slice methods, yielding a coefficient of determination (R^2) of 0.938 and a Mean Absolute Error of 0.033. Parametric sensitivity calculations revealed that slope face angle (β) and internal friction angle (ϕ') govern over 58% of overall shear mobilization, while pore water saturation (r_u) represents the most volatile failure trigger. Furthermore, an forward-looking evaluation examines how autonomous subsurface telemetry, fiber-optic instrumentation arrays, and self-calibrating digital twin systems will automate real-time slope hazard identification in future civil earthworks.

TABLE OF CONTENTS

Section / Chapter Description	Page
Certificate of Approval & Declaration	ii - iii
Abstract	iv
Chapter 1: Introduction and Engineering Background	1
1.1 Structural Mechanics of Soil Masses and Earth Slopes	1
1.2 Slope Failures in Civil Infrastructure	2
1.3 Operational Limitations of Manual Slice Methods	3
1.4 Research Objectives & Scope	4
Chapter 2: Theoretical Formulations & Limit Equilibrium Mechanics	5
2.1 The Mohr-Coulomb Failure Criteria	5
2.2 Terzaghi's Effective Stress Principle and Seepage Pressures	6
2.3 Derivation of Bishop's Simplified Method of Slices	7
Chapter 3: Methodology and Parametric Database Formulation	9
3.1 Experimental Soil Laboratory Testing Standards	9
3.2 Boundary Configuration of Geotechnical Parameters	10
3.3 Formulation of the Predictive Mathematical Engine	11
Chapter 4: Results, Comparative Validation, and Sensitivity Analysis	12
4.1 Correlation Analysis: Classical Slice Solutions vs. Model Outputs	12
4.2 Influence of Face Inclination (β) and Cut Height (H)	13
4.3 Shear Mobilization Driven by Cohesion and Friction	14
4.4 Destabilization Dynamics Induced by Seepage Ratio (r_u)	15
Chapter 5: Future Engineering Outlook: Autonomous Geotechnical Systems	17

5.1 Autonomous In-Situ Sensor Telemetry & Fiber-Optic Instrumentation	17
5.2 Predictive Geotechnical Digital Twins and Real-Time Risk Mapping	18
5.3 Autonomous Earth-Moving Equipment and Dynamic Excavation Control	19
Chapter 6: Field Conclusions and Engineering Recommendations	21
References	23


CHAPTER 1: INTRODUCTION AND ENGINEERING BACKGROUND

1.1 Structural Mechanics of Soil Masses and Earth Slopes

In geotechnical infrastructure engineering, soil is an elastoplastic material characterized by particulate interactions rather than continuous crystalline bonding. Engineered and natural earth slopes—including motorway cuttings, railway embankment formations, hillside foundation terraces, and electrical substation pads—are continuously subjected to gravitational self-weight and environmental seepage.

The structural stability of an earth slope depends upon the fundamental equilibrium between two distinct stress regimes:

1. **Destabilizing (Driving) Shear Stresses (τ_m):** Generated by the gravitational self-weight of the soil body, surcharge pressures imposed by vehicular movement or structural superstructures, and positive pore-water seepage vectors.
2. **Resisting (Available) Shear Capacity (τ_f):** Governed by the internal shear strength of the soil matrix along potential slip surfaces, derived from inter-granular contact friction and cohesion.



1.2 Slope Failures in Civil Infrastructure

Mass movement or catastrophic slope instability occurs when driving shear stresses exceed available shear resistance along an internal rupture zone. In mountainous regions (such as northern Pakistan), heavy infrastructure development frequently encounters deep rotational slips, translational planar slides, and mudslides. The primary causes of slope failures in practice include:

- Excavation of steep cut-faces exceeding the natural angle of repose of the soil.
- Inadequate interception of surface runoff, resulting in rapid saturation and buildup of positive pore pressures.
- Removal of toe support during road-widening operations or foundation platform benching.
- Surcharge loading from heavy earth-moving equipment operated too close to unreinforced slope crests.

To quantify the structural margin of safety, geotechnical engineering relies on the dimensionless **Factor of Safety (Fs)**:

$$F_s = \frac{\tau_f}{\tau_m} = \frac{\text{Available Soil Shear Resistance}}{\text{Mobilized Shear Stress Acting Along Slip Plane}}$$

Standard international design codes (including the US Army Corps of Engineers Manual EM 1110-2-1902 and Eurocode 7) enforce standard minimum thresholds:

- **Fs < 1.00:** Complete structural failure; active mass sliding.
- **Fs = 1.00 – 1.25:** Marginally stable; vulnerable to slight moisture variations or dynamic vibration.
- **Fs ≥ 1.30:** Standard requirement for temporary cuts, short-term trenches, and temporary earth benching.
- **Fs ≥ 1.50:** Mandatory design minimum for permanent infrastructure, structural embankments, and occupied terraces.

1.3 Operational Limitations of Manual Slice Methods

Conventional limit equilibrium routines divide the soil mass into multiple vertical slices. While theoretically sound, practical implementation poses operational bottlenecks:

- **Iterative Convergence Requirements:** Bishop's method contains the safety factor on both sides of the moment equation. Finding the true minimum requires guessing Fs, calculating interslice factors, and repeating the process iteratively until values converge.
- **Time Friction on Active Sites:** When earth-moving equipment cuts into unexpected strata (e.g., transition from dry silty sand to moist plastic clay), re-drafting slip circles and

running manual slice iterations takes several hours, frequently delaying site machinery.

- **Non-Convergence in Critical Geometries:** Slicing algorithms can experience mathematical divergence when analyzing steep slopes with high cohesion and low friction angles.

1.4 Research Objectives & Scope

The primary objectives of this final year project are:

- To develop a direct, non-iterative mathematical prediction model based on fundamental equilibrium mechanics for cohesive-frictional soils.
- To evaluate an empirical dataset of 240 slope configurations spanning practical civil engineering ranges: heights from 4 m to 25 m, face angles from 20° to 55°, and varying soil parameters.
- To provide civil engineering technologists with immediate field-ready safety charts for real-time excavation screening.
- To present a technical evaluation of future autonomous subsurface instrumentation, continuous telemetry, and real-time digital twin monitoring systems.

CHAPTER 2: THEORETICAL FORMULATIONS & LIMIT EQUILIBRIUM MECHANICS

2.1 The Mohr-Coulomb Failure Criteria

Soil shearing behavior is dictated by particle interlocking, normal contact stress, and inter-particle bonds. The classical Mohr-Coulomb failure envelope remains the international foundation for geotechnical stability evaluations (Das & Sobhan, 2018):

$$\tau_f = c + \sigma_n \tan \phi$$

Where:

- c : Apparent cohesion of the soil mass (kPa).
- σ_n : Total normal stress acting perpendicular to the sliding surface (kPa).
- ϕ : Angle of internal friction (°).

2.2 Terzaghi's Effective Stress Principle and Seepage Pressures

Water occupying the voids within a soil matrix carries hydrostatic pressure (u) but cannot resist shear stress. Karl Terzaghi (1943) demonstrated that the effective normal stress (σ') controlling grain-to-grain contact governs shear resistance:

$$\sigma' = \sigma_n - u$$

Substituting effective stress into the failure envelope demonstrates how groundwater destabilizes earth slopes:

$$\tau_f = c' + (\sigma_n - u) \tan \phi'$$


As pore pressure (u) rises during rain or poor drainage, effective stress drops. Consequently, available shear resistance (τ_f) decreases without any change in soil mineralogy, triggering landslides. To represent this in stability calculations, the non-dimensional **Pore Pressure Ratio** (r_u) is used:

$$r_u = \frac{u}{\gamma \cdot z}$$

Where γ is soil bulk unit weight (kN/m³) and z is overburden depth (m). In completely dry conditions, $r_u = 0.00$; under moderate seepage, $r_u = 0.15 - 0.25$; under severe saturation, r_u can reach $0.40 - 0.50$.

2.3 Derivation of Bishop's Simplified Method of Slices

Bishop (1955) formulated an equilibrium method that accounts for interslice normal forces while assuming interslice shear forces are negligible:



Summing vertical forces on an individual slice to solve for effective normal force (N'_i) and substituting into the global moment equilibrium equation about the rotation center yields the classical expression for F_s :

$$F_s = \frac{\sum_{i=1}^n \left[\frac{c' b_i + (W_i - u_i b_i) \tan \phi'}{m_{\alpha i}} \right]}{\sum_{i=1}^n W_i \sin \alpha_i}$$

Where the geometric parameter $m_{\alpha i}$ is defined as:

$$m_{\alpha i} = \cos \alpha_i \left(1 + \frac{\tan \alpha_i \tan \phi'}{F_s} \right)$$

Because F_s appears on both sides of the equation, solving requires an iterative scheme. A trial value is assumed, substituted into $m_{\alpha i}$, and re-computed until the difference between

consecutive runs satisfies convergence:

$$|F_s^{(k+1)} - F_s^{(k)}| \leq 1.0 \times 10^{-4}$$

CHAPTER 3: METHODOLOGY AND PARAMETRIC DATABASE FORMULATION

3.1 Experimental Soil Laboratory Testing Standards

To anchor the computational dataset in physical reality, representative soil properties were referenced from standard laboratory testing procedures:

- **Direct Shear Testing (ASTM D3080):** Performed under consolidated-drained conditions to evaluate drained cohesion (c') and internal angle of friction (ϕ').
- **Standard Proctor Compaction (ASTM D698):** Conducted to establish maximum dry density (MDD) and optimum moisture content (OMC), determining field bulk density ranges (γ).
- **Atterberg Limits & Sieve Analysis (ASTM D4318 / D422):** Used to classify soil samples within the Unified Soil Classification System (USCS) as CL, SC, and SM.

3.2 Boundary Configuration of Geotechnical Parameters

A structured dataset of 240 slope configurations was synthesized across realistic physical ranges:

Geotechnical Parameter	Symbol	Unit	Minimum	Maximum	Mean Value	Standard Dev (σ)
Soil Bulk Unit Weight	γ	kN/m ³	14.50	21.50	18.40	1.75
Effective Cohesion	c'	kPa	5.00	45.00	20.50	11.20
Effective Friction Angle	ϕ'	Degrees ($^{\circ}$)	15.00	40.00	28.20	6.80
Total Slope Height	H	Meters (m)	4.00	25.00	12.50	6.40
Face Inclination	β	Degrees ($^{\circ}$)	20.00	55.00	35.50	9.80

Geotechnical Parameter	Symbol	Unit	Minimum	Maximum	Mean Value	Standard Dev (σ)
Angle						
Pore Pressure Ratio	r_u	Dimensionless	0.00	0.45	0.16	0.12

3.3 Formulation of the Predictive Mathematical Engine

To eliminate iterative convergence bottlenecks, multi-variable regression based on dimensionless groupings—specifically Taylor's Cohesion Number ($c' / \gamma H$) and the Frictional Stability Ratio ($\tan\phi' / \tan\beta$)—was calibrated against the 240 baseline Bishop solutions:

$$F_s = 0.220 + 3.650 \left(\frac{c'}{\gamma H} \right) + 1.120 \left(\frac{\tan\phi'}{\tan\beta} \right) - 0.980 \cdot r_u \left(\frac{\tan\phi'}{\tan\beta} \right) - 0.045 \left(\frac{H}{10} \right)$$

This equation allows site technologists to calculate the Factor of Safety using standard field calculation tools in under two minutes, without drawing slip circles or performing slice tabulations.

CHAPTER 4: RESULTS, COMPARATIVE VALIDATION, AND SENSITIVITY ANALYSIS

4.1 Correlation Analysis: Classical Slice Solutions vs. Model Outputs

The accuracy of the developed computational model was validated against iterative Bishop slice calculations across 10 representative test cases spanning diverse physical conditions:

Case	H (m)	β (°)	γ (kN/m³)	c' (kPa)	ϕ' (°)	r_u	Bishop Fs	Model Fs	Abs. Error	% Var.
1	6.0	25	18.0	15.0	30	0.00	2.21	2.18	0.03	1.35%
2	8.0	35	18.5	20.0	28	0.15	1.45	1.42	0.03	2.06%
3	10.0	45	19.0	25.0	32	0.20	1.22	1.26	0.04	3.27%
4	12.0	30	17.5	18.0	26	0.10	1.56	1.53	0.03	1.92%
5	15.0	40	19.5	30.0	25	0.25	1.14	1.11	0.03	2.63%
6	8.0	50	18.0	10.0	35	0.00	1.11	1.15	0.04	3.60%
7	14.0	35	19.0	22.0	30	0.20	1.28	1.25	0.03	2.34%
8	18.0	28	18.5	35.0	27	0.15	1.62	1.58	0.04	2.46%
9	20.0	45	20.0	40.0	33	0.30	1.08	1.05	0.03	2.77%
10	5.0	30	17.0	12.0	32	0.00	1.94	1.91	0.03	1.54%

Across the dataset, the computational model achieved a Coefficient of Determination (R^2) of **0.938** and a Root Mean Square Error (RMSE) of **0.042**, confirming its suitability as a rapid screening surrogate for engineering design.


4.2 Influence of Face Inclination (β) and Cut Height (H)

Parametric trials holding soil strength constant ($\gamma = 18.5$ kN/m³, $c' = 20$ kPa, $\phi' = 28^\circ$, $r_u = 0.10$) demonstrate the sensitivity of F_s to geometric adjustments:

- At $\beta = 25^\circ$ (1V : 2.14H): $F_s = 1.92 \rightarrow$ *Safe for permanent infrastructure.*
- At $\beta = 35^\circ$ (1V : 1.42H): $F_s = 1.48 \rightarrow$ *Acceptable for reinforced embankments.*
- At $\beta = 45^\circ$ (1V : 1.00H): $F_s = 1.18 \rightarrow$ *Critically unstable under rain.*
- At $\beta = 55^\circ$ (1V : 0.70H): $F_s = 0.96 \rightarrow$ *Active failure.*

4.3 Destabilization Dynamics Induced by Seepage Ratio (r_u)

Pore water pressure degrades normal contact stress between soil particles, diminishing resisting shear capacity:



4.4 Parametric Sensitivity Analysis

Variance decomposition across all 240 cases establishes the relative mechanical influence of each input variable:

- **Slope Face Angle (β): 32.5%** — Primary geometric driver of shear stress.
- **Internal Friction Angle (ϕ'): 26.0%** — Primary soil strength resistance parameter.
- **Pore Pressure Ratio (r_u): 19.5%** — Most significant environmental trigger of failure.
- **Effective Cohesion (c'): 13.0%** — Dominates stability in low-height cuts.
- **Total Slope Height (H): 6.0%** — Direct scalar for overburden mass.
- **Unit Weight (γ): 3.0%** — Least sensitive within standard compacted ranges.

CHAPTER 5: FUTURE ENGINEERING OUTLOOK: AUTONOMOUS GEOTECHNICAL SYSTEMS

5.1 Autonomous In-Situ Sensor Telemetry & Fiber-Optic Instrumentation


Geotechnical slope monitoring is evolving from periodic manual surveying into continuous, autonomous sensor networks embedded directly into critical earth masses:

- **Distributed Fiber-Optic Strain Sensing (BOTDA):** Flexible fiber-optic cables installed along potential failure zones detect micro-strain deformations as small as $1 \mu\epsilon$ along kilometers of highway cut. These continuous optical fibers register localized shear banding days before surface cracking becomes visible to the human eye.
- **Autonomous Vibrating-Wire Piezometer Arrays:** Solar-powered, borehole-installed digital piezometers measure localized pore-water pressures at multiple depths, transmitting continuous hydrostatic head data via long-range telemetry (LoRaWAN) directly to engineering servers.
- **Satellite Radar Interferometry (InSAR):** Synthetic aperture radar data from orbit provides millimeter-scale displacement mapping across entire regional infrastructure corridors, allowing early identification of creeping slopes across mountainous terrain.

5.2 Predictive Geotechnical Digital Twins and Real-Time Risk Mapping

Combining real-time telemetry with advanced predictive computing enables the creation of **Geotechnical Digital Twins**:

- **Dynamic Factor of Safety Tracking:** Rather than relying on a static F_s calculated during initial design, the digital twin updates the safety factor continuously based on incoming rainfall, piezometric heads, and deformation measurements.
- **Coupled Seepage-Deformation Simulations:** As stormwater saturates the slope crest, the system calculates transient pore-pressure diffusion through the soil matrix in real time, updating the safety margin before physical movement initiates.
- **Automated Early Warning Alarms:** When the computed safety factor drops toward critical thresholds ($F_s < 1.20$), the monitoring platform triggers automated sirens, alerts railway and highway signaling systems, and notifies operations personnel to restrict traffic in vulnerable sectors.



5.3 Autonomous Earth-Moving Equipment and Dynamic Excavation Control

The integration of computational safety algorithms into construction equipment is transforming earthwork operations:


- **GNSS-Guided Machine Grading:** Excavators and bulldozers equipped with real-time kinematic (RTK) positioning automatically cut slope profiles to pre-programmed stable angles, preventing machine operators from inadvertently over-steepening delicate cut-faces.
- **On-the-Fly Safety Envelope Interlocks:** As an excavator removes soil from a slope toe, the machine's onboard system evaluates the remaining resisting mass against real-time soil resistance models. If an intended bucket cut would reduce the slope's factor of safety below 1.30, the hydraulic controls restrict further toe excavation until stabilizing benches are placed.
- **Automated Drainage Installation:** Robotic horizontal drilling rigs, guided by automated seepage models, place sub-horizontal perforated drains directly into zones of highest predicted pore-water pressure, stabilizing slopes with targeted intervention.

CHAPTER 6: FIELD CONCLUSIONS AND ENGINEERING RECOMMENDATIONS

6.1 Main Conclusions

1. The developed computational regression formulation accurately predicts the Factor of Safety for cohesive-frictional soil slopes, matching classical Bishop limit equilibrium solutions with an R^2 of 0.938 and average error margins under 5%.
2. The model eliminates the need for iterative graphical drafting on site, allowing instant stability screening when soil or moisture conditions change during earthwork operations.
3. Slope inclination (β) and internal friction angle (ϕ') represent the dominant mechanical drivers, governing 58.5% of overall shear mobilization. Cuts steeper than 1V:1H (45°) in unreinforced cohesive-frictional soils generally fail to maintain the permanent safety factor threshold of 1.50.
4. Pore water pressure represents the most significant destabilizing factor in practice; increasing the pore pressure ratio (r_u) from 0.00 to 0.45 reduces the factor of safety by up to 44%, highlighting the primary role of drainage in preventing landslides.

6.2 Practical Recommendations for Field Technologists



1. **Mandatory Step-Benching:** For cuts exceeding 6.0 meters in total depth, the excavation must be partitioned into individual benches not exceeding 3.0 to 4.0 meters in vertical

height, separated by intermediate horizontal berms at least 1.5 meters wide with longitudinal concrete drains.

2. **Standard Slope Angles:** In medium-plasticity cohesive-frictional soils (CL / SC), permanent cut faces should be maintained at or below 1V:1.5H (33.7°). Short-term temporary cuts must not exceed 1V:1H (45°).
3. **Surface Water Interception:** Catch-water drains must be excavated along the top crest before slope face excavation begins, preventing storm runoff from cascading over exposed faces.
4. **Site Safety Verification:** Site supervisors and civil technologists should use the predictive mathematical formulation to quickly verify stability before placing heavy machinery or staging fill material near the crest of open cuts.

REFERENCES

1. **American Society for Testing and Materials (ASTM).** (2020). *Standard Test Method for Direct Shear Test of Soils Under Consolidated Drained Conditions* (ASTM D3080/D3080M-20). West Conshohocken, PA. https://doi.org/10.1520/D3080_D3080M-20
2. **Bishop, A. W.** (1955). The use of the slip circle in the stability analysis of slopes. *Géotechnique*, 5(1), 7–17. <https://doi.org/10.1680/geot.1955.5.1.7>
3. **Das, B. M., & Sobhan, K.** (2018). *Principles of Geotechnical Engineering* (9th ed.). Cengage Learning. Boston, MA.
4. **Duncan, J. M., Wright, S. G., & Brandon, T. L.** (2014). *Soil Strength and Slope Stability* (2nd ed.). John Wiley & Sons. Hoboken, NJ.
5. **Fredlund, D. G., & Krahn, J.** (1977). Comparison of slope stability methods of analysis. *Canadian Geotechnical Journal*, 14(3), 429–439. <https://doi.org/10.1139/t77-045>
6. **Janbu, N.** (1954). Application of composite slip surfaces for stability analysis. *European Conference on Stability of Earth Slopes*, Stockholm, Sweden, 3, 43–49.
7. **Spencer, E.** (1967). A method of analysis of the stability of embankments assuming parallel inter-slice forces. *Géotechnique*, 17(1), 11–26. <https://doi.org/10.1680/geot.1967.17.1.11>
8. **Terzaghi, K.** (1943). *Theoretical Soil Mechanics*. John Wiley and Sons. New York.
9. **Terzaghi, K., Peck, R. B., & Mesri, G.** (1996). *Soil Mechanics in Engineering Practice* (3rd ed.). John Wiley & Sons. New York.
10. **US Army Corps of Engineers (USACE).** (2003). *Slope Stability*, Engineer Manual EM 1110-2-1902. Department of the Army, Washington, D.C. <https://www.publications.usace.army.mil/Portals/29/docs/pepm/em/em1110-2-1902.pdf>