

Environmental Compliance

Syed Motors · Document Code: COMP-02 · Type: compliance · Department: All Employees

Purpose

This document establishes environmental compliance requirements for activities at Syed Motors that can create, store, transfer, or dispose of environmentally controlled materials. It covers used oil disposal, tyre and battery disposal, paint booth emissions, and effluent handling.

The requirements apply to employees and operational teams involved in vehicle servicing, workshop activities, parts handling, body and paint operations, waste collection, storage, and disposal coordination. The purpose is to ensure that controlled materials are handled through documented processes and approved disposal channels.

Environmental controls must be followed during normal operations as well as during maintenance, cleaning, equipment servicing, and other activities that can generate regulated waste. Employees must use the designated collection and storage arrangements rather than disposing of controlled materials through ordinary waste streams.

Effective from the first working day of the current calendar year. Reviewed annually by the document owner and revised as necessary. Version 1.0.

1. Used Oil

Used engine oil generated during vehicle servicing must be collected in labelled drums intended specifically for used oil. Containers must remain suitable for the material being stored and must be kept closed or secured when oil is not actively being transferred.

Used oil must not be poured into floor drains, storm-water drains, soil, ordinary waste containers, or other locations that are not designated for controlled oil collection. Any employee who notices an incorrect disposal practice must stop the activity where safe to do so and notify the responsible supervisor.

Collection drums should be positioned in a controlled storage area where accidental contact, unauthorized removal, and unnecessary movement can be minimized. The collection area should be kept orderly so that staff can identify the correct container before transferring used oil.

Each collection container must carry a clear label identifying it as used engine oil. Labels should remain readable throughout the storage period. Containers that are damaged, leaking, or otherwise unsuitable must be reported and replaced through the responsible operational team.

Used oil quantities are weighed monthly. The monthly measurement provides a record of the amount generated and supports reconciliation with disposal documentation. The recorded quantity should be retained with the environmental compliance records for review.

Disposal is permitted only through the government-approved recycler. The responsible employee or department must confirm that the selected recycler is an approved disposal channel before arranging collection. Used oil must not be transferred to an unapproved buyer, informal collector, or other third party.

The recycler's certificate of disposal must be obtained after disposal and filed as part of the environmental record. The certificate should be available when environmental compliance records are reviewed or audited.

Where a collection or disposal record is incomplete, the responsible team should resolve the missing information before the record is considered complete. Records should allow the organization to demonstrate that collected used oil was measured and sent through the approved disposal route.

1. Used Oil — Operational Controls

Workshop personnel should take care when transferring used oil from service equipment into collection drums. Containers should be placed in a stable position before transfer, and unnecessary movement of full containers should be avoided.

Spills or leaks involving used oil must be reported promptly to the responsible supervisor and handled using the site's established spill-response arrangements. Contaminated absorbent material or other cleanup material must not automatically be placed into ordinary waste if the material is subject to a separate disposal requirement.

The monthly weighing record should identify the reporting period and the quantity recorded. Disposal records should be retained in a manner that allows the quantity collected to be compared with the corresponding disposal activity.

The document owner or responsible operational representative may review used-oil records to identify missing certificates, unexplained gaps, or repeated handling problems. Any issue identified during review should be documented and assigned for corrective action.

Employees must not assume that an item is acceptable for ordinary disposal merely because it contains a small quantity of oil. When the correct disposal route is uncertain, the employee should seek clarification from the responsible document owner or operational supervisor.

2. Tyres and Batteries

Old tyres and batteries removed during vehicle servicing must be separated from ordinary waste and kept for the approved return or recycling process. They must not be mixed with general workshop waste or placed in containers intended for routine disposal.

Old tyres and batteries are returned to the OEM or the approved recycler under a buy-back arrangement. The responsible team should maintain the relevant return or collection documentation so that the movement of these materials can be demonstrated during review.

No used tyres are sold to third parties. Employees must not arrange informal sales, transfers, exchanges, or disposal of used tyres outside the approved OEM or recycler arrangement.

Used batteries should be handled in a manner that reduces the possibility of damage or leakage during temporary storage. The designated storage location should be organized so that batteries awaiting return can be identified separately from serviceable stock.

Tyres awaiting return should be kept in the designated holding area and should not obstruct normal workshop movement, access routes, or equipment. The responsible team should arrange collection or return when the approved process requires it.

When a tyre or battery is removed from a vehicle, the responsible employee should place it in the designated environmental collection area rather than leaving it at the work location. This creates a clear separation between operational work and materials awaiting approved disposal or return.

Where a buy-back or return transaction is used, supporting documentation should be retained according to the site's recordkeeping arrangements. The record should provide sufficient evidence that the material was transferred through the approved channel.

2. Tyres and Batteries — Handling and Records

Employees should report damaged storage containers, unsafe stacking, leaking batteries, or other conditions that could interfere with controlled storage. The responsible supervisor should arrange corrective action before the condition creates an avoidable environmental or operational issue.

The responsible team should periodically review the holding area to identify accumulated materials that have not yet been returned or collected. Unnecessary accumulation should be addressed by coordinating the next approved return or recycling activity.

Used tyres must not be removed from the premises by employees for personal use or resale. Any exception to the normal return arrangement must be formally clarified by the document owner before the material is transferred.

3. Paint Booth

The paint booth must operate under negative pressure with functional exhaust filters. The ventilation arrangement is intended to control the movement of paint-related emissions and support the controlled operation of the booth during painting activities.

Employees assigned to paint booth operations should confirm that the booth is operating normally before beginning work. If the required exhaust or pressure-control function is not working, painting activity should not continue until the condition has been reported and the appropriate operational decision has been made.

Exhaust filters must be maintained and changed on a defined schedule. The replacement schedule should be followed rather than waiting for a visible failure of the filter. Maintenance personnel should record completed filter changes according to the site's maintenance record process.

Filters removed from the paint booth should not be treated automatically as ordinary office or general waste. The responsible team should follow the applicable handling and disposal arrangement for contaminated maintenance materials.

The paint booth's exhaust system should be kept clear of avoidable obstructions. Employees should not modify, block, disconnect, or bypass the exhaust arrangement in order to continue work when the system is not operating as intended.

Booth emissions are tested twice a year by an accredited laboratory. The responsible department should coordinate the testing schedule and retain the laboratory documentation as part of the environmental compliance record.

Laboratory reports should be filed so that the testing date, testing organization, and reported results can be identified during an audit or compliance review. If a report identifies an issue requiring action, the responsible team should document the follow-up rather than treating the test as a completed activity without review.

Paint booth maintenance, filter replacement, and emissions testing records should be retained together where practical so that the operational history of the booth can be reviewed.

3. Paint Booth — Monitoring and Corrective Action

The twice-yearly emissions test does not replace routine operational checks. Employees should remain alert to visible signs of abnormal exhaust operation, damaged filters, unusual equipment behavior, or other conditions that may indicate that the booth requires attention.

If an environmental control is found to be unavailable or defective, the issue should be reported to the responsible supervisor or maintenance team. Work should be managed according to the site's operational and safety arrangements until the required control is restored.

Corrective actions related to paint booth emissions should identify the issue, the responsible team, the action taken, and the relevant completion information. Supporting maintenance or laboratory records should be retained with the environmental documentation.

The document owner may review the records to confirm that the defined filter schedule and twice-yearly laboratory testing have been maintained. Missing records should be investigated and

completed where supporting evidence is available.

Environmental Records and Compliance Review

Environmental compliance records must be maintained so that Syed Motors can demonstrate how controlled materials are collected, transferred, tested, or disposed of. Records covered by this document include used-oil weighing information, recycler certificates, tyre and battery return documentation, paint booth filter records, and accredited laboratory emissions reports.

Records should be legible, identifiable, and retrievable when required for an internal review or audit. Employees responsible for creating or receiving environmental records should submit them through the designated recordkeeping process rather than retaining the only copy in an informal location.

A compliance review may examine whether used oil was sent through the approved recycler, whether the required certificate was retained, whether tyres and batteries were handled through the approved return or recycling arrangement, and whether paint booth controls and testing records were maintained.

Where records indicate a missed activity, delayed disposal, missing certificate, overdue filter change, or incomplete emissions test, the responsible department should document the issue and coordinate the necessary corrective action.

Employees should cooperate with environmental compliance reviews and provide records or operational information requested by the document owner. Information should be accurate and based on the available operational records.

Environmental requirements must be followed together with applicable company procedures and other controlled documents. Where another approved company document provides a specific process for handling an incident, record, or corrective action, employees should follow that applicable process as well.

Employee Responsibilities

All employees are responsible for following the environmental handling requirements relevant to their work. Workshop and paint operations personnel have particular responsibility for placing controlled materials in the correct collection arrangements and reporting environmental control issues.

Employees must not bypass approved disposal channels for convenience. They must not arrange unauthorized disposal, sale, transfer, or reuse of controlled waste materials covered by this document.

Supervisors are responsible for ensuring that employees under their direction understand the applicable collection and reporting requirements. They should also escalate recurring operational problems that could prevent the requirements from being consistently followed.

Employees who are uncertain about the correct handling route should seek clarification before disposing of or transferring the material. The document owner remains the designated point for questions and clarifications concerning this document.

Approval and Ownership

This document is owned by the HR department and approved by the Branch Manager. Questions or clarifications should be directed to the document owner.

The document is reviewed annually by the document owner and revised as necessary. The current version should be used for operational compliance activities, while superseded versions should be retained according to the organization's document-control arrangements.

Non-compliance is a disciplinary matter under the HR Policy Manual. Environmental compliance issues should therefore be reported and addressed through the appropriate management and company process rather than being ignored or handled through an unauthorized disposal arrangement.