## **Install PHP**

yum install php php-mysql php-pdo php-gd php-mbstring

```
Script PHP info
<?php phpinfo(); ?>
Samba
[Data Share]
path = /home/sharing
browseable = yes
writeable = yes
create mask = 2770
force create mode = 2770
directory mask = 2770
force create mode = 2770
valid users = @sharing
DNS
File named.conf.local
zone "rizal.linuxku" {
    type master;
    file "forward.rizal";
};
zone "88.168.192.in-addr.arpa" {
    type master;
    file "reverse.rizal";
};
File forward.rizal
: BIND data file for forward zone
$TTL 604800
@ IN SOA rizal.linuxku. root.rizal.linuxku. (
2; Serial
604800; Refresh
86400; Retry
2419200; Expire
604800); Negative Cache TTL
@ IN NS ns.rizal.linuxku.
@ IN A 192.168.88.100
@ IN MX 10 mail.rizal.linuxku.
ns IN A 192.168.88.100
www IN A 192.168.88.100
mail IN A 192.168.88.100
```

```
File reverse rizal
; BIND data file for reverse zone
$TTL 604800
@ IN SOA rizal.linuxku. root.rizal.linuxku. (
    2; Serial
    604800; Refresh
    86400; Retry
    2419200; Expire
604800);
@ IN NS ns.rizal.linuxku.
ns IN A 192.168.88.100
100 IN PTR ns.rizal.linuxku.
NFS
File exports
/data 192.168.88.0/24(rw,sync,no_root_squash,no_all_squash)
Konfigurasi Virtualhost
<VirtualHost *:80>
    ServerName rizal.com
    DocumentRoot "/var/www/html/rizalcom"
         <Directory "/var/www/html/rizalcom">
         Options Indexes FollowSymLinks MultiViews
     # AllowOverride controls what directives may be placed in .htaccess files.
              AllowOverride All
    # Controls who can get stuff from this server file
              Order allow, deny
              Allow from all
      </Directory>
    <IfModule mpm_peruser_module>
         ServerEnvironment apache apache
    </IfModule>
    ErrorLog /var/log/httpd/rizal.com-error.log
    CustomLog /var/log/httpd/rizal.com-access.log combined
</VirtualHost>
Script download a2ensite
```

wget https://dl.dropboxusercontent.com/u/64064946/a2ensite

## Script download a2dissite

wget https://dl.dropboxusercontent.com/u/64064946/a2dissite