In this thesis, I discussed several methods and applications of data matching in seismic data analysis. Chapter ?? focuses on introducing the three data matching operators that are used in this thesis—shifting, scaling, and filtering. Chapter ?? introduces different methods of frequency balancing using non-stationary smoothing. The first method to find the non-stationary smoothing radius, or number of samples each data point is averaged over with a triangle weight, took a theoretical approach based off of the assumption that the data we observe can be modeled by a summation of Ricker wavelets. This method worked well in certain situations, but was not robust enough to work for any given data set. In the second method, I introduced an iterative algorithm to find the smoothing radius, and this method converges quickly and works well in several presented situations. Finally, a modification to this algorithm was shown and allows smoothing for more complex data sets.

This chapter also discusses two applications of these algorithms—the frequency balancing algorithm was demonstrated on an application of matching high-resolution and legacy seismic images, and the modified algorithm was demonstrated on an application of multicomponent seismic image registration.

Chapter ?? goes into more detail of the application of matching and merging high-resolution and legacy seismic images. This example takes two seismic volumes, acquired over the same area but using different technologies, and first matches them before merging them together to produce an optimized third image. First, the method is demonstrated on a 2D line from the Gulf of Mexico. Then, the method is applied to a 3D seismic volume from a different part of the Gulf of Mexico.

Chapter ?? discusses another application of improving migration resolution by approximating the least-squares Hessian using non-stationary data matching operations. An approximation to the least-squares Hessian can be calculated by solving a data matching problem between two conventionally migrated images, and the Hessian can be represented by the combination of amplitude and frequency balancing operations. An example is applied to a 2D synthetic Sigsbee data set.

Future work

In the future, the work presented in Chapter ?? should be extended to involve real data and 3D examples. It also could benefit by comparing the results of the proposed approach taken in the chapter to other previous approaches presented to approximate the least-squares Hessian (????????), to see how it compares in different situations.

Another extension of this data matching procedure may be to incorporate the phase of the signal to be matched. Negligible improvements were made when trying to incorporate phase corrections into the high-resolution and legacy data matching problem of Chapter ??, but other data matching problems could benefit from these corrections.

Several applications of data matching were discussed in this thesis. However, many

applications remain unaddressed from a data matching standpoint. Problems such as seismic and well-log tying, deconvolution, automatic gain control (AGC), and surface-related multiple elimination (SRME) can also be recast as data matching problems. Looking at these problems in a new light may bring advancements to computational geophysics.

CODE

The examples in this thesis were implemented with the Madagascar open-source soft-ware environment for reproducible computational experiments (?). The package is available at http://www.ahay.org/.

The reproducible document for the results in this thesis, including code, is available at http://www.sygreer.com/research/honorsThesis. However, some of the data used in this thesis are proprietary, so those results may not directly be reproducible.

For brevity in this thesis, code is only included for one example of the main frequency balancing algorithm presented in Chapter ??. The code for the rest of the examples in this thesis are available online at the URL above.

Table 1: List of figures in this thesis and the locations of scripts and programs to generate them

Figures	Directory	Listings
??	chapter-locfreq/merge/	1, 2, 3
??, ??	chapter-background/dmExample/	
??, ??, ??, ??	chapter-merge/apache/	
??, ??, ??, ??	chapter-locfreq/merge/	1, 2, 3
??, ??	chapter-locfreq/vecta/	
??	chapter-locfreq/convergence/	
??, ??, ??, ??	chapter-merge/apache/	
??, ??	chapter-merge/pcable/	
??	chapter-merge/pcable2/	
??, ??, ??, ??, ??	chapter-merge/mighes/	
?? ,	chapter-merge/triop/	

Listing 1: chapter-locfreq/merge/SConstruct

Listing 2: chapter-locfreq/merge/radius.py

```
from rsf.proj import *
  def radius (high, low,
                                       # initial high and low frequency images
                                       # number of corrections
             niter,
                                       # 'step length' for radius corrections. Can
                                                be type int or float for constant c
                                                or type array for changing c.
              bias=-15, clip=30,
                                       # bias and clip for display
              rect1=40, rect2=80,
                                       # radius for local frequency calculation
              maxrad=1000,
                                       # maximum allowed radius
             theor=True.
                                       # use theoretical smoothing radius
                                       # scale for theoretical smoothing radius
              scale=9,
              initial=10,
                                       # initial value for contant smoothing radius
             minval=0, maxval=25,
                                       # min and max local frequency for display
14
              titlehigh="Hires",
              titlelow="Legacy"):
16
      if type(c) is float or type(c) is int:
18
          c = [c]*niter
      # plot image
      def seisplot(name):
          return 'grey title="%s"', name
      # local frequency
      locfreq = '''iphase order=10 rect1=%d rect2=%d hertz=y complex=y |
26
                    put label="Frequency" unit=Hz'', (rect1, rect2)
28
      def locfreqplot(name):
           return 'grey mean=y color=j scalebar=y title="%s" '%name
30
      # difference in local frequencies
      freqdif = 'add scale=-1,1 ${SOURCES[1]} | put label=Frequency'
      def freqdifplot(num):
          return ''', grey allpos=y color=j scalebar=y mean=y
36
                     title="Difference in Local Frequencies %s"
                     clip=%d bias=%d minval=%d
38
                     maxval=%d''' %(num,clip,bias,minval,maxval)
40
      # plot spectral content
42
      specplot = '''cat axis=2 ${SOURCES[1]} |
                    scale axis=1 | window max1=180 |
                    graph title="Normalized Spectra" label2="Amplitude" unit2=""','
      # plot smothing radius
46
      def rectplot(name):
          return ''', grey color=j mean=y title="%s" scalebar=y barlabel=Radius
48
                     barunit=samples'', %name
      # smooth with radius
```

```
52
       smooth = 'nsmooth1 rect=${SOURCES[1]}'
       54
56
       # plot images
       Result(high, seisplot(titlehigh))
       Result(low, seisplot(titlelow))
58
       # initial local frequency
       Flow('high-freq',high,locfreq)
       Result('high-freq',locfreqplot('%s Local Frequency'%titlehigh))
62
       Flow('low-freq',low,locfreq)
64
       Result('low-freq',locfreqplot('%s Local Frequency'%titlelow))
66
       # initial difference in local frequency
       Flow('freqdif','low-freq high-freq',freqdif)
68
       Result('freqdif', freqdifplot(''))
       # initial smoothing radius
       if (theor):
72
           from math import pi
           Flow('rect0','low-freq high-freq',''math f1=${SOURCES[1]}
           output="sqrt(%g*(1/(input*input)-1/(f1*f1)))/%g"'', %(scale,2*pi*0.001))
       else:
76
           Flow('rect0','low-freq','math output=%f'%initial)
       Result('rect0', rectplot("Smoothing Radius 0"))
80
       # smoothing using intial smoothing radius guess
82
       Flow('high-smooth0','%s rect0' % high, smooth)
       Result('high-smooth0', seisplot("%s Smooth 0"%titlehigh))
       # frequency spectra
       Flow('high-spec',high,'spectra all=y')
86
       Flow('low-spec',low,'spectra all=y')
       Flow('high-smooth-spec0','high-smooth0','spectra all=y')
88
       Result('nspectra', 'high-spec low-spec', specplot)
       Result('high-smooth-spec0', 'high-smooth-spec0 low-spec', specplot)
90
92
       Flow('high-smooth-freq0','high-smooth0',locfreq)
       Result ('high-smooth-freq0',
               locfreqplot("%s Local Frequency Smoothed %d" %(titlehigh,0)))
       Flow('freqdif-filt0','low-freq high-smooth-freq0',freqdif)
       Result('freqdif-filt0', freqdifplot('0'))
98
       prog=Program('radius.c')
       for i in range(1, niter+1):
100
           j = i-1
           # update smoothing radius
           Flow('rect%d'%i, 'rect%d freqdif-filt%d %s'%(j,j,prog[0]),
104
                './${SOURCES[2]} freq=${SOURCES[1]} c=%f'%c[j])
           Result('rect%d'%i,rectplot("Smoothing Radius %d")%i)
           # smooth image with radius
           Flow('high-smooth%d'%i,'%s rect%d'%(high,i),smooth)
           Result('high-smooth%d'%i, seisplot('%s Smooth %d'%(titlehigh,i)))
110
           # smoothed spectra
112
           Flow('high-smooth-spec%d'%i,'high-smooth%d'%i,'spectra all=y')
114
           Result('high-smooth-spec%d'%i,'high-smooth-spec%d low-spec'%i,specplot)
           # smoothed local frequency
116
           Flow('high-smooth-freq%d'%i,'high-smooth%d'%i,locfreq)
           Result ('high-smooth-freq%d'%i,
                  locfreqplot('%s Local Frequency Smoothed %d'%(titlehigh,i)))
```

```
# frequency residual

Flow('freqdif-filt%d'%i,'low-freq high-smooth-freq%d'%i,freqdif)

Result('freqdif-filt%d'%i,freqdifplot(str(i)))
```

Listing 3: chapter-locfreq/merge/radius.c

```
/* smoothing radius (min = 1) */
  #include <rsf.h>
  #include <math.h>
  int main (int argc, char* argv[])
  {
6
      int n1, n1f, n2, n2f, i, n12, n12f;
      float *rect, *fr, maxrad, c, *rad;
      sf_file in, out, freq;
10
      sf_init (argc,argv);
      in = sf_input("in");
      freq = sf_input("freq");
14
      out = sf_output("out");
16
      if (!sf_histint(in,"n1",&n1)) sf_error("No n1= in input.");
      if (!sf_histint(freq,"n1",&n1f)) sf_error("No n1= in frequency difference.");
18
      n2 = sf_leftsize(in,1);
20
      n2f = sf_leftsize(freq,1);
22
      n12 = n1*n2;
      n12f = n1f*n2f;
26
      if (n1 != n1f) sf_error("Need matching n1");
      if (n2 != n2f) sf_error("Need matching n2");
28
      if (!sf_getfloat("c",&c)) c=1.;
      if (!sf_getfloat("maxrad",&maxrad)) maxrad=1000.;
30
      rect = sf_floatalloc(n12);
32
      sf_floatread(rect,n12,in);
      fr = sf_floatalloc(n12f);
      sf_floatread(fr,n12,freq);
      rad = sf_floatalloc(n12);
38
      for (i=0; i < n12; i++) {</pre>
40
           /* update radius */
42
        rad[i] = rect[i]+c*fr[i];
           /* set constraint conditions: [1, maxrad] */
           if (rad[i] > maxrad)
                   rad[i] = maxrad;
           if (rad[i] < 1.0)</pre>
48
                   rad[i] = 1.0;
50
      sf_floatwrite(rad,n12,out);
       exit(0);
54 }
```