

Assignment 4: Data Wrangling (Fall 2025)

Sylvia Hipp

OVERVIEW

This exercise accompanies the lessons in Environmental Data Analytics on Data Wrangling

Directions

1. Rename this file `<FirstLast>_A04_DataWrangling.Rmd` (replacing `<FirstLast>` with your first and last name).
2. Change “Student Name” on line 3 (above) with your name.
3. Work through the steps, **creating code and output** that fulfill each instruction.
4. Be sure to **answer the questions** in this assignment document.
5. When you have completed the assignment, **Knit** the text and code into a single PDF file.
6. Ensure that code in code chunks does not extend off the page in the PDF.

Set up your session

- 1a. Load the `tidyverse`, `lubridate`, and `here` packages into your session.

```
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.4      v readr      2.1.5
## v forcats    1.0.0      v stringr   1.5.1
## v ggplot2    3.5.1      v tibble    3.2.1
## v lubridate  1.9.3      v tidyr     1.3.1
## v purrr      1.0.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
library(lubridate)
library(here)
```

```
## here() starts at /home/guest/EDE_Fall2025
```

```
library(janitor) # add janitor to clean column names for convenience
```

```
##
## Attaching package: 'janitor'
##
## The following objects are masked from 'package:stats':
##
##   chisq.test, fisher.test
```

1b. Check your working directory.

```
getwd()
```

```
## [1] "/home/guest/EDE_Fall2025"
```

1c. Read in all four raw data files associated with the EPA Air dataset, being sure to set string columns to be read in as factors. See the README file for the EPA air datasets for more information (especially if you have not worked with air quality data previously).

2. Add the appropriate code to reveal the dimensions of the four datasets.

```
#1a
# get list of all four filenames
epa_files <- list.files(here("Data/Raw"), pattern = "^EPAair.*csv")
filepath <- here("Data/Raw/")

#1b
# read csv for all files
EPAair_03_NC2018_raw <- read.csv(str_c(filepath, epa_files[1]),
                                stringsAsFactors = TRUE) %>% clean_names()
EPAair_03_NC2019_raw <- read.csv(str_c(filepath, epa_files[2]),
                                stringsAsFactors = TRUE) %>% clean_names()
EPAair_PM25_NC2018_raw <- read.csv(str_c(filepath, epa_files[3]),
                                   stringsAsFactors = TRUE) %>% clean_names()
EPAair_PM25_NC2019_raw <- read.csv(str_c(filepath, epa_files[4]),
                                   stringsAsFactors = TRUE) %>% clean_names()

#2
dim(EPAair_03_NC2018_raw)
```

```
## [1] 9737    20
```

```
dim(EPAair_03_NC2019_raw)
```

```
## [1] 10592    20
```

```
dim(EPAair_PM25_NC2018_raw)
```

```
## [1] 8983    20
```

```
dim(EPAair_PM25_NC2019_raw)
```

```
## [1] 8581 20
```

All four datasets should have the same number of columns but unique record counts (rows). Do your datasets follow this pattern? > Answer: Yes, all datasets have 20 columns

Wrangle individual datasets to create processed files.

3. Change the Date columns to be date objects.
4. Select the following columns: Date, DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC, COUNTY, SITE_LATITUDE, SITE_LONGITUDE
5. For the PM2.5 datasets, fill all cells in AQS_PARAMETER_DESC with “PM2.5” (all cells in this column should be identical).
6. Save all four processed datasets in the Processed folder. Use the same file names as the raw files but replace “raw” with “processed”.

```
# I created a function to process each dataframe to make my code more succinct
process_df <- function(df, file_name, type=""){
```

```
  processed_df <- df %>%
    # 3: change date cols
    mutate(date = mdy(date)) %>%
    # 4: select appropriate columns
    select(date, daily_aqi_value, site_name, aqs_parameter_desc, county,
           site_latitude, site_longitude)
```

```
    # 5: fill all cells equal to PM2.5
    if(type == "PM25"){
      processed_df <- processed_df %>%
        mutate(aqs_parameter_desc = "PM2.5")
    }
```

```
    # 6: write to processed folder
    write.csv(processed_df,
              file = str_c(here("Data/Processed/"), file_name, ".csv"))
```

```
  return(processed_df)
}
```

```
# 6: call function to process datasets and save to processed folder
EPAair_03_NC2018_processed <- process_df(EPAair_03_NC2018_raw,
                                         "EPAair_03_NC2018_processed")
EPAair_03_NC2019_processed <- process_df(EPAair_03_NC2019_raw,
                                         "EPAair_03_NC2019_processed")
EPAair_PM25_NC2018_processed <- process_df(EPAair_PM25_NC2018_raw,
                                           "EPAair_PM25_NC2018_processed",
                                           type = "PM25")
EPAair_PM25_NC2019_processed <- process_df(EPAair_PM25_NC2019_raw,
                                           "EPAair_PM25_NC2019_processed",
                                           type = "PM25")
```

Combine datasets

- Combine the four datasets with `rbind`. Make sure your column names are identical prior to running this code.
- Wrangle your new dataset with a pipe function (`%>%`) so that it fills the following conditions:

- Include only sites that the four data frames have in common:

“Linville Falls”, “Durham Armory”, “Leggett”, “Hattie Avenue”,
“Clemmons Middle”, “Mendenhall School”, “Frying Pan Mountain”, “West Johnston Co.”, “Garinger High School”, “Castle Hayne”, “Pitt Agri. Center”, “Bryson City”, “Millbrook School”

(the function `intersect` can figure out common factor levels - but it will include sites with missing site information, which you don’t want...)

- Some sites have multiple measurements per day. Use the split-apply-combine strategy to generate daily means: group by date, site name, AQS parameter, and county. Take the mean of the AQI value, latitude, and longitude.
 - Add columns for “Month” and “Year” by parsing your “Date” column (hint: `lubridate` package)
 - Hint: the dimensions of this dataset should be 14,752 x 9.
- Spread your datasets such that AQI values for ozone and PM2.5 are in separate columns. Each location on a specific date should now occupy only one row.
 - Call up the dimensions of your new tidy dataset.
 - Save your processed dataset with the following file name: “EPAair_O3_PM25_NC1819_Processed.csv”

```
#7
# Check columns are the same
glimpse(EPAair_O3_NC2018_processed)

## Rows: 9,737
## Columns: 7
## $ date          <date> 2018-03-01, 2018-03-02, 2018-03-03, 2018-03-04, 20~
## $ daily_aqi_value <int> 40, 43, 44, 45, 44, 28, 33, 41, 45, 40, 31, 43, 42,~
## $ site_name      <fct> Taylorsville Liledoun, Taylorsville Liledoun, Taylo~
## $ aqs_parameter_desc <fct> Ozone, Ozone, Ozone, Ozone, Ozone, Ozone, Ozone, Oz~
## $ county         <fct> Alexander, Alexander, Alexander, Alexander, Alexand~
## $ site_latitude   <dbl> 35.9138, 35.9138, 35.9138, 35.9138, 35.9138, 35.913~
## $ site_longitude  <dbl> -81.191, -81.191, -81.191, -81.191, -81.191, -81.19~
```

```
glimpse(EPAair_O3_NC2019_processed)

## Rows: 10,592
## Columns: 7
## $ date          <date> 2019-01-01, 2019-01-02, 2019-01-03, 2019-01-04, 20~
## $ daily_aqi_value <int> 27, 17, 15, 20, 34, 34, 27, 35, 35, 28, 27, 25, 31,~
## $ site_name      <fct> Taylorsville Liledoun, Taylorsville Liledoun, Taylo~
## $ aqs_parameter_desc <fct> Ozone, Ozone, Ozone, Ozone, Ozone, Ozone, Ozone, Oz~
## $ county         <fct> Alexander, Alexander, Alexander, Alexander, Alexand~
## $ site_latitude   <dbl> 35.9138, 35.9138, 35.9138, 35.9138, 35.9138, 35.913~
## $ site_longitude  <dbl> -81.191, -81.191, -81.191, -81.191, -81.191, -81.19~
```

```
glimpse(EPAair_PM25_NC2018_processed)
```

```
## Rows: 8,983
## Columns: 7
## $ date          <date> 2018-01-02, 2018-01-05, 2018-01-08, 2018-01-11, 20~
## $ daily_aqi_value <int> 12, 15, 22, 3, 10, 19, 8, 10, 18, 7, 24, 5, 9, 14, ~
## $ site_name      <fct> Linville Falls, Linville Falls, Linville Falls, Lin~
## $ aqs_parameter_desc <chr> "PM2.5", "PM2.5", "PM2.5", "PM2.5", "PM2.5", "PM2.5~
## $ county         <fct> Avery, Avery, Avery, Avery, Avery, Avery, Avery, Av~
## $ site_latitude   <dbl> 35.97235, 35.97235, 35.97235, 35.97235, 35.97235, 3~
## $ site_longitude  <dbl> -81.93307, -81.93307, -81.93307, -81.93307, -81.933~
```

```
glimpse(EPAair_PM25_NC2019_processed)
```

```
## Rows: 8,581
## Columns: 7
## $ date          <date> 2019-01-03, 2019-01-06, 2019-01-09, 2019-01-12, 20~
## $ daily_aqi_value <int> 7, 4, 5, 26, 11, 5, 6, 6, 15, 7, 14, 20, 8, 10, 8, ~
## $ site_name      <fct> Linville Falls, Linville Falls, Linville Falls, Lin~
## $ aqs_parameter_desc <chr> "PM2.5", "PM2.5", "PM2.5", "PM2.5", "PM2.5", "PM2.5~
## $ county         <fct> Avery, Avery, Avery, Avery, Avery, Avery, Avery, Av~
## $ site_latitude   <dbl> 35.97235, 35.97235, 35.97235, 35.97235, 35.97235, 3~
## $ site_longitude  <dbl> -81.93307, -81.93307, -81.93307, -81.93307, -81.933~
```

```
EPAair_df_stacked <- rbind(EPAair_03_NC2018_processed,
                           EPAair_03_NC2019_processed,
                           EPAair_PM25_NC2018_processed,
                           EPAair_PM25_NC2019_processed)
```

```
#8
```

```
# Wrangle dataset
```

```
# get which sites are common across all datasets
```

```
common_sites <- intersect(levels(EPAair_03_NC2018_processed$site_name),
                           levels(EPAair_03_NC2019_processed$site_name)) %>%
  intersect(levels(EPAair_PM25_NC2018_processed$site_name)) %>%
  intersect(levels(EPAair_PM25_NC2019_processed$site_name)) %>%
  str_subset(".*")
```

```
EPAair_df_processed <- EPAair_df_stacked %>%
  filter(site_name %in% common_sites) %>%
  group_by(date, site_name, aqs_parameter_desc, county) %>%
  summarize(avg_aqi_value = mean(daily_aqi_value),
            avg_latitude = mean(site_latitude),
            avg_longitude = mean(site_longitude)) %>%
  ungroup() %>%
  mutate(year = year(date),
         month = month(date))
```

```
## 'summarise()' has grouped output by 'date', 'site_name', 'aqs_parameter_desc'.
## You can override using the '.groups' argument.
```

```

#9
# pivot the dataset wide so air quality values for ozone and PM2.5 are separate
EPAair_df_processed_wide <- EPAair_df_processed %>%
  pivot_wider(id_cols = c("date", "year", "month", "site_name", "county",
                          "avg_latitude", "avg_longitude"),
              names_from = "aqs_parameter_desc",
              names_prefix = "aqi_value_",
              values_from = "avg_aqi_value")

#10
# call up dimensions
dim(EPAair_df_processed_wide) # 8976 rows x 9 columns

```

```
## [1] 8976    9
```

```

#11
write.csv(EPAair_df_processed_wide,
          file = here("Data/Processed/EPAair_O3_PM25_NC1819_Processed.csv"))

```

Generate summary tables

12. Use the split-apply-combine strategy to generate a summary data frame. Data should be grouped by site, month, and year. Generate the mean AQI values for ozone and PM2.5 for each group. Then, add a pipe to remove instances where mean **ozone** values are not available (use the function `drop_na` in your pipe). It's ok to have missing mean PM2.5 values in this result.
13. Call up the dimensions of the summary dataset.

```

#12
EPAair_df_summary <- EPAair_df_processed_wide %>%
  group_by(month, year, site_name) %>%
  summarize(avg_aqi_PM2.5 = mean(aqi_value_PM2.5),
            avg_aqi_ozone = mean(aqi_value_Ozone)) %>%
  ungroup() %>%
  drop_na(avg_aqi_ozone)

```

```
## 'summarise()' has grouped output by 'month', 'year'. You can override using the
## '.groups' argument.
```

```

#13
dim(EPAair_df_summary) # 182 rows x 5 columns

```

```
## [1] 182    5
```

14. Why did we use the function `drop_na` rather than `na.omit`? Hint: replace `drop_na` with `na.omit` in part 12 and observe what happens with the dimensions of the summary data frame.

Answer: `drop_na` only drops rows where the column given (e.g., `avg_aqi_ozone`) is NA and keeps observations where other columns are NA. Meanwhile `na.omit` drops all observations where any column is NA, so we lose observations with important data.