Smart Meters – Smart Behaviors? An Analysis of London Household Energy Use in Response to Dynamic Time-of-Use Tariffs

ENV 797: Time Series Analysis Final Project

Maeve Gualtieri-Reed, Sylvia Hipp, Sadie Kasten, Josh Salzberg

April 24, 2026

Contents

Introduction **4**

Dataset Information **4**

Raw Data 4

Data Wrangling 4

Analysis **5**

Methods 5

Models 5

Summary and Conclusions **5**

List of Tables

1 Household Load Raw Data 4
2 Tariff Schedule Raw Data 4

List of Figures

Introduction

Dataset Information

Raw Data

The dataset for this project was obtained from a study done by UK Power Networks titled SmartMeter Energy Consumption Data in London Households.[1] The dataset includes energy consumption readings every half hour over the period November 2011 to February 2014. The purpose of the study was to understand how price signals could support higher renewable penetration as well as reduce stress on local distribution grids. 5,566 households participated in the study and were selected as a balanced sample to represent the electricity usage of the Greater London population.

1,123 of the participating households were subject to Dynamic Time of Use (dToU) energy prices throughout 2013. The prices were given to the households a day ahead and were displayed on the customers' smart meter or texted to them directly. Tariffs ranged from High (67.20p/kWh), Normal (11.76p/kWh), or Low (3.99p/kWh). The remaining 4,443 customers ("Standard" households) were given a flat rate tariff of 14.228p/kWh throughout the entire study period. A glimpse of the raw load data by household is shown in [[**Table XX**]] below, where `LCLid` is the unique household i.d., and `stdorTou` indicates whether the households were given standard tariff rates or subject to dToU tariffs. A glimpse of the raw data containing the tariff schedule throughout 2013 is shown in [[**Table YY**]].

Table 1: Household Load Raw Data

LCLid	stdorToU	DateTime	kWhPerHalfHour
MAC000002	Std	2013-01-01 00:00:00.0000000	0.219
MAC000002	Std	2013-01-01 00:30:00.0000000	0.241
MAC000002	Std	2013-01-01 01:00:00.0000000	0.191
MAC000002	Std	2013-01-01 01:30:00.0000000	0.235
MAC000002	Std	2013-01-01 02:00:00.0000000	0.182

Table 2: Tariff Schedule Raw Data

TariffDateTime	Tariff
2013-01-01 00:00:00	Normal
2013-01-01 00:30:00	Normal
2013-01-01 01:00:00	Normal
2013-01-01 01:30:00	Normal
2013-01-01 02:00:00	Normal

Data Wrangling

Both the household load and tariff schedule data were aggregated to the hour as the native half-hour increments complicated the time series seasonality without improving the model. Household load was given as kWh per half hour for each household, so hourly load was taken as the total load over both half hours.[2] For

[1] UK Power Networks. (2015). *SmartMeter energy consumption data in London households.* London Datastore. https://data.london.gov.uk/dataset/smartmeter-energy-consumption-data-in-london-households-vqm0d/.

[2] The initial dataset of household load included over 200 million observations representing 2+ years of data at half-hour increments for over 5,500 households. To make the data more manageable in R, the data was initially wrangled in Python then exported to R. The code for this initial data wrangling can be found in `~/scripts/build/00_lcl_data_build.ipynb`.

the tariff schedule data, in cases where the tariff level differed between the top and bottom of the hour, the following logic was applied to infer tariff level for the whole hour:

1) High and Normal –> High
2) Low and Normal –> Low
3) High and Low –> Normal

After aggregating load data to the half hour, the load dataset was processed to exclude missing data. First, the entire dataset was limited to the period January 2012–December 2013 to exclude periods with sparse data in the last two months of 2011 and first two months of 2014. Second, households with over 2,880 hours of missing data (roughly four months) in 2012 were excluded from the analysis.[3] Finally, any household exhibiting extreme outlier behavior was removed.[4] Following this process, 1,528 Standard households and 362 dToU households remained.

Once the final sample of households was identified, households were separated by treatment group (Standard vs. dToU) and k-means clustering was used to aggregate households based on consumption behavior. Only load data from 2012 was used to identify the clusters so to avoid capturing First, each household's hourly demand was normalized relative to its

[[K-Means Clustering]]

[[Show glimpse of processed data for each time series (?) + plot of the time series]]

Analysis

Methods

Models

Summary and Conclusions

From Canvas: Report Sections:

Introduction, Motivation, Relevance, Objectives Write a few paragraphs detailing the rationale for your study. This should include both the context of the topic as well as a rationale for your choice of dataset (reason for location, variables, etc.). You may choose to include citations if you like or any other reference you may have used during the project (optional).

Dataset information [Sylvia] Provide information on how the dataset for this analysis were collected (source), the data contained in the dataset (format). Describe how you wrangled/processed your dataset to get the time series object.

Add a table that summarizes your data structure (variables, units, ranges and/or central tendencies, data source if multiple are used, etc.). This table should inserted as a `kable` function in an R chunk. Just show the first 10 rows of your data. Do not include the code used to generate your table.

[3] The models in this project were trained on household load data from 2012. Therefore, households with excessive missing data in this year were excluded.

[4] A household was identified as an outlier if the cumulative distance of its hourly usage from the mean was in the 99th percentile among all households.

Analysis (Methods and Models) Describe the analysis and tests that were performed. Described the components of the time series you identified. List any packages and functions used. Include visualizations of your dataset (i.e. time series plot, ACF, PACF, etc).

Format your R chunks so that graphs are displayed but code is not displayed. Accompany these graphs with text sections that describe the visualizations and provide context for further analyses.

Each figure should be accompanied by a caption, and referenced within the text if applicable.

Summary and Conclusions Summarize your major findings from your analyses in a few paragraphs and plots. What conclusions do you draw from your findings? Any insights on how to improve the model?