

Advanced Search

Simulated annealing

Yingyu Liang

`yliang@cs.wisc.edu`

Computer Sciences Department
University of Wisconsin, Madison

[Based on slides from Jerry Zhu, Andrew Moore <http://www.cs.cmu.edu/~awm/tutorials>]



2. SIMULATED ANNEALING

Simulated Annealing

anneal

- To subject (glass or metal) to a process of heating and slow cooling in order to toughen and reduce brittleness.

Simulated Annealing

1. Pick initial state s
2. Randomly pick t in neighbors(s)
3. IF $f(t)$ better THEN accept $s \leftarrow t$.
4. ELSE /* t is worse than s */
5. accept $s \leftarrow t$ with a small probability
6. GOTO 2 until bored.

Simulated Annealing

1. Pick initial state s
2. Randomly pick t in neighbors(s)
3. IF $f(t)$ better THEN accept $s \leftarrow t$.
4. ELSE /* t is worse than s */
5. accept $s \leftarrow t$ with a small probability
6. GOTO 2 until bored.

What are the two key differences from Hill-Climbing?

Simulated Annealing

1. Pick initial state s
2. Randomly pick t in neighbors(s)
3. IF $f(t)$ better THEN accept $s \leftarrow t$.
4. ELSE /* t is worse than s */
5. accept $s \leftarrow t$ with a small probability
6. GOTO 2 until bored.

How to choose the small probability?

idea 1: $p = 0.1$

Simulated Annealing

1. Pick initial state s
2. Randomly pick t in neighbors(s)
3. IF $f(t)$ better THEN accept $s \leftarrow t$.
4. ELSE /* t is worse than s */
5. accept $s \leftarrow t$ with a small probability
6. GOTO 2 until bored.

How to choose the small probability?

idea 1: $p = 0.1$

What's the drawback?

Hint: consider the case when we are at the global optimum

Simulated Annealing

1. Pick initial state s
2. Randomly pick t in neighbors(s)
3. IF $f(t)$ better THEN accept $s \leftarrow t$.
4. ELSE /* t is worse than s */
5. accept $s \leftarrow t$ with a small probability
6. GOTO 2 until bored.

How to choose the small probability?

idea 1: $p = 0.1$

idea 2: p decreases with time

Simulated Annealing

1. Pick initial state s
2. Randomly pick t in neighbors(s)
3. IF $f(t)$ better THEN accept $s \leftarrow t$.
4. ELSE /* t is worse than s */
5. accept $s \leftarrow t$ with a small probability
6. GOTO 2 until bored.

How to choose the small probability?

idea 1: $p = 0.1$


idea 2: p decreases with time

idea 3: p decreases with time, also as the 'badness'
 $|f(s) - f(t)|$ increases

Simulated Annealing

- If $f(t)$ better than $f(s)$, always accept t
- Otherwise, accept t with probability

$$\exp\left(-\frac{|f(s) - f(t)|}{Temp}\right)$$



Boltzmann
distribution

Simulated Annealing

- If $f(t)$ better than $f(s)$, always accept t
- Otherwise, accept t with probability

$$\exp\left(-\frac{|f(s) - f(t)|}{Temp}\right)$$

Boltzmann
distribution

- $Temp$ is a temperature parameter that 'cools' (anneals) over time, e.g. $Temp \leftarrow Temp * 0.9$ which gives $Temp = (T_0)^{\#iteration}$

Simulated Annealing

- If $f(t)$ better than $f(s)$, always accept t
- Otherwise, accept t with probability

$$\exp\left(-\frac{|f(s) - f(t)|}{Temp}\right)$$

Boltzmann
distribution

- $Temp$ is a temperature parameter that ‘cools’ (anneals) over time, e.g. $Temp \leftarrow Temp * 0.9$ which gives $Temp = (T_0)^{\#iteration}$
 - High temperature: almost always accept any t
 - Low temperature: first-choice hill climbing

Simulated Annealing

- If $f(t)$ better than $f(s)$, always accept t
- Otherwise, accept t with probability

$$\exp\left(-\frac{|f(s) - f(t)|}{Temp}\right)$$

Boltzmann
distribution

- $Temp$ is a temperature parameter that ‘cools’ (anneals) over time, e.g. $Temp \leftarrow Temp * 0.9$ which gives $Temp = (T_0)^{\#iteration}$
 - High temperature: almost always accept any t
 - Low temperature: first-choice hill climbing
- If the ‘badness’ (formally known as energy difference) $|f(s) - f(t)|$ is large, the probability is small.

SA algorithm

// assuming we want to maximize $f()$

current = Initial-State(problem)

for $t = 1$ **to** ∞ **do**

$T = \text{Schedule}(t)$; // T is the current temperature, which is monotonically decreasing with t

if $T=0$ **then return** current ; //halt when temperature = 0

next = Select-Random-Successor-State(current)

$\text{delta}E = f(\text{next}) - f(\text{current})$; // If positive, next is better than current. Otherwise, next is worse than current.

if $\text{delta}E > 0$ **then** current = next ; // always move to a better state

else current = next with probability $p = \exp(\text{delta}E / T)$; // as $T \rightarrow 0$, $p \rightarrow 0$; as $\text{delta}E \rightarrow -\infty$, $p \rightarrow 0$

end

Simulated Annealing issues

- Easy to implement.
- Intuitive: Proposed by **Metropolis** in 1953 based on the analogy that alloys manage to find a near global minimum energy state, when annealed slowly.

Simulated Annealing issues

- **Cooling scheme** important
- **Neighborhood design** is the real ingenuity, not the decision to use simulated annealing.
- Not much to say theoretically
 - With infinitely slow cooling rate, finds global optimum with probability 1.
- Try hill-climbing with random restarts first!