

Statistics 6910: Writing Your Own Functions (2)

Control Flow

Computing in R consists of sequentially evaluating statements. *Flow control* structures allow us to control which statements are evaluated and in what order.

In R, the primary ones consist of

- if/else statements and the ifelse function
- for and while loops

Expressions can be grouped together using curly braces “{” and “}”. A group of expressions is called a *block*. For today’s lecture, the word *statement* will refer to either a single expression or a block.

The basic syntax for an if/else statement is

```
if (condition) {
  statement1
} else {
  statement2
}
```

First, `condition` is evaluated. If the first element of the result is `TRUE` then `statement1` is evaluated. If the first element of the result is `FALSE` then `statement2` is evaluated. *Only the first element of the result is used.*

If the result is numeric, 0 is treated as `FALSE` and any other number as `TRUE`. If the result is not logical or numeric, or if it is `NA`, you will get an error.

When we discussed Boolean algebra before, we met the operators `&` (AND) and `|` (OR).

Recall that these are both *vectorized* operators.

If/else statements, on the other hand, are based on a single, “global” condition. So we often see constructions using `any` or `all` to express something related to the whole vector, like

```
if (any(x < -1 | x > 1))
  warning("Value(s) in x outside the interval [-1,1]")
```

(We'll discuss error handling more later.)

The result of an if/else statement can be assigned. For example,

```
> if (any(x <= 0)) y = log(1 + x) else y = log(x)
```

is the same as

```
> y = if (any(x <= 0)) log(1 + x) else log(x)
```

Also, the else clause is optional. Another way to do the above is

```
> if (any(x <= 0)) x = 1 + x
> y = log(x)
```

Note that this version changes `x` as well.

If/else statements can be nested.

```
if (condition1)
  statement1
else if (condition2)
  statement2
else if (condition3)
  statement3
else
  statement4
```

The conditions are evaluated, in order, until one evaluates to `TRUE`. The associated statement/block is evaluated. The statement in the final else clause is evaluated if none of the conditions evaluates to `TRUE`.

A note about formatting if/else statements:

When the if statement is not in a block, the else (if present) must appear on the same line as `statement1` or immediately following the closing brace. For example,

```
if (condition) {statement1}
else {statement2}
```

will be an error if not part of a larger block and/or function. Google's R Style Guide suggests using the format

```
if (condition) {
  statement1
} else {
  statement2
}
```

Some common uses of if/else clauses

1. With logical arguments to tell a function what to do

```
corplot = function(x, y, plotit = TRUE) {
  if (plotit)
    plot(x, y)
  cor(x, y)
}
```

2. To verify that the arguments of a function are as expected

```
if (!is.matrix(m))
  stop("m must be a matrix")
```

3. To handle common numerical errors

```
ratio = if (x != 0) y/x else NA
```

4. In general, to control which block of code is executed

```
normt = function(n, dist) {
  if (dist == "normal") {
    return(rnorm(n))
  } else if (dist == "t") {
    return(rt(n, df = 1, ncp = 0))
  } else {
    stop("distribution not implemented")
  }
}
```

These if/else constructions are useful for global tests, not tests applied to individual elements of a vector.

However, there is a vectorized function called `ifelse`.

```
> args(ifelse)
function (test, yes, no)
```

R object that can be coerced to logical R objects of the same size as test

For each element of `test`, the corresponding element of `yes` is returned if the element is `TRUE`, and the corresponding element of `no` is returned if it is `FALSE`.

Some examples of `ifelse`

```
ratio = ifelse(x != 0, y/x, NA) # (Compare with earlier)
```

```
US.indicator = ifelse(country == "USA", 1, 0)
```

```
plot(Income, Donations,
     col = ifelse(party == "Republican", "red", "blue"))
```


Environments and Scope

Environments and variable scope

R has a special mechanism for allowing you to use the same name in different places in your code and have it refer to different objects.

For example, you want to be able to create new variables in your functions and not worry if there are variables with the same name already in the workspace.

The solution relies on *environments* and the *variable scoping rules*.



When you call a function, R creates a new workspace containing just the variables defined by the arguments of that function. This collection of variables is called a *frame*.

```
> x = c(1, 3, 5, 7, 9); y = rep(2, 3); z = 17
> lookAt = function(x) {
  y = 3
  print(x)
  print(y)
  print(z)
}
```

`x` exists in the `lookAt` frame and so does `y`. However, `z` does not. R has a way of accessing variables that are not in the frame created by the function.

What is happening is that R is looking for variables with that name in a sequence of environments. An *environment* is just a frame (collection of variables) plus a pointer to the next environment to look in.

In our example, R didn't find the variable `z` in the environment defined by the function `lookAt`, so it went on to the next one. In this case, this was our main workspace, which is called the *Global Environment*.

The "next environment to look in" is called the parent environment.

If R reaches the Global Environment and still can't find the variable, it looks in something called the *search path*. This is a list of additional environments, which is used for packages of functions and user attached data. You can see the search path by typing `search()`.

This helps explain why we can write over built-in objects in R. What we're really doing is creating that object in the Global Environment, and then when we refer to it by name, R finds it here before it finds the predefined one.

```
> pi
> pi = 3
> pi
> rm(pi)
> pi
```

CRAN: <http://cran.r-project.org/>



CRAN
Mirrors
What's new?
Task Views
Search

About R
R Home page
The R Journal

Software
R Sources
R Binaries
Packages
Other

Documentation
Manuals
FAQs
Contributed

Contributed Packages

Available Packages

Currently, the CRAN package repository features **4063** available packages.

[Table of available packages, sorted by date of publication](#)

[Table of available packages, sorted by name](#)

Installation of Packages

Please type `help("INSTALL")` or `help("install.packages")` in R for information on how to install packages from this repository. The manual [R Installation and Administration \(PDF\)](#) (also contained in the R base sources) explains the process in detail.

[CRAN Task Views](#) allow you to browse packages by topic and provide tools to automatically install all packages for special areas of interest. Currently, 29 views are available.

Package Check Results

All packages are tested regularly on machines running [Debian GNU/Linux](#), [Fedora](#) and [Solaris](#). Packages are also checked under MacOS X and Windows, but typically only on the day the package appears on CRAN.

The results are summarized in the [check summary](#) (some [warnings](#) are also available). Additional details for Windows checking and building can be found in the [Windows check summary](#).

If a particular package is already installed on your system, you can access its contents by typing

```
> library("nameofpackage")
```

The authors of the package write documentation for the functions and datasets included in it, which you can read as usual using `help()`.

All packages come with a reference manual, which you can access by visiting CRAN. Go to <http://cran.r-project.org/>, click on "Packages," then scroll down for the particular package. This is just a hard copy of the help pages. A few packages also come with a tutorial.

If a particular package is not yet installed on your system, you have to install it first.

If you are using RStudio, choose *Tools*, then *Install Packages*, and type in the first few letters into the *Packages* field until RStudio recognizes the full package name.

You can select more than one package to install. Usually, you want to keep the default settings. Finally, click on *Install*.

Then, you can access your newly installed packages as indicated before:

```
> library("nameofpackage")
```

Search path

- As we load packages into our session, they get added to the search path.

```
> search()
[1] ".GlobalEnv"          "tools:rstudio"
[3] "package:stats"       "package:graphics"
[5] "package:grDevices"   "package:utils"
[7] "package:datasets"    "package:methods"
[9] "Autoloads"           "package:base"
> library(RColorBrewer)
> search()
[1] ".GlobalEnv"          "package:RColorBrewer"
[3] "tools:rstudio"       "package:stats"
[5] "package:graphics"    "package:grDevices"
[7] "package:utils"        "package:datasets"
[9] "package:methods"     "Autoloads"
[11] "package:base"
```

objects()

Show objects in global environment

```
> objects()
[1] "AP"          "Convert"     "age"
[4] "annualQuant" "bmi"         "day"
[7] "deltaWt"     "desiredWt"   "distToPt"
[10] "gender"      "height"      "numInts"
[13] "qqunif"      "rain"        "timesWt"
[16] "weight"      "wifi"
```

Display objects in RColorBrewer package

```
> objects(2)
[1] "brewer.pal"          "brewer.pal.info"
[3] "display.brewer.all"  "display.brewer.pal"
```

Catching Errors

Catching errors

1. The function `stop` stops execution of the current expression and prints a specified error message.

```
> showstop = function(x) {
  if (any(x < 0))
    stop("x must be >= 0")
  return("ok")
}

> showstop(1)
[1] "ok"

> showstop(c(-1, 1))
Error in showstop(c(-1, 1)) : x must be >= 0
```

2. A similar function is `stopifnot`. It has the advantage of being able to take multiple conditions.

```
> showstopifnot = function(x) {
  stopifnot(x >= 0, x %% 2 == 1)
  return("ok")
}

> showstopifnot(1)
[1] "ok"

> showstopifnot(c(1, -1))
Error: all(x >= 0) is not TRUE

> showstopifnot(c(1,2))
Error: x%%2 == 1 is not all TRUE
```

3. Finally, `warning` just prints a warning message without stopping the execution of the function.

```
> ratio.warn = function(x, y) {
  if (any(y == 0))
    warning("Dividing by zero")
  return(x/y)
}

> ratio.warn(x = 1, y = c(1, 0))
[1] 1 Inf
Warning message:
In ratio.warn(x = 1, y = c(1, 0)) : Dividing by zero

> ratio.warn(x = 1:3, y = 1:2)
[1] 1 1 3
Warning message:
In x/y : longer object length is not a multiple of shorter object length
```

The for statement

Looping is the repeated evaluation of a statement or block of statements.

Much of what is handled using loops in other languages can be more efficiently handled in R using vectorized calculations or one of the apply mechanisms.

However, certain algorithms, such as those requiring recursion, can only be handled by loops.

There are two main looping constructs in R: `for` and `while`.

For loops

A *for loop* repeats a statement or block of statements a predefined number of times.

The syntax in R is

```
for (name in vector) {
  statement
}
```

For each element in `vector`, the variable `name` is set to the value of that element and `statement` is evaluated.

`vector` often contains integers, but can be any valid type.

While loops

A *while loop* repeats a statement or block of statements for as many times as a particular condition is `TRUE`.

The syntax in R is

```
while (condition) {
  statement
}
```

`condition` is evaluated, and if it is `TRUE`, `statement` is evaluated. This process continues until `condition` evaluates to `FALSE`.

The expression

```
sample(c(1, 0), size = 1, prob = c(p, 1-p))
```

simulates a random coin flip, where the coin has probability p of coming up heads, represented by a 1.

If `prob` is omitted, all possible outcomes are equally likely.

The break statement causes a loop to exit. This is particularly useful with while loops, which, if we're not careful, might loop indefinitely (or until we kill R).

```
# Simulate number of tosses to get 10 Heads
```

```
max.iter = 1000
x = 0
steps = 0
while (x < 10) {
  x = x + sample(c(0, 1), 1)
  steps = steps + 1
  if (steps == max.iter) {
    warning("Maximum iteration reached")
    break
  }
}
```