

# Claude Code — Built-in Slash Commands Reference

**Source:** Official Claude Code Docs ([code.claude.com/docs/en/commands](https://code.claude.com/docs/en/commands))

**Last updated:** April 2026 | Claude Code v2.1.x

**Note:** Commands marked **[Skill]** are bundled skills (prompt-based, not hardcoded logic). Not every command appears for every user — availability depends on your platform, plan, and environment.

## Session & Context Management

| Command                                              | Purpose                                                                                                                                        |
|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>/clear</code>                                  | Clear conversation history and free up context. <b>Aliases:</b> <code>/reset</code> , <code>/new</code>                                        |
| <code>/compact</code><br><code>[instructions]</code> | Compact conversation with optional focus instructions (e.g., <code>/compact keep architecture decisions</code> )                               |
| <code>/context</code>                                | Visualize current context usage as a colored grid. Shows optimization suggestions and capacity warnings                                        |
| <code>/btw &lt;question&gt;</code>                   | Ask a quick side question without adding it to the main conversation thread                                                                    |
| <code>/rewind</code>                                 | Rewind the conversation and/or code to a previous checkpoint. <b>Alias:</b> <code>/checkpoint</code>                                           |
| <code>/resume [session]</code>                       | Resume a past session by ID or name, or open a session picker. <b>Alias:</b> <code>/continue</code>                                            |
| <code>/rename [name]</code>                          | Rename the current session. Without a name, auto-generates one from conversation history                                                       |
| <code>/branch [name]</code>                          | Create a branch (fork) of the current conversation at this point. <b>Alias:</b> <code>/fork</code>                                             |
| <code>/export [filename]</code>                      | Export the current conversation as plain text. Without filename, opens dialog to copy or save                                                  |
| <code>/copy [N]</code>                               | Copy the last assistant response to clipboard. <code>/copy 2</code> copies the second-to-last. Press <code>w</code> in picker to write to file |

## Model & Configuration

| Command                                                         | Purpose                                                                                                     |
|-----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| <code>/model [model]</code>                                     | Switch the AI model mid-session. Use left/right arrows to also adjust effort level                          |
| <code>/effort</code><br><code>[low medium high max auto]</code> | Set the model effort/thinking level. <code>max</code> is Opus 4.6 only and applies to current session only  |
| <code>/fast [on off]</code>                                     | Toggle fast mode on or off                                                                                  |
| <code>/config</code>                                            | Open the settings interface (theme, model, output style, preferences). <b>Alias:</b> <code>/settings</code> |
| <code>/theme</code>                                             | Change the color theme, including colorblind-accessible (daltonized) and ANSI variants                      |

|                                     |                                                                                                                             |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <code>/color [color default]</code> | Set the prompt bar color for the current session. Options: red, blue, green, yellow, purple, orange, pink, cyan             |
| <code>/output-style [style]</code>  | Set response formatting style (Default, Explanatory, Learning, or custom). Use <code>/output-style:new</code> to create one |

## Agentic Workflows (Bundled Skills)

These use the same skill mechanism you can write yourself — a prompt handed to Claude, which Claude can also invoke automatically.

| Command                                                 | Purpose                                                                                                                                                                                                                                                              |
|---------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>/batch</code><br><code>&lt;instruction&gt;</code> | <b>[Skill]</b> Orchestrate large-scale changes across a codebase in parallel. Decomposes into 5–30 independent units, spawns one background agent per unit in isolated git worktrees, each opens a PR. Example: <code>/batch migrate src/ from Solid to React</code> |
| <code>/simplify [focus]</code>                          | <b>[Skill]</b> Review recently changed files for code reuse, quality, and efficiency by spawning three review agents in parallel, then applies fixes. Example: <code>/simplify focus on memory efficiency</code>                                                     |
| <code>/debug</code><br><code>[description]</code>       | <b>[Skill]</b> Enable debug logging for the session and troubleshoot by reading the session debug log. Optionally describe the issue to focus analysis                                                                                                               |
| <code>/loop [interval]</code><br><code>[prompt]</code>  | <b>[Skill]</b> Run a prompt repeatedly while the session stays open. Claude self-paces if no interval is given. Example: <code>/loop 5m check if the deploy finished</code>                                                                                          |
| <code>/claude-api</code>                                | <b>[Skill]</b> Load Claude API reference material for your project's language (Python, TypeScript, Java, Go, etc.). Also auto-activates when your code imports the Anthropic SDK                                                                                     |

## Permissions & Tools

| Command                            | Purpose                                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <code>/permissions</code>          | Manage allow/ask/deny rules for tool permissions interactively. <b>Alias:</b> <code>/allowed-tools</code> |
| <code>/hooks</code>                | View and configure hook rules for tool events                                                             |
| <code>/mcp</code>                  | Manage MCP server connections and OAuth authentication                                                    |
| <code>/add-dir &lt;path&gt;</code> | Add a working directory for file access during the current session                                        |
| <code>/sandbox</code>              | Toggle sandbox mode (available on supported platforms only)                                               |

## Project Initialization & Memory

| Command            | Purpose                                                                                                                                                              |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>/init</code> | Initialize the project with a <code>CLAUDE.md</code> guide. Set <code>CLAUDE_CODE_NEW_INIT=1</code> for an interactive flow covering skills, hooks, and memory files |

|         |                                                                                       |
|---------|---------------------------------------------------------------------------------------|
| /memory | Edit CLAUDE.md memory files, enable/disable auto-memory, and view auto-memory entries |
| /skills | List all available skills                                                             |
| /agents | Manage subagent configurations — view, create, and edit subagents                     |

## Git, Code Review & CI

| Command                 | Purpose                                                                                                                              |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| /diff                   | Open an interactive diff viewer for uncommitted changes and per-turn diffs. Use arrows to navigate files and turns                   |
| /security-review        | Analyze pending changes on the current branch for security vulnerabilities (injection, auth issues, data exposure)                   |
| /autofix-pr<br>[prompt] | Spawn a web session that watches the current branch's PR and pushes fixes when CI fails or reviewers leave comments. Requires gh CLI |
| /install-github-app     | Set up the Claude GitHub Actions app for automated PR reviews                                                                        |

## IDE & Interface

| Command         | Purpose                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------|
| /ide            | Manage IDE integrations and show status                                                             |
| /desktop        | Continue the current session in the Claude Code Desktop app (macOS and Windows). <b>Alias:</b> /app |
| /terminal-setup | Configure terminal keybindings (Shift+Enter etc.) for VS Code, Alacritty, Warp                      |
| /keybindings    | Open or create your keybindings configuration file                                                  |

## Account & Billing

| Command      | Purpose                                                        |
|--------------|----------------------------------------------------------------|
| /login       | Sign in to your Anthropic account                              |
| /logout      | Sign out of your Anthropic account                             |
| /cost        | Show token usage and cost statistics                           |
| /usage       | Show plan usage limits and rate limit status                   |
| /extra-usage | Configure extra usage to keep working when rate limits are hit |
| /upgrade     | Open the upgrade page to switch to a higher plan tier          |

|                   |                                                                          |
|-------------------|--------------------------------------------------------------------------|
| /privacy-settings | View and update privacy settings (Pro and Max only)                      |
| /passes           | Share a free week of Claude Code with friends (only visible if eligible) |

## Cloud, Remote & Teleport

| Command                    | Purpose                                                                                                    |
|----------------------------|------------------------------------------------------------------------------------------------------------|
| /schedule<br>[description] | Create, update, list, or run Cloud scheduled tasks conversationally                                        |
| /remote-control            | Make this session available for remote control from claude.ai. <b>Alias:</b> /rc                           |
| /remote-env                | Configure the default remote environment for web sessions started with --remote                            |
| /teleport                  | Pull a Claude Code on the web session into your terminal — opens a session picker.<br><b>Alias:</b> /tp    |
| /ultraplan <prompt>        | Draft a plan in an ultraplan session, review it in browser, then execute remotely or send back to terminal |
| /autofix-pr [prompt]       | Spawn a web session watching the current PR for CI failures and review comments                            |

## Utility & Information

| Command                | Purpose                                                                                              |
|------------------------|------------------------------------------------------------------------------------------------------|
| /help                  | Show help and all available commands                                                                 |
| /doctor                | Diagnose and verify your Claude Code installation and settings                                       |
| /status                | Open Settings → Status tab (version, model, account, connectivity). Works while Claude is responding |
| /stats                 | Visualize daily usage, session history, streaks, and model preferences                               |
| /insights              | Generate a report analyzing your Claude Code sessions for patterns and friction points               |
| /context               | Visualize current context usage — shows free space and per-category breakdown                        |
| /release-notes         | View the changelog in an interactive version picker                                                  |
| /feedback [report]     | Submit feedback to Anthropic. <b>Alias:</b> /bug                                                     |
| /plan<br>[description] | Enter plan mode. Pass a description to begin immediately: /plan fix the auth bug                     |
| /tasks                 | List and manage background tasks. <b>Alias:</b> /bashes                                              |
| /powerup               | Walk through Claude Code features with interactive animated demos                                    |
| /team-onboarding       | Generate a team onboarding guide from your last 30 days of Claude Code usage                         |
| /voice                 | Toggle push-to-talk voice dictation (requires Claude.ai account)                                     |

|         |                                                                                |
|---------|--------------------------------------------------------------------------------|
| /mobile | Show QR code to download the Claude mobile app. <b>Aliases:</b> /ios, /android |
| /exit   | Exit the CLI. <b>Alias:</b> /quit                                              |

## Setup & Platform-Specific

| Command            | Purpose                                                                                                                     |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------|
| /setup-bedrock     | Configure Amazon Bedrock authentication, region, and model pins interactively (only visible when CLAUDE_CODE_USE_BEDROCK=1) |
| /setup-vertex      | Configure Google Vertex AI authentication, project, and region interactively (only visible when CLAUDE_CODE_USE_VERTEX=1)   |
| /install-slack-app | Install the Claude Slack app via OAuth browser flow                                                                         |
| /plugin            | Manage Claude Code plugins                                                                                                  |
| /reload-plugins    | Reload all active plugins to apply changes without restarting                                                               |
| /chrome            | Configure Claude in Chrome extension settings                                                                               |

## MCP Prompts (Dynamic)

MCP servers can expose prompts that appear as commands in the format:

```
/mcp__<server-name>__<prompt-name>
```

These are dynamically discovered from connected MCP servers and vary per user setup.

## Model Aliases (for /model command)

| Alias      | Resolves To                        | Best For                 |
|------------|------------------------------------|--------------------------|
| default    | Clears override, uses plan default | Resetting to recommended |
| best       | Latest Opus                        | Most capable available   |
| sonnet     | Sonnet 4.6                         | Daily coding (default)   |
| opus       | Opus 4.6                           | Complex reasoning        |
| haiku      | Haiku 4.5                          | Fast, simple tasks       |
| sonnet[1m] | Sonnet 4.6 (1M context)            | Very long sessions       |
| opus[1m]   | Opus 4.6 (1M context)              | Large codebase analysis  |
| opusplan   | Opus (plan) → Sonnet (execute)     | Best of both worlds      |

## Thinking Keywords (Prompt-Level)

These only work in Claude Code's terminal — not in claude.ai chat or the API.

| Keyword    | Effect                                                                  |
|------------|-------------------------------------------------------------------------|
| ultrathink | Triggers high effort for that one turn, then reverts to session default |

**Note:** The old tier ladder ( `think` → `think hard` → `megathink` → `ultrathink` ) was a v1 mechanism. On modern Claude 4.6 models with adaptive thinking, phrases like "think" and "think hard" are treated as regular prompt instructions, not system-mapped triggers. Use `/effort` for persistent control.

## Effort Levels (for `/effort` command)

| Level  | Behaviour               | Persists Across Sessions  |
|--------|-------------------------|---------------------------|
| low    | Faster, less thorough   | Yes                       |
| medium | Default for Pro/Max     | Yes                       |
| high   | Deep reasoning          | Yes                       |
| max    | Maximum (Opus 4.6 only) | No (current session only) |
| auto   | Reset to model default  | —                         |

## Key Keyboard Shortcuts

| Shortcut             | Action                                                            |
|----------------------|-------------------------------------------------------------------|
| Shift+Tab            | Cycle through permission modes: Normal → Auto-Accept → Plan Mode  |
| Ctrl+O               | Toggle verbose mode (shows extended thinking as gray italic text) |
| Ctrl+G               | Open current plan in your default text editor                     |
| Ctrl+T               | Toggle background task list display                               |
| Option+T / Alt+T     | Enable/disable extended thinking                                  |
| Esc Esc (double tap) | Time machine — browse all prompts from current session            |
| ↑ arrow              | Navigate back through past prompts (even from previous sessions)  |

## CLI Flags (at Startup)

```
claude --model <alias|name>           # Set model for this session
claude --name "session-name"          # Start with a named session
claude -n "session-name"              # Short form
claude --continue                     # Resume last session
claude -c                             # Short form
```

```
claude --resume [session]      # Open session picker or resume by name/ID
claude -r                      # Short form
claude --from-pr 142           # Resume session linked to a PR
claude --teleport [session-id] # Pull a cloud session to terminal
claude --remote "task description" # Start a task in the cloud
claude --permission-mode plan  # Start in Plan Mode
claude --worktree [name]       # Start in an isolated git worktree
claude --debug                 # Start with debug logging enabled
claude -p "prompt"             # Headless / non-interactive mode
```

---

## Where Sessions Are Stored

```
~/.claude/projects/<encoded-project-path>/*.jsonl
```

Each `.jsonl` file is a complete conversation record. Sessions never auto-delete.

---

Source: [Claude Code Commands Reference](#) — Official Anthropic Documentation