THE PRODUCT + ECOSYSTEM GUIDE / OCTOBER 2026

Discover synergy network



Security.
Intelligence.
Your control.

Your guide to security, Jarvis, and the connected ecosystem.

SECURE BY DESIGN
Explore a Layer-1 network that connects account protection, post-quantum authority, encrypted transaction handling, and purpose-built applications.

ONE CONNECTED EXPERIENCE
Learn how Jarvis brings questions, network information, and wallet-reviewed actions into one conversation.

MORE THAN A TRANSACTION
Trade, create, play, build, govern, and protect information without treating convenience as permission to take control.

START HERE

A network you can understand and use.

Security is the starting point. Everyday usefulness is the reason it matters.

05 Protect your account
10 Explore the technology
22 Meet Jarvis
25 Find your applications
31 Understand SNRG
36 Get clear answers

The idea in one minute

Synergy brings the account, transaction pipeline, application rules, and user experience into one connected architecture. Aegis governs cryptographic authority. Protected accounts separate ordinary spending from recovery. ETDAG prepares encrypted transactions and commits their order before reveal. SynQ and AIVM define how applications handle assets and execute. PoSy establishes the accepted result. Jarvis helps you navigate the experience without becoming the owner of your wallet.

Read benefits alongside their boundaries

Native means a protection belongs to Synergy's own account or protocol rules. A connected external wallet, exchange, website, or blockchain can have different rules. Matching names, familiar icons, or a single interface do not erase those differences. Throughout this guide, the important boundary appears beside the feature rather than being hidden in technical language.

Know which release and account you are using

This guide explains the product and security architecture. Feature availability and enabled protections depend on the network, account profile, application release, and connected service. Architecture descriptions are not evidence that every capability is deployed, independently audited, or available on every device. Check official release information and the actual account's security profile before relying on a feature.

Choose the experience. Understand the permission. Keep the decision.

SOURCES [1] Claim taxonomy and AI.14; [2] Sections 1-2, 12; [3]

THE SYNERGY DIFFERENCE

Security beyond the ledger.

A valid signature is only one part of a protected transaction.

Protect the account

Independent ordinary approvals and a separate recovery role reduce reliance on one device or one stolen secret. The protected recovery phrase is not a conventional master seed that recreates every spending key.

Limit the damage

Account rules address how much can leave, when protected funds become spendable, and which recipients are trusted. A valid signature does not automatically override those limits.

Protect the waiting transaction

ETDAG keeps protected contents encrypted until their eligible order is committed. Asynchronous preparation separates intake work from the block-production cycle without turning a queue receipt into settlement.

Make application powers explicit

SynQ and AIVM connect asset rules, limited permissions, readable effects, code checks, and controlled execution. An application does not gain unlimited authority just because you opened it.

Keep native authority post-quantum

Aegis manages role-specific keys and cryptographic profiles. The protected native model requires its post-quantum condition across sufficient control paths, including changes that could otherwise remove that protection.

Make the ecosystem approachable

Jarvis turns several services into one user journey. He can obtain token information, coordinate a requested quote, and send the action to mobile Wallet review. Your chat conversation is not a substitute for your signature.

The distinction is how the protections work together – before, during, and after an action.

SOURCES [1] AI.1-AI.14; Category 33; ETDAG; [2] Sections 1-2, 6, 11

THE WHOLE PICTURE

Different jobs.
One connected network.

You do not need to memorize the technology names. Start with what each part does for you.

PoSy + Aegis

Proof-of-Synergy establishes the accepted chain history. Aegis governs the keys, algorithms, and authorization used by native accounts and network roles. Neither a popular validator nor a familiar application can make an invalid action valid.

ETDAG + SynQ + AIVM

ETDAG handles encrypted transaction preparation and protected ordering. SynQ expresses application logic, assets, and permissions. AIVM admits and executes authorized work, checks its boundaries, and produces a result for consensus validation.

Wallet + identity + shared control

Wallet is the account-selection, review, and signing surface. SynID helps people recognize account relationships. Multi-signature policies distribute real authority. A name or matching address is not itself permission to spend.

SXCP + SCETP

SXCP verifies defined external-chain facts and coordinates authorized cross-chain workflows. SCETP handles properly authorized external or wallet-originated intent affecting Synergy. Carrying a request is not the same as owning the assets.

The product family

Portal is the hub. Wallet, Atlas, Forge, Keystone, and Horizon are core applications. Relay, Spark, and Vault provide trading, community and creation, and protected-document experiences. Spark contains Social, Launch, Create, and Arcade.

Jarvis across the experience

Jarvis is the Network Assistant, available through the described chat entry points in Portal, Atlas, the main website, and Relay. He connects services around your question or requested task; each service retains its own responsibilities and permission boundaries.

Connected does not mean one component has the power to do everything.

SOURCES [1] Sections 0.1-0.3; AI; [2] Sections 2, 11-12; [3]

PROTECTED ACCOUNTS

One device is not the whole wallet.

Ordinary native spending requires independent approval, not just another button in the same app.

Two signers, one exact action

The protected native account model requires a primary signer and an independent companion signer to approve the same transaction. Both review the network, sending account, recipient, asset, amount, requested permissions, and fee limits. Their signatures bind to the actual action rather than a reassuring label supplied by a website.

Independence has a real meaning

Two browser windows, two folders, or two virtual machines on one computer are not independent signing devices. The model separates the signing roles into distinct physical security domains. Copying a key or synchronizing a credential does not create another independent approval. This matters because a single compromised environment should not silently supply the full ordinary spending quorum.

Recovery is a different role

The recovery participant cannot replace either ordinary signer for a routine native transfer, application call, deployment, or permission grant. Its authority is limited to the enrolled recovery process. Even additional high-value approvals strengthen the ordinary requirements rather than removing them. Small payments are not a loophole that reduces the protected account to one signer.

Your account policy still applies

Correct signatures are necessary, but they are not the entire decision. Spending limits, recipient conditions, pending restrictions, protected-reserve rules, and the current account policy also apply. The selected account type matters: an imported legacy wallet or external account does not acquire this native model simply because Wallet displays it alongside a protected account.

Independent consent and active account policy are complementary protections.

Independent approval reduces a single-point failure. It does not eliminate deception, coercion, or compromise of all required authorities.

SOURCES [1] AI.3-AI.7; [2] Section 3

RECOVERY & CONTINUITY

Recover access.
Keep powers separate.

Losing a device should not mean giving a help desk a hidden master key.

The phrase is not the spending root

Fresh protected accounts generate their spending authority independently from their recovery material. The phrase protects a recovery package; it does not recreate all spending keys through a conventional master-seed path. Restoring the allowed package restores at most the recovery role, not a complete ordinary native spending quorum. The phrase remains sensitive and must still be kept private.

Replace a role through the account rules

The enrolled recovery path combines the recovery role with a surviving authorized participant and uses a delayed transition with the required review, cancellation, and veto rules. A replacement does not become active just because someone opens a recovery screen. Current policy controls the process until the authorized change takes effect.

Prove the backup before relying on it

Protected-funding readiness includes verified enrollment and an actual recovery drill. A newly displayed address is not enough. The account record, signing participants, provider capabilities, and recovery package must agree. A sponsor can help pay enrollment costs without gaining ownership. Support can explain the procedure without acquiring the ability to bypass it.

Keep continuity honest across networks

Eligible native key changes preserve the enrolled native account identifier while replacing current authority. External EVM address preservation depends on a supported process preserving the same aggregate public key. Replacing that key requires a new external address and an authorized migration. Refreshing honest shares does not revoke a full external private key or compatible old signing quorum already captured by an attacker.

A recovery process restores permitted authority. It does not undo every completed transfer.

Recovery availability depends on the enrolled roles, surviving participants, provider capability, and account policy. There is no staff override.

SOURCES [1] AI.2-AI.7; [2] Section 3

CLEAR CONSENT

Know exactly what you are signing.

An approval should describe a real action, not ask you to trust an unreadable request.

Read the effects, not just the button

Wallet review identifies the selected account and network, actual recipient or contract, assets leaving and expected to arrive, permission changes, and maximum fees. Human-readable action descriptions are checked against the proposed transaction. A batch must expose the relevant combined effects; an innocent-looking outer label must not hide an additional transfer or broader permission.

See a simulation before deciding

Simulation gives you evidence about the proposed action in a specific state and execution context. It helps reveal unexpected balance changes or permissions before signing. Required verification failures cannot be dismissed with a generic acknowledgment for protected operations. The review is not a guarantee of future market conditions, and an estimate is not the same as a completed result.

Grant a task, not an open-ended right

Scoped permissions limit the action, amount, recipient, context, and validity period. Approval expiry stops an old grant from remaining usable indefinitely. Spend-capable messages, token permits, trading orders, and NFT orders deserve the same seriousness as a transfer; a request described as a login must not secretly become financial authority.

Bind approval to the right context

Signed instructions carry account, network, operation, sequence, fee, and validity constraints. Reusing them elsewhere or changing reviewed terms is not authorized. Protected-v1 rules disable raw eth_sign, EIP-7702 authorization, and automatic agent/session spending. Jarvis and connected applications cannot use convenience to bypass those account requirements.

A question is not a purchase. A quote is not a signature. A signature is not unlimited permission.

Imported and connected external accounts retain their actual signing model. Always review the account and chain shown in the wallet.

SOURCES [1] AI.4, AI.7; Categories 1-4, 9-10, 14; [2] Sections 3, 7, 11

ANTI-DRAIN PROTECTION

Make a rapid loss harder to carry out.

Account security includes what happens after an attacker obtains some authority.

Separate daily spending from reserves

The account model distinguishes readily usable spending capacity from balances subject to stronger release rules. That makes room for ordinary activity without making an entire savings or treasury balance immediately available through the same path. Protected ordinary spending still requires the independent approvals; the smaller spending band does not remove them.

Count the total outflow

An attacker may divide a large withdrawal into many smaller attempts. Aggregate-outflow controls consider movement across a defined window, including pending commitments, rather than checking each payment in isolation. Parallel submissions do not erase the total. The active policy defines the limits; there is no universal dollar threshold that applies to every account.

A test payment does not create trust

Unknown or probationary recipients remain distinct from explicitly trusted destinations. A tiny successful payment proves delivery, not permission for unrestricted future payments. Promoting a recipient is its own authorized policy action. This closes an easy conceptual gap between checking an address and deciding how much authority it should receive.

Keep pending funds from becoming an escape route

A delayed protected transfer does not immediately give the recipient spendable value. Before release, the protected output cannot be forwarded, swapped, pledged, or routed away through the native execution path. That creates a defined interval in which eligible cancellation or containment can matter, instead of allowing a pending transfer to become the first hop of a rapid drain.

The model checks the movement of value – not only whether a signature is valid.

Limits and delays constrain particular paths. They do not insure asset values or guarantee recovery after funds become available on another network.

SOURCES [1] AI.4-AI.5; Categories 5, 33; [2] Section 4

CONTAINMENT & RESERVES

The power to stop is not the power to take.

Emergency response can restrict eligible activity without installing a new owner.

A bounded emergency stop

A separately enrolled stop-only authority can impose the restrictions its account policy permits, such as freezing protected outflow, cancelling eligible pending transfers, or blocking external egress. It does not need ordinary spending approval or completion of a replacement-key delay to impose that restriction. It cannot spend, choose a new recipient, install signers, or acquire general unfreeze authority.

Protection cannot disappear in one click

Raising limits, shortening delays, removing protective roles, broadening routes, or weakening reserve rules follows the authorized policy-change process. The security-policy latch preserves the required challenge window. A generic settings change, recovery action, or module update is not an alternative way to switch off a safeguard immediately.

Unlock first; spend through a separate step

Account-level Vault Mode separates a bounded reserve-unlock request and its challenge period from the later transfer. Direct spending and a same-step unlock-and-drain are not the specified route. This reserve feature is different from the Vault application, which handles documents and protected data.

Control the exit and preserve evidence

Moving protected funds to another chain is a separate security decision. The approved intent fixes the route, network, asset, recipient, fee and slippage limits, and expiry. Additional authorization or release conditions can apply. Security receipts record the relevant policy, approvals, effects, and outcome so authorized reviewers can investigate what happened without relying on a vague success message.

Contain the incident now. Replace authority only through the proper recovery process.

A compromised stop credential can disrupt availability. Its scope and restoration rules matter; it is not a central company kill switch or a rewind button.

SOURCES [1] AI.5, AI.9, AI.11, AI.14; Category 33; [2] Section 4

AEGIS

Post-quantum protection with a lifecycle.

Not just a stronger signature option – a model for how native authority is created, used, and changed.

What post-quantum means

Digital signatures prove that an action carries the required cryptographic authorization. Post-quantum methods address attacks that sufficiently capable quantum computers could bring against important classical public-key systems. They operate on ordinary computers. They do not require a quantum computer in your phone, and they do not make phishing or malicious applications disappear.

No classical-only shortcut around native protection

For protected native accounts and protocol authority, the required post-quantum condition remains part of every sufficient control path. Spending is not the only path that matters: recovery activation, signer policy, modules, verifiers, and upgrades cannot quietly remove it. An external signature or a post-quantum-signed relay report is not automatically the account's own required approval.

Different roles; different keys

Spending, recovery, consensus, and encrypted communications have different jobs. Aegis assigns role-specific keys and algorithm profiles instead of treating one credential as universal authority. Its lifecycle includes registration, rotation, revocation, and controlled migration. Cryptographic agility means protection can evolve through explicit rules rather than relying on a claim that one algorithm is perfect forever.

Understand the standards and the boundary

The specified native account-signature profile uses ML-DSA-87, and participant-channel profiles include ML-KEM. NIST standardizes these algorithm families in FIPS 204 and FIPS 203; that is not certification of Synergy's complete implementation. External EVM accounts still use the signature rules accepted by their destination chains. Better custody does not turn classical external signing into native post-quantum authorization.

Native protection is a defined authority boundary, not a badge that changes every connected chain.

SOURCES [1] AI.1, AI.6-AI.8; Categories 19-23; [2] Section 5; [4-5]

ETDAG

Commit the order.
Then reveal the transaction.

Protected pending instructions should not be a free preview for someone choosing where to place them.

Why the waiting period matters

A readable pending trade can reveal what a user intends to buy or sell before execution. That creates an opportunity to inspect the request and try to position around it. Synergy's Encrypted Transaction Directed Acyclic Graph – ETDAG – addresses that inspection advantage by connecting encrypted submission to a binding order-before-reveal rule.

Seal the instruction

The protected flow signs the complete transaction locally and encrypts it before network submission. The public transaction-data path exposes only the limited information needed for its admission and resource checks. Encryption protects the meaningful instruction while its place is still being established; it is not merely a private message sent to a single privileged operator.

Check that the sealed data exists

Validators establish durable possession and availability of the encrypted material before it becomes eligible for ordering. The network then closes the eligible set and commits its order. It cannot legitimately certify a batch it cannot retrieve, or reopen a fixed set to slip in a late transaction after learning what the earlier instructions contain.

Open only at the permitted point

Threshold reveal follows the required ordering commitment. The revealed transactions are checked and executed in that committed order. ETDAG does not make an invalid instruction valid, and its availability certificate is not final settlement. AIVM supplies controlled execution; PoSy remains the authority for the accepted chain result. Failure to complete the protected reveal path does not silently authorize plaintext publication.

Sealed instructions. Verified availability. Binding order. Controlled reveal.

ETDAG is not permanent anonymity, perfect arrival-order fairness, or elimination of all extractable value. Endpoint, metadata, collusion, and external-market risks have separate boundaries.

SOURCES [1] ETDAG Architecture and Lifecycle; Categories 16-18, 27; [2] Section 6

ASYNCHRONOUS ETDAG

A pipeline, not a single waiting line.

Transaction preparation and block production have different jobs – and do not have to run as one blocking step.

Prepare work separately

Receiving a request, storing ciphertext, checking eligibility, and establishing availability take different kinds of work from proposing and voting on a block. Asynchronous ETDAG schedules those preparation stages separately from PoSy's consensus cycle. Different batches can be at different stages while consensus handles material eligible for the actual block and preceding chain state.

Hand off evidence, not assumed success

The handoff consists of bounded, authenticated prepared material. It is not a set of pre-finalized future blocks. PoSy still checks the relevant height, state, and evidence. The selected scheduling direction retains target-bound signed material; moving work into a queue does not authorize silently retargeting it. An early receipt confirms a reached stage, not an unconditional promise of inclusion or success.

Keep the user's terms intact

Waiting does not let a service change the recipient, network, asset, amount, fees, expiry, or signed target. Closed ordering sets stay closed. Protected contents are not revealed early, and finalized blocks are not retroactively filled with new requests. An expired or materially changed trade needs the appropriate fresh proposal and authorization rather than a silent replacement.

Separate responsiveness from settlement

A user can receive meaningful progress information before the action settles. Wallet, Atlas, and Jarvis can describe the actual state using receipts and chain evidence. That is a clearer experience than treating every stage as either nothing or done. It does not prove an instant settlement time, unlimited queue capacity, or a particular transactions-per-second result.

Asynchronous describes when work happens. It does not remove ordering, authority, or finality checks.

Asynchronous preparation is not automatically parallel state execution. Dependent transactions still respect balances, account sequences, and the agreed result.

SOURCES [2] Section 6 and S7 scheduling source; [1] ETDAG; AI.4; Category 31

FOLLOW YOUR TRANSACTION

Received is not the same as completed.

A useful progress screen tells you what is known, what is still pending, and what the final result actually says.

01
Received and durably queued

Receipt of a request and durable storage are different milestones. A durable acknowledgment means the encrypted submission is stored for processing. It does not prove that it has been admitted, executed, or settled. A receipt lookup helps identify an existing request after an interrupted connection.

02
Admitted and available

The request meets the applicable target-admission conditions, and the required encrypted material has availability evidence. Possession of that data does not prove that the hidden action will succeed. Account policy, balance, sequence, and other execution conditions still matter.

03
Ordered and revealed

The eligible set closes and its protected order becomes binding. Only the authorized reveal stage makes contents readable. The revealed action must match the committed material; neither a later arrival nor a better-looking trade can justify changing that order.

04
Executed and finalized

Eligible work is considered for the correct block and state. An execution result is not finality by itself. PoSy establishes the accepted chain result, and the recorded outcome distinguishes success from failure. Rejection, expiry, or a failed included action must not be reported as a completed payment.

Pressure, retries, and restarts

Bounded queues make overload explicit instead of pretending that capacity is unlimited. Durable receipts and duplicate reconciliation prevent an ambiguous reply from becoming an accidental second spend. An intake backlog must not create an unbounded consensus wait, but progress still depends on quorum and valid evidence.

Jarvis reports; the network decides

Jarvis can explain a queued, ordered, processing, or finalized state from the relevant service. Asking for a status update is not permission to issue a replacement trade. A chat can remain useful while the chain does its work, without becoming the authority that decides whether the payment happened.

Quick acknowledgment is a user-experience benefit. Finalized success is a separate result.

SOURCES [2] Section 6; Jarvis lifecycle; S7 scheduling source; [1] AI.7, AI.14

PROOF-OF-SYNERGY

Agreement comes before a speed claim.

PoSy turns eligible transactions and execution evidence into the network's accepted history.

Cooperation with independent checks

Proof-of-Synergy is the consensus system. Validators independently check the blocks, transactions, results, and evidence required by the active rules. Finality depends on the required quorum and certificates. Cooperation, participation, and contribution are useful only when the result still satisfies those rules.

What Synergy Score contributes

Synergy Score can influence eligibility, incentives, or network policy in the documented architecture. A good reputation or useful service does not turn an invalid transaction into a valid one. Score, cryptographic correctness, and the voting requirements for finality are distinct responsibilities rather than interchangeable measures of trust.

Reliability includes bad conditions

Durable signing safety, authenticated peers, diverse discovery, bounded resources, retained evidence, and controlled recovery address restarts, delays, deceptive peers, and partitions. When required conditions fail, preserving safety can mean refusing progress rather than accepting conflicting history. A chain that pauses safely is different from one that silently changes its rules.

Measure the complete job

ETDAG preparation, protected ordering, AIVM execution, and PoSy finality are separate stages. Submission volume, queue entries, ordered envelopes, successful execution, and finalized throughput are not the same metric. Faster empty blocks do not establish faster completed payments. Useful comparisons specify the workload, hardware, release, failures, and final result rather than just a headline number.

Prepare independently. Verify independently. Agree on one accepted result.

Consensus assumptions, network availability, and implementation quality still matter. No unverified throughput, latency, energy, or fee advantage is implied.

SOURCES [1] Categories 16-18, 25-27, 31; [2] Section 10; S7 scheduling source

IDENTITY & TRUST

Names that help. Proof that matters.

An account can be recognizable without confusing appearance, identity, and authority.

A name is not a signing key

SynID gives human-readable .syn names a place in the user experience. Name control, payment destination, account identity, and signing authority remain separate. Linking an ENS name or Basename needs evidence of the relevant current relationships; a signature from a receiving address alone does not necessarily prove ownership of the name.

Familiar account bytes; distinct chains

The protected native/EVM profile uses matching underlying account bytes with the appropriate synw and 0x presentations. That simplifies recognition across supported networks, but balances, fees, account sequences, code, and permissions remain chain-specific. Other network families use their own address models and explicit relationships. A common name does not merge them into one universal account.

Freeze the destination before approval

The actual chain-specific recipient and naming evidence are fixed into the transaction intent. A later name change cannot rewrite an already approved destination. Missing or stale routing evidence is not permission to guess. Checksums, strict parsing, verified contacts, and QR-based flows complement that process; none makes a dishonest recipient trustworthy by itself.

Genuine assets are more than a ticker

A copied symbol, logo, collection image, or verification-looking label does not establish asset identity. The model connects presentation to the canonical asset and issuer evidence. Token and contract counterpart links also require authenticated relationships and current upgrade state. An authentic issuer or deployment can still have poor economics or risky business logic: verified identity is not investment approval.

Recognize the name. Verify the asset. Review the real destination.

SOURCES [1] AI.2, AI.10, AI.12; Categories 6-7, 15; [2] Section 8

MULTISIGNATURE ACCOUNTS

Shared control should actually be shared.

A multisig is an account policy, not a list of names hiding one master owner.

A public identity and a real policy

The native multi-signature design separates a stable public account identity from the policy that names its current signers and thresholds. There is no hidden singleton identity key with permission to bypass the whole group. This makes shared accounts relevant to teams, clubs, councils, treasuries, and organizations that need more than one person involved.

Count actual independent authorities

The same underlying key represented on several chains must not become several independent votes. A nested protected wallet counts as one logical signer in the outer account even if it uses multiple signatures internally. Different keys also do not automatically mean different people or organizations. The policy distinguishes demonstrated independence from a larger-looking signer list.

Separate ordinary use from changing the rules

Paying an approved expense is not equivalent to lowering a threshold, installing an execution module, changing a verifier, or replacing recovery authority. These changes use the current policy and applicable delays. A new signer cannot approve its own admission. Old proposals and approvals follow explicit invalidation rules when the policy changes.

Cross-chain participation without a hidden downgrade

Supported external keys and chain-resident authorities can participate under their registered verification rules. A protected native account still requires its independent post-quantum authorization condition. External signatures or relay reports cannot remove it. Counterparts need current policy evidence; stale cross-chain policy is not a reason to continue under obsolete authority.

The right question is not only how many signatures – but which paths can move funds or change control.

A pause guardian is not a spender. Any alternate destination-side recovery or continuity power must be disclosed as real authority.

SOURCES [1] AI.8-AI.9, AI.11; Category 33; [2] Section 9

CROSS-CHAIN CONNECTIONS

Connect networks.
Keep the trust boundaries visible.

Interoperability is more useful when you can see what each network, service, and settlement route is responsible for.

SXCP verifies defined outside facts

The Synergy Cross-Chain Protocol establishes which external facts and approvals can be accepted under the route's evidence and finality rules. An ordinary key signature differs from approval by a mutable smart account or program whose authority depends on current chain state. Correct source, destination, account, intent, freshness, and verification method all matter.

A custody model beyond a pooled bridge

The documented cross-chain direction avoids making a permanent pooled bridge reserve and synthetic wrapped liability the default center of custody. Native assets can remain on their own networks while settlement follows the authorized intent and chain-specific evidence. A route can still use liquidity providers, local contracts, or per-transaction escrow. Bridge-free does not mean dependency-free.

Names and matching addresses do not prove a counterpart

A related deployment needs authenticated code and initialization, publisher or administrator authority, actual deployment evidence, and current upgrade state. Copying code or producing a similar address does not make it official. A proxy upgrade can invalidate old evidence. A stale or paused relationship should not continue driving automatic routing as though it were current.

One source of policy is not instant synchronization

Synergy is the canonical policy ledger for the described Synergy-created multichain multisig profile. Destination execution needs sufficiently fresh policy evidence; the high-assurance route pauses when that cannot be established. SCETP similarly keeps externally initiated same-chain intent within explicit authorization. A service that carries or coordinates an instruction does not gain ownership of the user's account.

A verified outside fact is evidence. It is not unlimited permission or a guarantee about another chain.

External finality, reorganization, censorship, fees, liquidity, contract behavior, and classical-key risks remain. A multichain batch is not automatically atomic.

SOURCES [1] Section 0.3; AI.11-AI.12; Category 33; [2] Sections 2, 9

SYNQ + AIVM

Safer applications start below the interface.

Security connects what a developer writes to what the network actually executes.

SynQ describes the rules

SynQ is Synergy's smart-contract language and toolchain. It expresses application logic, assets, permissions, effects, and security conditions. Its significance is not simply being a custom language: it gives developers explicit ways to describe what a program may touch and what must remain true when it changes state.

Assets have accountable lifecycles

The linear-asset model treats value as a resource that must follow an authorized move, split, use, or storage path, rather than ordinary copyable data. Conservation rules and declared mint or burn authority complement that model. Temporary obligations must be completed before commit. These are accounting and execution properties, not promises that every project has sound economics.

AIVM enforces controlled execution

AIVM is the node-side orchestration and isolation environment, with SynQ-VM as its deterministic interpreter. It admits authorized artifacts, constructs the permitted execution context, meters resources, journals changes, and produces evidence for consensus. It does not independently invent account authority or finalize the chain.

Source rules are only the beginning

A convincing source file is not enough if a compiler is compromised or the deployed package changes. Independent proof checking, artifact identity, bytecode validation, dependency evidence, and runtime checks connect the reviewed program to execution. The next two pages translate all eighteen canonical SynQ security-property families into practical language.

Write the permissions. Check the program. Enforce the execution.

These properties have defined language, proof, admission, and runtime boundaries. EVM-compatible contracts do not automatically inherit them.

SOURCES [1] SynQ/AIVM definition; Categories 28-32; SQ-01-SQ-18; [2] Section 7

SYNQ / THE COMPLETE PROPERTY GUIDE

Rules for assets, permissions, and safe calls.

The first nine property families explain how compliant SynQ work accounts for value and limits application behavior.

01
Linear asset handling
Assets follow authorized movement or storage paths. They cannot be casually copied or dropped from the accounting like ordinary application data. Ownership must remain explicit through every allowed path.

02
Approval expiry
A permission carries a validity limit. An old approval does not remain an indefinitely reusable right simply because the user once granted it.

03
Scoped approvals
An approval defines its allowed action, amount, context, and time. Permission for one operation must not silently authorize another destination, larger value, or unrelated function.

04
Checked arithmetic
Invalid number operations, including overflow or division errors, are rejected where provable or produce defined runtime failure. Balance logic should not change silently because arithmetic behaved unexpectedly.

05
Asset-call discipline
Calls preserve resource accounting and prevent reuse of the same asset reference through an unsafe call pattern. Non-asset business logic still needs its own reentrancy and state checks.

06
No raw delegatecall
The specified model excludes the untyped route for executing another program inside the caller's state context. Composition uses explicit interfaces and admitted code instead.

07
Bounded control flow
Loops, recursion, and calls must fit defined limits. A program cannot assume endless computation, and the runtime still accounts for resource use.

08
Explicit composition
Dependencies and interactions are declared through clear interfaces and effects rather than hidden or ambiguous inheritance behavior. Reviewers can see the components on which execution depends.

09
Module-scoped access
Resources and state are reached through declared module and capability interfaces. Being part of the same application environment does not provide unrestricted access to every asset or record.

Limited permissions and accountable resources make the intended action easier to reason about.

SOURCES [1] SQ-01-SQ-09; [2] Section 7

SYNQ / THE COMPLETE PROPERTY GUIDE

Rules for evidence, results, and failure.

The remaining nine families connect application intent to verified information and consistent state changes.

10
Asset conservation

Creation, destruction, and movement must match declared authority and accounting rules. Runtime journals reinforce the requirement that authorized effects commit together.

11
Formal verification

Important properties have explicit proof requirements, assumptions, and independently checked evidence. A proof checks stated properties; it is not a certificate that every imaginable risk is absent.

12
Readable action manifests

Public functions describe their expected effects. Wallets can compare those declarations with simulation evidence and signed constraints instead of relying on a vague button label.

13
Capability-based authorization

The right to act comes from a valid, scoped permission bound to the relevant identity and context. A convincing address field is not a substitute for authority.

14
Temporary obligations

Non-droppable obligations must be discharged on every valid path before commit. A temporary financial obligation cannot simply disappear because an application took a different branch.

15
No mid-transfer user callbacks

Ordinary asset movement is not an opportunity for arbitrary synchronous user code to run halfway through the transfer. Notifications use events or separately authorized later actions.

16
Deterministic execution

The same accepted inputs and state produce the same canonical result across compliant implementations. An optimization is not allowed to change the agreed financial outcome.

17
Declared authority and facts

State changes identify the permissions, provenance, context, and verified outside information they need. Stale evidence or a fact from another invocation cannot silently acquire new authority.

18
Explicit failure and atomic effects

Failure has defined consequences. Action-level state and effects follow rollback rules rather than publishing arbitrary half-completed results. Fees and transaction-sequence consumption remain separately defined.

A complete security story includes what happens when an operation cannot safely succeed.

SOURCES [1] SQ-10-SQ-18; AI.4; [2] Section 7

EXECUTION YOU CAN EXAMINE

From reviewed code to an accountable result.

The safety checks do not end when the source code compiles.

Admit the right executable

The deployment package binds code, interface, metadata, proof evidence, dependencies, compiler identity, and execution target. Bytecode and artifact checks address malformed or substituted programs before they execute. An approved system-contract label or a familiar address does not waive those checks. A related Solidity deployment also needs evidence of its actual supported relationship, not an assumption of identical behavior.

Keep workloads in their permitted space

AIVM bounds memory, host access, resources, and state interaction. Programs do not receive unrestricted files, network calls, operating-system processes, or another workload's assets. The broader compartment model applies limited state and capability boundaries to users, tasks, agents, AI jobs, and settlements. An allowed tool is not permission to use every tool.

Commit correctly, including after failure

State journals and atomic action effects prevent arbitrary partial results from becoming the accepted state. Deterministic execution makes results comparable across implementations. Parallel or speculative work is an optimization only when it preserves the canonical outcome. A failed included action can still consume its defined fee and transaction sequence; rollback does not automatically mean free execution.

Keep assurance independent and specific

The security framework combines feature tests, adversarial tests, formal proofs for stated properties, independent audit, and continuing release checks. Reproducible builds and fixed dependency identity address software substitution. SynQ's ecosystem security-services material names CertiK as a provider for builders; that relationship is distinct from a completed audit of the language, runtime, wallet, or network. Always check a report's actual version and scope.

A source file, a proof, a deployment, and an audit each answer different questions.

A safer execution model does not make every application economically sound. Compatibility code and external dependencies keep their own limitations.

SOURCES [1] Categories 28-32; Overall Verification Framework; [2] Section 7 and S5

MEET JARVIS

One conversation.
A connected ecosystem.

Your Network Assistant helps you understand the network and prepare the next step – while your wallet keeps the approval.

ASK › UNDERSTAND › REVIEW › AUTHORIZE › TRACK

More than a website FAQ

Jarvis is Synergy's Network Assistant, described as an on-chain AI agent integrated with network services and user-directed workflows. He answers questions and coordinates requested tasks across the ecosystem instead of leaving you to assemble each step manually. Start in Portal, on Atlas or the main Synergy website, or inside Relay. The page where the chat begins does not limit the question to that one service.

Ask the service that knows

A token-price question goes to Relay. A question about token holders goes to Atlas. A swap request combines the selected account's balance information with a Relay quote. Jarvis explains the response in the conversation, identifying the relevant asset and network. He is not supposed to guess a market price or invent holder information from model memory.

Get help without giving away authority

Jarvis can prepare a specific proposed action and ask whether to send it for review. The mobile Wallet then presents the actual summary and simulated effects. You can reject the request or satisfy the account's required signing approvals. Jarvis does not need your private keys, recovery phrase, or independent signer secrets to coordinate that workflow.

One assistant, distinct responsibilities

Jarvis is not another name for Horizon. Horizon is the broader AI ecosystem application; AIVM supplies controlled execution; Atlas supplies chain information; Relay supplies trading functions; Wallet handles approval. Calling Jarvis an on-chain agent does not mean every model computation runs in consensus or that every chat message is stored publicly on-chain.

Jarvis handles the coordination. You keep the decision.

SOURCES [2] Section 11; S6 product clarification; [1] AI.4, AI.6-AI.7

JARVIS / THE EVERYDAY JOURNEY

From a token question to a reviewed swap.

A single conversation can connect research, a quote, and mobile-wallet approval.

Ask about the price

You ask, “What is the price of Token B?” Jarvis queries Relay and explains the relevant trading information. The actual token and network matter more than a shared ticker or a familiar icon.

Explore who holds it

You ask, “How many people own it?” Jarvis queries Atlas and reports the available holder metric. Holder addresses or accounts are not automatically a verified count of unique people.

Describe the exchange

You ask to swap an amount of Token A for Token B. Jarvis establishes the sending account and network, checks the relevant balance through Atlas, and asks Relay to prepare the requested exchange.

Understand the quote

Jarvis explains the input, estimated output, relevant fees, permission requests, and limits. A market price is not a trade-specific quote, and an estimated output is not a promise about the final amount received.

Confirm the wallet handoff

Jarvis asks whether to send the proposal to your mobile Wallet. Saying yes starts that review step. It does not sign a transfer or grant permission for future trades. Declining stops that requested progression.

Review the actual transaction

Wallet shows the clearly explained summary and simulation: what leaves, what may arrive, which account and network are involved, and the relevant destination, permissions, and fees. This is the concrete action, not just a repeated chat description.

Sign under your account policy

You reject or provide the required signing approvals. Any companion signer, multisig threshold, post-quantum condition, spending rule, or release restriction remains applicable. Jarvis cannot supply a missing approval for you.

Track the real result

Jarvis, Wallet, and Atlas distinguish a prepared request, submitted transaction, durable queue stage, committed ordering, and finalized outcome. Expiry or failure remains visible. A status check does not authorize a replacement spend.

Ask → understand → prepare → review in Wallet → sign → verify the result.

Token A and Token B are illustrative labels. No prices, balances, holder counts, or completed trades are fabricated here.

SOURCES [2] Section 11; S6-S7; [1] AI.4, AI.7, AI.14

JARVIS / CONTROL BY DESIGN

Helpful is not the same as authorized.

The assistant removes coordination work, not the boundaries that protect your account.

Chat consent and signing are different

Your question permits a relevant information lookup within allowed access. A quote request is not a purchase instruction. A yes to the mobile-wallet handoff is not a spending signature or standing approval. The signing environment is where you review the actual proposed transaction and supply the required account authorization.

The proposal must match the action

Account, chain, assets, amount, recipient, permissions, and limits carry through to wallet review. Material changes require an updated proposal and fresh approval where required. Jarvis cannot silently choose a broader permission, revive an expired quote, substitute another destination, or remove a reserve restriction simply to complete a task.

Information cannot promote itself into authority

A website response, token description, or retrieved document can provide data. It cannot grant Jarvis new rights or instruct him to bypass the wallet. Tool access stays limited to the requested task and responsible application. This is a permission boundary, not a claim that a model can never misunderstand hostile or misleading content.

Uncertainty remains visible

If required data is missing or stale, the assistant reports that limitation. Atlas balance information supports preparation; execution still checks the actual conditions. Simulated results help you review a request but do not remove market movement, fees, contract risk, or external-chain limitations. An assistant response is not a validator vote, transaction signature, or proof of finality.

Ask Jarvis. Understand the answer. Review the action. Keep control.

Network-wide integration describes the assistant's reach, not unrestricted network-wide privileges. Protected-v1 automatic agent/session spending remains disabled.

SOURCES [2] Section 11; [1] AI.4, AI.6-AI.7, AI.14; Categories 2-3, 24, 32-33

YOUR STARTING POINT

Portal + Wallet

A connected workspace, with a deliberate place to approve what matters.

PORTAL

Find your way around

Portal is the ecosystem hub for discovering applications, choosing accounts, navigating services, and arranging relevant tools. It gives the wider product family a coherent entry point rather than a collection of disconnected destinations. Jarvis adds a conversational route: ask in Portal, retrieve information from Atlas or Relay, and move a requested action toward wallet review.

PORTAL

Two editions, clear roles

The general Synergy Portal serves everyday ecosystem use. Synergy Portal for Developers & Node Operators places Forge, the integrated development workflow, and node-operation tools in a specialized workspace. Wallet is available within both product directions. Opening a tool in the same shell does not give it permission to inspect signing secrets or approve unrelated actions.

WALLET

Know which account is acting

Wallet brings together assets, account selection, transaction review, application connections, protected approvals, and recovery workflows. It distinguishes the protected native profile from connected external wallets, imported legacy accounts, hardware and smart accounts, and watch-only entries. Portfolio convenience is not a claim that all visible assets share the same custody, recovery, or signing rules.

WALLET

Your review checkpoint

In the Jarvis journey, the mobile Wallet receives a prepared action and displays the actual transaction summary and simulated results. You can reject it or provide the required signatures. Independent companion or multisignature approvals still apply. The sending account, network, recipient, permission changes, and costs remain visible so the final decision is about a concrete operation.

Portal connects the tools. Wallet preserves the approval boundary.

A connected wallet is not an imported private key. A watch-only account cannot sign. Linking an identity does not grant spending access.

SOURCES [2] Section 12; [1] AI.3-AI.7, AI.14; [3]

UNDERSTAND & EXCHANGE

Atlas + Relay

See the evidence behind activity, then approach a trade with clear information and permission.

ATLAS

More than a list of hashes

Atlas is the explorer and network-intelligence surface for blocks, transactions, accounts, contracts, assets, and network activity. Synergy's richer security model also gives it execution receipts, account-policy information, counterpart verification states, and public or authorized evidence to explain. The explorer makes records understandable; it does not gain authority to change them.

ATLAS

See what stage an action reached

Submitted, queued, ordered, executed, and finalized are different states. Atlas should make that difference legible rather than showing one ambiguous green check. A stale counterpart or unverified asset should not look like a current verified one. In the Jarvis workflow, Atlas supplies holder information and relevant account balances, with the underlying metric kept distinct from a count of unique human owners.

RELAY

Trading and liquidity

Relay is Synergy's decentralized exchange and liquidity application. It connects token discovery, trading information, quotes, and swap preparation to the native account and execution model. Jarvis can query Relay from another ecosystem entry point and bring a requested quote into the conversation. Relay supplies the trading function; the user's wallet supplies the required approval.

RELAY

Understand the route

A same-chain trade and a route involving another network, liquidity provider, or escrow have different dependencies. Relevant fees, liquidity, price impact, slippage limits, permissions, and settlement conditions belong in the review. Protected ETDAG handling addresses the transaction's pre-execution path where applicable; it does not promise zero slippage, a better price than every exchange, or a profitable trade.

Research through Atlas. Quote through Relay. Approve through Wallet.

An authentic token or accurate explorer record is not a recommendation to buy. A quote remains an estimate under its own terms.

SOURCES [2] Sections 6, 11-12; [1] AI.7, AI.11, AI.14; [3]

SPARK / CONNECT & LAUNCH

Your community.
Your next idea.

Spark brings Social, Launch, Create, and Arcade into one connected platform.

SOCIAL

Bring people together

Spark Social covers posts, community interaction, live streams, direct messages, group chat, and group live experiences. It gives creators, players, projects, and ordinary network users a place to connect around activity rather than treating each product as an isolated website. A social identity can make participation recognizable without becoming a permission to spend from an account.

SOCIAL

Keep participation separate from control

Joining a community, reacting to a post, or viewing a stream should not quietly grant financial authority. The same distinction applies when an interaction leads to an asset or launch: the responsible application requests its actual permissions, and wallet review handles spending or other account actions. Familiar people, popular content, and a polished project profile are not substitutes for verification.

LAUNCH

Turn an idea into an asset workflow

Spark Launch is the guided launch surface for network tokens, meme coins, NFTs, and community or creator projects. It gives non-specialists a route into standardized issuance workflows rather than requiring every project to start from a blank code editor. Professional developers can work through Forge and SynQ; guided creation should still lead into the same underlying token and authorization rules.

LAUNCH

Understand what is being issued

An asset's identity, supply policy, mint or burn powers, and relevant administrative controls matter more than its name or artwork. A launch is not an endorsement of its economics, a promise of liquidity, or a guarantee of future listings. The connected experience is useful because the same community can discuss, create, launch, and inspect an asset without treating social momentum as security evidence.

Interact, create, launch, and play – without confusing participation with permission.

SOURCES [2] Section 12; [3] Spark Social, Launch, Create, Arcade product direction

SPARK / CREATE & ARCADE

Make something. Play something. Build a community.

Creative work and interactive experiences belong in the same ecosystem as identity, assets, and user control.

CREATE

A home for digital work

Spark Create is the area for music, images, video, and other digital media. It brings the former Prism direction into Spark rather than presenting it as a separate product. Creator workflows can connect to recognizable identity, provenance records, digital-asset issuance, community discovery, and controlled access across the ecosystem.

CREATE

Records are useful; rights still matter

A provenance record can help show that a particular account published or signed a digital item. An NFT can represent an application-defined ownership claim. Neither automatically establishes copyright ownership, transfers every legal right, or authorizes using someone else's work. The relevant license, permissions, and project terms still determine what the holder may actually do.

ARCADE

Single-player, multiplayer, tournaments

Spark Arcade brings the former Quest gaming direction into an arcade environment for single-player, multiplayer, and tournament-style experiences. Identity, inventories, achievements, and game assets can connect to the shared account and token system. The name is Spark Arcade, alongside Spark Social, Spark Launch, and Spark Create.

ARCADE

Know the rules before playing

Where an enabled game uses arcade tokens, paid entry, prizes, or redemption, its rules need to explain costs, eligibility, how results are determined, and what can be redeemed. Rewards are not guaranteed income. Wallet approval, game-specific permissions, and jurisdictional requirements remain distinct from the entertainment experience. A game should receive only the authority its supported action needs.

A connected creative and gaming experience – not a promise of automatic earnings.

SOURCES [2] Section 12; [3] Spark consolidation and Arcade naming

BUILD & EXPLORE INTELLIGENCE

Forge + Horizon

Professional tools for builders, and an AI ecosystem that keeps useful computation separate from sovereign authority.

FORGE

From an idea to an admitted application

Forge brings code, templates, testing, simulation, proof and artifact review, deployment, diagnostics, and execution evidence into a developer workflow. The specialized Portal edition also includes the integrated development and node-operation direction. SDKs, APIs, command-line tooling, and documentation connect application work to the same canonical rules.

FORGE

One set of rules for every creation route

A guided template and a hand-written contract should follow the same SynQ, Aegis, and AIVM model. Dependency identity, readable effects, target compatibility, and deployment evidence are part of the build process. Native and Solidity-related outputs need explicit source, build, and deployment relationships; a dual-target label is not proof of identical behavior or compatibility with every outside application.

HORIZON

Intelligence as a useful service

Horizon is the broader AI ecosystem surface for model and provider discovery, inference, evaluation, agents, workflow composition, and provenance. It makes the intelligence architecture accessible while distinguishing an advisory model answer from a result that satisfies the policy required to affect an application.

HORIZON

Bounded work, not unlimited power

Probabilistic model computation is kept separate from deterministic authorization and consensus. A provider can return a result with contextual evidence; the applicable policy decides whether it can be used. Workloads can be restricted by tools, budget, recipients, and execution scope. Jarvis is the cross-ecosystem assistant, not a synonym for Horizon, and neither an AI response nor a provider's claim replaces the user's approval.

Forge makes the architecture buildable. Horizon makes intelligence usable within explicit limits.

AI output can be wrong. A signed receipt establishes defined provenance or context, not automatic truth or permission to act.

SOURCES [2] Sections 7, 10-12; [1] Categories 28-32; [3]

GOVERN & PROTECT INFORMATION

Keystone + Vault

The same attention to authority extends to shared decisions and sensitive documents.

KEYSTONE

Follow a decision from proposal to effect

Keystone is the governance interface for proposals, discussion, voting or approval workflows under the active model, treasury decisions, and records of enacted changes. It helps participants understand what is proposed, which approvals apply, when a change can take effect, and what was actually enacted.

KEYSTONE

An interface is not governance authority

Changes to cryptography, account powers, execution policy, or system upgrades are security-sensitive. The relevant accounts, signatures, contracts, and protocol rules govern them; a dashboard cannot waive an approval or challenge period. Distinguishing a proposal from an executed change makes collective control more understandable without confusing the interface with the source of power.

VAULT

Documents and protected data

Vault is the application for encrypted files, secure transfer, cryptographic document signing, controlled sharing, integrity records, and access evidence. It extends the network's usefulness beyond trading: people and organizations need to know which file they received, whether it changed, who can access it, and which action was authorized.

VAULT

Keep access and ownership explicit

Document permissions are not wallet-spending permissions. A share, download, or signature has its own context and scope. Cryptographic evidence can support integrity and authorization without automatically settling every legal question about enforceability or intellectual property. Vault the application is also distinct from account-level Vault Mode, which governs protected financial reserves.

Use clear authority for collective decisions, financial assets, and sensitive information.

SOURCES [2] Section 12; [1] AI.8-AI.9; Category 11; [3]

SNRG & DIGITAL ASSETS

The native coin.
A wider asset toolkit.

Network utility and application-created assets have different roles.

SNRG / Network activity

SNRG is Synergy's native coin, rather than an application token issued on an unrelated chain. Its documented utility covers transaction and execution fees, staking and network-security participation, approved service incentives, governance participation under applicable rules, and ecosystem activity. Different programs have different permissions and economic terms; using one service does not create an entitlement to every reward.

SNRG / A defined supply model

The documented supply model is 12 billion SNRG with nine decimal places. Supply allocation, custody, release conditions, vesting, service compensation, and staking rewards are separate mechanisms. A fixed supply is not a promise of price appreciation. This guide does not offer a projected token price, guaranteed yield, exchange listing, or expected investment return.

Fungible assets and unique objects

The token-system description includes fungible assets such as application currencies or points, and non-fungible assets for distinct objects such as collectibles, media records, or individual items. Developers choose the applicable issuance and authority rules; an asset's symbol is not its complete identity. Its supply, mint and burn powers, and other controls still need examination.

Inventories, credentials, and creation routes

Multi-asset systems support collections of asset types, quantities, inventories, tickets, or bundles. Identity and credential tokens represent application-defined memberships, roles, qualifications, or attestations. Forge, SynQ, and guided Spark workflows connect these ideas to a common underlying model. A digital record does not automatically establish every off-chain legal right, and a credential is only as meaningful as its issuer and verification context.

SNRG supports network utility. Application assets express the rules of their own projects.

Economic descriptions explain the documented model, not an offer or a guarantee. Check the applicable network, asset, program, and governing terms.

SOURCES [2] Sections 8, 12; S3 public whitepaper Section 5; [3]

REAL-LIFE SITUATIONS

When the next step is not the obvious one.

The value of the architecture becomes clearest when an ordinary task meets an unexpected problem.

A signing device is lost

The enrolled native recovery path separates replacement of a participant from spending. The recovery phrase alone is not a complete spending quorum, and a support agent cannot supply a missing owner role. Applicable delays and veto rules still matter. Account continuity is not an unconditional promise that every loss scenario is recoverable.

A small payment becomes a larger request

A successful test transfer does not automatically promote its recipient into a trusted high-value destination. The account's aggregate-outflow and recipient policies continue to apply. Several small payments do not erase the total, and protected pending value cannot immediately be reused as a laundering hop.

A quote expires while the request waits

Asynchronous handling preserves the signed terms. Jarvis can explain the actual status, but cannot revive an expired authorization or silently replace the trade. A materially different quote returns through the appropriate proposal and wallet-review process. A fast acknowledgment is not evidence that the swap has settled.

A team changes who can approve

A departing signer, new employee, or changed threshold is a policy event, not a cosmetic contact edit. The current authorized policy controls the transition. A newly added signer cannot authorize its own admission, and old approvals do not remain valid without the defined transition rules.

A familiar-looking token appears

The ticker and icon may look right while the issuer or contract is wrong. Canonical asset identity and current verification state help separate appearance from evidence. Even a genuine asset can have risky economics, so identity checks complement rather than replace the user's judgment.

A cross-chain route loses fresh evidence

The high-assurance counterpart path pauses rather than pretending an old policy is current. External chains do not synchronize instantaneously, and previously exported authorizations are not magically revoked. Any alternate continuity authority is a real control path that must be visible to the user.

A useful protection has a clear response to the situation – not just a reassuring label.

These are explanatory situations, not customer testimonials, reported attacks, completed tests, or claims of recovered funds.

SOURCES [1] AI.3-AI.12; Category 33; [2] Sections 6, 11, 13

THE WIDER SAFETY NET

Everyday mistakes are security problems too.

The security model covers misleading requests, overbroad authority, unsafe code, and rapid asset movement – not only cryptographic attacks.

Permissions and messages

Excessive approvals, deceptive permits, spend-capable messages, and replayed authorizations receive explicit scope and context checks. Permission has an action, value, identity, and validity boundary. A harmless-looking message is not exempt merely because it does not immediately broadcast a transfer.

Signing screens and hidden actions

Transaction presentation, social engineering, and multicall abuse can hide what an operation really does. Review binds meaningful effects to the actual intent and complete batch. Independent signers do not simply approve a convenient string supplied by an untrusted interface.

Recipients and lookalikes

Naming, address poisoning, clipboard substitution, counterfeit symbols, and copied artwork all exploit recognition. Parsing, checksums, destination evidence, issuer identity, and current verification states serve different purposes. A familiar display does not itself prove ownership or safety.

Contracts, upgrades, and delegation

Asset and permission rules combine with proof, admission, and runtime checks. Implementation changes and external delegation are security-sensitive; a wrapper or compatibility lane cannot silently inherit native guarantees. Newly emerging integration patterns still need evidence about what actually executes.

Stolen keys and automated drains

Independent ordinary roles, separate recovery material, delayed eligible transfers, reserve controls, and bounded emergency stopping address different stages of a compromise. The aim is to reduce single-point authority and contain harmful movement rather than presume that keys can never be stolen.

Splitting, hopping, and weakening policy

Aggregate-outflow checks, new-recipient rules, pending-output restrictions, delayed policy relaxation, and cross-domain egress controls address attempts to move around one safeguard through another route. The protections are cumulative: satisfying one does not waive the others.

Security is also about what people see, approve, and can still stop.

SOURCES [1] Categories 1-15, 33; [2] Section 16

THE WIDER SAFETY NET

Protection beneath the visible experience.

A dependable interface also needs disciplined data handling, execution, operations, and change control underneath it.

Available data and honest ordering

ETDAG addresses missing or withheld ciphertext, conflicting or replayed ordering evidence, and failed threshold-reveal participation. Durable data precedes availability certification. Ordering precedes reveal. Failure does not silently authorize a readable fallback or a weaker consensus decision.

Evidence after a fault

Recovery, pruning, and administration rules preserve the information needed to reconstruct events and validate history. Public data access is separated from privileged maintenance. Restarting a service is not permission to forget signing safety or erase still-relevant evidence.

Cryptography over the long term

The scope includes active and long-lived classical-key exposure, consensus-key compromise, proof-system assumptions, and long-horizon external cryptographic risk. A post-quantum signature on one component does not certify every external key, proof setup, transport, or connected service.

Prices that affect protection

When value determines a security tier, manipulated, stale, thin-market, or conflicting price data can become a way around a safeguard. Multiple-source and confidence rules prevent uncertainty from silently downgrading protection. An accepted valuation records the evidence behind the decision.

Peers, software, and releases

Authenticated peers, diverse discovery, network-partition safety, independent implementation comparisons, reproducible releases, and controlled upgrades address infrastructure failures. A single DNS answer or software family should not be mistaken for independent verification. External operating systems and networks remain real dependencies.

Source code through final state

Compiler and proof-tool compromise, substituted artifacts, sandbox escape, excessive host access, inconsistent execution, partial state, stale authority, and reused external facts all sit inside the assurance scope. Code review, proof, deployment admission, runtime checks, and release evidence answer complementary questions.

The specification covers 33 attack categories; that scope is not a claim of 33 proven eliminations.

SOURCES [1] Categories 16-32; Overall Verification Framework; [2] Section 16

WHY THE COMBINATION MATTERS

Look beyond a single headline.

Synergy's distinction is the coordinated treatment of account authority, transactions, applications, and everyday use.

More than a signature algorithm

Post-quantum authority is important, but it does not explain how a person recognizes a malicious request or slows a rapid drain. Synergy connects Aegis to independent account approval, readable effects, recovery separation, and active spending policy. Each layer answers a different part of the same user problem.

More than an encrypted queue

Secrecy before execution needs retrievable data, binding ordering, controlled reveal, and matching execution. Asynchronous preparation also needs bounded resources, durable status, duplicate handling, and a clear finality boundary. These mechanics make a more useful story than encryption or speed in isolation.

More than a new programming language

A custom language is meaningful when its asset and permission rules survive compilation, deployment, runtime execution, and upgrades. SynQ's eighteen property families connect to AIVM and consensus-recognized evidence. The name is not the assurance; the enforcement and verification are.

More than a collection of apps

Jarvis gives the integration a practical shape: question, sourced answer, requested quote, wallet review, required signatures, and traceable result. Portal, Atlas, Relay, and Wallet retain distinct roles while serving one goal. Spark, Forge, Keystone, Horizon, and Vault extend that pattern into other kinds of activity.

The point is the integrated experience – not an unsupported first, only, fastest, or safest claim.

When comparing systems, examine the actual account profile, enabled features, independent evidence, and external dependencies. Shared building blocks do not erase differences in how they are combined.

SOURCES [2] Sections 1, 14-15; [1] claim taxonomy

QUESTIONS PEOPLE ASK

Clear answers without the jargon.

The most important distinctions are often the simplest ones.

Can Jarvis spend without me?

The described workflow lets Jarvis retrieve information and prepare your requested action. Saying yes in chat permits a wallet-review handoff; it is not a spending signature. Wallet and the account's required approvals still decide authorization.

Is the recovery phrase safe to share?

No. It remains sensitive recovery material. In a fresh protected account, it is not a master spending seed. That distinction reduces one compromise path; it does not make disclosure harmless or apply automatically to an imported legacy wallet.

Does encrypted mean anonymous forever?

No. ETDAG protects contents before the permitted reveal point. Revealed and finalized activity can be public as required by the chain. Traffic metadata, endpoints, and other risks have their own boundaries.

Why is a transaction queued but not done?

Receipt, durable storage, admission, ordering, execution, and finality are different milestones. Asynchronous handling separates preparation from block production. A stored request can still fail or expire, and a submitted request is not a settled payment.

Do external assets inherit every protection?

No. The destination chain and account type retain their own signature, finality, execution, and recovery rules. Better custody, a verified link, or a Jarvis interface does not turn an external EVM account into a protected native account.

Does simulation guarantee the result?

No. It provides evidence in a particular state and context. It is useful for spotting unexpected effects, but market movement and changed conditions still matter. Signed limits and mandatory verification remain important.

Is the network unhackable or fully certified?

No such blanket claim follows from a specification. Controls have explicit boundaries. An audit applies to its named version and scope, and a service-provider relationship is not a completed audit of the entire stack.

Does owning SNRG guarantee returns?

No. Native utility, supply rules, staking programs, and market value are different matters. Neither this guide nor the security architecture guarantees income, price appreciation, redemption, or an exchange listing.

Understanding the boundary is part of using the feature well.

SOURCES [1] Sections 0.1-0.3; AI.3-AI.7; [2] Sections 3-6, 11-12

CHOOSE YOUR FIRST JOURNEY

Start with a goal. Keep the checks.

You do not need to become a protocol engineer before you begin exploring.

Learn and explore

Start from Synergy's official website and follow its official product links. Use Atlas to understand network activity and Jarvis to ask what an unfamiliar term or transaction stage means. Public account or asset data can support research without granting access to private signing material.

Manage and exchange

Use Portal to reach the appropriate application and Wallet to identify the account and network involved. In a Jarvis-assisted trade, inspect the quote and then the real wallet request. Check the asset, recipient, amount, fees, limits, and permissions. Treat a changed or expired proposal as a new review decision.

Create, play, and participate

Explore Spark Social, Launch, Create, and Arcade according to your goal. Read the relevant community, asset, licensing, entry, reward, and redemption terms. Use Keystone to understand proposals and enacted governance. Participation in a community or game is not permission to take control of your funds.

Build or organize

Forge and the developer/operator Portal connect professional tooling to the canonical execution model. Teams can explore shared-account policy and reserve protection. Vault addresses documents and controlled sharing; Horizon addresses bounded AI services. Confirm the exact enabled feature and account profile before depending on it for important work.

Never provide a recovery phrase or signing secret to a chat, support message, website form, or unsolicited contact.

Use official release information to distinguish network environments and available features. A test transaction is not a substitute for checking the actual destination and permissions.

SOURCES [2] Sections 11-12; [1] AI.6-AI.7; [3]; [6]

A SMALL GLOSSARY

The words behind the experience.

Enough terminology to understand the features without turning this into a technical manual.

Layer-1 / native

A Layer-1 is a base blockchain with its own accepted-state rules. Native means a rule belongs inside Synergy's own boundary, rather than merely appearing in an app.

Account authority / quorum

Authority is the actual right to approve an action. A quorum is the set or threshold of valid approvals required by the relevant account or network rule.

Capability / security profile

A capability is a limited permission. A security profile describes the account's actual authority paths, protections, assumptions, and relevant evidence.

Post-quantum / cryptographic agility

Post-quantum methods address relevant quantum-computing attacks. Agility means changing approved algorithms and keys through controlled rules as security requirements evolve.

ETDAG / asynchronous

ETDAG is the protected encrypted transaction pipeline. Asynchronous handling schedules preparation separately from block production while retaining the required security sequence.

Availability / finality

Availability establishes that required data can be retrieved. Finality is the accepted point at which the protocol treats a chain result as settled under its rules.

Deterministic / atomic

Deterministic means the same accepted inputs and state produce the same canonical result. Atomic action effects commit together or follow the defined rollback behavior.

Simulation / quote

Simulation estimates execution effects in a particular state. A quote estimates a specific exchange under its terms. Neither is a completed transaction or a guaranteed outcome.

Multisig / counterpart

A multisig account follows a policy requiring multiple logical approvals. A counterpart is an explicitly authorized related account or deployment on another chain.

Jarvis / Horizon

Jarvis is the cross-ecosystem Network Assistant. Horizon is the broader AI ecosystem application. Neither label provides permission to sign on the user's behalf.

Formal verification / audit

Formal verification checks stated properties under assumptions. An audit is an independent assessment with a defined scope and version. Neither proves the absence of all risk.

Vault / Vault Mode

Vault is the protected-document application. Vault Mode is a separate account-reserve control governing how eligible financial value is unlocked and spent.

A useful label explains a responsibility. It does not create authority.

SOURCES [1] definitions and claim taxonomy; [2] Section 17

READ FURTHER

The detail behind the guide.

Product explanations and technical assurance should remain connected to their sources.

[1]
Security architecture

Synergy Network Security Implementation Specification, version 9.0, October 2026. The source for protected-account roles, anti-drain controls, Aegis, ETDAG, SynQ/AIVM, cross-chain boundaries, the 33 attack categories, and verification requirements. It is an internal engineering reference; this guide does not reproduce private configuration or operational procedures.

[2]
Complete feature and product basis

Synergy PR Differentiation Brief, version 1.2, October 2026. Consolidates the security descriptions, public-whitepaper context, Jarvis workflow, full ecosystem portfolio, and asynchronous ETDAG scheduling explanation. Its technical ancestry includes the Address and Identity Specification v1.0 and the October scheduling notes. Source descriptions do not certify production activation.

[3]
Product-owner clarifications

October 2026 directions establish Jarvis as the Network Assistant across Portal, Atlas, the main website, and Relay; Relay price and quote queries; Atlas holder and balance queries; and mobile-Wallet summary, simulation, and required signing. They also confirm Spark Social, Launch, Create, and Arcade, with the earlier Quest and Prism directions consolidated into Spark.

[4-5]
Cryptographic standards

NIST FIPS 204, Module-Lattice-Based Digital Signature Standard, defines ML-DSA. NIST FIPS 203, Module-Lattice-Based Key-Encapsulation Mechanism Standard, defines ML-KEM. The standards explain those algorithm families; they do not certify the complete Synergy implementation. Public standard pages were checked on 21 October 2026.

[6]
Official starting point

synergy-network.io is the starting point for Synergy information and official service links. Check current releases, the selected network, and each account or route's actual security profile. Documentation, product scope, enabled software, audit evidence, and observed performance are distinct sources of information.

Scope and risk

This guide explains the documented product and security model. It is not an implementation audit, investment offer, legal opinion, insurance policy, or guarantee of results. Native protections do not automatically extend to external chains, imported accounts, operating systems, websites, or third-party services. Illustrative journeys contain no invented live balances, prices, users, or transaction evidence.

Discover the product. Examine the evidence. Understand the scope.

SOURCES [1-6]

synergynetwork



DISCOVER

One ecosystem.
More understanding.
Your decision.

Security beyond the ledger. Assistance without surrendering control.

ASK JARVIS

Explore an idea, understand network information, and prepare a requested next step through one conversation.

REVIEW IN WALLET

See the actual action, inspect its simulated effects, and give only the authorization your account requires.

EXPLORE THE ECOSYSTEM

Portal. Wallet. Atlas. Relay. Spark. Forge. Keystone. Horizon. Vault. Connected by a common attention to identity, permissions, and accountable execution.

synergy-network.io

Secure by Design