

## Spring Cloud Stream Configuration

### Project Dependencies for RabbitMQ

- spring-cloud-stream
- spring-cloud-stream-binder-rabbit
- spring-boot-starter-test
- spring-cloud-stream-test-binder

### Steps to create Messaging Server

1. Add following properties in application.yml file –

```
server.port = 9010
spring.application.name = "message"
spring.cloud.function.definition = email|sms
spring.cloud.stream.bindings.emailsms-in-0.destination = send-communication
spring.cloud.stream.bindings.emailsms-in-0.group = ${spring.application.name}
spring.rabbitmq.host = localhost
spring.rabbitmq.port = 5672
spring.rabbitmq.username = guest
spring.rabbitmq.password = guest
spring.rabbitmq.connection-timeout = 10s
```

2. Add below dependencies in other microservices to connect with rabbitmq –
  - a. Spring-cloud-stream
  - b. Spring-cloud-stream-binder-rabbit
3. Create DTO (AccountsMsgDto) in other Microservices as well
4. Add below properties in application.yml file in other microservices –

```
spring.cloud.stream.bindings.sendCommunication-out-0.destination =send-communication
spring.rabbitmq.host = localhost
spring.rabbitmq.port = 5672
spring.rabbitmq.username = guest
spring.rabbitmq.password = guest
spring.rabbitmq.connection-timeout = 10s
```

5. Inject **StreamBridge** dependency in other microservice service impl class
6. Invoke **streamBridg.send("sendCommunication-out-0", AccountsMsgDto)**
7. Run RabbitMQ using below docker command –

```
docker run -d -it --rm --name rabbitmq -p 5672:5672 -p 15672:15672 rabbitmq:3.13-management
```
8. Check for RabbitMQ console by visiting below link –

<http://localhost:15672> (username / password - guest)

## **Apache Kafka Configuration**

Project Dependency: (remove rabbit related dependency)

- spring-cloud-stream-binder-kafka

1. Add Kafka related properties inside application.yml file of both accounts and message services –

`spring.cloud.stream.kafka.binder.brokers (- localhost:9092 )`

2. Remove all properties related to RabbitMQ