

React

A JavaScript library for building user interfaces

What is React?

React is a JavaScript library used to build the user interface for web applications


React was developed and maintained by the folks at Facebook

An open source project with an active developer community.


Write less and do more!!

More About React App

In a React application, you should **break down** your site, page or feature **into smaller pieces** of components. It means that your site will be built by the combination of different components. These components are also built on the top of other components and so on.



Key Terminologies



Key Terminologies

JSX (JavaScript Extension)	JSX Allows us to include 'HTML' in the same file along with 'JavaScript' (HTML+JS=JSX). Each component in React generates some HTML which is rendered by the DOM
ES6 (ES2015)	The sixth version of JavaScript is standardized by ECMA International in 2015. Hence the language is referred to as ECMAScript.
ES5(ES2009)	The fifth JavaScript version and is widely accepted by all modern browsers,
Webpack	A module bundler which generates a build file joining all the dependencies
Babel	This is the tool used to convert ES6 to ES5. This is done because not all web browsers can render React (ES6+JSX) directly.

Why React?

Easy to understand for developers with the knowledge of XML/HTML

UI state becomes difficult to handle with Vanilla JavaScript

High Performant Apps

Huge Ecosystem

Active community

Easy to test

React Internals

Understanding React internally

React Internals - Virtual DOM

Virtual DOM is in memory lightweight representation of actual DOM.

For every DOM object, there is a corresponding Virtual DOM object.

Pure JS intermediate representation.

React never reads from real DOM, only writes to it.

Manipulating the DOM is slow. Manipulating the virtual DOM is much faster, because nothing gets drawn onscreen.

Virtual DOM Update Process

The virtual DOM gets compared to previous vs current virtual DOM



React figures out what object has changed.



The changed objects, and the changed objects only, get updated on the real DOM.



Changes on the real DOM cause the screen to change.

Virtual DOM in Nutshell

To track down model changes and apply them on the DOM (*rendering*) we have to be aware of two important things:

When data has changed?


For the change detection, React uses an observer model instead of dirty checking (*continuous model checking for changes*). That's why it doesn't have to calculate what is changed, it knows immediately.

Which DOM element(s) to be updated?

For the **DOM changing challenge**, React builds the tree representation of the DOM in the memory and calculates which DOM element should change.

React tries to keep as **much DOM elements untouched as possible**. Given the less DOM manipulation can be calculated faster based on the object representation, the costs of the DOM changes are reduced nicely

How React renders the View?



Components

Components let you split the UI into independent, reusable pieces, and think about each piece in isolation.

React components are the core building blocks of a React application that represent how a particular element would be visualized on the User Interface.

Combining tens to thousands of components together makes up your application.

A component must be designed in a way that makes it reusable across any page or even projects.

A component may be responsible for performing a single task

A typical React app is a component tree having one root component ("App") and then a potentially infinite amount of nested child components.

Create-react-app : The React CLI Tool

CRA involves configuring a combination of things such as webpack, babel, and react.

To install CRA

- `npm install -g create-react-app`

To create an App

- `create-react-app <app-name>`

CRA Commands

- `npm run start`
- `npm run build`
- `npm run eject`

Component Types

Functional Component

All function component is created using a JavaScript function.

Function component can be a named function or using an arrow function

Function components are also referred as Stateless components.

Class Based Component

Class components as its name suggests are created using the ES6 class syntax.

Every class that extends the `React.Component` class is obligated to implement the `render()` method.

The `render()` method returns a React element

JSX : A Syntax Extension To JavaScript

JSX is a Markup language used in order to create React elements.

JSX produces React “elements”.

You can put any valid JavaScript expression inside the curly braces in JSX, but not the reserved keywords eg class, for etc.

After compilation, JSX expressions become regular JavaScript function calls and evaluate to JavaScript objects.

You can put any valid JavaScript expression inside the curly braces in JSX.

Unidirectional (One way) Data Flow


Unidirectional data flow means that data has one, and only one, way to be transferred to other parts of the application.

State is passed to the view and to child components

Actions are triggered by the view

Actions can update the state

The state change is passed to the view and to child components



Props

A React component is a reusable component which can be used over and over again in the UI, but not always we are going to render the same component with same data. Sometimes we have to change the data or content inside a component. That's why ***props*** are introduced in React.

Props allow you to pass data from a parent component to a child component

Only changes in props and/or state trigger React to re-render your components and potentially update the DOM in the browser.

Props are considered as “immutable”

Props are supplied as attribute to components

State

A state in React Component is its own local state, the state cannot be accessed and modified outside the component and can only be used inside the component

React components can be made dynamic by adding state to it.

State is used when component needs to change independently of its parent.

Changes to state also trigger an UI update.

React component's state can be updated using `setState()`

Best practice : top level components are stateful which keep all interaction logic, manage UI state, and pass the state down to hierarchy to stateless components using props.

Class Based Component


React Class Components were introduced with JavaScript ES6, because JS classes were made available to the language.

All the internal React Component logic comes from the `extends React.Component` via object-oriented inheritance

React class components offer several lifecycle methods for the mounting, updating, and un-mounting of the component.

By using `this.state`, `this.setState()`, and lifecycle methods, state management and side-effects can be used side by side in a React class component

Component Life Cycle Methods



Component Life Cycle Methods

Lifecycle methods are various methods which are invoked at different phases of the lifecycle of a component.

Mounting

- Mounting refers to the loading of components on the DOM.
- This phase contains a set of methods which get invoked when the component is getting initialized, and loaded on to the DOM.

Updating

- This phase starts when the react component has taken birth on the browser and grows by receiving new updates.
- The component can be updated in two ways, sending new props from parents or updating the current state.

Unmounting

- In this phase, the component is not needed and the component will get unmounted from the DOM.

Mounting Phase Methods

constructor

This is the first method that gets called whenever a component is created. The constructor is called only once in the whole lifecycle of a component. It's used to set up the initial values of variables and component state.

render

This is the required method in a React component, as this method prepares the element that gets mounted on to the browser DOM.

componentDidMount

This is the hook method which is invoked immediately after the component **did** mount on the browser DOM.

Updating Phase Methods

shouldComponentUpdate

This method tells React that when the component is being updated, it should re-render or skip rendering altogether.

render

And then the component gets rendered

componentDidUpdate

executed when the newly updated component has been updated in the DOM.

Unmounting Phase Method

`componentWillUnmount`

This method is the last method in the lifecycle. This is executed just before the component gets removed from the DOM

Why Functional Components ?

Functional components make your code easier to read and understand

functional components are easier to test. No hidden state / props.

Avoid unnecessary overhead such as lifecycle events.

Functional components depend only on the props they are given to produce an output which makes debugging easier.

Functional components can reduce coupling

Add Keys : Rendering List Of Items

Each child in an array or iteration must be uniquely identified by assigning unique key with the help of “key” prop.

The key should always be supplied directly to the components in an array, not to the container element.

Identity and state of each component must be maintained across render passes.

The key is not really about performance, its more about identity (which in turns makes your app performant).

Forms

Accepting User Inputs

Working with Forms

Form elements naturally keep some internal state.

An input form element whose value is controlled by React in this way is called a “controlled component”.

With a controlled component, the input’s value is always driven by the React state.

A controlled component takes its current value through props and notifies the changes through callbacks like an onChange event.

Create Account

Email:

Password:

Country:

☐ I accept the terms of service

Submit

Accessing User Input Using Refs

There are mainly two types of form input in React.

- Controlled : Element state managed by React Component
- Uncontrolled : Element state managed by DOM itself

HTML elements maintain their own state that will be updated when the input value changes.

For Uncontrolled elements, there is no need to write an event handler for every state update. You can use a *ref* to access the input field value of the form from the DOM

Hooks

Making Functional Components Powerful

Hooks

Hooks are a new addition in React 16.8. e.g. `useState`, `useEffect`, `useContext`, `useReducer` and many more.

They let you use state and other React features without writing a class component.

Don't call Hooks inside loops, conditions, or nested functions. Only call Hooks at the top level.

Only call Hooks from React functional components

Hook : useState()

```
const [state, setState] = useState(initialState);
```

Returns a stateful value, and a function to update it.

During the initial render, the returned state is the same as the value passed as the first argument (initialState).

The setState function is used to update the state. It accepts a new state value and re-render the component

If the new state is computed using the previous state, you can pass a function to setState. The function will receive the previous value, and return an updated value.

Hook : useEffect()

```
useEffect(didUpdate);
```

Accepts a function that contains imperative, possibly effectful code.

All side-effects can run eg. Mutations, subscriptions, timers, logging, and other possible side effects.

By default, effects run after every completed render, but you can choose to fire them only when certain values have changed.

useEffect may return a clean-up function.

Routing & Navigation

Creating Single Page Apps

Routing in React

```
npm install react-router-dom
```

React Router is a standard library for routing in React

It enables the navigation among views of various components in a React Application.

React Router allows changing the browser URL and keeps the UI in sync with the URL.

Main Components of React Router

BrowserRouter

BrowserRouter is a router implementation that uses the HTML5 history API to keep your UI in sync with the URL.

Route

Route is the conditionally shown component that renders some UI when its path matches the current URL.

Link

Link component is used to create links to different routes and implement navigation around the application. It works like HTML anchor tag.

Switch

Renders the first child `<Route>` or `<Redirect>` that matches the location.

Thank You

Now you have required foundation to go ahead on you exciting and lucrative journey.

ALL THE BEST