

ERP.1 Audit & Accountability Infrastructure:

Formal Taxonomy, Multi-Plane Cryptographic
Logs, and NIST SP 800-53 Attestation

SYNRC Research Group
<https://synrc.com>

August 4, 2026

Abstract

This document presents the formal specification, architecture, and theoretical foundation of the `synrc/audit` library for high-assurance operating environments based on the ERP.1 three-plane architecture. Built upon standard Erlang/OTP primitives and standard NIST cryptography (ECDSA P-384, SHA-384, HMAC-SHA-512), `synrc/audit` enforces strict privilege segregation, fail-secure append-only event logging, deterministic CRDT Merkle-log merging across multi-DC deployments, cold-storage log archiving, and complete compliance with NIST SP 800-53 Rev. 5 Audit and Accountability (AU) controls.

Contents

1	Introduction & Motivation	3
2	Audit and Accountability	3
2.1	ERP.1 Three-Plane Isolation Model	3
2.1.1	Plane Descriptions	3
2.2	Formal Distributed Audit Model	3
2.2.1	Audit Invariants	3
2.2.2	Data Models (<code>#audit_record{}</code> and <code>#audit_checkpoint{}</code>)	4
2.2.3	Multi-Node CRDT Log Merge	5
2.3	NIST Cryptographic Profile	5
2.4	NIST SP 800-53 Rev. 5 AU Control Attestation	6
2.5	Comprehensive Audit Usage & Code Examples	6
2.5.1	1. Starting the Audit Service	6
2.5.2	2. Logging Standard Application Events (AU-12)	6
2.5.3	3. Logging Critical Security Events with ECDSA Signatures	7
2.5.4	4. Generating and Verifying Merkle Checkpoints	7
2.5.5	5. Multi-Node CRDT Log Merging, Delta & Sync	7
2.5.6	6. Pure Offline Verification (<code>audit_verify</code>)	7
2.5.7	7. Cold Storage Log Archiving & Sealing (<code>audit_archive</code>)	8
2.5.8	8. SIEM & OSCAL Export (<code>audit_export</code>)	8
2.6	Erlang Module API Reference	8
2.6.1	<code>audit_client</code>	8
2.6.2	<code>audit_core</code>	8
2.6.3	<code>audit_record</code>	9
2.6.4	<code>audit_chain</code>	10
2.6.5	<code>audit_checkpoint</code>	10
2.6.6	<code>audit_merge</code>	11
2.6.7	<code>audit_verify</code>	11
2.6.8	<code>audit_archive</code>	12
2.6.9	<code>audit_export</code>	12
2.6.10	<code>audit_crypto</code>	12
2.6.11	<code>audit_app</code> & <code>audit_sup</code>	13
3	Conclusion	13

1 Introduction & Motivation

High-integrity critical systems (defense appliances, state registries, electronic healthcare, infrastructure control systems) demand rigorous mathematical assurance, non-repudiation, and architectural privilege isolation. Traditional POSIX models featuring monolithic `root` processes violate Zero Trust Architecture principles by exposing broad ambient authority.

The ERP.1 architecture reduces the Trusted Computing Base (TCB) to a minimal cryptographic core running on Erlang/OTP on UKI Alpine Linux. The `synrc/audit` library isolates audit generation, aggregation, and signature capabilities across three execution planes, guaranteeing that audit logs remain immutable, cryptographically verifiable, and fail-secure under all operating conditions.

2 Audit and Accountability

2.1 ERP.1 Three-Plane Isolation Model

Following the fundamental OS.1 taxonomy defined in `synrc/os/os.txt`, the execution environment is partitioned into three distinct planes:

2.1.1 Plane Descriptions

1. **Security Admin BEAM [S]**: Houses `synrc/ca`, `synrc/tss`, and sealed `synrc/kvs`. Long-term private keys never leave this plane. It provides RFC 3161 timestamps and ECDSA signatures for critical events.
2. **System Admin BEAM [C]**: Runs `audit_core`. Handles capability broker passing via `SCM_RIGHTS`, maintains the append-only record chain, applies HMAC-SHA-512 integrity tags, and publishes periodic checkpoints.
3. **Application BEAM [A]**: Runs `audit_client`. Untrusted workloads operating under strict Landlock, seccomp-bpf, and cgroups v2 boundaries.

2.2 Formal Distributed Audit Model

2.2.1 Audit Invariants

Audit processing in ERP.1 satisfies four fundamental invariants:

1. **Irreversibility**: Audit entries form an append-only cryptographic hash chain linked via SHA-384 hashes. Past entries cannot be modified or reordered.
2. **Non-Repudiation**: Critical records and batch checkpoints are signed by Security Admin BEAM using ECDSA P-384 keys and sealed with RFC 3161 timestamps.




Figure 1: ERP.1 Three-Plane Architecture Isolation Diagram.

3. **Isolation:** Application BEAMs cannot read or mutate audit structures of higher planes.
4. **Completeness:** No privileged action (certificate issuance, key unsealing, ABAC policy change, device grant) can execute without a synchronous audit record commit (fail-secure, AU-5).

2.2.2 Data Models (#audit_record{} and #audit_checkpoint{})

Every audit event follows the mandatory schema specified by NIST AU-3:

```

-record(audit_record, {
  id      :: binary(),           % Monotonic ID (64-bit TS + Rand)
  ts      :: integer(),         % Milliseconds UTC / HLC
  plane   :: security | system | application,
  subject :: binary(),          % Subject identity

```

```

event      :: atom(),           % Event type
resource   :: binary(),        % Resource identifier
action     :: atom(),          % Action performed
outcome    :: success | failure, % Result
meta = #{} :: map(),           % Metadata context
prev_hash  :: binary(),        % SHA-384 of previous link
hmac       :: binary(),        % HMAC-SHA-512 (System plane)
sig        :: binary() | undefined, % ECDSA P-384 (Security plane)
tsp        :: binary() | undefined % RFC 3161 timestamp
}).

```

Periodic Merkle checkpoints and log segment seals utilize the `#audit_checkpoint{}` record schema:

```

-record(audit_checkpoint, {
  node_id      :: binary(),      % Originating node identifier
  from_id      :: binary(),      % First record ID in checkpoint
  to_id        :: binary(),      % Last record ID in checkpoint
  head_hash    :: binary(),      % Top hash of local hash chain
  record_count :: non_neg_integer(), % Total records in segment
  merkle_root  :: binary(),      % SHA-384 Merkle root of records
  sig          :: binary() | undefined, % Security Admin ECDSA P-384 sig
  tsp          :: binary() | undefined % RFC 3161 timestamp token
}).

```

2.2.3 Multi-Node CRDT Log Merge

In multi-node / multi-DC environments, each node maintains a local sequential hash chain. Global consensus is achieved using an **Add-only Merkle-CRDT** (G-Set of signed checkpoints):

$$\text{GlobalLog} = \text{G-Set}(\{\text{NodeId}, \text{HeadHash}, \text{SignedCheckpoint}, \text{MerkleRoot}\}) \quad (1)$$

Merging two node logs L_A and L_B is deterministic and conflict-free:

$$\text{merge}(L_A, L_B) = L_A \cup L_B \quad (2)$$

Linearization sorts records by the tuple $(TS, \text{NodeId}, \text{RecordId})$, producing a deterministic global sequence without altering original node hash chains.

2.3 NIST Cryptographic Profile

All cryptographic primitives are standard FIPS/NIST compliant:

Purpose	Algorithm	Specification	NIST
Chain	Merkle Hashing	SHA-384 (or SHA-512)	NIST FIPS 180-4
Message Integrity	HMAC-SHA-512	NIST FIPS 198-1	
Digital Signature	ECDSA P-384	NIST FIPS 186-4 (secp384r1)	
Timestamp	RFC 3161	SHA-384 / SHA-512 TimeStampToken	
Key Generation	ECDH P-384	NIST SP 800-56A	

Table 1: NIST Cryptographic Profile for `synrc/audit`.

2.4 NIST SP 800-53 Rev. 5 AU Control Attestation

Control	Control Name	Plane	Implementation in synrc/audit
AU-1	Audit Policy and Procedures	[C]	Defined in CMDB metadata.
AU-2	Event Selection	[C],[A]	Configurable event masks per plane.
AU-3	Content of Audit Records	[C]	Mandatory <code>#audit_record{}</code> schema.
AU-4	Storage Capacity	[C]	ETS / KVS sizing and segmentation.
AU-5	Response to Processing Failures	[C]	Synchronous fail-secure <code>gen_server</code> call.
AU-6	Review, Analysis, Reporting	[C],[S]	Offline verifier (<code>audit_verify</code>) & SIEM export.
AU-7	Audit Reduction	[C]	Filtered queries and Merkle proofs.
AU-8	Time Stamps	[C],[S]	UTC ms / HLC + RFC 3161 timestamps.
AU-9	Protection of Audit Info	[C],[S]	Append-only SHA-384 chain + HMAC-SHA-512.
AU-10	Non-Repudiation	[S]	ECDSA P-384 signatures by Security plane.
AU-11	Audit Record Retention	[C]	Archiving tool (<code>audit_archive</code>) for cold storage.
AU-12	Audit Generation	[A],[C]	Real-time generation via capability bridge.

Table 2: NIST SP 800-53 Rev. 5 AU Controls Attestation Matrix.

2.5 Comprehensive Audit Usage & Code Examples

2.5.1 1. Starting the Audit Service

To initialize the System Admin BEAM aggregator with ECDSA P-384 Security keys:

```
{PubKey, PrivKey} = audit_crypto:generate_keypair(),
MacKey = audit_crypto:generate_mac_key(),

{ok, Pid} = audit_core:start_link(#{
  node_id      => <<"DC1-Node01">>,
  boot_time    => erlang:system_time(milliseconds),
  mac_key      => MacKey,
  sec_keypair  => {PubKey, PrivKey}}).
```

2.5.2 2. Logging Standard Application Events (AU-12)

From any Application plane process:

```
ok = audit_client:log(
  application,
  <<"user_session_42">>,
```

```

user_login,
<<"/api/v1/auth">>,
authenticate,
success,
#{<<"ip">> => <<"192.168.1.100">>, <<"seat">> => <<"seat0">>}}).

```

2.5.3 3. Logging Critical Security Events with ECDSA Signatures

For high-assurance operations requiring non-repudiation (AU-10):

```

ok = audit_client:log_critical(
  security,
  <<"security_admin">>,
  cert_issuance,
  <<"CA-Root-2026">>,
  sign_certificate,
  success,
  #{<<"subject_dn">> => <<"CN=SystemAdmin">>}}).

```

2.5.4 4. Generating and Verifying Merkle Checkpoints

To generate a signed checkpoint for active records:

```

Checkpoint = audit_core:get_checkpoint(),
Valid      = audit_checkpoint:verify(Checkpoint, PubKey),
io:format("Checkpoint valid: ~p~n", [Valid]).

```

2.5.5 5. Multi-Node CRDT Log Merging, Delta & Sync

Merging, diffing, and linearizing audit streams from independent nodes:

```

SetA      = audit_merge:add_node_log(audit_merge:new_log_set(),
  CheckpointA, RecordsA),
SetB      = audit_merge:add_node_log(audit_merge:new_log_set(),
  CheckpointB, RecordsB),
MergedSet = audit_merge:merge(SetA, SetB),
true      = audit_merge:verify_merged(MergedSet, PubKey),
LinearRecords = audit_merge:linearize(MergedSet, #{plane => security, limit
=> 50}),

%% Calculate synchronization delta and missing entries diff
DiffSet   = audit_merge:diff(SetA, SetB),
DeltaSet  = audit_merge:delta(MergedSet, #{<<"DC1-Node01">> => 10}),
Stats     = audit_merge:stats(MergedSet).

```

2.5.6 6. Pure Offline Verification (audit_verify)

Perform independent offline verification of a record chain and Merkle inclusion:

```

GenesisHash = audit_chain:genesis_hash(<<"DC1-Node01">>, BootTime),
case audit_verify:verify_chain(Records, GenesisHash, MacKey, PubKey) of
ok -> io:format("Chain integrity verified.~n");
{error, {tampered_record, Index, BadRecord}} ->
  io:format("Tampering detected at record ~p!~n", [Index])
end,
IsIncluded = audit_verify:verify_inclusion(Record, Checkpoint).

```

2.5.7 7. Cold Storage Log Archiving & Sealing (audit_archive)

Splitting, sealing, and serializing log segments for long-term cold storage (AU-11):

```
{Segment, Remaining} = audit_archive:cut_segment(Records, CutoffTimestamp),
SealedCP              = audit_archive:seal_segment(Segment, <<"DC1-Node01">>,
PrivKey),
ArchiveBin            = audit_archive:serialize_archive(Segment, SealedCP),

{ok, RestoredCP, RestoredRecords} = audit_archive:deserialize_archive(
ArchiveBin).
```

2.5.8 8. SIEM & OSCAL Export (audit_export)

Exporting log entries for Wazuh / Syslog or compliance evidence:

```
CEFString = audit_export:to_siem(Record),
JSONData  = audit_export:to_json(Records),
OscalMap  = audit_export:to_oscal(Checkpoint, Records).
```

2.6 Erlang Module API Reference

This section provides the complete reference specification for all exported functions across the 12 modules in `synrc/au`.

2.6.1 audit_client

High-level Application Plane client interface for emitting audit events to `audit_core`.

- `log(Subject, Event, Resource, Action, Outcome, Meta) -> ok | {error, term()}`
Submits a standard audit event defaulting to the `application` plane.
- `log(Plane, Subject, Event, Resource, Action, Outcome, Meta) -> ok | {error, term()}`
Submits a standard audit event targeting the specified execution plane (`security`, `system`, or `application`).
- `log_critical(Plane, Subject, Event, Resource, Action, Outcome, Meta) -> ok | {error, term()}`
Submits a high-assurance audit event requiring Security Admin ECDSA P-384 signature and RFC 3161 timestamping.

2.6.2 audit_core

OTP `gen_server` managing local ETS storage, append-only hash chain linking, and checkpoint generation.

- `start_link() -> {ok, pid()} | {error, term()}`
Starts the audit core server with default node options.

- `start_link(Opts::map()) -> {ok, pid()} | {error, term()}`
Starts the audit core server with custom options (`node_id`, `boot_time`, `mac_key`, `sec_keypair`).
- `stop() -> ok`
Gracefully stops the `audit_core` server.
- `log_event(Record::#audit_record{}) -> ok | {error, term()}`
Synchronously appends a standard audit record to the local hash chain and ETS table.
- `log_critical_event(Record::#audit_record{}) -> ok | {error, term()}`
Synchronously appends a signed critical audit record to the local hash chain and ETS table.
- `get_head_hash() -> binary()`
Returns the current 384-bit SHA-384 head hash of the node's local audit chain.
- `get_records() -> [#audit_record{}]`
Retrieves all audit records stored in the local ETS table in chronological sequence.
- `get_checkpoint() -> #audit_checkpoint{}`
Generates a signed `#audit_checkpoint{}` spanning all currently accumulated records.
- `set_security_keys(PubKey::binary(), PrivKey::binary()) -> ok`
Dynamically configures or updates the Security Admin ECDSA P-384 keypair.

2.6.3 audit_record

Constructs, validates, encodes, and formats individual NIST AU-3 audit record instances.

- `new(Plane, Subject, Event, Resource, Action, Outcome, Meta) -> #audit_record{}`
Instantiates and validates a new `#audit_record{}` with automatic monotonically increasing ID generation.
- `validate(Record::term()) -> ok | {error, term()}`
Enforces NIST AU-3 schema validation on record fields.
- `canonical_payload(#audit_record{}) -> binary()`
Computes a deterministic binary payload encoding (excluding transient hashes/signatures) used for hashing and MAC generation.
- `encode(#audit_record{}) -> binary()`
Encodes an audit record into a deterministic binary term format.

- `decode(Bin::binary()) -> {ok, #audit_record{}} | {error, term()}`
Decodes a binary term into a validated `#audit_record{}`.
- `new_id() -> binary()`
Generates a monotonic 16-byte record identifier (64-bit UTC ms timestamp + 8-byte random entropy).
- `now_ms() -> integer()`
Returns current UTC timestamp in milliseconds.

2.6.4 audit_chain

Implements append-only hash chain linking, HMAC tag calculation, and link verification.

- `genesis_hash(NodeId::binary(), BootTime::integer()) -> binary()`
Computes the root genesis hash for a node audit chain (`ERP.1-AUDIT-ROOT:NodeId:BootTime`).
- `append_record(Record, PrevHash, MacKey) -> #audit_record{}`
Calculates `prev_hash` via SHA-384 and `hmac` via HMAC-SHA-512 over (`PrevHash || Payload`).
- `append_critical_record(Record, PrevHash, MacKey, SecPrivKey) -> #audit_record{}`
Appends standard chain hashes and attaches an ECDSA P-384 signature and RFC 3161 timestamp token.
- `verify_record(Record, PrevPrevHash, MacKey, SecPubKey) -> boolean()`
Validates single record hash continuity, HMAC tag, ECDSA signature, and timestamp token.

2.6.5 audit_checkpoint

Constructs and verifies Merkle checkpoints over log segments.

- `create(NodeId, Records, HeadHash, SecPrivKey) -> #audit_checkpoint{}`
Builds a `#audit_checkpoint{}`, computes the Merkle tree root over record canonical payloads, and applies an optional ECDSA signature.
- `verify(Checkpoint::#audit_checkpoint{}, SecPubKey) -> boolean()`
Validates ECDSA P-384 signature and RFC 3161 timestamp token on a checkpoint.
- `compute_merkle_root([#audit_record{...}]) -> binary()`
Computes the binary Merkle root hash (SHA-384) over a list of audit records.

2.6.6 audit_merge

Add-only Merkle-CRDT G-Set engine for multi-node log synchronization, diffing, delta tracking, and linearization.

- `new_log_set() -> log_set()`
Returns an empty G-Set map.
- `add_node_log(LogSet, Checkpoint, Records) -> log_set()`
Adds or updates a node log entry in the G-Set, merging records if the node exists.
- `merge(LogSetA, LogSetB) -> log_set()`
Computes the deterministic CRDT G-Set union of two log sets.
- `linearize(LogSet) -> [#audit_record{}]`
Produces a total order sequence of all records across nodes sorted by (TS, NodeId, RecordId).
- `linearize(LogSet, Opts::map()) -> [#audit_record{}]`
Linearizes records with filtering options (`from_ts`, `to_ts`, `plane`, `limit`).
- `global_merkle_root(LogSet) -> binary()`
Computes a cluster-wide global Merkle root over sorted node head hashes.
- `verify_merged(LogSet, SecPubKey) -> boolean()`
Verifies all checkpoints and record hash chains contained within a merged log set.
- `diff(LogSetA, LogSetB) -> log_set()`
Calculates missing records present in LogSetB but absent in LogSetA.
- `delta(LogSet, KnownCounts::map()) -> log_set()`
Generates a delta log set containing only records newer than specified per-node counts.
- `apply_delta(LocalSet, DeltaSet) -> log_set()`
Applies a delta log set into a local log set via CRDT merge.
- `stats(LogSet) -> map()`
Computes aggregate cluster metrics (`node_count`, `total_records`, `min_timestamp`, `max_timestamp`, `global_merkle_root`).

2.6.7 audit_verify

Pure offline cryptographic chain and checkpoint verifier.

- `verify_chain(Records, GenesisHash, MacKey, SecPubKey) -> ok | {error, {tampered_record, integer(), term()}}`
Iteratively verifies chain continuity, HMAC tags, and ECDSA signatures from genesis.

- `verify_checkpoint(Checkpoint, SecPubKey) -> boolean()`
Verifies a checkpoint's signature and timestamp offline.
- `verify_inclusion(Record, Checkpoint) -> boolean()`
Verifies whether a record payload hash is included in a checkpoint's Merkle root.

2.6.8 audit_archive

Cold storage segmentation, sealing, and serialization primitives.

- `cut_segment(Records, CutoffTS) -> {Segment, Remaining}`
Partitions audit records at a timestamp boundary.
- `seal_segment(Segment, NodeId, SecPrivKey) -> #audit_checkpoint{}`
Seals a record segment into a signed `#audit_checkpoint{}`.
- `serialize_archive(Segment, Checkpoint) -> binary()`
Compresses and serializes a segment and its checkpoint into binary format.
- `deserialize_archive(Bin::binary()) -> {ok, #audit_checkpoint{}},
[#audit_record{}}] | {error, term()}`
Deserializes and validates an archive binary blob.

2.6.9 audit_export

Formats audit evidence into standard SIEM, JSON, and OSCAL representations.

- `to_json(RecordOrRecords) -> binary()`
Formats record(s) into structured JSON.
- `to_siem(Record) -> binary()`
Formats an audit record into Wazuh / Syslog Common Event Format (CEF).
- `to_oscal(Checkpoint, Records) -> map()`
Formats checkpoint and records into a NIST OSCAL Assessment Results structure.

2.6.10 audit_crypto

FIPS/NIST cryptographic primitives (ECDSA P-384, SHA-384, HMAC-SHA-512, RFC 3161 timestamps).

- `generate_keypair() -> {PubKey, PrivKey}`
Generates a fresh ECDSA P-384 (`secp384r1`) keypair.
- `generate_mac_key() -> binary()`
Generates a 256-bit symmetric key for HMAC calculation.

- `hash(Data::binary()) -> binary()`
Computes SHA-384 hash of binary data.
- `hash(Algo, Data::binary()) -> binary()`
Computes specified digest (`sha384` or `sha512`).
- `hmac(Key, Data) -> binary()`
Computes HMAC-SHA-512 over data using symmetric key.
- `sign(PrivKey, Data) -> binary()`
Signs data digest using ECDSA P-384 with SHA-384 digest.
- `verify(PubKey, Data, Signature) -> boolean()`
Verifies ECDSA P-384 signature over data.
- `timestamp_token(Digest, TS) -> binary()`
Generates a simulated RFC 3161 timestamp token for a given digest and timestamp.
- `verify_timestamp(Token, Digest, TS) -> boolean()`
Verifies an RFC 3161 timestamp token.

2.6.11 `audit_app` & `audit_sup`

OTP application lifecycle and supervisor specification.

- `audit_app:start(StartType, StartArgs) -> {ok, pid()} | {error, term()}`
Starts the `au` OTP application and supervisor tree.
- `audit_app:stop(State) -> ok`
Stops the application.
- `audit_sup:start_link() -> {ok, pid()} | {error, term()}`
Starts the `audit_sup` supervisor (`one_for_one` strategy supervising `audit_core`).
- `audit_sup:init(Args) -> {ok, {SupFlags, [ChildSpec]}}`
OTP supervisor callback specifying child worker parameters.

3 Conclusion

The `synrc/audit` library provides a minimal, self-contained, and cryptographically verifiable audit infrastructure for ERP.1 systems. By combining standard NIST algorithms, Erlang/OTP supervision, three-plane capability separation, CRDT Merkle log merging, cold storage log archiving, and comprehensive export capabilities, it fulfills the full spectrum of NIST SP 800-53 Rev. 5 AU requirements without external dependencies.