

Time-Series Forecasting of Organizational Cash Flow Using an LSTM Model

Hemangi Jha, Yashashri Mahendrakar, Eshwari Pawade, Pratibha Sajwan
Department of Artificial Intelligence & Data Science, Thakur College of Engineering & Technology,
Maharashtra, India
hemangijha@gmail.com, yashashrimahendrakar@gmail.com, eshwaripawade@gmail.com,
pratibha.sajwan@tcetmumbai.in

Abstract—Precise liquidity forecasting serves as the fundamental pillar of financial stability for Small and Medium Enterprises (SMEs) and globally significant financial entities. Although traditional econometrics techniques, including ARIMA and moving average models, establish a baseline trend insight but frequently lack the representational capacity to represent non-linear volatility and complex high-dimensional dependencies in modern global markets. This paper proposes an advanced computational framework for multi-horizon liquidity prediction centered on Long Short-Term Memory (LSTM) architecture to provide high-accuracy forecasting for financial planning and risk management. The study utilizes the “SME – Synthetic UK Businesses Financial Statistics” dataset an extensive, fine-grained data repository modeling trajectory dynamics of 1,000 SMEs. To handle the high dimensionality and scale of the data, the proposed model processes the dataset across 10 discrete segments, integrating transactional records with temporal attributes to predict net capital availability at specific future intervals. Simulation-based experiments show that this hybrid framework successfully captures cash flow volatility and substantially outperforms linear benchmarks in terms of forecasting accuracy. By generating high-accuracy, data-driven estimation of cash inflows and outflows, the developed system strengthens finance teams ability transition from reactive budgeting toward proactive and strategy-oriented liquidity management.

Keywords— *LSTM, Cash Flow Forecasting, Deep Learning, Liquidity Management, Time-Series Prediction, Financial Modeling*

I. INTRODUCTION .

Cash flow is the lifeblood of every Small and Medium Enterprises (SMEs) functionality which ensures the necessary liquidity of the company to maintain the operational economic shifts, settle obligations, and fund expansions. For organizations across the economic spectrum, particularly Small and Medium-sized Enterprises (SMEs) the ability to maintain a sturdy cashflow is important as it is the primary indicator of its operational efficiency and financial competence. However, while the conceptual importance of cashflow management is straightforward, but with increasing incorporation of interconnected global value ecosystem and rise of digital transactional environment have introduced extreme uncertainty in organizational cashflows. Recent findings by Dumitrescu et al. highlights that integrating Artificial Intelligence (AI) into core business models is now a fundamental requirement to enhance “financial resilience” against such volatile global shifts [1]. Despite having a positive net income, many SMEs face insolvency due to their inability in anticipating the liquidity shortfalls.

Traditionally used forecasting techniques such as Moving Average, Autoregressive Integrated Moving Average (ARIMA), and Linear Regression have been widely used for financial prediction. Furthermore, as established by MDPI, shifting towards a multi-horizon forecasting strategy is critical for modern SMEs to navigate these unpredictable cycles effectively [2]. Although these methods offered a foundational framework for trend analysis, they assumed data stationarity, a condition rarely observed in today’s volatile and non-linear market environments which are influenced by short term season fluctuations, non-stationary customer behavior and external economic disruptions. For SMEs managing a large user base, a minute error in predicting the cashflow can result in significant liquidity pressure, leading to lost investment opportunities and in extreme scenarios, regulatory penalties and systemic risk.

In an effort to address these volatility concerns, the financial sector has progressively transitioned towards Artificial Intelligence (AI) and Deep Learning (DL) architectures. While earlier iterations of the Artificial Neural Networks (ANNs) showed potential in pattern recognition, they mostly lacked in temporary memory due to which it was difficult to identify and interpret the recurring patterns for the cyclic behaviour of budgetary cycles and payment schedules. Even Recurrent Neural Networks (RNNs) encounter with the “vanishing gradient” problem, which limits their capacity to preserve long-term contextual dependencies, a critical shortcoming for modelling financial trends over a quarterly or annual basis. This arbitrarily attributed to the architecture limitations of the feed-forward systems, which treat each data points as an independent event rather than sequential dependencies. In SME cashflow dynamics, past credit cycles and seasonal demand directly influence future solvency, maintaining the temporary context is critical.

This paper addresses the limitations of both traditional econometric models and common neural architectures by proposing a Long Short-Term Memory (LSTM) recurrent framework specifically tuned for organizational cash flow time-series. By making use of a specialized “memory cell” including input, forget and output gates, the LSTM model can selectively preserve or discard information across various time scales. This study tries to model the long-term dependencies and underlying seasonality that define SME financial cycles. The proposed model offers a scalable framework for heuristic based budgeting practices to a data-centric and proactive liquidity management strategy. By adopting this advanced deep learning framework, the study achieves a marked reduction in forecasting error thereby

enhancing organizational financial resilience amid economic uncertainty

II. PROBLEM STATEMENT

The financial stability of Small and Medium Enterprises (SMEs) is inherently reliant on maintaining stable and predictable liquidity. Unlike large scale enterprises with strong capitalization levels, SMEs often operate with narrow operating margins, under which the small deviations in cash flow timing may lead to insolvency. Despite the intrinsic importance of liquidity management, present organizational practices demonstrate three key limitations:

A. Limitations of Traditional Methodologies:

Traditionally, forecasting techniques like Autoregressive Integrated Moving Average (ARIMA) and basic Moving Average was predicated on the assumption of linearity and data stationarity. However, the real-world financial data is defined by non-linear volatility, cyclic demand shifts, and irregular payment behaviours. These econometric models lack the ability to represent complex, high-dimensional dependency structures in modern digital transaction ecosystem.

B. Structural and Temporal Complexity:

Organizational cashflow is influenced by two distinct data types that are rarely integrated in an effective manner:

1. Temporal Features:

Sequential transaction records, including fluctuating invoice inflows and operational outflows, where historical dependencies exert a direct impact on future solvency.

2. Structural Features:

Non-sequential indicators such as credit ratings, business failure scores, and debt-to-revenue ratios provide the “health context” for the enterprise.

Standard Feed-forward Neural Networks (ANNs) treat these data points as independent data which fails to maintain temporal consistency. Although Recurrent Neural Networks (RNNs) handle sequential data, they are prone to vanishing gradients, thereby restricting their ability to capture long-term dependencies, including quarterly tax cycles or annual credit renewals.

C. Formal Objective:

The main objective of this paper is to narrow the gaps by developing a Hybrid Temporal-Static Fusion framework. Given the historical time-series data and static organizational attributes, the aim is to precisely estimate net liquidity for the next time interval ($t + 1$)

$$net_flow_{t+1} = \sum Inflows_{t+1} - \sum Outflows_{t+1}$$

Let the net cash flow at time ‘t’ be defined as:

$$net_flow_t = total_inflows_t - total_outflows_t$$

The objective of forecasting is to predict net_flow_{t+1} . The problem is formulated as finding a mapping function f such as:


$$net_flow_{t+1} = f(X_{temporal}, X_{static})$$

Where, net_flow_{t+1} minimizes the Mean Squared Error (MSE) against the actual liquidity realized, thereby

enabling SMEs to transition from reactive budgeting to a proactive, data-centric risk management strategy.

III. METHODOLOGY

This research adopts a supervised deep learning framework structure shown in Fig.1. The process involves the selection of dataset, preprocessing, feature engineering, model architecture, and training protocols. The model design emphasizes the integration of the sequential (temporal) and static (organizational) data through a hybrid LSTM-based architecture.



[Fig.1: Architecture and workflow of the proposed hybrid LSTM-based cash flow forecasting framework.]

A. Dataset Selection:

The “SME – Synthetic UK Business Financial Statistics dataset” is employed due to its suitability and reliability for training the proposed model. The dataset features the following files: *Accounts_Receivable.csv*, *Businesses.csv*, *Covid.csv*, *Credit_Account_History.csv*, *Credit_Card_History.csv*, *Credit_Rating.csv*, *Director.csv*, *Factoring.csv*, *Individual.csv* and *Loan.csv*. Out of the ten featured files only six were incorporated in model training. The remaining four files were excluded due to their outlier tendencies.

B. Data Preprocessing:

The preprocessing stage focuses on integrating the varied data sources into one unified analytical framework that maintains the temporal integrity of the dataset

i. Data Integration: The system consolidates six different financial resources, *Accounts_Receivable.csv*,

Businesses.csv, *Credit_Account_History.csv*, *Credit_Card_History.csv*, *Credit_Rating.csv*, and *Loan.csv* using the *company_reg_number* as the main join key.

- ii. Data Selection & Cleaning: The *covid.csv* and *Individual.csv* were filtered out because they comprised of companies' performance during the COVID-19 Pandemic, which had an outlier tendency resulting in inaccurate outcomes.
- iii. Missing Value Estimation: Missing credit card payment records are initialized to zero, while missing loan interest rates are imputed using the dataset median to ensure a continuous feature space.
- iv. Data Normalization: The temporal sequences and the static features are standardized by using the *StandardScaler* to map all the present variables into a common scale
 $z = (x - \mu)/s$ This is essential for stable gradient descent in deep learning models.
- v. Chronological Splitting: In order to eliminate potential data leakage, the dataset is split using temporal cutoff ; the first 80% of the data is used for training purposes while the subsequent 20% data serves as the test set for evaluating the future performance.

C. Feature Engineering: The feature engineering process transforms raw financial transactions into informative indicators for liquidity and risk.

- i. Temporal Features:
 - a. Payment Cycle Analysis: A *payment_delay* feature is retrieved by calculating the difference between the *end_date* and the *invoice_date*.
 - b. Transactional Inflows: Business deposit amounts and monthly invoice totals are combined to estimate total periodic capital inflow.
 - c. Obligatory Outflows: Loan repayments are approximated based on outstanding interest and maturity schedules to represent fixed monthly cash outflows.
- ii. Static Features:
 - a. Risk Anchors: Fixed indicators such as *credit_score*, *failure_score* and *debt_to_revenue_ratio* are filtered to serve as a baseline for organizational safety of the model.
 - b. Asset Liquidity: The present assets and liabilities are analyzed to determine the SME's underlying liquidity position independently of monthly fluctuations.
- iii. Target Variable Construction: The predictive target is defined as the net cash flow for the succeeding month ($t + 1$), measured as the difference between total inflows and the total outflows:

$$net_flow_{t+1} = \sum Inflows_{t+1} - \sum Outflows_{t+1}$$

D. Model Architecture:

The core of the methodology is the “Hybrid Temporal-Static Fusion” network which is designed to overcome the limitations of the standard LSTM models while handling the non-sequential organizational data.

- i. LSTM Branch: This branch processes data into 6-month sliding window. It comprises of 128 hidden units for pattern recognition this is then followed by temporal pooling to compress the time-series history into a fixed-size feature vector.
- ii. Dense Branch: Operates in parallel with LSTM branch. This is a branch of fully connected layers which process static health indicators such as credit scores and failure scores. Batch Normalization stabilizes training alongside Dropout rate of 0.3 to prevent overfitting.
- iii. Feature Fusion: Outputs from both branches are concatenated ($fused = h_{temporal}; h_{static}$) and is passed through a final dense head along with ReLU activation to predict the continuous cash flow value.

E. Training Protocols:

- i. Loss Function: The model is optimized by minimizing the Mean Squared Error (MSE) loss function, given by:

$$L_{MSE} = \frac{1}{N} \sum_{i=1}^N (y_i - \hat{y}_i)^2$$

- ii. Optimization: The training process uses the **Adam** optimizer with a learning rate of 0.001 and batch size of 32.
- iii. Temporal Validation: To prevent potential data leakage, a chronological split is used. The model is trained on first 80% of the sequential data and remaining 20% if data is used for validation. An early stopping mechanism is implemented which monitors the validation loss with a patience of 7 epoch to determine the optimal convergence point.

IV. LITERATURE SURVEY

The evolution of financial forecasting has shifted from linear econometric models to more complex deep learning architectures as market volatility increases. Traditionally, the Autoregressive Integrated Moving Average (ARIMA) served as the industry standard for time-series analysis. However, research by Weytjens et al. (2021) demonstrates that while ARIMA provides a baseline for stationary data, it lacks the representational capacity to handle the non-linear high-dimensional dependencies found in modern organizational cash flows [3]. This is particularly evident in the Small and Medium Enterprise (SME) sector, where liquidity is heavily influenced by irregular payment behaviors and seasonal shifts.

To address these non-linearities, Long Short-Term Memory (LSTM) networks have emerged as a superior alternative for modeling financial trends. Unlike standard Recurrent Neural Networks (RNNs) that suffer from the vanishing gradient problem, LSTMs utilize a

specialized “memory cell” with input, forget, and output gates.


This architecture, pioneered by Hochreiter and Schmidhuber (1997), allows the model to preserve long-term contextual dependencies, such as quarterly tax cycles or annual credit renewals, which are critical for solvency modeling [4]. Fischer and Krauss (2018) further validated the efficacy of LSTMs in financial markets, showing they significantly outperform traditional machine learning benchmarks by capturing complex temporal patterns [5]. To further refine these temporal captures, recent developments by Chen et al. (2023) introduce attention-based LSTM layers, which permit the network to selectively focus on volatile transactional peaks that traditional LSTMs might otherwise smooth over [6].

Recent studies have begun exploring Hybrid Architectures to further enhance precision in niche financial sectors. Lenderink (2022) explored the integration of temporal sequences with static data, finding that hybrid structures yield more accurate results for accounts receivable forecasting than standalone models [7]. Similarly, Vancsura (2025) emphasizes that AI-driven financial forecasting must account for both sequential transaction records and “health context” indicators, such as credit ratings and debt-to-revenue ratios, to ensure stability [8]. This methodology is corroborated by Francis Magloire (2025), who posits that anchoring time-series data with static technical indicators prevents the “drift” often seen in purely sequential models during periods of high market turbulence [9].

This research aligns with the objective of this paper: developing a Hybrid Temporal-Static Fusion framework that grounds time-series predictions in the fixed financial health metrics of the enterprise. Furthermore, the SAI Organization (2024) suggests that the integration of such heterogeneous data streams is a precursor to more advanced Temporal Fusion Transformers (TFT), which represent the next threshold in organizational liquidity modeling [10]. Finally, Fernaldy et al. (2026) highlight that optimizing these forecasts is essential for SMEs to transition from reactive budgeting to proactive risk management [11].


V. RESULTS AND DISCUSSION

The Hybrid Temporal-static network evaluation focuses on the model’s ability to minimize the prediction error by combining the temporal financial sequences with non-variant organization risk metrics.



[Figure 2: Training and validation MSE curves during model training.]

- A. **Model Convergence:** The training process was executed for a total of 25 Epochs using the Adam optimizer algorithm for the hybrid model. The training and validation loss converged steadily. However, an early stopping mechanism was triggered at Epoch 13 shown in Fig 2., when the validation loss failed to improve for seven consequent iterations. The best model state was observed and preserved from Epoch 6 where the validation loss reached its minimum of 0.2166. This fast convergence observed suggests that the model has successfully captured the stable relationship between historical payment cycles and static credit health. This in turn suggests that the model possesses an ability to generalize beyond the training data, reducing the likelihood of overfitting while preserving predictive reliability.
- B. **Analysis of Error Distributions:** The predictive performance of the hybrid architecture was evaluated using the through an analysis of Mean Absolute Error (MAE) and the residual behavior on the test set



[Figure 3: Validation Mean Absolute Error (MAE) across training epochs.]

MAE Distribution: During the initial training stages as shown in Fig, the training logs show that the validation MAE declined noticeably from the initial value of 0.6409, indicating the rapid improvement in model fit. By the selected checkpoint at Epoch 6, the MAE had reduced to 0.3487. This achievement is particularly significant when compared to modern benchmarks; for instance, recent hybrid frameworks like EMD-TI-LSTM have demonstrated that such specialized deep learning configurations can achieve performance improvements of approximately 39% over standard architectures, a trend mirrored by the sharp error reduction observed in this study [12]. This reduction suggests that the model was able to estimate cash flow values with good accuracy for most enterprise profiles rather than fitting only a narrow subset of cases.

Residual Analysis: It indicates that the LSTM branch effectively captured the dominant seasonal patterns of the organizational cash inflows. This is determined by the high concentration of errors around zero, which suggests that the model's predictions are generally accurate for standard operations. A sparse tail in the error distribution is associated with cases that involve irregular *payment_delay* or *disputed* invoice flags, which may signal a high-risk financial behavior that is outside standard liquidity cycles. This uneven distribution suggests that the model separates the small subset of volatile cash flow from the dense cluster of predictable SME activity.

C. **Discussion and Implications:** The results confirm the research hypothesis: integrating temporal feature sequences (LSTM branch) with static organizational context (Dense branch) enhances forecasting precision. A standalone LSTM might fail to account for "risk anchors" like the *failure_score* or *debt_to_revenue_ratio*, while a standalone dense network would be noisy, failing to recognize cyclical repayment trends. The hybrid model reduces forecast volatility by ensuring predictions are grounded in the enterprise's fixed financial health metrics. Furthermore, the architecture demonstrates operational scalability. The temporal sequence processing can be parallelized across different *company_reg_number* groups. The fusion head, once trained, acts as a highly efficient feed-forward network that generalizes across diverse SME sectors, including newly established businesses with limited historical data but established static credit ratings.

VI. CONCLUSION

This research presented and evaluated a hybrid financial forecasting framework that integrates a Long Short-Term Memory network with dense neural layers for modeling complex cash flow behavior in small and medium enterprises. The LSTM component captures long-range temporal dependencies in transactional sequences such as payment delays, recurring inflows, and seasonal outflows on the other hand dense network incorporates static organizational health indicators including credit scores, failure risk, and debt ratios.

Experimental evaluation conducted on the SME – Synthetic UK Business Financial Statistics dataset on comprising financial records of 1,000 enterprises which demonstrates that this combined modeling strategy significantly improves prediction reliability. The proposed framework achieved stable convergence with a minimum validation loss of 0.2166 and reduced to the Mean Absolute Error from 0.6409 to 0.3487 which indicates effective learning across the diverse enterprise profiles. The resulting fused prediction space provides a more robust and interpretable basis for liquidity assessment enabling earlier identification of cash flow stress and supporting proactive financial planning. As a result, the model offers a scalable computational tool for mitigating insolvency risk in volatile and digitally driven market environments.

VII. ACKNOWLEDGMENT

The authors would like to express their gratitude to Dr. B. K. Mishra, Principal, Thakur College of Engineering and Technology, for providing all the necessary facilities and a supportive environment for carrying out this research project. The authors also wish to thank Dr. Prachi Janrao, Head of the Department of Artificial Intelligence and Data Science, for her constant guidance, encouragement, and continuous support throughout the course of study.

The authors are deeply thankful to their project guide, Ms. Pratibha Sajwan, for her constant guidance, valuable suggestions, and on-time feedback, which made a major contribution to the successful completion of this project. Her patience, motivation, and technical input were of utmost importance in shaping the work.

The authors also acknowledge the support and cooperation of the faculty members of the Department of Artificial Intelligence and Data Science, whose assistance and expertise in the field were helpful at various stages of the project. A sense of appreciation is also extended to the laboratory staff for their support and for providing the necessary resources.

Finally, the authors would like to thank their friends and family for their constant encouragement and moral support throughout the duration of the project, which helped them stay motivated and focused.

References:

- [1] A. Dumitrescu et al., "Integrating Artificial Intelligence (AI) into business models to enhance financial resilience," *Journal of Business Strategy*, vol. 46, no. 2, 2025.
- [2] MDPI, "Deep Learning-Based Hybrid Model with Multi-Head Attention for Multi-Horizon Stock Price Prediction," *Applied Sciences*, vol. 14, no. 3, 2024.
- [3] H. Weytjens, E. Lohmann, and M. Kleinsteinuber, "Cash flow prediction: MLP and LSTM compared to ARIMA and Prophet," *Electronic Commerce Research*, vol. 21, pp. 371-391, 2021.
- [4] H. Hochreiter and J. Schmidhuber, "Long Short-Term Memory," *Neural Computation*, vol. 9, no. 8, pp. 1735-1780, 1997.
- [5] T. Fischer and C. Krauss, "Deep learning with long short-term memory networks for financial market predictions," *European Journal of Operational*

Research, vol. 270, no. 2, pp. 654-669, 2018.

- [6] M. Lenderink, "Accounts Receivable Cash Flow Forecasting: A comparison between SES, ARIMA, LSTM and Hybrid ARIMA-LSTM," Master's thesis, Univ. Twente, Enschede, Netherlands, 2022.
- [7] G. Vancsura, "Navigating AI-Driven Financial Forecasting: A Systematic Comparison of LSTM, TDNN, and ARIMA," *Journal of Financial Intelligence*, vol. 12, no. 1, pp. 45-62, 2025.
- [8] A. Fernaldy, S. Hansun, and J. S. Suroso, "Literature Review on Optimizing Cash Flow Forecasting Using Machine Learning in Small and Medium Enterprises," *International Journal of Advanced Trends in Computer Science and Engineering*, vol. 15, no. 1, 2026.
- [9] Y. Chen, L. Wang, and J. Zhang, "Time series prediction based on LSTM-attention-LSTM model," *J. Phys. Conf. Ser.*, vol. 2425, no. 1, 2023.
- [10] P. F. Francis Magloire, "Hybrid Machine Learning Models for Long-Term Stock Market Forecasting: Integrating Technical Indicators," *Big Data Cogn. Comput.*, vol. 9, no. 1, 2025.
- [11] MDPI, "A Novel Hybrid Model (EMD-TI-LSTM) for Enhanced Financial Forecasting," *Mathematics*, vol. 12, no. 4, 2024.
- [12] Science and Information (SAI) Organization, "Temporal Fusion Transformers for Enhanced Multivariate Time Series Forecasting," *Int. J. Adv. Comput. Sci. Appl.*, vol. 15, no. 2, 2024.