Aluminium-Enhanced Detonation Simulation

Kevin Nordin-Bates

October 14, 2026

Abstract

This report describes the development of a simulation capability for aluminised high explosives, from detonation of the charge to afterburning in air, built on the open-source `blastFoam` solver suite (OpenFOAM-12). The target problem is a Composition B charge with 30% aluminium by mass (Comp-B/Al). The modelling uses the multi-fluid solver `blastEulerFoam`, with separate phases for the detonation products, the aluminium particles and the surrounding reactive gas. The report sets out the physical problem and the models chosen for each part of it, distinguishes the capability that existed in `blastFoam` from what was added or changed in this work, describes the verification performed so far, and assesses the status against the aims. At present the detonation and early product expansion are modelled and verified in one dimension; the transfer of products to a reactive gas phase is verified in isolation but not yet used in the Comp-B/Al cases, and the aluminium heating, ignition and combustion models exist only as standalone reference models. No comparison with experimental data for aluminised charges has been made yet.

Contents

1 Introduction **2**
- 1.1 Aim . . . 2
- 1.2 Approach . . . 2
- 1.3 Structure of the report . . . 3

2 Modelling Framework **3**
- 2.1 Phases . . . 3
- 2.2 Governing equations . . . 3
- 2.3 Interphase coupling . . . 3
- 2.4 Pre-existing capability and contributions of this work . . . 4

3 Explosive Charge and Detonation Products **5**
- 3.1 Composition and treatment of the aluminium . . . 5
- 3.2 Programmed burn . . . 5
- 3.3 The eJWLC equation of state . . . 5
- 3.4 Parameters for Comp-B/Al . . . 6
- 3.5 Limitations . . . 6

4 Transfer of the Products to a Reactive Gas Phase **7**
- 4.1 Transfer criterion . . . 7
- 4.2 The `pressurePhaseChange` model . . . 7
- 4.3 The gas phase . . . 7
- 4.4 Reconciliation of the two equations of state . . . 8
- 4.5 Status . . . 8

5 Aluminium Particles **8**
- 5.1 Physical processes . . . 8
- 5.2 Modelling approaches . . . 9
- 5.3 Current implementation . . . 10

6 Mixing, Turbulence and Afterburning **10**
6.1 Mixing of products, particles and air . . . 10
6.2 Turbulence and turbulence–chemistry interaction . . . 10
6.3 Thermal radiation . . . 10

7 Numerical Methods **11**
7.1 Discretisation . . . 11
7.2 Multiphase numerics: conservation and trace phases . . . 11

8 Verification Approach **12**
8.1 Verification and validation . . . 12
8.2 Test hierarchy and automation . . . 12

9 Results **13**
9.1 0D: transfer of products to gas . . . 13
9.2 1D canonical problems . . . 13
9.3 Spherical blast of a C4 charge . . . 14
9.4 Spherical Comp-B/Al charge . . . 14
9.5 Reference models for aluminium particles . . . 17

10 Status and Plan **18**
10.1 Status against the aims . . . 18
10.2 Open issues . . . 18
10.3 Plan . . . 19

A Upstream Demonstration Cases **19**

1 Introduction

1.1 Aim

The aim of this work is a validated simulation method for the detonation of an aluminised explosive charge and the subsequent blast and afterburning in air. The process has four parts, each with its own physics and time scale:

1. detonation of the charge and early expansion of the detonation products, governed by a high-pressure equation of state (microseconds);
2. mixing of the products with the surrounding air and finite-rate combustion of the fuel-rich products (CO, H_2, ...) in this mixture (tens of microseconds to milliseconds);
3. transport, heating, ignition and combustion of the aluminium particles dispersed in the expanding gas (hundreds of microseconds to milliseconds);
4. afterburning of the aluminium in the mixture of products and air, which raises the late-time pressure and the positive impulse.

The final target is a multi-dimensional simulation of a Comp-B/Al charge whose peak overpressure, arrival time and positive impulse agree with free-field gauge data (within 8%, Section 10).

1.2 Approach

The work builds on `blastFoam` [1], an OpenFOAM-based suite for high-explosive detonation and airblast. Two of its solvers are relevant. `blastFoam` solves multiphase flows with a single mixture velocity and energy; `blastEulerFoam` is a multi-fluid (Euler–Euler) solver in which each phase has its own mass, momentum and energy equations, coupled through finite-rate exchange terms. Since the aluminium particles lag the gas, heat up at their own rate and burn after a delay, they are modelled as a separate phase, and the work therefore uses `blastEulerFoam`. The development is staged from zero-dimensional (0D) unit tests through one-dimensional (1D) planar and spherical cases to multi-dimensional simulations, with an automated test suite at each level (Section 8).

External tools are used for reference data: the ideal detonation code `EuDetCode` (chemical equilibrium, CJ state, expansion isentropes and JWL fits; a separate code, not part of the `blastFoam` repository) and the 1D multiphase code `gunIB1D` for cross-solver comparison of granular shock problems.

1.3 Structure of the report

Section 2 describes the multi-fluid modelling framework and lists what was pre-existing and what was developed in this work. Sections 3–6 cover the physical models for the four parts of the problem: the explosive and its products, the transfer of the products to a reactive gas, the aluminium particles, and mixing and afterburning. Section 7 describes the numerical methods, including the changes needed to make the multi-fluid solver conservative and stable for this problem. Section 8 describes the verification approach and Section 9 the results. Section 10 assesses the status against the aims and gives the plan for the remaining work. Throughout, [UPSTREAM] marks capability that existed in `blastFoam` before this work, and [THIS WORK] marks what was added or changed.

2 Modelling Framework

2.1 Phases

A Comp-B/Al charge is modelled with three phases:

- `compBAl`: the explosive and its detonation products, a 'detonating' fluid phase in which a reaction progress variable λ moves the state from the unreacted explosive (Murnaghan EOS) to the products (`eJWLC` EOS, Section 3);
- `Al`: the aluminium particles, a granular phase with a compressible solid EOS (Murnaghan) and kinetic theory for the particle stresses;
- `gas`: the surrounding air and, once transferred, the detonation products as a multicomponent reactive gas (JANAF thermodynamics, Abel–Nobel EOS, Section 4).

Initially the charge region holds $\alpha_{\mathrm{compBAl}} = 0.818$ and $\alpha_{\mathrm{Al}} = 0.182$ (27% of the charge mass as inert Al at $1820\,\mathrm{kg/m^3}$; Section 3.1), and the gas fills the rest of the domain.

2.2 Governing equations

`blastEulerFoam` [UPSTREAM] solves, for each phase k with volume fraction α_k, density ρ_k, velocity $\mathbf{u}_k$, pressure p_k and specific total energy $E_k = e_k + \frac{1}{2}|\mathbf{u}_k|^2$, a set of balance equations of Baer–Nunziato type [3, 4]:

$$\frac{\partial \alpha_k \rho_k}{\partial t} + \nabla \cdot (\alpha_k \rho_k \mathbf{u}_k) = \Gamma_k, \tag{1}$$

$$\frac{\partial \alpha_k \rho_k \mathbf{u}_k}{\partial t} + \nabla \cdot (\alpha_k \rho_k \mathbf{u}_k \mathbf{u}_k + \alpha_k p_k \mathbf{I}) = p_I \nabla \alpha_k + \mathbf{M}_k + \Gamma_k \mathbf{u}_I, \tag{2}$$

$$\frac{\partial \alpha_k \rho_k E_k}{\partial t} + \nabla \cdot \big(\alpha_k (\rho_k E_k + p_k) \mathbf{u}_k\big) = -p_I \frac{\partial \alpha_k}{\partial t} + \mathbf{M}_k \cdot \mathbf{u}_I + Q_k + \Gamma_k E_I, \tag{3}$$

where Γ_k is the interphase mass transfer, $\mathbf{M}_k$ the interphase momentum transfer (drag), Q_k the interphase heat transfer, and p_I, $\mathbf{u}_I$, E_I are interfacial values set per phase pair (`interfacialPressure`, `interfacialVelocity`). The volume fractions sum to one; the fluid volume fractions are advected with the mixture velocity, and the granular phase adds the kinetic-theory stresses (granular temperature Θ, Lun et al. collisional pressure, Johnson–Jackson frictional stress [10]). Species mass fractions in the gas are transported with the gas mass flux and react through finite-rate chemistry (Section 4.3).

2.3 Interphase coupling

The phases exchange momentum and energy through finite-rate models and through relaxation steps applied after each stage of the time integration:

- *Particle drag and heat transfer* [UPSTREAM]: Gidaspow–Ergun–Wen–Yu drag and Ranz–Marshall heat transfer between the Al and each fluid phase. None of the available drag laws depends on the particle Mach number (Section 5.3).

- *Products/gas velocity*: the two fluid phases are relaxed instantaneously to a common velocity (`VRelaxation instant`) [UPSTREAM]; the energy update was made conservative [THIS WORK] (Section 7.2).
- *Products/gas pressure and temperature* [THIS WORK]: in cells where the products and the gas are numerically mixed, the volumes of the non-carrier fluid phases are exchanged until the pressures agree (`equilibrateDiluteVolumes`, with the $\bar{p}\,\Delta\alpha$ work moved between the phase energies), and the temperatures are relaxed by a stiff constant-coefficient heat transfer integrated exactly. The upstream pressure-relaxation solver collapses the time step in these cells and is not used.
- *Mass transfer*: products → gas by the `pressurePhaseChange` model [THIS WORK] (Section 4); Al → gas by the reacting-particle model with an empirical burn rate [UPSTREAM], limited to gas-phase oxidiser [THIS WORK] (Section 5.3).

2.4 Pre-existing capability and contributions of this work

The work is on a fork of `blastFoam`; all changes are relative to the upstream commit `71b97fd7`, and are listed in detail in `UPDATES.md` of the repository. Table 1 summarises the division.

Table 1: Capability used in this work: pre-existing in `blastFoam` (upstream `71b97fd7`) and added or changed in this work.

Area	**Pre-existing in `blastFoam`**	**Added or changed in this work**
Solvers	`blastFoam`, `blastEulerFoam` (multi-fluid, kinetic theory, drag and heat-transfer models, relaxation), `blastParcelFoam` (Lagrangian), `blastReactingFoam`	Conservative phase decode; dilute-phase volume equilibration; energy-conserving velocity relaxation and drag work; granular phase transports thermal energy (with compression energy) instead of total energy; mixture-pressure buoyancy on the granular phase; no density floor in the fluid decode
Detonation	JWL, JWLC, BKW and other EOS; `programmedIgnition` activation; detonating phase thermo	`eJWLC` EOS (3-term isentrope, energy-based, T_{CJ}/ω_T temperature closure); `nodeProgrammed` activation; products-only fitting procedure and E_0/ω_T calibration
Reactive gas	JANAF thermo, Abel–Nobel EOS, multicomponent mixtures, chemistry and combustion models (single-phase systems)	Multicomponent and reacting thermo for individual phases of a multiphase system; JANAF extrapolation with constant c_p above the fit range; mass-weighted covolume mixing
Phase transfer	Temperature-based transfer was not available in this code base	`pressurePhaseChange` (pressure-interval transfer with species allocation; conservative mass, momentum and energy transfer in `blastEulerFoam`)
Aluminium	Reacting diameter model with empirical rates (pressure-based, Arrhenius); reacting-particle mass transfer	Oxidiser limit on the burn rate; registered initial diameter (fixes AMR crash); Al gas-phase reactions in the test cases; standalone reference models for heating, ignition, d^n combustion and condensation (not in the solver)
Numerics	HLL, HLLC, AUSM+, Kurganov–Tadmor flux schemes; MUSCL reconstruction; RK time integration; AMR and load balancing	HLLC phase flux rewritten to the standard star-state form; trace-phase mixture impedance (`alphaTrace`); covolume and temperature-range guards; Courant number with mass exchange
Post-processing	Probes, field function objects	`temporalMax`, `temporalIntegral` (peak pressure and impulse maps, AMR-aware)
Testing	Tutorials (no automated verification)	0D/1D/1D-spherical test cases with verification scripts; regression runner (`bin/run_blast_tests.py`); EOS fitter (`utilities/thermo_fitter`); report figure generation

3 Explosive Charge and Detonation Products

3.1 Composition and treatment of the aluminium

In an aluminised explosive the charge is a mixture of the high explosive and aluminium particles. Micron-sized particles ($d \gtrsim 1\,\mu$m) react little in the detonation zone ($\sim$ 10–100 ns); they act as a momentum and heat sink that lowers the detonation velocity and pressure, and burn later in the expanding products and in air [12]. Nano-sized particles can react partly in the early expansion.

The inert part of the aluminium is modelled as a separate granular phase. This lets the particles develop their own velocity and temperature, which matters for the ignition delay and the spatial distribution of the later energy release. It also means that the products EOS must describe the products alone: the thermochemical calculation includes the aluminium in the reactants, but the JWL-type fit is made to the products isentrope with the volume of the inert aluminium excluded, so that the aluminium is not counted twice. For the Comp-B/Al charge (70% Comp-B, 30% Al), 90% of the aluminium is taken as inert in the detonation, i.e. 27% of the charge mass, giving $\alpha_{\mathrm{Al}} = 0.182$ and a products-phase initial density $\rho_0 = 1624.45\,\mathrm{kg/m^3}$.

3.2 Programmed burn

The detonation is not resolved; the reaction front is prescribed (programmed burn). In the `nodeProgrammed` activation model [THIS WORK], the arrival times $t = t_0 + |\mathbf{x} - \mathbf{x}_{\mathrm{ign}}|/D_{\mathrm{CJ}}$ at the vertices of each cell give a start and end time t_{start}, t_{end}, and the progress variable ramps linearly across the cell,

$$\lambda = \min\left(1, \max\left(0, \frac{t - t_{\mathrm{start}}}{t_{\mathrm{end}} - t_{\mathrm{start}}}\right)\right), \tag{4}$$

optionally also triggered by compression ahead of the front (`PROGRAMMEDBETA`). The detonating phase blends the unreacted and products states with λ. Because the front speed is imposed, a correct detonation velocity in a simulation is not a test of the model; what can be tested is the pressure and flow behind the front, which depend on the EOS and on the resolution (Section 9.4). The detonation velocity D_{CJ} and pressure p_{CJ} come from `EuDetCode`.

3.3 The eJWLC equation of state

The products are described by the energy-based Mie–Grüneisen form `eJWLC` [THIS WORK], built on the three-term (JWLC) isentrope through the CJ state. With $V = \rho_0/\rho$,

$$p_s(V) = A\,e^{-R_1 V} + B\,e^{-R_2 V} + C\,V^{-(\omega+1)}, \tag{5}$$

$$e_s(V) = v_0\left[\frac{A}{R_1}e^{-R_1 V} + \frac{B}{R_2}e^{-R_2 V} + \frac{C}{\omega}V^{-\omega}\right] + E_0, \tag{6}$$

$$p(\rho, e) = p_s(V) + \omega\rho\,\big(e - e_s(V)\big), \tag{7}$$

where e_s follows from $\mathrm{d}e_s = -p_s\,\mathrm{d}v$ along the isentrope, $v_0 = 1/\rho_0$, and ω is the (constant) Grüneisen coefficient. The constant E_0 sets the energy datum; it does not change $p(\rho, e)$ for given $e - e_s$, and is used to put the products on the same datum as the gas phase (Section 4.4).

JWL-type equations are mechanical: they relate p, v and e but do not define a temperature. A temperature is needed for the heat transfer to the particles and to the gas. `eJWLC` uses a power law along the isentrope and a constant heat capacity off it:

$$T_s(V) = T_{\mathrm{CJ}}\left(\frac{V_{\mathrm{CJ}}}{V}\right)^{\omega_T}, \qquad T(\rho, e) = T_s(V) + \frac{e - e_s(V)}{C_v}, \tag{8}$$

with T_{CJ} and $V_{\mathrm{CJ}} = \rho_0/\rho_{\mathrm{CJ}}$ from `EuDetCode`. The exponent ω_T defaults to ω; since it does not enter the pressure, it can be chosen so that T_s also passes through a second known state, here the temperature of the gas formed at the transfer pressure (Section 4.4). With $\omega_T \neq \omega$ the closure is not thermodynamically consistent with a constant-C_v Mie–Grüneisen EOS; it is a temperature closure only.

3.4 Parameters for Comp-B/Al

The parameters are fitted to the CJ state and expansion isentrope from `EuDetCode` (BKW EOS, `Gas24CHNO` database, reactants RDX 0.42, TNT 0.28, Al 0.30 by mass, 90% of the Al inert). Table 2 lists the fit to the products alone, used in all Comp-B/Al cases, and the fit to the full mixture for comparison; Figure 1 shows the isentropes. The products fit is within 5% of the equilibrium isentrope below 2 GPa (3.8% at the 100 bar transfer pressure, −5.8% at 20 bar) but up to 15% high near 9 GPa; the full-mixture fit has errors of similar size. The products fit gives $D_{\mathrm{CJ}} = 7154.23\,\mathrm{m/s}$, $p_{\mathrm{CJ}} = 20.15\,\mathrm{GPa}$, $T_{\mathrm{CJ}} = 3844.39\,\mathrm{K}$ and $\rho_{\mathrm{CJ}} = 2150.55\,\mathrm{kg/m^3}$. In the cases, $C_v = 1450\,\mathrm{J/(kg\,K)}$ (JANAF c_v of the frozen product gas at 2500 K), $E_0 = -503.47\,\mathrm{kJ/kg}$ and $\omega_T = 0.3711$ (Section 4.4).

Table 2: eJWLC parameters for 70% Comp-B / 30% Al (90% of the Al inert) fitted to the `EuDetCode` isentrope. The products fit is used in the simulations, with the C_v, E_0 and ω_T of Section 3.4.

Parameter	Full mixture	Products only	Unit
ρ_0	1820	1624.45	$\mathrm{kg/m^3}$
A	1428.3	224.94	GPa
B	12.17	2.773	GPa
C	1.133	1.470	GPa
R_1	5.858	3.456	–
R_2	1.386	0.8134	–
ω	0.3013	0.3027	–




Figure 1: CJ expansion isentropes from `EuDetCode` for 70% Comp-B / 30% Al (90% of the Al inert), down to 20 bar: (a) full mixture (v_{total}), products (v_{prod}) and inert aluminium (v_{inert}), with the full-mixture and products JWL fits; (b) relative error of the fits along the isentrope.

3.5 Limitations

- *Range.* The fit covers expansion to $V/V_{\mathrm{CJ}} \approx 10$–$20$. Beyond that the constant-ω tail is not reliable, which is one reason for transferring the products to a gas EOS (Section 4).
- *Temperature.* The power law with constant exponent does not follow the equilibrium isentrope temperature: along the expansion the equilibrium temperature falls faster, and the power law with $\omega_T = \omega$ is 550–820 K too high between 0.1 and 1 GPa (Figure 2). With the calibrated ω_T the error is reduced to 270–630 K there and changes sign near the transfer pressure (−80 K at 100 bar, −190 K at 20 bar). The constant C_v ignores shifting equilibria and vibrational excitation. Temperature errors of this size affect the heat transfer to the particles and therefore the ignition delay.




Figure 2: Temperature along the CJ isentrope of the products of 70% Comp-B / 30% Al: equilibrium (`EuDetCode`) and the eJWLC power law with $\omega_T = \omega$ and with the calibrated ω_T used in the cases, against (a) pressure and (b) specific volume. The circle is the gas-EOS temperature at the 100 bar transfer state.

4 Transfer of the Products to a Reactive Gas Phase

The detonating phase does not carry species. To model combustion of the fuel-rich products with air, the products are transferred, once expanded, to the multicomponent gas phase with a frozen product composition.

4.1 Transfer criterion

The transfer is triggered by pressure rather than temperature. The eJWLC pressure follows the equilibrium isentrope to within about 5% between 2 GPa and 20 bar for this fit, while its temperature is in error by hundreds of kelvin (Section 3.5), so a temperature threshold would trigger at the wrong state. A pressure window also corresponds to the physical freeze-out of the product chemistry, which occurs at roughly 50–200 bar as the expansion becomes faster than the recombination reactions.

4.2 The `pressurePhaseChange` model

The `pressurePhaseChange` model [THIS WORK] transfers mass from a source phase (the products) to one or more target phases at the rate

$$\dot{m} = \frac{\alpha_s \rho_s}{\tau}\,\Gamma(p)\,\lambda_s, \tag{9}$$

where τ is a relaxation time, λ_s the burn fraction of the source, and $\Gamma(p)$ a smooth window between p_{lower} and p_{upper} of width p_{range},

$$\Gamma(p) = \tfrac{1}{4}\left(1 + \tanh\frac{p_{\text{upper}} - p}{p_{\text{range}}}\right)\left(1 + \tanh\frac{p - p_{\text{lower}}}{p_{\text{range}}}\right), \tag{10}$$

cut off two widths outside the window (a one-sided form is used for $p_{\text{lower}} = 0$). The transferred mass is distributed over the target species with prescribed mass or mole fractions (the frozen `EuDetCode` composition at freeze-out). In `blastEulerFoam` the transferred mass carries the source velocity and specific total energy, and the volume moves with the mass; mass, momentum and total energy are then conserved by the transfer itself. The energy datums of the two phases must agree; this is arranged offline through E_0 (Section 4.4), and no state-dependent energy correction is applied at run time.

4.3 The gas phase

The gas phase is a multicomponent mixture of air and product species (O_2, N_2, CO, CO_2, H_2O, H_2, NH_3, CH_4, C_2H_6, C(gr), Al, Al_2O_3(s)) with JANAF 7-coefficient thermodynamics, Sutherland transport and the Abel–Nobel (covolume) EOS

$$p = \frac{\rho R_{\text{mix}} T}{1 - b\rho}, \qquad b = \sum_k Y_k b_k, \tag{11}$$

which accounts for the excluded volume of the dense product gas and tends to the ideal gas for $b\rho \ll 1$. Species are transported with the gas mass flux and react by finite-rate chemistry (laminar, one-step reactions for CH_4, CO, H_2 and Al oxidation in the current cases, integrated with an adaptive Runge–Kutta solver). The multicomponent and reacting thermo for an individual phase of a multiphase system was added in this work; the underlying JANAF, Abel–Nobel and chemistry models are upstream.

High temperatures. The JANAF fits of the air species end at 5000 K. In `blastFoam` the properties were evaluated at the clamped temperature, so the gas could not exceed 5000 K and the energy of strongly shocked air was misrepresented. In this work the properties are extrapolated with constant c_p above the fit range, with enthalpy and entropy extended consistently, and the decode temperature cap is raised to 50 000 K. This removes the cap but not the physics that is missing: there is no dissociation, so strongly shocked air is too hot (up to 14 400 K in the spherical cases and 24 800 K in a planar case, where equilibrium air would stay near 10 000 K or below). NASA-9 polynomials to 20 000 K with $O_2/N_2/NO$ dissociation are planned (Section 10).

4.4 Reconciliation of the two equations of state

The two phases measure energy from different datums. The JANAF datum includes the heats of formation, so the frozen product gas has a large negative energy; the eJWLC datum is arbitrary (the constant E_0). If the datums are not reconciled, mass transferred at constant specific energy arrives in the gas at the wrong temperature and pressure; with $E_0 = 0$ the pressure after transfer at 100 bar would be about 50% too high.

The matching is done at the transfer pressure $p_{\mathrm{tr}} = 100\,\mathrm{bar}$, on the products isentrope ($v_{\mathrm{tr}} = 2.838 \times 10^{-2}\,\mathrm{m^3/kg}$):

1. *Pressure continuity.* The gas temperature at $(p_{\mathrm{tr}}, v_{\mathrm{tr}})$ follows from the Abel–Nobel EOS of the frozen composition ($R_{\mathrm{mix}} = 324.35\,\mathrm{J/(kg\,K)}$, $b = 1.263 \times 10^{-3}\,\mathrm{m^3/kg}$): $T_{\mathrm{tr}} = p_{\mathrm{tr}}(v_{\mathrm{tr}} - b)/R_{\mathrm{mix}} = 836.10\,\mathrm{K}$.

2. *Energy datum.* E_0 is chosen so that the eJWLC energy at v_{tr} equals the gas energy at T_{tr} on the `blastFoam` gas convention, $e_{\mathrm{gas}} = \sum_k Y_k(h_{s,k} - R_k T) = 0.4341\,\mathrm{MJ/kg}$; this gives $E_0 = -503.47\,\mathrm{kJ/kg}$.

3. *Temperature continuity.* ω_T is chosen so that $T_s(V_{\mathrm{tr}}) = T_{\mathrm{tr}}$ with T_{CJ} unchanged:

$$\omega_T = \frac{\ln(T_{\mathrm{CJ}}/T_{\mathrm{tr}})}{\ln(V_{\mathrm{tr}}/V_{\mathrm{CJ}})} = 0.3711.$$

The procedure is implemented in `utilities/thermo_fitter/products_only_fit.py` [THIS WORK]. It gives exact pressure and temperature continuity at the matching state; elsewhere in the transfer window the mismatch depends on how closely the two EOS agree. A further step, matching the slope of the isentrope (C^1 continuity) by setting the asymptotic ω to $\gamma_{\mathrm{mix}} - 1$ of the frozen gas, is implemented in the fitter (`fit_ejwlc_nobleabel.py`) but is not used in the current fit, which keeps the `EuDetCode` value of ω. Figure 3 compares the two descriptions along the expansion.

A state-dependent energy correction (e.g. the difference between the two EOS energies at the local temperature) is deliberately not used: it adds energy in proportion to the JWL temperature error. In a 0D test it added about 480 kJ/kg and raised the pressure by 56%.

4.5 Status

The transfer is verified in a 0D reactor and in a planar detonation (Section 9). It is not yet enabled in the Comp-B/Al spherical cases or tutorials, where the products remain in the eJWLC phase; enabling it is the next step for modelling the products afterburning (Section 10).

5 Aluminium Particles

5.1 Physical processes

Heating, melting and ignition. The particles are heated by convection from the products and the shocked air. Aluminium melts at 933 K ($\Delta H_{\mathrm{fus}} \approx 397\,\mathrm{kJ/kg}$), which holds the particle temperature during melting. The particles are coated with an oxide shell that prevents combustion until it fails, at about 2050–2300 K near the oxide melting point; the ignition temperature depends on the heating rate and the




Figure 3: Products and gas around the transfer state for 70% Comp-B / 30% Al: (a) isentropes of the equilibrium products (`EuDetCode`), the eJWLC fit, and the Abel–Nobel frozen gas through the 100 bar transfer state; (b) temperatures along the expansion (eJWLC with the calibrated ω_T). The pressure error of the fit along the isentrope is shown in Figure 1(b).

environment. At the heating rates behind a blast wave ($h \sim 10^4$–10^5 W/(m^{2}K)) the particle interior lags its surface, which ignites first.

Combustion. Micron-sized particles burn with a detached vapour-phase diffusion flame; the burn time scales as $t_b \propto d^n$ with $n \approx 1.8$–2. Nano-sized particles burn by surface kinetics with $n \approx 1$. A widely used correlation for micron particles in mixed oxidisers is that of Beckstead [12],

$$t_b\,[\mathrm{ms}] = \frac{a\,d^{\,n}}{X_{\mathrm{eff}}\,p^{0.1}\,T_0^{0.2}}, \qquad X_{\mathrm{eff}} = X_{\mathrm{O_2}} + 0.6X_{\mathrm{H_2O}} + 0.22X_{\mathrm{CO_2}}, \tag{12}$$

with $a = 0.00735$, $n = 1.8$, d in μm, p in atm and the ambient temperature T_0 in K. For the 20–40 μm powders of typical aluminised explosives the correlation gives 1.6–5.5 ms in air at 2800 K, so the aluminium is essentially unburnt during the detonation and early expansion and releases its energy in the fireball.

Reactions and energy. The aluminium reacts with O_2 (31 MJ/kg Al to Al_2O_3), H_2O (15.4 MJ/kg) and CO_2 (13.6 MJ/kg). The reactions with H_2O and CO_2 allow burning inside the products before air is entrained. The flame forms gaseous sub-oxides and Al_2O_3 vapour, which condense to sub-micron oxide smoke; the condensation (about 18–19 MJ/kg of oxide) is a large part of the heat release and holds the flame temperature near the oxide boiling point (about 3800–4000 K at elevated pressure). The smoke is a strong emitter, so radiation can be a significant loss from the fireball (Section 6.3).

5.2 Modelling approaches

Four approaches are candidates for the particle phase; their selection is part of the planned work (Section 10).

- *Eulerian multi-fluid* (current): the particles are a continuum phase with its own velocity and temperature. Appropriate in the dense charge ($\alpha_{\mathrm{Al}} \approx 0.2$) and early expansion; a single size class per phase; numerical diffusion at the edge of the dispersing cloud.
- *Lagrangian parcels* (`blastParcelFoam` [UPSTREAM]): particle trajectories with their own size, temperature and burn history; natural polydispersity and no numerical diffusion. Standard implementations neglect the particle volume, which is not acceptable in the dense charge; a dense formulation (gas volume fraction in the carrier equations, particle stress, kernel projection of parcel volume) would be needed.
- *Population balance*: size classes (sectional) or transported moments (QMOM) of the size distribution in the Eulerian framework, with burning as a moment source.

- *Hybrid*: Eulerian in the dense core, converted conservatively to Lagrangian parcels where α_{Al} falls below a threshold (about 10^{-3}).

5.3 Current implementation

In the solver the aluminium is a granular Eulerian phase [UPSTREAM] with a compressible solid EOS (Murnaghan), Gidaspow–Ergun–Wen–Yu drag and Ranz–Marshall heat transfer. The burn rate of the reacting diameter model [UPSTREAM] is the empirical pressure law $r_b = a\,(p/1\,\mathrm{MPa})^n$ for $p \geq p_{\min}$ ($a = 5 \times 10^{-5}$ m/s, $n = 0.7$, $p_{\min} = 2$ bar, $d_0 = 30\,\mu$m), chosen to give a burn time of the order of 0.5 ms. This law is not a physical model of aluminium combustion: it has no ignition delay and no oxidiser dependence. This work added a limit to gas-phase oxidiser (the rate is multiplied by the gas fraction of the surrounding fluid and by $\min(1, \sum Y_{\mathrm{ox}}/Y_{\mathrm{ref}})$ over O_2, CO_2, H_2O), so that the particles do not burn inside the products, and a correction so that the granular phase transports its thermal energy with the compression energy of the solid EOS (before, the particles cooled to the 100 K floor behind the detonation).

Not in the solver: Mach- and Knudsen-number-dependent drag (the relative Mach number behind the blast exceeds 0.3, where incompressible correlations overestimate the drag), melting, the ignition criterion, the Beckstead rate and the oxide condensation. These exist as standalone Python reference models (Section 9.5), to be implemented in the solver.

6 Mixing, Turbulence and Afterburning

6.1 Mixing of products, particles and air

The products and the aluminium can only burn with air after mixing with it. At the product–air contact the mixing is driven by the Richtmyer–Meshkov instability (shock passage across the density interface, including the reflected shocks), the Rayleigh–Taylor instability (deceleration of the dense products by the air) and Kelvin–Helmholtz instability of the resulting shear layers. At fireball temperatures the gas-phase reactions and the burning of small particles are fast compared with the mixing (Damköhler number $\gg 1$), so the afterburning rate is controlled by the mixing.

The gas and the particles mix differently. Gas-phase products follow the flow and mix down to molecular scales; their combustion is confined to the turbulent mixing layer. Particles have inertia, characterised by the Stokes number $\mathrm{St} = \tau_p/\tau_f$ with $\tau_p = \rho_p d^2/(18\mu_g)$: large particles ($\mathrm{St} > 1$, $d \gtrsim 15$–$30\,\mu$m) decouple from the decelerating gas and penetrate ahead of the products into fresh air, small particles follow the gas, and particles with $\mathrm{St} \sim 1$ concentrate between vortices. The aluminium can therefore burn in a distributed volume ahead of the gaseous fireball, which sustains the late-time pressure.

These effects are multi-dimensional; in 1D the particle cloud stays inside the products except at its dilute edge (Section 9.4).

6.2 Turbulence and turbulence–chemistry interaction

Large-eddy simulation (LES, with e.g. WALE or dynamic Smagorinsky subgrid models) is the natural choice for instability-driven mixing, which is dominated by large coherent structures; RANS (k–ω SST with compressibility corrections) is cheaper for parametric studies in 2D. The mean reaction rate cannot be evaluated at the mean temperature and composition; subgrid closures such as the partially stirred reactor (PaSR, rate reduced by $\kappa = \tau_c/(\tau_c + \tau_{\mathrm{mix}})$) or the eddy dissipation concept account for the unresolved mixing. Turbulence models are available in OpenFOAM and `blastFoam` [UPSTREAM]; their use for this problem has not been assessed.

6.3 Thermal radiation

Radiation from the oxide smoke at 3000–4000 K can be a significant energy loss from the fireball. The radiative transfer equation can be solved in the P1 or discrete-ordinates approximation with a Planck-mean absorption coefficient of the smoke. Radiation models are available in `src/radiationModels` [UPSTREAM], but no solver used here couples them to the multi-fluid energy equations; this would be needed if the radiative loss turns out to be significant.

7 Numerical Methods

7.1 Discretisation

The equations are solved by a finite-volume Godunov method [UPSTREAM]. Each phase has its own approximate Riemann solver; the Comp-B/Al cases use HLLC [5] for all phases, with second-order MUSCL reconstruction (Minmod limiter) and a two-stage strong-stability-preserving Runge–Kutta scheme (RK2SSP). AUSM+, HLL and Kurganov–Tadmor are also available. The time step is limited by the phase Courant numbers (0.2 in the Comp-B/Al cases) and, in this work, by the rate of interphase mass loss. Adaptive mesh refinement (AMR) and load balancing are available [UPSTREAM] but not yet used in the Comp-B/Al cases.

This work rewrote the HLLC phase flux to the standard star-state form $F + S(U^* - U)$ with separate owner and neighbour star states, an explicit branch for left-moving waves and a guarded contact speed.

7.2 Multiphase numerics: conservation and trace phases

A multi-fluid solver must handle cells where a phase is absent or present only as a trace, which in a detonation problem is most of the domain for each phase. The upstream treatment and the first version of this work reset dilute phases ($\alpha < 0.01$) towards reference states and wrote the result back to the conserved variables. This destroyed energy (1–2% in the 0D transfer test) and removed the energy of the products expanding into the air. The following changes were made [THIS WORK]; together they make the solver conservative and keep trace phases bounded.

- *Conservative decode.* The conserved variables $\alpha\rho$, $\alpha\rho\mathbf{u}$, $\alpha\rho E$ are modified only where a phase is residual ($\alpha \leq$ `residualAlpha`, 10^{-6}); bounds on velocity and temperature act on the primitive variables only. The decoded density is no longer bounded below by a reference density, which had held expanded gas at ambient density and overstated its pressure up to twenty-fold.

- *Pressure of trace phases.* Without pressure relaxation, all fluid phases in a cell undergo the same volumetric strain, so a trace of one fluid in another acquires an unrelated density and pressure. Non-carrier fluid phases are brought to pressure equilibrium with the carrier by a damped Newton volume exchange, $\Delta\alpha = (p_k - p_c)/(\rho_k c_k^2/\alpha_k + \rho_c c_c^2/\alpha_c)$, with the work $\bar{p}\,\Delta\alpha$ moved between the phase energies. Trial states outside the range of an EOS (e.g. gas compressed past its covolume) are rejected. In numerically mixed products/air cells the temperatures are relaxed with a stiff heat transfer integrated exactly; without it, products that are a trace by mass reached 10^5 K.

- *Energy of the relaxation and drag.* The instantaneous velocity relaxation added the dissipated kinetic energy to the total energy a second time; it now keeps each phase's internal energy plus its own dissipation. The work of the implicit drag is evaluated at the interfacial velocity averaged over the update.

- *Trace phases in the Riemann fluxes.* A phase that is a trace on one side of a face was given its own impedance in the HLLC flux. For a trace of explosive in an air cell this impedance is that of the explosive, and a small velocity of the air caused large face-pressure changes that destabilised the charge/air interface. Where a fluid phase is a trace on a side ($\alpha <$ `alphaTrace` $= 10^{-3}$, blended linearly), the wave speeds and the common star pressure now use the mixture density, sound speed, velocity and pressure of that side, while the fluxes still carry the phase's own mass and energy; a residual upwind side carries no flux. A stationary unreacted charge next to air then stays at rest (Section 9.4).

- *Residual stabilisation.* The upstream fluid momentum and energy equations added their residual-cell stabilisation with the wrong sign, which lowered the matrix diagonal to $(\alpha\rho - \alpha_{\mathrm{res}}\rho_{\mathrm{res}})/\Delta t$: zero where α equals the residual fraction. This caused the floating-point exceptions of the 2D Comp-B/Al tutorial at 116 and 171 μs; with the sign corrected the run reaches 200 μs.

- *Granular phase.* The particle packing limit is enforced by the frictional stress (with a small `alphaDeltaMin`), not by removing mass; the buoyancy on the particles uses the mixture fluid pressure, since the individual fluid pressures are undefined where a phase is absent.

The remaining known defects at this level are a few time steps in which trace gas ($\alpha \sim 10^{-6}$) inside the products reaches the 50 000 K decode cap, which is energetically negligible but not understood, (Section 10).

8 Verification Approach

8.1 Verification and validation

Verification checks that the equations are solved correctly: conservation, agreement with exact or reference solutions, and agreement with another code solving the same model. *Validation* checks that the model describes reality, by comparison with experiments. Most of the work so far is verification. The only comparison with empirical data is with the Kinney–Graham correlations for TNT, for a C4 charge (Section 9.3); no experimental data for aluminised charges have been used yet.

8.2 Test hierarchy and automation

Each model is tested in the simplest configuration that isolates it, from 0D reactors (one cell, no transport) through 1D planar problems to 1D spherical blasts; multi-dimensional cases follow. Every test has a verification script with explicit pass criteria. The runner `bin/run_blast_tests.py` [THIS WORK] runs the 18 tests in four tiers (Table 3), checks the solver logs for errors and for normal completion, and runs the scripts. Some tests depend on external builds (`EuDetCode`, `gunIB1D`).

Three limitations of the current verification should be noted. First, the programmed burn imposes the detonation velocity, so agreement of the front speed with D_{CJ} only checks the setup. Second, no mesh-convergence studies have been made; the reported values are for one mesh per case. Third, several tests check reference models outside the solver (the aluminium and high-temperature air models) and are marked as such.

Table 3: Automated tests: what each checks, and the result of the most recent run. "Model" marks a standalone reference model that does not run the solver.

Tier	Test	What is checked	Result	Status
0	`EuDetCode` unit tests	CJ, ZND, isentrope calculations of the reference code	169/169	Pass
0	EOS fitter	Pressure continuity of the fitted EOS at 100 bar	$\Delta p = 0$	Pass
1	`phaseTransfer_0D`, `_3phase`	0D products → gas transfer (`blastEulerFoam`), with and without inert Al: conservation, pressure, temperature	Energy 4.2×10^{-9} / 2.2×10^{-9}, $\Delta p/p = 3 \times 10^{-7}$, 99.4% converted	Pass
1	Al particle kinetics	Heating, melting, ignition, Beckstead burning, oxide condensation	Reference behaviour reproduced	Model
1	High-T air	NASA-9 thermodynamics and O_2/N_2 dissociation equilibrium to 6000 K	Agreement with tabulated data	Model
1	`pressurePhaseChangeTest`	1D transfer with species allocation (`blastFoam`)	Runs to completion	Pass
2	`ChargeCompBAl_1D` (tutorial)	Planar Comp-B/Al detonation and breakout into air	Runs to completion; air at 24 800 K (no dissociation)	Pass
2	`shock_dissociating_air`	Mach 14.5 shock ($T_2 \approx 10\,000$ K): exact jump (i) for the solver's air thermodynamics, (ii) for air in equilibrium	(i) within 1.2%; (ii) T_2 29% high, ρ_2 13% low (no dissociation)	Fail[c]
2	`multiphase_advection`	Contact advection, four flux schemes	Position < 1 cell; $\Delta p/p < 0.8\%$ (target 10^{-6})	Pass
2	`gunib1d_houim1-3`	Granular shock problems against `gunIB1D`	Within 1.2% (shock speed), 0.6% (peak pressure)	Pass
2	`planar_znd`	Planar Comp-B detonation: front position, CJ state, Taylor wave	Front 0.08% (imposed); front pressure spike grows to 135 GPa (artefact, not checked)	Pass
2	`planar_znd_phaseTransfer`	Transfer behind a planar detonation	Smooth conversion below 100 bar	Pass
3	`spherical_blast`	1 kg C4 (`blastFoam`) against Kinney–Graham (TNT)	Peak overpressure 10–21% low; impulse 3–32%	Pass[a]
3	`ChargeCompBAl_1D_spherical`	Spherical Comp-B/Al, inert Al	Peak 16.6 GPa, breakout 3.06 GPa	Pass
3	`..._reacting`	As above with gas-phase chemistry	No heat release (no products transfer)	Fail[b]
3	`..._alCombustion`	As above with Al burning	No burning in the products; 4.8×10^{-5} of the Al burnt	Pass
3	`..._interface`	Unreacted charge next to air stays at rest	< 0.001 m/s, mass and energy 1.5×10^{-9}	Pass

[a] The pass criteria are monotonic decay, overpressure within 25% and impulse within 40% per station; these do not meet the 5% target of the plan. [b] Expected until the products → gas transfer is enabled (Section 10). [c] Expected until the gas thermodynamics include dissociation (Section 10, plan step C).

9 Results

9.1 0D: transfer of products to gas

A single closed cell is initialised at the matching state (100 bar, $\rho = 35.234\,\mathrm{kg/m^3}$, 836.10 K) with eJWLC products, which transfer to the multicomponent gas with $\tau = 20\,\mu\mathrm{s}$; the three-phase variant adds inert aluminium (Figure 4). After 99.4% of the products mass has transferred, the total energy is conserved to 4.2×10^{-9} (2.2×10^{-9} with aluminium), the mass to 2.4×10^{-9}, and the net momentum is zero. The gas forms at the products temperature (difference $< 10^{-3}\,\mathrm{K}$) and the pressure stays constant to 3×10^{-7}. This confirms the conservation of the transfer and the datum reconciliation of Section 4.4. With the earlier datum convention ($\int c_v\,\mathrm{d}T$ from 298.15 K) the pressure rose by 0.58%; with the conservative decode not yet in place, the reset of the dilute products removed 1.8% of the energy. The isobaric variant of the test planned in Stage 1 has not been made.




Figure 4: 0D products → gas transfer in `blastEulerFoam` at 100 bar: (a) phase mass fractions; (b) relative total energy error ($\leq 4.2 \times 10^{-9}$); (c) pressure; (d) phase temperatures.

9.2 1D canonical problems

Shock in air. A driver at 1700 bar and 7500 K drives a shock into air at 1 atm and 300 K (400 cells, 1 m, `blastFoam`, HLLC). The shock moves at 5040 m/s (Mach 14.5), measured by a fit of the sub-cell shock position over the last three writes, and the solver gives $p_2 = 259\,\mathrm{bar}$, $T_2 = 9990\,\mathrm{K}$, $\rho_2 = 9.01\,\mathrm{kg/m^3}$ and $u_2 = 4370\,\mathrm{m/s}$ (Figure 5). At the measured shock speed these agree with the exact jump conditions for the solver's own thermodynamics (the case JANAF air, extrapolated with constant c_p above its fit range, no dissociation) to within 1.2%, which verifies the shock capturing. They do not agree with air in chemical equilibrium: the equilibrium jump gives $T_2 = 7730\,\mathrm{K}$ and $\rho_2 = 10.4\,\mathrm{kg/m^3}$ with $Y_\mathrm{O} = 0.14$

and $Y_N = 0.03$ (more than half of the O_2 dissociated), so the solver's temperature is 29% too high and its density 13% too low. The test is designed to fail in this way until dissociation is added to the gas phase (plan step C). The equilibrium reference uses fitted equilibrium constants and NASA-7 polynomials (fitted to 6000 K) without NO or ionisation, so it is itself approximate at these temperatures; a reference based on chemical-equilibrium tables is part of step C.

Contact advection. A density contact (116 / 16 kg/m^3) advected at 500 m/s and 100 bar stays within one cell of its exact position for HLLC, AUSM+, Kurganov and Tadmor (Figure 6). Spurious pressure oscillations at the contact are 4.0–4.4% with the van Leer limiter and below 0.8% with Minmod, which is why Minmod is used; the target of 10^{-6} is not met, as expected of a scheme that is not designed to be pressure-equilibrium-preserving.

Granular shock problems. Three problems of Houim and Oran type (advection of a particle curtain, a shock passing through a particle bed, and compaction of a dense bed) are solved with `blastEulerFoam` and with `gunIB1D` (Figure 7). The curtain advection is identical; for the shock tube the transmitted shock speed differs by 1.20% (489.2 vs 495.1 m/s), the post-shock pressure by 0.42% and the gas velocity by 0.67%; for the compaction problem the peak pressure differs by 0.59%, and the compaction wave speed of `blastEulerFoam` (183.8 m/s) is within 0.8% of the reference value. The compaction result required the frictional stress to act (`alphaDeltaMin` 10^{-6}); with the upstream tutorial value the bed packed to the maximum fraction and the old decode removed 41% of the particle mass.

Planar detonation. A planar Comp-B charge (without aluminium, 1720 kg/m^3) is initiated at a closed end (`blastFoam`, 400 cells, 0.5 mm). Behind the front the solution follows the Taylor expansion to a wall pressure of about 11 GPa (Figure 8). At the front, however, the pressure spike grows as the wave runs: about 55, 95 and 135 GPa at 5, 10 and 15 μs, against $p_{CJ} = 24.8$ GPa and a von Neumann pressure that for Comp-B is expected near 35–40 GPa. This is a numerical artefact of the programmed burn in this `blastFoam` setup and has not been analysed; the test checks only the front position, which the burn imposes. The variant with `pressurePhaseChange` converts the products to gas below 100 bar without disturbing the wave.

9.3 Spherical blast of a C4 charge

A 1 kg spherical C4 charge (JWL, `blastFoam`) is detonated at the centre of a 1D spherical domain of 6 m with 300 cells ($\Delta r = 20$ mm), and the peak overpressure and positive impulse are recorded in every cell with `temporalMax` and `temporalIntegral` (Figure 9). The reference is the Kinney–Graham correlation for TNT [9] (the verification script is named after Kingery–Bulmash [8], but evaluates the Kinney–Graham formulas; the C4 mass is used without TNT equivalence). The peak overpressure is low at all scaled distances: 35.8 vs 40.0 bar at $Z = 0.5$ m/kg$^{1/3}$, 8.5 vs 10.1 bar at $Z = 1$, 1.69 vs 2.08 bar at $Z = 2$ and 0.74 vs 0.82 bar at $Z = 3$ (10–21%). The positive impulse differs by 3.4%, 32%, 29%, 8.5% and 20% at $Z = 0.5$, 1, 1.5, 2 and 3. Since C4 is more energetic than TNT (TNT equivalence about 1.2–1.4), the simulated overpressures would be expected to lie above the TNT curve; the low peaks therefore point to the resolution (20 mm cells smear the shock) and to the JWL parameters of the case. A mesh-convergence study and a TNT or Comp-B case are needed before the 5% target of the plan can be assessed.

9.4 Spherical Comp-B/Al charge

A spherical Comp-B/Al charge of radius 50 mm (0.95 kg) is initiated at its centre in a 1D spherical domain of 0.2 m with 400 cells ($\Delta r = 0.5$ mm) and run to 40 μs with `blastEulerFoam`. Three variants share the thermodynamics: inert aluminium, the same with gas-phase chemistry, and the same with aluminium burning (Figure 10).

- *Detonation.* The front moves at 7163 m/s, as imposed. The peak pressure grows to 16.6 GPa at the charge edge, 82% of p_{CJ}; the CJ spike is not resolved on this mesh, and the effect of resolution has not been quantified.
- *Breakout and air shock.* The pressure drops to 3.06 GPa at the charge/air interface. The air shock is 47 MPa at 80 mm, 35 MPa at 100 mm (arrival 14.1 μs) and 21 MPa at 150 mm. These values changed substantially during the work (e.g. 0.16 GPa at 100 mm before the density floor was removed, 29 MPa before the constant-c_p extrapolation), which shows the sensitivity of the near field to the




Figure 5: Mach 14.5 shock in air: (a) post-shock temperature and (b) density ratio against shock Mach number for an ideal gas, the solver's JANAF air without dissociation, and air in chemical equilibrium (analytic), with the `blastFoam` result; (c) temperature and (d) density at 100 μs, with the equilibrium post-shock values over the shocked layer.




Figure 6: Contact advection at 500 m/s, 100 bar: (a) volume fraction at 0.6 ms for four flux schemes; (b) pressure at the contact with HLLC and the van Leer and Minmod limiters.




Figure 7: Granular shock tube (Houim 2) at 0.184 ms, `blastEulerFoam` against `gunIB1D`: (a) gas pressure; (b) gas and particle velocities.




Figure 8: Planar Comp-B detonation (`blastFoam`): (a) pressure at 5, 10 and 15 μs; (b) velocity and density at 10 μs.




Figure 9: 1 kg C4 spherical blast: (a) peak overpressure against scaled distance; (b) positive impulse, with the Kinney–Graham correlations for TNT; (c) pressure histories at 0.5–2 m.

treatment of trace phases and high-temperature air. The shocked air reaches 14 400 K, too hot without dissociation.

- *Aluminium.* Drag accelerates the aluminium to 1890–2300 m/s where $\alpha_{\mathrm{Al}} > 10^{-3}$ (the higher value in the inert case, which applies drag also to the dilute edge of the cloud). The particles are heated to at most 578 K by 40 μs, far below ignition. With the burn rate limited to gas-phase oxidiser, there is no burning inside the products (diameter change $\leq 0.0023\%$); in 1D the particle cloud stays inside the products except at its dilute edge, and 4.8×10^{-5} of the aluminium mass burns in 40 μs.
- *Chemistry.* Since the products are not transferred to the gas, the gas contains only air; the reacting variant releases no heat, and in the aluminium variant the only heat release is from Al vapour with O_2 (up to 2.2 kW/m^3).
- *Interface.* A separate case with an unreacted charge next to air stays at rest: velocities below 10^{-3} m/s at 5 μs and below 1.4 mm/s for 40 μs, pressure at 1.013 bar, mass and energy conserved to 1.5×10^{-9}. Before the trace-phase changes of Section 7.2 this case became unstable within microseconds.

These cases show that the detonation, breakout and early air shock of a three-phase charge run stably and conservatively. They do not yet test the afterburning, which needs the products transfer, the aluminium ignition and combustion models, a domain of metres and run times of milliseconds.




Figure 10: Spherical Comp-B/Al charge in `blastEulerFoam` (inert, reacting and Al-combustion variants): (a) peak pressure against radius (`temporalMax`); (b) pressure histories at 20, 40, 50 and 80 mm; (c) pressure profiles at 5, 10, 20 and 40 μs; (d) particle diameter and volume fractions.

9.5 Reference models for aluminium particles

The standalone particle model (`tests/0D/verify_al_particle_kinetics.py`) integrates the heating of a single particle with an internal temperature profile (Goodman heat-balance integral, parabolic profile), melting, ignition at 2050 K, Beckstead burning and oxide condensation (Figure 11). For a 20 μm particle

at $h = 3 \times 10^5\,\mathrm{W/(m^2K)}$ in gas at 2800 K the surface reaches the ignition temperature at 32.9 μs, 15.5% earlier than with a uniform particle temperature (38.9 μs), and the Beckstead correlation gives a burn time of 1.6 ms in air. (Until 2026-10-14 the burn-time function of this model used a dimensionally inconsistent rate constant that gave burn times of seconds; it now evaluates the published correlation.) The model has not been compared with experimental ignition delays or burn times; it serves as the reference for the solver implementation.




Figure 11: Reference particle model (not in the solver): (a) surface, mean, centre and uniform (lumped) temperatures of a 20 μm particle in gas at 2800 K; (b) internal temperature profiles; (c) diameter and heat release after ignition, with the Beckstead burn time in air.

10 Status and Plan

10.1 Status against the aims

Table 4 summarises the status for the four parts of the problem.

Table 4: Status against the aims (October 2026).

Part	In place and verified	Missing
Detonation and early expansion	Products-only eJWLC fit; programmed burn; three-phase spherical charge, conservative and stable through breakout; stable charge/air interface	Resolution of the CJ state; dissociation in shocked air; mesh convergence
Products/air mixing and chemistry	Products → gas transfer (0D, planar); multicomponent reacting gas phase	Transfer enabled in the Comp-B/Al cases; products afterburning; domains of metres and run times of milliseconds
Al heating, ignition, combustion	Granular Al phase with drag and heat transfer; empirical burn rate limited to gas-phase oxidiser	Mach-dependent drag, melting, ignition, Beckstead rate and oxide condensation in the solver; experimental comparison
Afterburning in air	Gas-phase Al and CO/H_2 reactions in the cases	Multi-dimensional mixing; turbulence and turbulence–chemistry closures; radiation; validation

10.2 Open issues

- The products → gas transfer is not enabled in the Comp-B/Al cases.
- The aluminium models beyond the empirical burn rate are not in the solver.
- Strongly shocked air is too hot without dissociation.
- The only blast comparison is for C4 against the Kinney–Graham TNT correlations, on a coarse mesh; peak overpressure is 10–21% low.
- The 2D axisymmetric Comp-B/Al tutorial has reached 200 μs only from a restart (after the residual-stabilisation fix); a complete run from the start remains to be made. A few steps of trace gas reach the temperature cap.

- In the planar programmed-burn detonation (`blastFoam`) the pressure spike at the front grows to several times p_{CJ} as the wave runs; not analysed.
- No mesh-convergence studies; no experimental data for an aluminised charge identified.

10.3 Plan

The plan (details in `report/status_review_2026-10-14.md`) is ordered by the path to the final validation:

A. *Consolidate*: documentation consistent with the code, verification scripts that fail on incomplete or non-reacting runs, one complete regression run, the 2D crash and the remaining trace-phase defects.

B. *Products afterburning*: enable the transfer in the spherical cases, extend them to 2 m and 2 ms, study the sensitivity to the transfer pressure and time (target: gauge pressures varying by less than 1.5% for 100–200 bar), and add a reduced $CO/H_2/O_2$ mechanism.

C. *High-temperature air*: NASA-9 thermodynamics with three temperature ranges to 20 000 K and $O_2/N_2/NO$ dissociation, verified against chemical-equilibrium data, after which the Mach 14.5 shock test (Section 9.2) must match the equilibrium jump.

D. *Aluminium in the solver*: melting, Mach-dependent drag, an ignition criterion with the Beckstead rate, and oxide condensation, each with a 0D solver test, and comparison with experimental ignition delays and burn times.

E. *1D validation*: an aluminium-free Comp-B baseline against the Kingery–Bulmash data (with TNT equivalence) and a mesh-convergence study, then the inert and reacting Comp-B/Al charge to quantify the impulse gain from afterburning.

F. *Particle method*: compare the existing Eulerian and Lagrangian solvers on the same cloud problem; develop population-balance or hybrid methods only if this shows a need.

G. *Multi-dimensional*: 2D axisymmetric repeat of the spherical case with AMR, cylindrical charges, instability-driven mixing with LES and a turbulence–chemistry closure, and radiation where significant.

H. *Validation*: identify an experimental Comp-B/Al dataset now, then simulate the trial geometry (targets: arrival time within 3%, peak overpressure within 7%, positive impulse within 8%).

B, C and D are independent and can proceed in parallel after A; E needs B–D, and the multi-dimensional work needs E.

A Upstream Demonstration Cases

The following `blastFoam` tutorials [UPSTREAM] cover phenomena relevant to the problem but have not been assessed in this work: `shock_Air_Al_Air` (shock through a particle curtain), `reactingParticles` (`blastEulerFoam` shock tube with reacting particles; its time step collapses at 0.27 ms, not analysed), `multicomponent_shock_bubble` (Richtmyer–Meshkov instability), `twoChargeDetonation` (blast wave interaction and Mach reflection), `axisymmetricChargeMod` and `axisymmetricChargeReacting` (2D axisymmetric charge with AMR), and `multiphase_reacting_bubble` (detonation, transfer and afterburning in `blastFoam`). The `blastEulerFoam` tutorials `ChargeCompBAl`, `ChargeCompBAl_1D` and `StationaryCharge_1D` [THIS WORK] use the settings of the spherical test cases.

References

[1] Synthetik Applied Technologies, *blastFoam User Guide and Technical Reference*, 2024.

[2] OpenFOAM Foundation, *OpenFOAM: The Open Source CFD Toolbox*, Version 12, 2024.

[3] M. R. Baer and J. W. Nunziato, A two-phase mixture theory for the deflagration-to-detonation transition (DDT) in reactive granular materials, *Int. J. Multiphase Flow* 12 (1986) 861–889.

[4] R. Saurel and R. Abgrall, A multiphase Godunov method for compressible multifluid and multiphase flows, *J. Comput. Phys.* 150 (1999) 425–467.

[5] E. F. Toro, *Riemann Solvers and Numerical Methods for Fluid Dynamics*, 3rd ed., Springer, 2009.

[6] E. L. Lee, H. C. Hornig and J. W. Kury, *Adiabatic Expansion of High Explosive Detonation Products*, LLNL Report UCRL-50422, 1968.

[7] L. E. Fried, W. M. Howard and P. C. Souers, *CHEETAH 2.0 User's Manual*, LLNL, 1998.

[8] C. N. Kingery and G. Bulmash, *Airblast Parameters from TNT Spherical Air Burst and Hemispherical Surface Burst*, US Army ARBRL-TR-02555, 1984.

[9] G. F. Kinney and K. J. Graham, *Explosive Shocks in Air*, 2nd ed., Springer, 1985.

[10] D. Gidaspow, *Multiphase Flow and Fluidization: Continuum and Kinetic Theory Descriptions*, Academic Press, 1994.

[11] D. L. Marchisio and R. O. Fox, *Computational Models for Polydisperse Particulate and Multiphase Systems*, Cambridge University Press, 2013.

[12] M. W. Beckstead, *A Summary of Aluminum Combustion*, RTO-EN-023, 2004.