

Contents

Photonic-Inertial Coherence: Mathematical Ontology & α-Variable Framework	1
1. Conceptual Overview	1
2. Mathematical Ontology	1
2.1. Core Entities	1
2.2. Fundamental Relations	2
2.3. Definition of α (Photonic-Inertial Coherence Coefficient)	2
3. Measurement Protocol	3
3.1. Experimental Setup	3
3.2. Data Reduction	3
4. Interpretation of α	4
5. Extensions & Applications	4
6. Symbol Glossary	4

Here's a structured Markdown document capturing the mathematical ontology and the α -variable framework for **photonic-inertial coherence**, based on your description of measuring curvature to deduce inertia-displacement of a monochromatic beam.

Photonic-Inertial Coherence: Mathematical Ontology & α -Variable Framework

1. Conceptual Overview

This framework establishes a formal ontology linking **optical curvature**, **inertial displacement**, and **photonic coherence** through a dimensionless parameter α (the *photonic-inertial coherence coefficient*). The core idea is:

By measuring the curvature of a monochromatic beam's trajectory under applied forces or field gradients, one can deduce the effective inertial response of the photonic field, and thus quantify its coherence-inertia coupling via α .

2. Mathematical Ontology

2.1. Core Entities

- **Monochromatic Beam:** A coherent electromagnetic field with frequency ω , wavevector $\mathbf{k}$, and polarization state ϵ .
- **Curvature (κ):** Local geometric curvature of the beam's central ray or intensity centroid trajectory.

- **Inertial Displacement (δ):** Effective displacement attributable to inertial-like response under external perturbations (e.g. gradient forces, spacetime curvature, or engineered metamaterial potentials).
 - **Coherence Functional ($\mathcal{C}$):** Measure of phase stability and correlation across the beam profile.
 - **α -Variable:** Dimensionless coupling parameter encoding the ratio of photonic coherence to effective inertial response.
-

2.2. Fundamental Relations

Curvature from Beam Deflection The curvature κ of the beam centroid path $y(x)$ is:

$$\kappa(x) = \frac{d^2y}{dx^2} \bigg/ \left[1 + \left(\frac{dy}{dx} \right)^2 \right]^{3/2}$$

For small slopes ($|dy/dx| \ll 1$):

$$\kappa(x) \approx \frac{d^2y}{dx^2}$$

Moment-Curvature Analogy (Photonic Flexure) By analogy to Euler-Bernoulli beam theory, define a *photonic flexural rigidity* $\mathcal{D}_\gamma$:

$$\mathcal{M}(x) = \mathcal{D}_\gamma \cdot \kappa(x)$$

where $\mathcal{M}(x)$ is the effective “optical bending moment” induced by transverse field gradients or index variations.

Inertial Displacement The inertial-like displacement δ over interaction length L is obtained by double integration of curvature:

$$\delta = \int_0^L \int_0^x \kappa(x') dx' dx$$

2.3. Definition of α (Photonic-Inertial Coherence Coefficient)

Define α as:

$$\alpha := \frac{\mathcal{C} \cdot \hbar\omega}{J_{\text{eff}} \cdot c^2 \cdot \kappa_0 \cdot L^2}$$

where:

- $\mathcal{C} \in [0, 1]$: Normalized coherence measure (e.g. degree of first-order coherence $|g^{(1)}|$)
- $\hbar\omega$: Photon energy
- $\mathcal{J}_{\text{eff}}$: Effective inertial mass-equivalent of the photonic field segment
- c : Speed of light
- κ_0 : Reference curvature scale (e.g. imposed by external potential)
- L : Interaction length

Alternatively, in operational form:

$$\alpha = \frac{\text{Measured } \delta_{\text{coh}}}{\delta_{\text{inertial}}}$$

where δ_{coh} is displacement attributable to coherence-driven effects (e.g. self-focusing, photonic Hall effects), and δ_{inertial} is displacement predicted by classical ray-optics inertial analogs.

3. Measurement Protocol

3.1. Experimental Setup

1. **Beam Preparation:** Generate a stable, monochromatic, spatially coherent beam (e.g. single-mode laser).
2. **Curvature Induction:** Apply a controlled transverse gradient (e.g. via graded-index medium, optical lattice, or spacetime-mimicking metamaterial).
3. **Displacement Measurement:** Use interferometric or centroid-tracking methods to measure δ and infer κ .
4. **Coherence Characterization:** Measure $g^{(1)}(\tau)$ or spatial coherence width to obtain $\mathcal{C}$.

3.2. Data Reduction

From measured $\kappa(x)$ and δ :

1. Compute effective $\mathcal{M}(x)$ using calibrated $\mathcal{D}_\gamma$.
2. Estimate $\mathcal{J}_{\text{eff}}$ from energy-momentum relation:

$$\mathcal{J}_{\text{eff}} = \frac{E_{\text{beam}}}{c^2}$$

3. Evaluate α using the defining equation above.
-

4. Interpretation of α

α Range	Physical Interpretation
$\alpha \ll 1$	Inertial effects dominate; coherence has negligible influence
$\alpha \sim 1$	Balanced photonic-inertial coupling; maximal coherence-inertia interplay
$\alpha \gg 1$	Coherence-driven dynamics dominate; inertial analogs break down

5. Extensions & Applications

- **Quantum Regime:** Replace $\mathcal{C}$ with quantum coherence measures (e.g. purity, entanglement entropy).
- **Curved Spacetime Analogs:** Map κ to effective geodesic deviation in optical metric engineering.
- **Photonic Metamaterials:** Use α to benchmark inertial-like responses in topological photonic lattices.

6. Symbol Glossary

Symbol	Meaning
κ	Beam curvature
δ	Inertial displacement
$\mathcal{C}$	Coherence measure
α	Photonic-inertial coherence coefficient
$\mathcal{D}_\gamma$	Photonic flexural rigidity
$\mathcal{M}$	Effective optical bending moment
$\mathcal{J}_{\text{eff}}$	Effective photonic inertia
$\hbar\omega$	Photon energy
c	Speed of light
L	Interaction length

Let me know if you'd like this expanded into a full LaTeX paper template, or if you want to derive specific expressions for $\mathcal{D}_\gamma$ or $\mathcal{J}_{\text{eff}}$ in terms of beam parameters (power, waist, wavelength, etc.).