

SOFTWARE REQUIREMENTS SPECIFICATION

for

GET
2d Game Engine Toolbox

Version 1.0 approved

Prepared by Kier Lindsay and Léo Abiguime

CMPT-376W

April 9, 2020

Contents

1	Introduction	6
1.1	Purpose	6
1.2	Document Conventions	6
1.3	Intended Audience and Reading Suggestions	6
1.4	Project Scope	6
1.5	References	7
2	Overall Description	8
2.1	Product Perspective	8
2.2	Product Functions	8
2.3	User Classes and Characteristics	9
2.4	Operating Environment	9
2.5	Design and Implementation Constraints	10
2.6	User Documentation	10
2.7	Assumptions and Dependencies	10
3	External Interface Requirements	11
3.1	User Interfaces	11
3.2	Software Interfaces	11
4	System Features	12
4.1	Engine Module	12
4.1.1	Description and Priority	12
4.1.2	Stimulus/Response Sequences	12
4.1.3	Functional Requirements	12
4.2	Physics Module	13
4.2.1	Description and Priority	13
4.2.2	Stimulus/Response Sequences	13
4.2.3	Functional Requirements	14
4.3	User Interface Module	15
4.3.1	Description and Priority	15
4.3.2	Stimulus/Response Sequences	15
4.3.3	Functional Requirements	16
5	Other Nonfunctional Requirements	17
5.1	Performance Requirements	17
5.2	Safety Requirements	17
5.3	Security Requirements	18

5.4	Software Quality Attributes	18
5.5	Business Rules	18
6	Other Requirements	19
6.1	Appendix A: Glossary	19
6.2	Appendix B: Analysis Model	19

Revision History

Name	Date	Reason For Changes	Version
Kier Lindsay	April 9, 2020	Initial Copy	1

1 Introduction

1.1 Purpose

This document refers to the GET software, version 1.0. GET stands for Game Engine Toolbox and it is a two-dimensional (2D) game engine designed to bridge a gap between existing graphics library and large complete three-dimensional (3D) game engines. It will extend the capabilities of graphics Library and provide common systems and feature needed to develop a game without forcing the user into a large complex engine. In its first iteration (version 1.0), GET is based on the C++ Simple and Fast Multimedia Library (SFML) engine. This SRS will cover the entirety of GET

1.2 Document Conventions

This document follows the IEEE SRS template. It also makes use of the KISS mentality in order to make things easy to parse.

1.3 Intended Audience and Reading Suggestions

This document is intended for the developers who will be implementing the game engine. We would also like to consider users of the engine as this document may offer a high level overview of what the product offers and its design philosophy. We recommend that developers start by reading chapter 2 (Overall Description), especially section 2.2 (Product Functions) as they will be in charge of implementing the components mentioned there. Then, they can move on to chapter 4 which elaborates the system features of each module of the software.

1.4 Project Scope

This project is meant to complement an existing graphics library providing the core functionalities all games require and tools for developers to use. It is meant to provide a more advanced and highly customization starting point for game developers who want to have full control over their game. It is also meant to be modular so that developers are not forced into using our designs and have the freedom to incorporate as many or as few of the features we provide. The current iteration of GET focuses on SFML which is a C++ multimedia library. It is used as the backbone of the software and the aim is to cover more libraries in the next versions.

1.5 References

SFML ImGui SDL2 RayLib

Minimal programming guides.

others as we write them or references to documentation for implementation

<List any other documents or Web addresses to which this SRS refers. These may include user interface style guides, contracts, standards, system requirements specifications, use case documents, or a vision and scope document. Provide enough information so that the reader could access a copy of each reference, including title, author, version number, date, and source or location.>

2 Overall Description

2.1 Product Perspective

The product being specified in this SRS is completely new. It advertises itself as a game engine that comes handy when using the SFML library for the reason that it augments the functionalities of that library. It originates from the need to develop games faster without compromising on stability and security. It is self-contained in the sense that it does not have any dependencies that require additional steps to be taken by its user, even though it relies on the SFML library. However, since it comes as an addon to the aforementioned library, GET can only run on an SFML dependent application.

2.2 Product Functions

GET is organized into three modules. Each module provides a set of functions that are enumerated below:

1. Engine Module
 - Timing - Setups at maintain a core game loop
 - Allows users to choose between using real deltaTime or a fixed tick time so that each tick is a consistent time
 - Allows users to set tickrate and framerate independently
 - Allows users to hook into update and render calls
 - States - Manages switching between game states
 - Allows users to bind a number of game states to an engine, each with its own update and render functions
 - Allows users to toggle states
 - Assets - Manages the loading and management of game assets such as fonts and textures.
 - Supports Fonts
 - Supports Sprites
 - Supports Textures
 - Supports Animations
 - Supports Sound files

2. Physics Module

- Body - Links the physics module to a shape in order to apply constraints to it through the manager or functions
- Manager - Used to hold bodies and can be linked to a background of the UI module
- Functions - A set of functions that can be applied onto bodies or the managers

3. User Interface

- Shapes - Create complex shapes
 - Allows users to generate a shape using a sprite file loaded as an asset
 - Allows users to generate humanoid shape based on a set of parameters
 - Allows users to link shapes to a body
- Background - Link a set of shapes together to form an object on top of which complex shapes can be displayed
 - Offers a set of parameters to initialize a background
 - Allows users to initialize the background object with non-complex shapes as a parameter
 - Allows users to link the background to an instance of Manager class from the physics module
 - Allows users to add music to the background

2.3 User Classes and Characteristics

We can distinguish between two categories of users: full users and partial users.

Full users will use this engine as their starting point and build their game around our components and tools. That means that they do not use GET to augment the functionalities provided by SFML but rather as a full fledged game engine.

Then, we have **partial users** who will use SFML as their starting point and may incorporate some components of our software into their project.

2.4 Operating Environment

Since our software is dependent on SFML, we should expect a similar operating environment. As such, we have the following:

- Operating System: Windows(10, 8, 7, Vista, XP), Linux, macOS. x64 and x86 systems are both supported.

- Dependencies: SFML, OpenGL, ImGui
- Language Target: C++

2.5 Design and Implementation Constraints

This software is not intended to be used to develop 3D projects because SFML does not inherently support 3D. Therefore the software architecture should be designed in a way that makes it hard for users to develop 3D applications. Moreover, GET is not meant to be supported in any programming language other than C++ since partial users, as defined in the user classes, might use SFML as the backbone of their application and SFML is only supported in C++.

2.6 User Documentation

The following user documentation components will be delivered along with the software:

- README file: will be included in the repository from which GET will be downloaded. It will serve as a setup guide.
- Tutorials: will be available on the official website to get the user started with the product.
- API Reference: will elaborate on each module to provide users with the expected behaviour and the intended use of each component.

2.7 Assumptions and Dependencies

It is assumed that the user's system is running of SFML version 2.2 or above. Any version below that is seriously outdated and might lead to unexpected behaviors.

3 External Interface Requirements

3.1 User Interfaces

The user interface will be the user's terminal. GET will interact with the user interface through log messages. We can distinguish between the following types:

- Information: Used to display basic events. Ex: user running the software.
- Status: Used to display 'significant' events that require a status code.
- Warning: User or system errors that do not cause failure of a component.
- Error: User or system errors that cause failure of a component.

The following requirements must be respected when dealing with user interface's log message.

REQ-UI1: On successfully running GET, a log message that includes the name and the version of the software must be printed out.

REQ-UI2: A log message must be printed out everytime an event occurs.

REQ-UI3: Each log out message must indicate its category.

REQ-UI4: All logs must be saved inside a log.txt file under the main folder.

3.2 Software Interfaces

As stated numerous times, this game engine is based on SFML. Therefore, the data must be stored in a way such that it can interact with SFML in the case were the users are only partial users.

REQ-SI1: Every class must implement an SFML class as a superclass.

REQ-SI2: Every SFML function must behave as intended on custom objects defined by our software.

REQ-SI3: Users are able to use SFML objects and GET objects interchangeably.

4 System Features

4.1 Engine Module

4.1.1 Description and Priority

This feature provides the core game loop and state functionality it is an essential feature and is high priority. The timing component we allow users to manage the main loop speed, and when it calls the current states update and render functions. These can be different so games can run at a constant physics rate and scale that as necessary but only render when needed or at a fixed frame rate. It will have game states that can be switched between from events within the update function. This is meant to be extended by the users game and the update and render functions overridden with games specific code.

4.1.2 Stimulus/Response Sequences

- Stimulus: Time adjusted
Response: Internal time variables set so the new timing take effect the next tick
- Stimulus: State changed
Response: the corresponding states update and draw function will be used on the next tick.
- Stimulus: New Tick
Response: Current states update function is called and if it is time to draw a frame the render function is also called
- Stimulus: Camera Set
Response: Current states Camera is set and the cameras transformation from world coordinates to Camera coordinates is applied while rendering

4.1.3 Functional Requirements

REQ-ET1: Tick rate and Frame rate must be controlled independently

REQ-ET2: When calling Update in a tick the Tick time must be sent as a parameter

- REQ-ET3:** If ticks cannot be computed in time render frames may be dropped.
- REQ-ES1:** The update and render function should be called for all active states.
- REQ-ES2:** States should be able toggle states from within the update function.
- REQ-ES3:** States Should have an Identifier, Update function, and Draw function
- REQ-ES4:** States should accept a camera transformation which applies to the render function.
- REQ-ES5:** States should be able to be given indexes for rendering order. This should default to the order they were added

4.2 Physics Module

4.2.1 Description and Priority

The Physics Module will be a high priority. This will have three components the *Physics Manager* which can be used to hold *Physics Bodies* and manage the relationships between them as well as the *Physics Functions* which will provided many useful physics calculations and can be used on bodies independently or be used by the physics manager to update the bodies it manages..

4.2.2 Stimulus/Response Sequences

- Stimulus: New Body Created
Response: Body Initialized with provided parameters and is returned to user for use
- Stimulus: New Manager Created
Response: Physics Manager Initialized with universal constants provided and environment for bodies is setup
- Stimulus: Body Added to manager
Response: Body is added to the manager and will be updated and rendered all world relationships will be applied to it
- Stimulus: Relationship Added to manager
Response: Bodies referenced by the relationship will have it applied to them
- Stimulus: Collision Detected between Bodies
Response: Bodies are separated and appropriate forces are applied.

- Stimulus: Body Updated delta time
Response: All applied relationships are computed and bodies parameters are updated
- Stimulus: Body Rendered
Response: Body is drawn to screen at corresponding position
- Stimulus: Body Deleted
Response: All relationships are removed and corresponding managers and bodies are notified then body is deleted.

4.2.3 Functional Requirements

- REQ-PB1:** The Physics Body class should store all physical properties required by the Functions this includes: Shape, Position, Velocity, Acceleration, Rotation, Rotational Velocity, Friction, Elasticity, Shape
- REQ-PB2:** The Physics Body class should have an *Update* function which updates the bodies property according to classical mechanics when called, this function will take in a delta time parameter
- REQ-PB3:** The Physics Body class should have an *Render* function which Draws the bodies shape. This should be designed to be overridden by users.
- REQ-PB4:** The Physics Body class should keep an list of relationships it is a part of so that is can apply them all when updated.
- REQ-PF1:** The Physics Function should accept universals constants as parameters or allow global defaults be set.
- REQ-PF2:** The Physics Function should include *Collision detection* between two bodies with *Minimum Translation Vectors* (MTV). It should include fast approximate bounding box collision detection as well.
- REQ-PF3:** The Physics Function should include *collision solving* functions which will apply the necessary forces to handle a collision between two bodies.
- REQ-PF4:** The Physics Function should include *gravity* functions to apply gravity between two bodies.
- REQ-PF5:** The Physics Function should include *constant force* functions to apply constant forces to a body these could be used to create world gravity or wind forces.
- REQ-PM1:** The Physics Manager should create an environment to hold Body' s as well as set world constants for the bodies it manages.

REQ-PM2: The Physics Manager should allow relationships to be made between bodies which define additional iterations. This includes forces and whether or not bodies should interact with each other.

REQ-PM3: The Physics Manager should have an *Update* function which applies all relations and updates all bodies

REQ-PM4: The Physics Manager should have an *Render* function which renders all bodies. This should allow for bodies to be drawn in a defined order

REQ-PM5: The Physics Manager should allow bodies to be grouped and relations or physics functions can be defined for the whole group or for each pair of bodies in the group.

REQ-PM6: The Physics Manager should allow world Relationships to be set which apply to all bodies. These include global forces and n-body gravity as well as other optional relationships as appropriate.

REQ-PM7: The Physics Manager should allow preform collision detection between select objects this should be efficiently implemented so that full collision detection is only used when necessary not at all times.

4.3 User Interface Module

4.3.1 Description and Priority

The User Interface module provides the developer with functionalities that augment the graphics module of their game engine. It is meant to be built on top of the Physics Module as it is a visual interpretation of the constraints implemented there. Its priority level is low since it is not required for the game to run and its purpose is to enable the players to interact with the game.

4.3.2 Stimulus/Response Sequences

- Stimulus: New Humanoid Shape Created
Response: Humanoid shape is initialized with its parameters and is returned to user for use.
- Stimulus: Humanoid Shape linked to Body
Response: Humanoid shape is added to an already instantiated body from the Physics Module. Its behavior handling is passed to the Body's manager.
- Stimulus: New Miscellaneous Shape Created
Response: Miscellaneous shape is created using the provided image files and is

returned to user for use.

- Stimulus: Miscellaneous Shape linked to Body
Response: Miscellaneous shape is added to an already instantiated body from the Physics Module. Its behavior handling is passed to the Body's manager.
- Stimulus: New Background Created
Response: Background is initialized with its parameters and is returned to user for use.
- Stimulus: Background linked to Physics Manager
Response: Background is link to an instance of Physics Manager and all its property will be valid within the background.

4.3.3 Functional Requirements

REQ-SH1: The Humanoid and Miscellaneous shapes are custom shapes that inherit all the attributes of an SFML shape.

REQ-SH2: The Humanoid shape is a custom class that adds the following attributes on top of the abstract class `sf::Shape`: head size, body size, body weight, height, weight, feet size, body color, hair color, hair type, eyes color, humanoid type.

REQ-SH3: The Miscellaneous shape is a custom class that uses convex shape to draw a loaded sprite that has been passed as a parameter.

REQ-SH4: The custom shapes can be linked to a body object and their behaviour will be controlled by the physics module through method Override.

REQ-BA1: A background is a set of `sf::Shape` that are linked together in a single custom object defined by a class

REQ-BA2: The background class constructor allows the user to pass the following parameters: color, shapes, main shape, physics manager, sound

REQ-BA3: The background class' main shape will be on the first layer and thus be at the bottom of the superposition stack

REQ-BA4: The background class' shapes are superposed in the order that they have been instantiated

REQ-BA5: The background class' variables cannot be altered after having been instantiated. The user must create a new object.

5 Other Nonfunctional Requirements

5.1 Performance Requirements

The size of the library should not exceed that of SFML. This is on the order of 10 MB this limit aim to keep the loading and download times of developers games low. Reasons to exead this may be analized on a case by case basis but if component exceed this limit they should be optional so that developers can exclude them if not needed.

REQ-NFP1: Physics management must fast and able to support thousands of objects. Ideally man collision algorithm will faster then $O(n!)$ This would be the speed of an naive implementation and there should be speedups that we can use to improve upon this. The target performance should be $O(n\log(n))$ as this would allow many more object to exist in the words but this may not be possible.

REQ-NFP2: We hope that the library reaches reasonable time and memory complexity. But in general component should be using the time and space complexities of the latest research on whichever component is being used. This will be found during implementation when the component is being designed.

REQ-NFP3: Should not have any memory leaks or other performance degradation over time.

5.2 Safety Requirements

This library although aimed towards game developers should attempt to be as stable and reliable as possible if it is uses to develop mission critical applications and therefor should meat these requirements

REQ-NFD1: Be well tested for reliability and crash tolerance. This involves maintain reliable operation for extended periods of time without degrading performance. see REC-NFP3

REQ-NFD2: The documentation should include detailed operational parameter ranges. with a guarantee of correctness for operation within them. These allow developers to use this library in mission critical application and easily audit our code for correctness.

5.3 Security Requirements

Although this library does not have networked components game hacking is a large problem these days the problem is very hard to mitigate and ultimately any solution we implement may not make a difference since the software can always be read. These solutions would land on the shoulders of game developers to implement across their entire game. For other corporate applications application we would like consider a few things though.

REQ-NFS1: The library should operate entirely in user space if possible this would prevent it from allowing privilege escalation attack entirely. If not possible more scrutiny should be applied to those components security on a case by case basis.

5.4 Software Quality Attributes

This project should strive to offer great value The aim should be to produce high quality code that performs well and developer love to use. It is the hope that the usefulness and power of this project are high so that it is recognised as a useful tool and can find its place in the large game development ecosystem.

5.5 Business Rules

Honesty is important and this project should both be honest to each other while developing it about what is happening. This will make the development process easier and more fluid. We should also be honest to the users by not making our code or documentation ambiguous. This just makes everything easier for everyone.

6 Other Requirements

6.1 Appendix A: Glossary

- Graphics Library or GL - is a library the provides a window and functions to draw to the window. Examples of graphics libraries are SFML and SDL2
- SFML - Simple fast media layer, this is a graphics library
- Body - Our usage of the term body references physics body's or objects.

6.2 Appendix B: Analysis Model

