

Contents

1	OMNIType Theory	3
1.1	Datatypes	3
1.2	Theorems	3
2	ssm11 Theory	4
2.1	Datatypes	4
2.2	Definitions	4
2.3	Theorems	5
3	ssm Theory	11
3.1	Datatypes	11
3.2	Definitions	12
3.3	Theorems	13
4	satList Theory	21
4.1	Definitions	21
4.2	Theorems	21
5	PBTypeIntegrated Theory	21
5.1	Datatypes	21
5.2	Theorems	22
6	PBIntegratedDef Theory	23
6.1	Definitions	23
6.2	Theorems	24
7	ssmPBIntegrated Theory	28
7.1	Theorems	28
8	ssmConductORP Theory	35
8.1	Theorems	35
9	ConductORPType Theory	44
9.1	Datatypes	44
9.2	Theorems	45
10	ConductORPDef Theory	46
10.1	Definitions	46
10.2	Theorems	47
11	ssmConductPB Theory	51
11.1	Definitions	51
11.2	Theorems	52

12 ConductPBType Theory	57
12.1 Datatypes	57
12.2 Theorems	57
13 ssmMoveToORP Theory	58
13.1 Definitions	58
13.2 Theorems	58
14 MoveToORPType Theory	62
14.1 Datatypes	62
14.2 Theorems	63
15 ssmMoveToPB Theory	63
15.1 Definitions	63
15.2 Theorems	64
16 MoveToPBType Theory	68
16.1 Datatypes	68
16.2 Theorems	68
17 ssmPlanPB Theory	69
17.1 Theorems	69
18 PlanPBType Theory	79
18.1 Datatypes	79
18.2 Theorems	79
19 PlanPBDef Theory	82
19.1 Definitions	82
19.2 Theorems	83

1 OMNITYPE Theory

Built: 10 June 2018

Parent Theories: indexedLists, patternMatches

1.1 Datatypes

```
command = ESCc escCommand | SLc 'slCommand

escCommand = returnToBase | changeMission | resupply
             | reactToContact

escOutput = ReturnToBase | ChangeMission | Resupply
           | ReactToContact

escState = RTB | CM | RESUPPLY | RTC

output = ESCo escOutput | SLo 'slOutput

principal = SR 'stateRole

state = ESCs escState | SLs 'slState
```

1.2 Theorems

[command_distinct_clauses]

$\vdash \forall a' a. \text{ESCc } a \neq \text{SLc } a'$

[command_one_one]

$\vdash (\forall a a'. (\text{ESCc } a = \text{ESCc } a') \iff (a = a')) \wedge$
 $\quad \forall a a'. (\text{SLc } a = \text{SLc } a') \iff (a = a')$

[escCommand_distinct_clauses]

$\vdash \text{returnToBase} \neq \text{changeMission} \wedge \text{returnToBase} \neq \text{resupply} \wedge$
 $\quad \text{returnToBase} \neq \text{reactToContact} \wedge \text{changeMission} \neq \text{resupply} \wedge$
 $\quad \text{changeMission} \neq \text{reactToContact} \wedge \text{resupply} \neq \text{reactToContact}$

[escOutput_distinct_clauses]

$\vdash \text{ReturnToBase} \neq \text{ChangeMission} \wedge \text{ReturnToBase} \neq \text{Resupply} \wedge$
 $\quad \text{ReturnToBase} \neq \text{ReactToContact} \wedge \text{ChangeMission} \neq \text{Resupply} \wedge$
 $\quad \text{ChangeMission} \neq \text{ReactToContact} \wedge \text{Resupply} \neq \text{ReactToContact}$

[escState_distinct_clauses]

$\vdash \text{RTB} \neq \text{CM} \wedge \text{RTB} \neq \text{RESUPPLY} \wedge \text{RTB} \neq \text{RTC} \wedge \text{CM} \neq \text{RESUPPLY} \wedge$
 $\quad \text{CM} \neq \text{RTC} \wedge \text{RESUPPLY} \neq \text{RTC}$

[output_distinct_clauses]

$\vdash \forall a' a. \text{ESCo } a \neq \text{SLo } a'$

[output_one_one]

$\vdash (\forall a a'. (\text{ESCo } a = \text{ESCo } a') \iff (a = a')) \wedge$
 $\quad \forall a a'. (\text{SLo } a = \text{SLo } a') \iff (a = a')$

[principal_one_one]

$\vdash \forall a a'. (\text{SR } a = \text{SR } a') \iff (a = a')$

[state_distinct_clauses]

$\vdash \forall a' a. \text{ESCs } a \neq \text{SLs } a'$

[state_one_one]

$\vdash (\forall a a'. (\text{ESCs } a = \text{ESCs } a') \iff (a = a')) \wedge$
 $\quad \forall a a'. (\text{SLs } a = \text{SLs } a') \iff (a = a')$

2 ssm11 Theory

Built: 10 June 2018

Parent Theories: satList

2.1 Datatypes

```
configuration =
  CFG (('command order, 'principal, 'd, 'e) Form -> bool)
      (('state -> ('command order, 'principal, 'd, 'e) Form)
      (('command order, 'principal, 'd, 'e) Form list)
      (('command order, 'principal, 'd, 'e) Form list) 'state
      ('output list)

order = SOME 'command | NONE

trType = discard 'command | trap 'command | exec 'command
```

2.2 Definitions

[TR_def]

$\vdash \text{TR} =$
 $\quad (\lambda a_0 a_1 a_2 a_3.$
 $\quad \quad \forall TR'.$
 $\quad \quad (\forall a_0 a_1 a_2 a_3.$
 $\quad \quad \quad (\exists \text{authenticationTest } P \text{ NS } M \text{ Oi } Os \text{ Out } s$
 $\quad \quad \quad \quad \text{securityContext stateInterp cmd ins outs.}$
 $\quad \quad \quad \quad (a_0 = (M, Oi, Os)) \wedge (a_1 = \text{exec cmd}) \wedge$
 $\quad \quad \quad \quad (a_2 =$

```

CFG authenticationTest stateInterp
  securityContext (P says prop (SOME cmd)::ins) s
  outs) ∧
(a3 =
  CFG authenticationTest stateInterp
    securityContext ins (NS s (exec cmd))
    (Out s (exec cmd)::outs)) ∧
authenticationTest (P says prop (SOME cmd)) ∧
CFGInterpret (M, Oi, Os)
  (CFG authenticationTest stateInterp
    securityContext (P says prop (SOME cmd)::ins)
    s outs)) ∨
(∃ authenticationTest P NS M Oi Os Out s
  securityContext stateInterp cmd ins outs.
  (a0 = (M, Oi, Os)) ∧ (a1 = trap cmd) ∧
  (a2 =
    CFG authenticationTest stateInterp
      securityContext (P says prop (SOME cmd)::ins) s
      outs) ∧
  (a3 =
    CFG authenticationTest stateInterp
      securityContext ins (NS s (trap cmd))
      (Out s (trap cmd)::outs)) ∧
  authenticationTest (P says prop (SOME cmd)) ∧
  CFGInterpret (M, Oi, Os)
    (CFG authenticationTest stateInterp
      securityContext (P says prop (SOME cmd)::ins)
      s outs)) ∨
(∃ authenticationTest NS M Oi Os Out s securityContext
  stateInterp cmd x ins outs.
  (a0 = (M, Oi, Os)) ∧ (a1 = discard cmd) ∧
  (a2 =
    CFG authenticationTest stateInterp
      securityContext (x::ins) s outs) ∧
  (a3 =
    CFG authenticationTest stateInterp
      securityContext ins (NS s (discard cmd))
      (Out s (discard cmd)::outs)) ∧
  ¬authenticationTest x) ⇒
  TR' a0 a1 a2 a3) ⇒
  TR' a0 a1 a2 a3)

```

2.3 Theorems

[CFGInterpret_def]

```

⊢ CFGInterpret (M, Oi, Os)
  (CFG authenticationTest stateInterp securityContext
    (input::ins) state outputStream) ⇔

```

$$(M, Oi, Os) \text{ satList } securityContext \wedge (M, Oi, Os) \text{ sat } input \wedge \\ (M, Oi, Os) \text{ sat } stateInterp \text{ state}$$

[CFGInterpret_ind]

$$\vdash \forall P. \\ (\forall M \ Oi \ Os \ authenticationTest \ stateInterp \ securityContext \\ input \ ins \ state \ outputStream. \\ P \ (M, Oi, Os) \\ (CFG \ authenticationTest \ stateInterp \ securityContext \\ (input :: ins) \ state \ outputStream)) \wedge \\ (\forall v_{15} \ v_{10} \ v_{11} \ v_{12} \ v_{13} \ v_{14}. \\ P \ v_{15} \ (CFG \ v_{10} \ v_{11} \ v_{12} \ [] \ v_{13} \ v_{14})) \Rightarrow \\ \forall v \ v_1 \ v_2 \ v_3. \ P \ (v, v_1, v_2) \ v_3$$

[configuration_one_one]

$$\vdash \forall a_0 \ a_1 \ a_2 \ a_3 \ a_4 \ a_5 \ a'_0 \ a'_1 \ a'_2 \ a'_3 \ a'_4 \ a'_5. \\ (CFG \ a_0 \ a_1 \ a_2 \ a_3 \ a_4 \ a_5 = CFG \ a'_0 \ a'_1 \ a'_2 \ a'_3 \ a'_4 \ a'_5) \iff \\ (a_0 = a'_0) \wedge (a_1 = a'_1) \wedge (a_2 = a'_2) \wedge (a_3 = a'_3) \wedge \\ (a_4 = a'_4) \wedge (a_5 = a'_5)$$

[order_distinct_clauses]

$$\vdash \forall a. \text{ SOME } a \neq \text{ NONE}$$

[order_one_one]

$$\vdash \forall a \ a'. (\text{SOME } a = \text{SOME } a') \iff (a = a')$$

[TR_cases]

$$\vdash \forall a_0 \ a_1 \ a_2 \ a_3. \\ \text{TR } a_0 \ a_1 \ a_2 \ a_3 \iff \\ (\exists authenticationTest \ P \ NS \ M \ Oi \ Os \ Out \ s \ securityContext \\ stateInterp \ cmd \ ins \ outs. \\ (a_0 = (M, Oi, Os)) \wedge (a_1 = \text{exec } cmd) \wedge \\ (a_2 = \\ CFG \ authenticationTest \ stateInterp \ securityContext \\ (P \text{ says prop } (\text{SOME } cmd) :: ins) \ s \ outs) \wedge \\ (a_3 = \\ CFG \ authenticationTest \ stateInterp \ securityContext \ ins \\ (NS \ s \ (\text{exec } cmd)) \ (Out \ s \ (\text{exec } cmd) :: outs)) \wedge \\ authenticationTest \ (P \text{ says prop } (\text{SOME } cmd)) \wedge \\ CFGInterpret \ (M, Oi, Os) \\ (CFG \ authenticationTest \ stateInterp \ securityContext \\ (P \text{ says prop } (\text{SOME } cmd) :: ins) \ s \ outs)) \vee \\ (\exists authenticationTest \ P \ NS \ M \ Oi \ Os \ Out \ s \ securityContext \\ stateInterp \ cmd \ ins \ outs. \\ (a_0 = (M, Oi, Os)) \wedge (a_1 = \text{trap } cmd) \wedge \\ (a_2 = \\ CFG \ authenticationTest \ stateInterp \ securityContext \\ (P \text{ says prop } (\text{SOME } cmd) :: ins) \ s \ outs) \wedge$$

$(a_3 =$
 $\text{CFG authenticationTest stateInterp securityContext ins}$
 $(\text{NS } s (\text{trap cmd})) (\text{Out } s (\text{trap cmd})::\text{outs})) \wedge$
 $\text{authenticationTest } (P \text{ says prop } (\text{SOME cmd})) \wedge$
 $\text{CFGInterpret } (M, Oi, Os)$
 $(\text{CFG authenticationTest stateInterp securityContext}$
 $(P \text{ says prop } (\text{SOME cmd})::\text{ins}) s \text{ outs})) \vee$
 $\exists \text{ authenticationTest NS } M \text{ Oi } Os \text{ Out } s \text{ securityContext}$
 $\text{stateInterp cmd } x \text{ ins outs.}$
 $(a_0 = (M, Oi, Os)) \wedge (a_1 = \text{discard cmd}) \wedge$
 $(a_2 =$
 $\text{CFG authenticationTest stateInterp securityContext}$
 $(x::\text{ins}) s \text{ outs}) \wedge$
 $(a_3 =$
 $\text{CFG authenticationTest stateInterp securityContext ins}$
 $(\text{NS } s (\text{discard cmd})) (\text{Out } s (\text{discard cmd})::\text{outs})) \wedge$
 $\neg \text{authenticationTest } x$

[TR_discard_cmd_rule]

$\vdash \text{TR } (M, Oi, Os) (\text{discard cmd})$
 $(\text{CFG authenticationTest stateInterp securityContext}$
 $(x::\text{ins}) s \text{ outs})$
 $(\text{CFG authenticationTest stateInterp securityContext ins}$
 $(\text{NS } s (\text{discard cmd})) (\text{Out } s (\text{discard cmd})::\text{outs})) \iff$
 $\neg \text{authenticationTest } x$

[TR_EQ_rules_thm]

$\vdash (\text{TR } (M, Oi, Os) (\text{exec cmd})$
 $(\text{CFG authenticationTest stateInterp securityContext}$
 $(P \text{ says prop } (\text{SOME cmd})::\text{ins}) s \text{ outs})$
 $(\text{CFG authenticationTest stateInterp securityContext ins}$
 $(\text{NS } s (\text{exec cmd})) (\text{Out } s (\text{exec cmd})::\text{outs})) \iff$
 $\text{authenticationTest } (P \text{ says prop } (\text{SOME cmd})) \wedge$
 $\text{CFGInterpret } (M, Oi, Os)$
 $(\text{CFG authenticationTest stateInterp securityContext}$
 $(P \text{ says prop } (\text{SOME cmd})::\text{ins}) s \text{ outs})) \wedge$
 $(\text{TR } (M, Oi, Os) (\text{trap cmd})$
 $(\text{CFG authenticationTest stateInterp securityContext}$
 $(P \text{ says prop } (\text{SOME cmd})::\text{ins}) s \text{ outs})$
 $(\text{CFG authenticationTest stateInterp securityContext ins}$
 $(\text{NS } s (\text{trap cmd})) (\text{Out } s (\text{trap cmd})::\text{outs})) \iff$
 $\text{authenticationTest } (P \text{ says prop } (\text{SOME cmd})) \wedge$
 $\text{CFGInterpret } (M, Oi, Os)$
 $(\text{CFG authenticationTest stateInterp securityContext}$
 $(P \text{ says prop } (\text{SOME cmd})::\text{ins}) s \text{ outs})) \wedge$
 $(\text{TR } (M, Oi, Os) (\text{discard cmd})$
 $(\text{CFG authenticationTest stateInterp securityContext}$
 $(x::\text{ins}) s \text{ outs})$
 $(\text{CFG authenticationTest stateInterp securityContext ins}$

$$(NS\ s\ (\text{discard}\ cmd))\ (Out\ s\ (\text{discard}\ cmd)::outs)) \iff \neg authenticationTest\ x)$$

[TR_exec_cmd_rule]

$$\begin{aligned} &\vdash \forall authenticationTest\ securityContext\ stateInterp\ P\ cmd\ ins\ s\ outs. \\ &\quad (\forall M\ Oi\ Os. \\ &\quad \quad CFGInterpret\ (M, Oi, Os) \\ &\quad \quad \quad (CFG\ authenticationTest\ stateInterp\ securityContext \\ &\quad \quad \quad \quad (P\ \text{says}\ \text{prop}\ (SOME\ cmd)::ins)\ s\ outs) \Rightarrow \\ &\quad \quad \quad (M, Oi, Os)\ \text{sat}\ \text{prop}\ (SOME\ cmd)) \Rightarrow \\ &\quad \forall NS\ Out\ M\ Oi\ Os. \\ &\quad TR\ (M, Oi, Os)\ (\text{exec}\ cmd) \\ &\quad \quad (CFG\ authenticationTest\ stateInterp\ securityContext \\ &\quad \quad \quad (P\ \text{says}\ \text{prop}\ (SOME\ cmd)::ins)\ s\ outs) \\ &\quad \quad (CFG\ authenticationTest\ stateInterp\ securityContext\ ins \\ &\quad \quad \quad (NS\ s\ (\text{exec}\ cmd))\ (Out\ s\ (\text{exec}\ cmd)::outs)) \iff \\ &\quad authenticationTest\ (P\ \text{says}\ \text{prop}\ (SOME\ cmd)) \wedge \\ &\quad CFGInterpret\ (M, Oi, Os) \\ &\quad \quad (CFG\ authenticationTest\ stateInterp\ securityContext \\ &\quad \quad \quad (P\ \text{says}\ \text{prop}\ (SOME\ cmd)::ins)\ s\ outs) \wedge \\ &\quad (M, Oi, Os)\ \text{sat}\ \text{prop}\ (SOME\ cmd)) \end{aligned}$$

[TR_ind]

$$\begin{aligned} &\vdash \forall TR'. \\ &\quad (\forall authenticationTest\ P\ NS\ M\ Oi\ Os\ Out\ s\ securityContext \\ &\quad \quad stateInterp\ cmd\ ins\ outs. \\ &\quad \quad authenticationTest\ (P\ \text{says}\ \text{prop}\ (SOME\ cmd)) \wedge \\ &\quad \quad CFGInterpret\ (M, Oi, Os) \\ &\quad \quad \quad (CFG\ authenticationTest\ stateInterp\ securityContext \\ &\quad \quad \quad \quad (P\ \text{says}\ \text{prop}\ (SOME\ cmd)::ins)\ s\ outs) \Rightarrow \\ &\quad \quad TR'\ (M, Oi, Os)\ (\text{exec}\ cmd) \\ &\quad \quad \quad (CFG\ authenticationTest\ stateInterp\ securityContext \\ &\quad \quad \quad \quad (P\ \text{says}\ \text{prop}\ (SOME\ cmd)::ins)\ s\ outs) \\ &\quad \quad \quad (CFG\ authenticationTest\ stateInterp\ securityContext\ ins \\ &\quad \quad \quad \quad (NS\ s\ (\text{exec}\ cmd))\ (Out\ s\ (\text{exec}\ cmd)::outs))) \wedge \\ &\quad (\forall authenticationTest\ P\ NS\ M\ Oi\ Os\ Out\ s\ securityContext \\ &\quad \quad stateInterp\ cmd\ ins\ outs. \\ &\quad \quad authenticationTest\ (P\ \text{says}\ \text{prop}\ (SOME\ cmd)) \wedge \\ &\quad \quad CFGInterpret\ (M, Oi, Os) \\ &\quad \quad \quad (CFG\ authenticationTest\ stateInterp\ securityContext \\ &\quad \quad \quad \quad (P\ \text{says}\ \text{prop}\ (SOME\ cmd)::ins)\ s\ outs) \Rightarrow \\ &\quad \quad TR'\ (M, Oi, Os)\ (\text{trap}\ cmd) \\ &\quad \quad \quad (CFG\ authenticationTest\ stateInterp\ securityContext \\ &\quad \quad \quad \quad (P\ \text{says}\ \text{prop}\ (SOME\ cmd)::ins)\ s\ outs) \\ &\quad \quad \quad (CFG\ authenticationTest\ stateInterp\ securityContext\ ins \\ &\quad \quad \quad \quad (NS\ s\ (\text{trap}\ cmd))\ (Out\ s\ (\text{trap}\ cmd)::outs))) \wedge \\ &\quad (\forall authenticationTest\ NS\ M\ Oi\ Os\ Out\ s\ securityContext \\ &\quad \quad stateInterp\ cmd\ x\ ins\ outs. \end{aligned}$$

$$\begin{aligned}
& \neg \text{authenticationTest } x \Rightarrow \\
& \text{TR}' (M, Oi, Os) (\text{discard } cmd) \\
& \quad (\text{CFG authenticationTest stateInterp securityContext} \\
& \quad \quad (x :: ins) s outs) \\
& \quad (\text{CFG authenticationTest stateInterp securityContext} \\
& \quad \quad ins (NS s (\text{discard } cmd))) \\
& \quad (\text{Out } s (\text{discard } cmd) :: outs))) \Rightarrow \\
& \forall a_0 a_1 a_2 a_3. \text{TR } a_0 a_1 a_2 a_3 \Rightarrow \text{TR}' a_0 a_1 a_2 a_3
\end{aligned}$$

[TR_rules]

$$\begin{aligned}
& \vdash (\forall \text{authenticationTest } P \text{ NS } M \text{ Oi } Os \text{ Out } s \text{ securityContext} \\
& \quad \text{stateInterp } cmd \text{ ins } outs. \\
& \quad \text{authenticationTest } (P \text{ says prop (SOME } cmd)) \wedge \\
& \quad \text{CFGInterpret } (M, Oi, Os) \\
& \quad \quad (\text{CFG authenticationTest stateInterp securityContext} \\
& \quad \quad \quad (P \text{ says prop (SOME } cmd) :: ins) s outs) \Rightarrow \\
& \quad \text{TR } (M, Oi, Os) (\text{exec } cmd) \\
& \quad \quad (\text{CFG authenticationTest stateInterp securityContext} \\
& \quad \quad \quad (P \text{ says prop (SOME } cmd) :: ins) s outs) \\
& \quad \quad (\text{CFG authenticationTest stateInterp securityContext ins} \\
& \quad \quad \quad (NS s (\text{exec } cmd)) (\text{Out } s (\text{exec } cmd) :: outs))) \wedge \\
& (\forall \text{authenticationTest } P \text{ NS } M \text{ Oi } Os \text{ Out } s \text{ securityContext} \\
& \quad \text{stateInterp } cmd \text{ ins } outs. \\
& \quad \text{authenticationTest } (P \text{ says prop (SOME } cmd)) \wedge \\
& \quad \text{CFGInterpret } (M, Oi, Os) \\
& \quad \quad (\text{CFG authenticationTest stateInterp securityContext} \\
& \quad \quad \quad (P \text{ says prop (SOME } cmd) :: ins) s outs) \Rightarrow \\
& \quad \text{TR } (M, Oi, Os) (\text{trap } cmd) \\
& \quad \quad (\text{CFG authenticationTest stateInterp securityContext} \\
& \quad \quad \quad (P \text{ says prop (SOME } cmd) :: ins) s outs) \\
& \quad \quad (\text{CFG authenticationTest stateInterp securityContext ins} \\
& \quad \quad \quad (NS s (\text{trap } cmd)) (\text{Out } s (\text{trap } cmd) :: outs))) \wedge \\
& \forall \text{authenticationTest } NS \text{ M } Oi \text{ Os } Out \text{ s securityContext} \\
& \quad \text{stateInterp } cmd \text{ x ins } outs. \\
& \neg \text{authenticationTest } x \Rightarrow \\
& \text{TR } (M, Oi, Os) (\text{discard } cmd) \\
& \quad (\text{CFG authenticationTest stateInterp securityContext} \\
& \quad \quad (x :: ins) s outs) \\
& \quad (\text{CFG authenticationTest stateInterp securityContext ins} \\
& \quad \quad (NS s (\text{discard } cmd)) (\text{Out } s (\text{discard } cmd) :: outs)))
\end{aligned}$$

[TR_strongind]

$$\begin{aligned}
& \vdash \forall \text{TR}'. \\
& \quad (\forall \text{authenticationTest } P \text{ NS } M \text{ Oi } Os \text{ Out } s \text{ securityContext} \\
& \quad \quad \text{stateInterp } cmd \text{ ins } outs. \\
& \quad \quad \text{authenticationTest } (P \text{ says prop (SOME } cmd)) \wedge \\
& \quad \quad \text{CFGInterpret } (M, Oi, Os) \\
& \quad \quad \quad (\text{CFG authenticationTest stateInterp securityContext} \\
& \quad \quad \quad \quad (P \text{ says prop (SOME } cmd) :: ins) s outs) \Rightarrow
\end{aligned}$$

$$\begin{aligned}
& TR' (M, Oi, Os) (\text{exec } cmd) \\
& \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext} \\
& \quad \quad (P \text{ says prop } (SOME \text{ cmd})::ins) \text{ s outs}) \\
& \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext} \\
& \quad \quad \quad ins (NS \text{ s } (\text{exec } cmd)) (Out \text{ s } (\text{exec } cmd)::outs))) \wedge \\
& (\forall \text{ authenticationTest } P \text{ NS } M \text{ Oi } Os \text{ Out } s \text{ securityContext} \\
& \quad \quad \quad stateInterp \text{ cmd } ins \text{ outs}. \\
& \text{authenticationTest } (P \text{ says prop } (SOME \text{ cmd})) \wedge \\
& \text{CFGInterpret } (M, Oi, Os) \\
& \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext} \\
& \quad \quad (P \text{ says prop } (SOME \text{ cmd})::ins) \text{ s outs}) \Rightarrow \\
& TR' (M, Oi, Os) (\text{trap } cmd) \\
& \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext} \\
& \quad \quad (P \text{ says prop } (SOME \text{ cmd})::ins) \text{ s outs}) \\
& \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext} \\
& \quad \quad \quad ins (NS \text{ s } (\text{trap } cmd)) (Out \text{ s } (\text{trap } cmd)::outs))) \wedge \\
& (\forall \text{ authenticationTest } NS \text{ M } Oi \text{ Os } Out \text{ s } securityContext \\
& \quad \quad \quad stateInterp \text{ cmd } x \text{ ins } outs. \\
& \neg \text{authenticationTest } x \Rightarrow \\
& TR' (M, Oi, Os) (\text{discard } cmd) \\
& \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext} \\
& \quad \quad (x::ins) \text{ s outs}) \\
& \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext} \\
& \quad \quad \quad ins (NS \text{ s } (\text{discard } cmd)) \\
& \quad \quad \quad \quad (Out \text{ s } (\text{discard } cmd)::outs))) \Rightarrow \\
& \forall a_0 \ a_1 \ a_2 \ a_3. TR \ a_0 \ a_1 \ a_2 \ a_3 \Rightarrow TR' \ a_0 \ a_1 \ a_2 \ a_3
\end{aligned}$$

[TR_trap_cmd_rule]

$$\begin{aligned}
& \vdash \forall \text{ authenticationTest } stateInterp \text{ securityContext } P \text{ cmd } ins \text{ s} \\
& \quad \quad \quad outs. \\
& (\forall M \text{ Oi } Os. \\
& \quad \text{CFGInterpret } (M, Oi, Os) \\
& \quad \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext} \\
& \quad \quad \quad (P \text{ says prop } (SOME \text{ cmd})::ins) \text{ s outs}) \Rightarrow \\
& \quad \quad (M, Oi, Os) \text{ sat prop NONE}) \Rightarrow \\
& \forall NS \text{ Out } M \text{ Oi } Os. \\
& \quad TR (M, Oi, Os) (\text{trap } cmd) \\
& \quad \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext} \\
& \quad \quad \quad (P \text{ says prop } (SOME \text{ cmd})::ins) \text{ s outs}) \\
& \quad \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext } ins \\
& \quad \quad \quad \quad (NS \text{ s } (\text{trap } cmd)) (Out \text{ s } (\text{trap } cmd)::outs)) \iff \\
& \quad \quad \text{authenticationTest } (P \text{ says prop } (SOME \text{ cmd})) \wedge \\
& \quad \quad \text{CFGInterpret } (M, Oi, Os) \\
& \quad \quad \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext} \\
& \quad \quad \quad \quad (P \text{ says prop } (SOME \text{ cmd})::ins) \text{ s outs}) \wedge \\
& \quad \quad (M, Oi, Os) \text{ sat prop NONE}
\end{aligned}$$

[TRrule0]

$$\begin{aligned}
& \vdash TR (M, Oi, Os) (\text{exec } cmd) \\
& \quad (CFG \text{ authenticationTest } stateInterp \text{ securityContext}
\end{aligned}$$

```

(P says prop (SOME cmd)::ins) s outs)
(CFG authenticationTest stateInterp securityContext ins
 (NS s (exec cmd)) (Out s (exec cmd)::outs))  $\iff$ 
authenticationTest (P says prop (SOME cmd))  $\wedge$ 
CFGInterpret (M, Oi, Os)
 (CFG authenticationTest stateInterp securityContext
  (P says prop (SOME cmd)::ins) s outs)

```

[TRrule1]

```

 $\vdash$  TR (M, Oi, Os) (trap cmd)
  (CFG authenticationTest stateInterp securityContext
   (P says prop (SOME cmd)::ins) s outs)
  (CFG authenticationTest stateInterp securityContext ins
   (NS s (trap cmd)) (Out s (trap cmd)::outs))  $\iff$ 
authenticationTest (P says prop (SOME cmd))  $\wedge$ 
CFGInterpret (M, Oi, Os)
  (CFG authenticationTest stateInterp securityContext
   (P says prop (SOME cmd)::ins) s outs)

```

[trType_distinct_clauses]

```

 $\vdash (\forall a'. \text{discard } a \neq \text{trap } a') \wedge (\forall a'. \text{discard } a \neq \text{exec } a') \wedge$ 
 $\forall a'. \text{trap } a \neq \text{exec } a'$ 

```

[trType_one_one]

```

 $\vdash (\forall a a'. (\text{discard } a = \text{discard } a') \iff (a = a')) \wedge$ 
 $(\forall a a'. (\text{trap } a = \text{trap } a') \iff (a = a')) \wedge$ 
 $\forall a a'. (\text{exec } a = \text{exec } a') \iff (a = a')$ 

```

3 ssm Theory

Built: 10 June 2018

Parent Theories: satList

3.1 Datatypes

```

configuration =
  CFG (('command option, 'principal, 'd, 'e) Form -> bool)
    ('state ->
      ('command option, 'principal, 'd, 'e) Form list ->
        ('command option, 'principal, 'd, 'e) Form list)
      (('command option, 'principal, 'd, 'e) Form list ->
        ('command option, 'principal, 'd, 'e) Form list)
      (('command option, 'principal, 'd, 'e) Form list list)
      'state ('output list)

trType = discard 'cmdlist | trap 'cmdlist | exec 'cmdlist

```

3.2 Definitions

[authenticationTest_def]

$$\vdash \forall \text{elementTest } x. \\ \text{authenticationTest } \text{elementTest } x \iff \\ \text{FOLDR } (\lambda p \ q. \ p \wedge \ q) \ \text{T} \ (\text{MAP } \text{elementTest } x)$$

[commandList_def]

$$\vdash \forall x. \text{commandList } x = \text{MAP } \text{extractCommand } x$$

[inputList_def]

$$\vdash \forall xs. \text{inputList } xs = \text{MAP } \text{extractInput } xs$$

[propCommandList_def]

$$\vdash \forall x. \text{propCommandList } x = \text{MAP } \text{extractPropCommand } x$$

[TR_def]

$$\vdash \text{TR} = \\ (\lambda a_0 \ a_1 \ a_2 \ a_3. \\ \forall TR'. \\ (\forall a_0 \ a_1 \ a_2 \ a_3. \\ (\exists \text{elementTest } NS \ M \ Oi \ Os \ Out \ s \ \text{context } \text{stateInterp } x \\ \text{ins } \text{outs}. \\ (a_0 = (M, Oi, Os)) \wedge (a_1 = \text{exec } (\text{inputList } x)) \wedge \\ (a_2 = \\ \text{CFG } \text{elementTest } \text{stateInterp } \text{context } (x::\text{ins}) \ s \\ \text{outs}) \wedge \\ (a_3 = \\ \text{CFG } \text{elementTest } \text{stateInterp } \text{context } \text{ins} \\ (NS \ s \ (\text{exec } (\text{inputList } x))) \\ (Out \ s \ (\text{exec } (\text{inputList } x)::\text{outs})) \wedge \\ \text{authenticationTest } \text{elementTest } x \wedge \\ \text{CFGInterpret } (M, Oi, Os) \\ (\text{CFG } \text{elementTest } \text{stateInterp } \text{context } (x::\text{ins}) \ s \\ \text{outs})) \vee \\ (\exists \text{elementTest } NS \ M \ Oi \ Os \ Out \ s \ \text{context } \text{stateInterp } x \\ \text{ins } \text{outs}. \\ (a_0 = (M, Oi, Os)) \wedge (a_1 = \text{trap } (\text{inputList } x)) \wedge \\ (a_2 = \\ \text{CFG } \text{elementTest } \text{stateInterp } \text{context } (x::\text{ins}) \ s \\ \text{outs}) \wedge \\ (a_3 = \\ \text{CFG } \text{elementTest } \text{stateInterp } \text{context } \text{ins} \\ (NS \ s \ (\text{trap } (\text{inputList } x))) \\ (Out \ s \ (\text{trap } (\text{inputList } x)::\text{outs})) \wedge \\ \text{authenticationTest } \text{elementTest } x \wedge \\ \text{CFGInterpret } (M, Oi, Os) \\ (\text{CFG } \text{elementTest } \text{stateInterp } \text{context } (x::\text{ins}) \ s$$

$$\begin{aligned}
& \text{outs})) \vee \\
& (\exists \text{elementTest } NS \ M \ Oi \ Os \ Out \ s \ \text{context } stateInterp \ x \\
& \quad \text{ins } outs. \\
& \quad (a_0 = (M, Oi, Os)) \wedge (a_1 = \text{discard } (\text{inputList } x)) \wedge \\
& \quad (a_2 = \\
& \quad \quad \text{CFG } \text{elementTest } stateInterp \ \text{context } (x::ins) \ s \\
& \quad \quad \text{outs}) \wedge \\
& \quad (a_3 = \\
& \quad \quad \text{CFG } \text{elementTest } stateInterp \ \text{context } ins \\
& \quad \quad (NS \ s \ (\text{discard } (\text{inputList } x))) \\
& \quad \quad (Out \ s \ (\text{discard } (\text{inputList } x))::outs)) \wedge \\
& \quad \neg \text{authenticationTest } \text{elementTest } x) \Rightarrow \\
& TR' \ a_0 \ a_1 \ a_2 \ a_3) \Rightarrow \\
& TR' \ a_0 \ a_1 \ a_2 \ a_3)
\end{aligned}$$

3.3 Theorems

[CFGInterpret_def]

$$\begin{aligned}
& \vdash \text{CFGInterpret } (M, Oi, Os) \\
& \quad (\text{CFG } \text{elementTest } stateInterp \ \text{context } (x::ins) \ state \\
& \quad \quad \text{outStream}) \iff \\
& \quad (M, Oi, Os) \ \text{satList } \text{context } x \wedge (M, Oi, Os) \ \text{satList } x \wedge \\
& \quad (M, Oi, Os) \ \text{satList } stateInterp \ state \ x
\end{aligned}$$

[CFGInterpret_ind]

$$\begin{aligned}
& \vdash \forall P. \\
& \quad (\forall M \ Oi \ Os \ \text{elementTest } stateInterp \ \text{context } x \ \text{ins } state \\
& \quad \quad \text{outStream}. \\
& \quad \quad P \ (M, Oi, Os) \\
& \quad \quad (\text{CFG } \text{elementTest } stateInterp \ \text{context } (x::ins) \ state \\
& \quad \quad \quad \text{outStream})) \wedge \\
& \quad (\forall v_{15} \ v_{10} \ v_{11} \ v_{12} \ v_{13} \ v_{14}. \\
& \quad \quad P \ v_{15} \ (\text{CFG } v_{10} \ v_{11} \ v_{12} \ [] \ v_{13} \ v_{14})) \Rightarrow \\
& \quad \forall v \ v_1 \ v_2 \ v_3. \ P \ (v, v_1, v_2) \ v_3
\end{aligned}$$

[configuration_one_one]

$$\begin{aligned}
& \vdash \forall a_0 \ a_1 \ a_2 \ a_3 \ a_4 \ a_5 \ a'_0 \ a'_1 \ a'_2 \ a'_3 \ a'_4 \ a'_5. \\
& \quad (\text{CFG } a_0 \ a_1 \ a_2 \ a_3 \ a_4 \ a_5 = \text{CFG } a'_0 \ a'_1 \ a'_2 \ a'_3 \ a'_4 \ a'_5) \iff \\
& \quad (a_0 = a'_0) \wedge (a_1 = a'_1) \wedge (a_2 = a'_2) \wedge (a_3 = a'_3) \wedge \\
& \quad (a_4 = a'_4) \wedge (a_5 = a'_5)
\end{aligned}$$

[extractCommand_def]

$$\vdash \text{extractCommand } (P \ \text{says prop } (\text{SOME } cmd)) = cmd$$

[extractCommand_ind]

$$\begin{aligned}
& \vdash \forall P'. \\
& \quad (\forall P \ cmd. \ P' \ (P \ \text{says prop } (\text{SOME } cmd))) \wedge P' \ \text{TT} \wedge P' \ \text{FF} \wedge \\
& \quad (\forall v_1. \ P' \ (\text{prop } v_1)) \wedge (\forall v_3. \ P' \ (\text{notf } v_3)) \wedge
\end{aligned}$$

$$\begin{aligned}
& (\forall v_6 v_7. P' (v_6 \text{ andf } v_7)) \wedge (\forall v_{10} v_{11}. P' (v_{10} \text{ orf } v_{11})) \wedge \\
& (\forall v_{14} v_{15}. P' (v_{14} \text{ impf } v_{15})) \wedge \\
& (\forall v_{18} v_{19}. P' (v_{18} \text{ eqf } v_{19})) \wedge (\forall v_{129}. P' (v_{129} \text{ says TT})) \wedge \\
& (\forall v_{130}. P' (v_{130} \text{ says FF})) \wedge \\
& (\forall v_{132}. P' (v_{132} \text{ says prop NONE})) \wedge \\
& (\forall v_{133} v_{66}. P' (v_{133} \text{ says notf } v_{66})) \wedge \\
& (\forall v_{134} v_{69} v_{70}. P' (v_{134} \text{ says } (v_{69} \text{ andf } v_{70}))) \wedge \\
& (\forall v_{135} v_{73} v_{74}. P' (v_{135} \text{ says } (v_{73} \text{ orf } v_{74}))) \wedge \\
& (\forall v_{136} v_{77} v_{78}. P' (v_{136} \text{ says } (v_{77} \text{ impf } v_{78}))) \wedge \\
& (\forall v_{137} v_{81} v_{82}. P' (v_{137} \text{ says } (v_{81} \text{ eqf } v_{82}))) \wedge \\
& (\forall v_{138} v_{85} v_{86}. P' (v_{138} \text{ says } v_{85} \text{ says } v_{86})) \wedge \\
& (\forall v_{139} v_{89} v_{90}. P' (v_{139} \text{ says } v_{89} \text{ speaks_for } v_{90})) \wedge \\
& (\forall v_{140} v_{93} v_{94}. P' (v_{140} \text{ says } v_{93} \text{ controls } v_{94})) \wedge \\
& (\forall v_{141} v_{98} v_{99} v_{100}. P' (v_{141} \text{ says reps } v_{98} v_{99} v_{100})) \wedge \\
& (\forall v_{142} v_{103} v_{104}. P' (v_{142} \text{ says } v_{103} \text{ domi } v_{104})) \wedge \\
& (\forall v_{143} v_{107} v_{108}. P' (v_{143} \text{ says } v_{107} \text{ eqi } v_{108})) \wedge \\
& (\forall v_{144} v_{111} v_{112}. P' (v_{144} \text{ says } v_{111} \text{ doms } v_{112})) \wedge \\
& (\forall v_{145} v_{115} v_{116}. P' (v_{145} \text{ says } v_{115} \text{ eqs } v_{116})) \wedge \\
& (\forall v_{146} v_{119} v_{120}. P' (v_{146} \text{ says } v_{119} \text{ eqn } v_{120})) \wedge \\
& (\forall v_{147} v_{123} v_{124}. P' (v_{147} \text{ says } v_{123} \text{ lte } v_{124})) \wedge \\
& (\forall v_{148} v_{127} v_{128}. P' (v_{148} \text{ says } v_{127} \text{ lt } v_{128})) \wedge \\
& (\forall v_{24} v_{25}. P' (v_{24} \text{ speaks_for } v_{25})) \wedge \\
& (\forall v_{28} v_{29}. P' (v_{28} \text{ controls } v_{29})) \wedge \\
& (\forall v_{33} v_{34} v_{35}. P' (\text{reps } v_{33} v_{34} v_{35})) \wedge \\
& (\forall v_{38} v_{39}. P' (v_{38} \text{ domi } v_{39})) \wedge \\
& (\forall v_{42} v_{43}. P' (v_{42} \text{ eqi } v_{43})) \wedge \\
& (\forall v_{46} v_{47}. P' (v_{46} \text{ doms } v_{47})) \wedge \\
& (\forall v_{50} v_{51}. P' (v_{50} \text{ eqs } v_{51})) \wedge \\
& (\forall v_{54} v_{55}. P' (v_{54} \text{ eqn } v_{55})) \wedge \\
& (\forall v_{58} v_{59}. P' (v_{58} \text{ lte } v_{59})) \wedge \\
& (\forall v_{62} v_{63}. P' (v_{62} \text{ lt } v_{63})) \Rightarrow \\
& \forall v. P' v
\end{aligned}$$

[extractInput_def]

$\vdash \text{extractInput } (P \text{ says prop } x) = x$

[extractInput_ind]

$\vdash \forall P'.$

$$\begin{aligned}
& (\forall P x. P' (P \text{ says prop } x)) \wedge P' \text{ TT} \wedge P' \text{ FF} \wedge \\
& (\forall v_1. P' (\text{prop } v_1)) \wedge (\forall v_3. P' (\text{notf } v_3)) \wedge \\
& (\forall v_6 v_7. P' (v_6 \text{ andf } v_7)) \wedge (\forall v_{10} v_{11}. P' (v_{10} \text{ orf } v_{11})) \wedge \\
& (\forall v_{14} v_{15}. P' (v_{14} \text{ impf } v_{15})) \wedge \\
& (\forall v_{18} v_{19}. P' (v_{18} \text{ eqf } v_{19})) \wedge (\forall v_{129}. P' (v_{129} \text{ says TT})) \wedge \\
& (\forall v_{130}. P' (v_{130} \text{ says FF})) \wedge \\
& (\forall v_{131} v_{66}. P' (v_{131} \text{ says notf } v_{66})) \wedge \\
& (\forall v_{132} v_{69} v_{70}. P' (v_{132} \text{ says } (v_{69} \text{ andf } v_{70}))) \wedge \\
& (\forall v_{133} v_{73} v_{74}. P' (v_{133} \text{ says } (v_{73} \text{ orf } v_{74}))) \wedge \\
& (\forall v_{134} v_{77} v_{78}. P' (v_{134} \text{ says } (v_{77} \text{ impf } v_{78}))) \wedge \\
& (\forall v_{135} v_{81} v_{82}. P' (v_{135} \text{ says } (v_{81} \text{ eqf } v_{82}))) \wedge
\end{aligned}$$

$$\begin{aligned}
& (\forall v136 \ v85 \ v86. \ P' \ (v136 \ \text{says} \ v85 \ \text{says} \ v86)) \wedge \\
& (\forall v137 \ v89 \ v90. \ P' \ (v137 \ \text{says} \ v89 \ \text{speaks_for} \ v90)) \wedge \\
& (\forall v138 \ v93 \ v94. \ P' \ (v138 \ \text{says} \ v93 \ \text{controls} \ v94)) \wedge \\
& (\forall v139 \ v98 \ v99 \ v100. \ P' \ (v139 \ \text{says} \ \text{reps} \ v98 \ v99 \ v100)) \wedge \\
& (\forall v140 \ v103 \ v104. \ P' \ (v140 \ \text{says} \ v103 \ \text{domi} \ v104)) \wedge \\
& (\forall v141 \ v107 \ v108. \ P' \ (v141 \ \text{says} \ v107 \ \text{eqi} \ v108)) \wedge \\
& (\forall v142 \ v111 \ v112. \ P' \ (v142 \ \text{says} \ v111 \ \text{doms} \ v112)) \wedge \\
& (\forall v143 \ v115 \ v116. \ P' \ (v143 \ \text{says} \ v115 \ \text{eqs} \ v116)) \wedge \\
& (\forall v144 \ v119 \ v120. \ P' \ (v144 \ \text{says} \ v119 \ \text{eqn} \ v120)) \wedge \\
& (\forall v145 \ v123 \ v124. \ P' \ (v145 \ \text{says} \ v123 \ \text{lte} \ v124)) \wedge \\
& (\forall v146 \ v127 \ v128. \ P' \ (v146 \ \text{says} \ v127 \ \text{lt} \ v128)) \wedge \\
& (\forall v24 \ v25. \ P' \ (v24 \ \text{speaks_for} \ v25)) \wedge \\
& (\forall v28 \ v29. \ P' \ (v28 \ \text{controls} \ v29)) \wedge \\
& (\forall v33 \ v34 \ v35. \ P' \ (\text{reps} \ v33 \ v34 \ v35)) \wedge \\
& (\forall v38 \ v39. \ P' \ (v38 \ \text{domi} \ v39)) \wedge \\
& (\forall v42 \ v43. \ P' \ (v42 \ \text{eqi} \ v43)) \wedge \\
& (\forall v46 \ v47. \ P' \ (v46 \ \text{doms} \ v47)) \wedge \\
& (\forall v50 \ v51. \ P' \ (v50 \ \text{eqs} \ v51)) \wedge \\
& (\forall v54 \ v55. \ P' \ (v54 \ \text{eqn} \ v55)) \wedge \\
& (\forall v58 \ v59. \ P' \ (v58 \ \text{lte} \ v59)) \wedge \\
& (\forall v62 \ v63. \ P' \ (v62 \ \text{lt} \ v63)) \Rightarrow \\
& \forall v. \ P' \ v
\end{aligned}$$

[extractPropCommand_def]

$$\vdash \text{extractPropCommand} \ (P \ \text{says} \ \text{prop} \ (\text{SOME} \ \text{cmd})) = \text{prop} \ (\text{SOME} \ \text{cmd})$$

[extractPropCommand_ind]

$$\begin{aligned}
& \vdash \forall P'. \\
& \quad (\forall P \ \text{cmd}. \ P' \ (P \ \text{says} \ \text{prop} \ (\text{SOME} \ \text{cmd}))) \wedge P' \ \text{TT} \wedge P' \ \text{FF} \wedge \\
& \quad (\forall v_1. \ P' \ (\text{prop} \ v_1)) \wedge (\forall v_3. \ P' \ (\text{notf} \ v_3)) \wedge \\
& \quad (\forall v_6 \ v_7. \ P' \ (v_6 \ \text{andf} \ v_7)) \wedge (\forall v_{10} \ v_{11}. \ P' \ (v_{10} \ \text{orf} \ v_{11})) \wedge \\
& \quad (\forall v_{14} \ v_{15}. \ P' \ (v_{14} \ \text{impf} \ v_{15})) \wedge \\
& \quad (\forall v_{18} \ v_{19}. \ P' \ (v_{18} \ \text{eqf} \ v_{19})) \wedge (\forall v_{129}. \ P' \ (v_{129} \ \text{says} \ \text{TT})) \wedge \\
& \quad (\forall v_{130}. \ P' \ (v_{130} \ \text{says} \ \text{FF})) \wedge \\
& \quad (\forall v_{132}. \ P' \ (v_{132} \ \text{says} \ \text{prop} \ \text{NONE})) \wedge \\
& \quad (\forall v_{133} \ v_{66}. \ P' \ (v_{133} \ \text{says} \ \text{notf} \ v_{66})) \wedge \\
& \quad (\forall v_{134} \ v_{69} \ v_{70}. \ P' \ (v_{134} \ \text{says} \ (v_{69} \ \text{andf} \ v_{70}))) \wedge \\
& \quad (\forall v_{135} \ v_{73} \ v_{74}. \ P' \ (v_{135} \ \text{says} \ (v_{73} \ \text{orf} \ v_{74}))) \wedge \\
& \quad (\forall v_{136} \ v_{77} \ v_{78}. \ P' \ (v_{136} \ \text{says} \ (v_{77} \ \text{impf} \ v_{78}))) \wedge \\
& \quad (\forall v_{137} \ v_{81} \ v_{82}. \ P' \ (v_{137} \ \text{says} \ (v_{81} \ \text{eqf} \ v_{82}))) \wedge \\
& \quad (\forall v_{138} \ v_{85} \ v_{86}. \ P' \ (v_{138} \ \text{says} \ v_{85} \ \text{says} \ v_{86})) \wedge \\
& \quad (\forall v_{139} \ v_{89} \ v_{90}. \ P' \ (v_{139} \ \text{says} \ v_{89} \ \text{speaks_for} \ v_{90})) \wedge \\
& \quad (\forall v_{140} \ v_{93} \ v_{94}. \ P' \ (v_{140} \ \text{says} \ v_{93} \ \text{controls} \ v_{94})) \wedge \\
& \quad (\forall v_{141} \ v_{98} \ v_{99} \ v_{100}. \ P' \ (v_{141} \ \text{says} \ \text{reps} \ v_{98} \ v_{99} \ v_{100})) \wedge \\
& \quad (\forall v_{142} \ v_{103} \ v_{104}. \ P' \ (v_{142} \ \text{says} \ v_{103} \ \text{domi} \ v_{104})) \wedge \\
& \quad (\forall v_{143} \ v_{107} \ v_{108}. \ P' \ (v_{143} \ \text{says} \ v_{107} \ \text{eqi} \ v_{108})) \wedge \\
& \quad (\forall v_{144} \ v_{111} \ v_{112}. \ P' \ (v_{144} \ \text{says} \ v_{111} \ \text{doms} \ v_{112})) \wedge \\
& \quad (\forall v_{145} \ v_{115} \ v_{116}. \ P' \ (v_{145} \ \text{says} \ v_{115} \ \text{eqs} \ v_{116})) \wedge \\
& \quad (\forall v_{146} \ v_{119} \ v_{120}. \ P' \ (v_{146} \ \text{says} \ v_{119} \ \text{eqn} \ v_{120})) \wedge
\end{aligned}$$

$$\begin{aligned}
& (\forall v_{147} v_{123} v_{124}. P' (v_{147} \text{ says } v_{123} \text{ lte } v_{124})) \wedge \\
& (\forall v_{148} v_{127} v_{128}. P' (v_{148} \text{ says } v_{127} \text{ lt } v_{128})) \wedge \\
& (\forall v_{24} v_{25}. P' (v_{24} \text{ speaks_for } v_{25})) \wedge \\
& (\forall v_{28} v_{29}. P' (v_{28} \text{ controls } v_{29})) \wedge \\
& (\forall v_{33} v_{34} v_{35}. P' (\text{reps } v_{33} v_{34} v_{35})) \wedge \\
& (\forall v_{38} v_{39}. P' (v_{38} \text{ domi } v_{39})) \wedge \\
& (\forall v_{42} v_{43}. P' (v_{42} \text{ eqi } v_{43})) \wedge \\
& (\forall v_{46} v_{47}. P' (v_{46} \text{ doms } v_{47})) \wedge \\
& (\forall v_{50} v_{51}. P' (v_{50} \text{ eqs } v_{51})) \wedge \\
& (\forall v_{54} v_{55}. P' (v_{54} \text{ eqn } v_{55})) \wedge \\
& (\forall v_{58} v_{59}. P' (v_{58} \text{ lte } v_{59})) \wedge \\
& (\forall v_{62} v_{63}. P' (v_{62} \text{ lt } v_{63})) \Rightarrow \\
& \forall v. P' v
\end{aligned}$$

[TR_cases]

$$\begin{aligned}
& \vdash \forall a_0 a_1 a_2 a_3. \\
& \text{TR } a_0 a_1 a_2 a_3 \iff \\
& (\exists \text{elementTest } NS \ M \ Oi \ Os \ Out \ s \ context \ stateInterp \ x \ ins \\
& \quad outs. \\
& \quad (a_0 = (M, Oi, Os)) \wedge (a_1 = \text{exec } (\text{inputList } x)) \wedge \\
& \quad (a_2 = \\
& \quad \quad \text{CFG elementTest stateInterp context } (x::ins) \ s \ outs) \wedge \\
& \quad (a_3 = \\
& \quad \quad \text{CFG elementTest stateInterp context } ins \\
& \quad \quad \quad (NS \ s \ (\text{exec } (\text{inputList } x))) \\
& \quad \quad \quad (Out \ s \ (\text{exec } (\text{inputList } x))::outs)) \wedge \\
& \quad \text{authenticationTest elementTest } x \wedge \\
& \quad \text{CFGInterpret } (M, Oi, Os) \\
& \quad \quad (\text{CFG elementTest stateInterp context } (x::ins) \ s \\
& \quad \quad \quad outs)) \vee \\
& (\exists \text{elementTest } NS \ M \ Oi \ Os \ Out \ s \ context \ stateInterp \ x \ ins \\
& \quad outs. \\
& \quad (a_0 = (M, Oi, Os)) \wedge (a_1 = \text{trap } (\text{inputList } x)) \wedge \\
& \quad (a_2 = \\
& \quad \quad \text{CFG elementTest stateInterp context } (x::ins) \ s \ outs) \wedge \\
& \quad (a_3 = \\
& \quad \quad \text{CFG elementTest stateInterp context } ins \\
& \quad \quad \quad (NS \ s \ (\text{trap } (\text{inputList } x))) \\
& \quad \quad \quad (Out \ s \ (\text{trap } (\text{inputList } x))::outs)) \wedge \\
& \quad \text{authenticationTest elementTest } x \wedge \\
& \quad \text{CFGInterpret } (M, Oi, Os) \\
& \quad \quad (\text{CFG elementTest stateInterp context } (x::ins) \ s \\
& \quad \quad \quad outs)) \vee \\
& \exists \text{elementTest } NS \ M \ Oi \ Os \ Out \ s \ context \ stateInterp \ x \ ins \\
& \quad outs. \\
& \quad (a_0 = (M, Oi, Os)) \wedge (a_1 = \text{discard } (\text{inputList } x)) \wedge \\
& \quad (a_2 = \\
& \quad \quad \text{CFG elementTest stateInterp context } (x::ins) \ s \ outs) \wedge \\
& \quad (a_3 =
\end{aligned}$$

CFG elementTest stateInterp context ins
 (NS s (discard (inputList x)))
 (Out s (discard (inputList x))::outs)) \wedge
 \neg authenticationTest elementTest x

[TR_discard_cmd_rule]

\vdash TR (M, Oi, Os) (discard (inputList x))
 (CFG elementTest stateInterp context (x::ins) s outs)
 (CFG elementTest stateInterp context ins
 (NS s (discard (inputList x)))
 (Out s (discard (inputList x))::outs)) \iff
 \neg authenticationTest elementTest x

[TR_EQ_rules_thm]

\vdash (TR (M, Oi, Os) (exec (inputList x))
 (CFG elementTest stateInterp context (x::ins) s outs)
 (CFG elementTest stateInterp context ins
 (NS s (exec (inputList x)))
 (Out s (exec (inputList x))::outs)) \iff
 authenticationTest elementTest x \wedge
 CFGInterpret (M, Oi, Os)
 (CFG elementTest stateInterp context (x::ins) s outs)) \wedge
 (TR (M, Oi, Os) (trap (inputList x))
 (CFG elementTest stateInterp context (x::ins) s outs)
 (CFG elementTest stateInterp context ins
 (NS s (trap (inputList x)))
 (Out s (trap (inputList x))::outs)) \iff
 authenticationTest elementTest x \wedge
 CFGInterpret (M, Oi, Os)
 (CFG elementTest stateInterp context (x::ins) s outs)) \wedge
 (TR (M, Oi, Os) (discard (inputList x))
 (CFG elementTest stateInterp context (x::ins) s outs)
 (CFG elementTest stateInterp context ins
 (NS s (discard (inputList x)))
 (Out s (discard (inputList x))::outs)) \iff
 \neg authenticationTest elementTest x)

[TR_exec_cmd_rule]

$\vdash \forall$ elementTest context stateInterp x ins s outs.
 (\forall M Oi Os.
 CFGInterpret (M, Oi, Os)
 (CFG elementTest stateInterp context (x::ins) s
 outs) \Rightarrow
 (M, Oi, Os) satList propCommandList x) \Rightarrow
 \forall NS Out M Oi Os.
 TR (M, Oi, Os) (exec (inputList x))
 (CFG elementTest stateInterp context (x::ins) s outs)
 (CFG elementTest stateInterp context ins

$$\begin{aligned}
& (NS \ s \ (\text{exec} \ (\text{inputList} \ x))) \\
& (\text{Out} \ s \ (\text{exec} \ (\text{inputList} \ x))::\text{outs})) \iff \\
& \text{authenticationTest} \ \text{elementTest} \ x \wedge \\
& \text{CFGInterpret} \ (M, Oi, Os) \\
& \quad (\text{CFG} \ \text{elementTest} \ \text{stateInterp} \ \text{context} \ (x::\text{ins}) \ s \ \text{outs}) \wedge \\
& (M, Oi, Os) \ \text{satList} \ \text{propCommandList} \ x
\end{aligned}$$

[TR_ind]

 $\vdash \forall TR'.$

$$\begin{aligned}
& (\forall \text{elementTest} \ NS \ M \ Oi \ Os \ Out \ s \ \text{context} \ \text{stateInterp} \ x \ \text{ins} \\
& \quad \text{outs}. \\
& \text{authenticationTest} \ \text{elementTest} \ x \wedge \\
& \text{CFGInterpret} \ (M, Oi, Os) \\
& \quad (\text{CFG} \ \text{elementTest} \ \text{stateInterp} \ \text{context} \ (x::\text{ins}) \ s \\
& \quad \text{outs}) \Rightarrow \\
& TR' \ (M, Oi, Os) \ (\text{exec} \ (\text{inputList} \ x)) \\
& \quad (\text{CFG} \ \text{elementTest} \ \text{stateInterp} \ \text{context} \ (x::\text{ins}) \ s \ \text{outs}) \\
& \quad (\text{CFG} \ \text{elementTest} \ \text{stateInterp} \ \text{context} \ \text{ins} \\
& \quad \quad (NS \ s \ (\text{exec} \ (\text{inputList} \ x))) \\
& \quad \quad (\text{Out} \ s \ (\text{exec} \ (\text{inputList} \ x))::\text{outs}))) \wedge \\
& (\forall \text{elementTest} \ NS \ M \ Oi \ Os \ Out \ s \ \text{context} \ \text{stateInterp} \ x \ \text{ins} \\
& \quad \text{outs}. \\
& \text{authenticationTest} \ \text{elementTest} \ x \wedge \\
& \text{CFGInterpret} \ (M, Oi, Os) \\
& \quad (\text{CFG} \ \text{elementTest} \ \text{stateInterp} \ \text{context} \ (x::\text{ins}) \ s \\
& \quad \text{outs}) \Rightarrow \\
& TR' \ (M, Oi, Os) \ (\text{trap} \ (\text{inputList} \ x)) \\
& \quad (\text{CFG} \ \text{elementTest} \ \text{stateInterp} \ \text{context} \ (x::\text{ins}) \ s \ \text{outs}) \\
& \quad (\text{CFG} \ \text{elementTest} \ \text{stateInterp} \ \text{context} \ \text{ins} \\
& \quad \quad (NS \ s \ (\text{trap} \ (\text{inputList} \ x))) \\
& \quad \quad (\text{Out} \ s \ (\text{trap} \ (\text{inputList} \ x))::\text{outs}))) \wedge \\
& (\forall \text{elementTest} \ NS \ M \ Oi \ Os \ Out \ s \ \text{context} \ \text{stateInterp} \ x \ \text{ins} \\
& \quad \text{outs}. \\
& \neg \text{authenticationTest} \ \text{elementTest} \ x \Rightarrow \\
& TR' \ (M, Oi, Os) \ (\text{discard} \ (\text{inputList} \ x)) \\
& \quad (\text{CFG} \ \text{elementTest} \ \text{stateInterp} \ \text{context} \ (x::\text{ins}) \ s \ \text{outs}) \\
& \quad (\text{CFG} \ \text{elementTest} \ \text{stateInterp} \ \text{context} \ \text{ins} \\
& \quad \quad (NS \ s \ (\text{discard} \ (\text{inputList} \ x))) \\
& \quad \quad (\text{Out} \ s \ (\text{discard} \ (\text{inputList} \ x))::\text{outs}))) \Rightarrow \\
& \forall a_0 \ a_1 \ a_2 \ a_3. \ TR \ a_0 \ a_1 \ a_2 \ a_3 \Rightarrow TR' \ a_0 \ a_1 \ a_2 \ a_3
\end{aligned}$$

[TR_rules]

$$\begin{aligned}
& \vdash (\forall \text{elementTest} \ NS \ M \ Oi \ Os \ Out \ s \ \text{context} \ \text{stateInterp} \ x \ \text{ins} \\
& \quad \text{outs}. \\
& \text{authenticationTest} \ \text{elementTest} \ x \wedge \\
& \text{CFGInterpret} \ (M, Oi, Os) \\
& \quad (\text{CFG} \ \text{elementTest} \ \text{stateInterp} \ \text{context} \ (x::\text{ins}) \ s \ \text{outs}) \Rightarrow \\
& TR \ (M, Oi, Os) \ (\text{exec} \ (\text{inputList} \ x)) \\
& \quad (\text{CFG} \ \text{elementTest} \ \text{stateInterp} \ \text{context} \ (x::\text{ins}) \ s \ \text{outs})
\end{aligned}$$

```

(CFG elementTest stateInterp context ins
  (NS s (exec (inputList x)))
  (Out s (exec (inputList x))::outs))) ∧
(∀ elementTest NS M Oi Os Out s context stateInterp x ins
  outs.
  authenticationTest elementTest x ∧
  CFGInterpret (M, Oi, Os)
    (CFG elementTest stateInterp context (x::ins) s outs) ⇒
  TR (M, Oi, Os) (trap (inputList x))
    (CFG elementTest stateInterp context (x::ins) s outs)
    (CFG elementTest stateInterp context ins
      (NS s (trap (inputList x)))
      (Out s (trap (inputList x))::outs))) ∧
  ∀ elementTest NS M Oi Os Out s context stateInterp x ins outs.
    ¬authenticationTest elementTest x ⇒
  TR (M, Oi, Os) (discard (inputList x))
    (CFG elementTest stateInterp context (x::ins) s outs)
    (CFG elementTest stateInterp context ins
      (NS s (discard (inputList x)))
      (Out s (discard (inputList x))::outs)))

```

[TR_strongind]

```

⊢ ∀ TR'.
  (∀ elementTest NS M Oi Os Out s context stateInterp x ins
    outs.
    authenticationTest elementTest x ∧
    CFGInterpret (M, Oi, Os)
      (CFG elementTest stateInterp context (x::ins) s
        outs) ⇒
    TR' (M, Oi, Os) (exec (inputList x))
      (CFG elementTest stateInterp context (x::ins) s outs)
      (CFG elementTest stateInterp context ins
        (NS s (exec (inputList x)))
        (Out s (exec (inputList x))::outs))) ∧
    (∀ elementTest NS M Oi Os Out s context stateInterp x ins
      outs.
      authenticationTest elementTest x ∧
      CFGInterpret (M, Oi, Os)
        (CFG elementTest stateInterp context (x::ins) s
          outs) ⇒
      TR' (M, Oi, Os) (trap (inputList x))
        (CFG elementTest stateInterp context (x::ins) s outs)
        (CFG elementTest stateInterp context ins
          (NS s (trap (inputList x)))
          (Out s (trap (inputList x))::outs))) ∧
      (∀ elementTest NS M Oi Os Out s context stateInterp x ins
        outs.
        ¬authenticationTest elementTest x ⇒
        TR' (M, Oi, Os) (discard (inputList x))

```

$$\begin{aligned}
& (\text{CFG elementTest stateInterp context } (x::\text{ins}) \text{ s outs}) \\
& (\text{CFG elementTest stateInterp context ins} \\
& \quad (\text{NS s (discard (inputList x))}) \\
& \quad (\text{Out s (discard (inputList x))::outs})) \Rightarrow \\
& \forall a_0 \ a_1 \ a_2 \ a_3. \text{TR } a_0 \ a_1 \ a_2 \ a_3 \Rightarrow \text{TR}' a_0 \ a_1 \ a_2 \ a_3
\end{aligned}$$

[TR_trap_cmd_rule]

$$\begin{aligned}
& \vdash \forall \text{elementTest context stateInterp x ins s outs.} \\
& \quad (\forall M \ Oi \ Os. \\
& \quad \quad \text{CFGInterpret } (M, Oi, Os) \\
& \quad \quad (\text{CFG elementTest stateInterp context } (x::\text{ins}) \text{ s} \\
& \quad \quad \quad \text{outs}) \Rightarrow \\
& \quad \quad (M, Oi, Os) \text{ sat prop NONE}) \Rightarrow \\
& \quad \forall \text{NS Out M Oi Os.} \\
& \quad \text{TR } (M, Oi, Os) (\text{trap (inputList x)}) \\
& \quad (\text{CFG elementTest stateInterp context } (x::\text{ins}) \text{ s outs}) \\
& \quad (\text{CFG elementTest stateInterp context ins} \\
& \quad \quad (\text{NS s (trap (inputList x))}) \\
& \quad \quad (\text{Out s (trap (inputList x))::outs})) \iff \\
& \quad \text{authenticationTest elementTest x} \wedge \\
& \quad \text{CFGInterpret } (M, Oi, Os) \\
& \quad \quad (\text{CFG elementTest stateInterp context } (x::\text{ins}) \text{ s outs}) \wedge \\
& \quad \quad (M, Oi, Os) \text{ sat prop NONE}
\end{aligned}$$

[TRrule0]

$$\begin{aligned}
& \vdash \text{TR } (M, Oi, Os) (\text{exec (inputList x)}) \\
& \quad (\text{CFG elementTest stateInterp context } (x::\text{ins}) \text{ s outs}) \\
& \quad (\text{CFG elementTest stateInterp context ins} \\
& \quad \quad (\text{NS s (exec (inputList x))}) \\
& \quad \quad (\text{Out s (exec (inputList x))::outs})) \iff \\
& \quad \text{authenticationTest elementTest x} \wedge \\
& \quad \text{CFGInterpret } (M, Oi, Os) \\
& \quad \quad (\text{CFG elementTest stateInterp context } (x::\text{ins}) \text{ s outs})
\end{aligned}$$

[TRrule1]

$$\begin{aligned}
& \vdash \text{TR } (M, Oi, Os) (\text{trap (inputList x)}) \\
& \quad (\text{CFG elementTest stateInterp context } (x::\text{ins}) \text{ s outs}) \\
& \quad (\text{CFG elementTest stateInterp context ins} \\
& \quad \quad (\text{NS s (trap (inputList x))}) \\
& \quad \quad (\text{Out s (trap (inputList x))::outs})) \iff \\
& \quad \text{authenticationTest elementTest x} \wedge \\
& \quad \text{CFGInterpret } (M, Oi, Os) \\
& \quad \quad (\text{CFG elementTest stateInterp context } (x::\text{ins}) \text{ s outs})
\end{aligned}$$

[trType_distinct_clauses]

$$\begin{aligned}
& \vdash (\forall a' \ a. \text{discard } a \neq \text{trap } a') \wedge (\forall a' \ a. \text{discard } a \neq \text{exec } a') \wedge \\
& \quad \forall a' \ a. \text{trap } a \neq \text{exec } a'
\end{aligned}$$

[trType_one_one]

$$\begin{aligned} \vdash (\forall a \ a'. (\text{discard } a = \text{discard } a') \iff (a = a')) \wedge \\ (\forall a \ a'. (\text{trap } a = \text{trap } a') \iff (a = a')) \wedge \\ \forall a \ a'. (\text{exec } a = \text{exec } a') \iff (a = a') \end{aligned}$$

4 satList Theory

Built: 10 June 2018

Parent Theories: aclDrules

4.1 Definitions

[satList_def]

$$\begin{aligned} \vdash \forall M \ Oi \ Os \ formList. \\ (M, Oi, Os) \text{ satList } formList \iff \\ \text{FOLDR } (\lambda x \ y. x \wedge y) \ T \ (\text{MAP } (\lambda f. (M, Oi, Os) \text{ sat } f) \ formList) \end{aligned}$$

4.2 Theorems

[satList_conj]

$$\begin{aligned} \vdash \forall l_1 \ l_2 \ M \ Oi \ Os. \\ (M, Oi, Os) \text{ satList } l_1 \wedge (M, Oi, Os) \text{ satList } l_2 \iff \\ (M, Oi, Os) \text{ satList } (l_1 ++ l_2) \end{aligned}$$

[satList_CONS]

$$\begin{aligned} \vdash \forall h \ t \ M \ Oi \ Os. \\ (M, Oi, Os) \text{ satList } (h :: t) \iff \\ (M, Oi, Os) \text{ sat } h \wedge (M, Oi, Os) \text{ satList } t \end{aligned}$$

[satList_nil]

$$\vdash (M, Oi, Os) \text{ satList } []$$

5 PBTypeIntegrated Theory

Built: 11 June 2018

Parent Theories: OMNIType

5.1 Datatypes

```
omniCommand = ssmPlanPBComplete | ssmMoveToORPComplete
              | ssmConductORPComplete | ssmMoveToPBComplete
              | ssmConductPBComplete | invalidOmniCommand
```

```
plCommand = crossLD | conductORP | moveToPB | conductPB
            | completePB | incomplete
```

```

slCommand =
  PL PBTYPESINTEGRATED$plCommand
  | OMNI PBTYPESINTEGRATED$omniCommand

slOutput = PlanPB | MoveToORP | ConductORP | MoveToPB
           | ConductPB | CompletePB | unAuthenticated
           | unAuthorized

slState = PLAN_PB | MOVE_TO_ORP | CONDUCT_ORP | MOVE_TO_PB
          | CONDUCT_PB | COMPLETE_PB

stateRole = PlatoonLeader | Omni

```

5.2 Theorems

[omniCommand_distinct_clauses]

```

⊢ ssmPlanPBComplete ≠ ssmMoveToORPComplete ∧
  ssmPlanPBComplete ≠ ssmConductORPComplete ∧
  ssmPlanPBComplete ≠ ssmMoveToPBComplete ∧
  ssmPlanPBComplete ≠ ssmConductPBComplete ∧
  ssmPlanPBComplete ≠ invalidOmniCommand ∧
  ssmMoveToORPComplete ≠ ssmConductORPComplete ∧
  ssmMoveToORPComplete ≠ ssmMoveToPBComplete ∧
  ssmMoveToORPComplete ≠ ssmConductPBComplete ∧
  ssmMoveToORPComplete ≠ invalidOmniCommand ∧
  ssmConductORPComplete ≠ ssmMoveToPBComplete ∧
  ssmConductORPComplete ≠ ssmConductPBComplete ∧
  ssmConductORPComplete ≠ invalidOmniCommand ∧
  ssmMoveToPBComplete ≠ ssmConductPBComplete ∧
  ssmMoveToPBComplete ≠ invalidOmniCommand ∧
  ssmConductPBComplete ≠ invalidOmniCommand

```

[plCommand_distinct_clauses]

```

⊢ crossLD ≠ conductORP ∧ crossLD ≠ moveToPB ∧
  crossLD ≠ conductPB ∧ crossLD ≠ completePB ∧
  crossLD ≠ incomplete ∧ conductORP ≠ moveToPB ∧
  conductORP ≠ conductPB ∧ conductORP ≠ completePB ∧
  conductORP ≠ incomplete ∧ moveToPB ≠ conductPB ∧
  moveToPB ≠ completePB ∧ moveToPB ≠ incomplete ∧
  conductPB ≠ completePB ∧ conductPB ≠ incomplete ∧
  completePB ≠ incomplete

```

[slCommand_distinct_clauses]

```

⊢ ∀ a' a. PL a ≠ OMNI a'

```

[slCommand_one_one]

```

⊢ (∀ a a'. (PL a = PL a') ⇔ (a = a')) ∧
  ∀ a a'. (OMNI a = OMNI a') ⇔ (a = a')

```

[slOutput_distinct_clauses]

$$\begin{aligned}
&\vdash \text{PlanPB} \neq \text{MoveToORP} \wedge \text{PlanPB} \neq \text{ConductORP} \wedge \\
&\quad \text{PlanPB} \neq \text{MoveToPB} \wedge \text{PlanPB} \neq \text{ConductPB} \wedge \\
&\quad \text{PlanPB} \neq \text{CompletePB} \wedge \text{PlanPB} \neq \text{unAuthenticated} \wedge \\
&\quad \text{PlanPB} \neq \text{unAuthorized} \wedge \text{MoveToORP} \neq \text{ConductORP} \wedge \\
&\quad \text{MoveToORP} \neq \text{MoveToPB} \wedge \text{MoveToORP} \neq \text{ConductPB} \wedge \\
&\quad \text{MoveToORP} \neq \text{CompletePB} \wedge \text{MoveToORP} \neq \text{unAuthenticated} \wedge \\
&\quad \text{MoveToORP} \neq \text{unAuthorized} \wedge \text{ConductORP} \neq \text{MoveToPB} \wedge \\
&\quad \text{ConductORP} \neq \text{ConductPB} \wedge \text{ConductORP} \neq \text{CompletePB} \wedge \\
&\quad \text{ConductORP} \neq \text{unAuthenticated} \wedge \text{ConductORP} \neq \text{unAuthorized} \wedge \\
&\quad \text{MoveToPB} \neq \text{ConductPB} \wedge \text{MoveToPB} \neq \text{CompletePB} \wedge \\
&\quad \text{MoveToPB} \neq \text{unAuthenticated} \wedge \text{MoveToPB} \neq \text{unAuthorized} \wedge \\
&\quad \text{ConductPB} \neq \text{CompletePB} \wedge \text{ConductPB} \neq \text{unAuthenticated} \wedge \\
&\quad \text{ConductPB} \neq \text{unAuthorized} \wedge \text{CompletePB} \neq \text{unAuthenticated} \wedge \\
&\quad \text{CompletePB} \neq \text{unAuthorized} \wedge \text{unAuthenticated} \neq \text{unAuthorized}
\end{aligned}$$
[slState_distinct_clauses]

$$\begin{aligned}
&\vdash \text{PLAN_PB} \neq \text{MOVE_TO_ORP} \wedge \text{PLAN_PB} \neq \text{CONDUCT_ORP} \wedge \\
&\quad \text{PLAN_PB} \neq \text{MOVE_TO_PB} \wedge \text{PLAN_PB} \neq \text{CONDUCT_PB} \wedge \\
&\quad \text{PLAN_PB} \neq \text{COMPLETE_PB} \wedge \text{MOVE_TO_ORP} \neq \text{CONDUCT_ORP} \wedge \\
&\quad \text{MOVE_TO_ORP} \neq \text{MOVE_TO_PB} \wedge \text{MOVE_TO_ORP} \neq \text{CONDUCT_PB} \wedge \\
&\quad \text{MOVE_TO_ORP} \neq \text{COMPLETE_PB} \wedge \text{CONDUCT_ORP} \neq \text{MOVE_TO_PB} \wedge \\
&\quad \text{CONDUCT_ORP} \neq \text{CONDUCT_PB} \wedge \text{CONDUCT_ORP} \neq \text{COMPLETE_PB} \wedge \\
&\quad \text{MOVE_TO_PB} \neq \text{CONDUCT_PB} \wedge \text{MOVE_TO_PB} \neq \text{COMPLETE_PB} \wedge \\
&\quad \text{CONDUCT_PB} \neq \text{COMPLETE_PB}
\end{aligned}$$
[stateRole_distinct_clauses]

$$\vdash \text{PlatoonLeader} \neq \text{Omni}$$

6 PBIntegratedDef Theory

Built: 11 June 2018**Parent Theories:** PBTypeIntegrated, aclfoundation

6.1 Definitions

[secAuthorization_def]

$$\vdash \forall xs. \text{secAuthorization } xs = \text{secHelper } (\text{getOmniCommand } xs)$$
[secContext_def]

$$\begin{aligned}
&\vdash (\forall xs. \\
&\quad \text{secContext PLAN_PB } xs = \\
&\quad \text{if } \text{getOmniCommand } xs = \text{ssmPlanPBComplete} \text{ then} \\
&\quad \quad [\text{prop } (\text{SOME } (\text{SLc } (\text{OMNI ssmPlanPBComplete}))) \text{ impf} \\
&\quad \quad \quad \text{Name PlatoonLeader controls} \\
&\quad \quad \text{prop } (\text{SOME } (\text{SLc } (\text{PL crossLD})))])
\end{aligned}$$

```

    else [prop NONE]) ∧
  (∀ xs.
    secContext MOVE_TO_ORP xs =
    if getOmniCommand xs = ssmMoveToORPComplete then
      [prop (SOME (SLc (OMNI ssmMoveToORPComplete))) impf
        Name PlatoonLeader controls
        prop (SOME (SLc (PL conductORP)))])
    else [prop NONE]) ∧
  (∀ xs.
    secContext CONDUCT_ORP xs =
    if getOmniCommand xs = ssmConductORPComplete then
      [prop (SOME (SLc (OMNI ssmConductORPComplete))) impf
        Name PlatoonLeader controls
        prop (SOME (SLc (PL moveToPB)))])
    else [prop NONE]) ∧
  (∀ xs.
    secContext MOVE_TO_PB xs =
    if getOmniCommand xs = ssmConductORPComplete then
      [prop (SOME (SLc (OMNI ssmMoveToPBComplete))) impf
        Name PlatoonLeader controls
        prop (SOME (SLc (PL conductPB)))])
    else [prop NONE]) ∧
  (∀ xs.
    secContext CONDUCT_PB xs =
    if getOmniCommand xs = ssmConductPBComplete then
      [prop (SOME (SLc (OMNI ssmConductPBComplete))) impf
        Name PlatoonLeader controls
        prop (SOME (SLc (PL completePB)))])
    else [prop NONE]
  )

```

[secHelper_def]

```

⊢ ∀ cmd.
  secHelper cmd =
  [Name Omni controls prop (SOME (SLc (OMNI cmd)))]

```

6.2 Theorems

[getOmniCommand_def]

```

⊢ (getOmniCommand [] = invalidOmniCommand) ∧
  (∀ xs cmd.
    getOmniCommand
      (Name Omni says prop (SOME (SLc (OMNI cmd))))::xs =
      cmd) ∧
  (∀ xs. getOmniCommand (TT::xs) = getOmniCommand xs) ∧
  (∀ xs. getOmniCommand (FF::xs) = getOmniCommand xs) ∧
  (∀ xs v2. getOmniCommand (prop v2::xs) = getOmniCommand xs) ∧
  (∀ xs v3. getOmniCommand (notf v3::xs) = getOmniCommand xs) ∧
  (∀ xs v5 v4.

```

```

    getOmniCommand (v4 andf v5::xs) = getOmniCommand xs) ∧
  (∀ xs v7 v6.
    getOmniCommand (v6 orf v7::xs) = getOmniCommand xs) ∧
  (∀ xs v9 v8.
    getOmniCommand (v8 impf v9::xs) = getOmniCommand xs) ∧
  (∀ xs v11 v10.
    getOmniCommand (v10 eqf v11::xs) = getOmniCommand xs) ∧
  (∀ xs v12.
    getOmniCommand (v12 says TT::xs) = getOmniCommand xs) ∧
  (∀ xs v12.
    getOmniCommand (v12 says FF::xs) = getOmniCommand xs) ∧
  (∀ xs v134.
    getOmniCommand (Name v134 says prop NONE::xs) =
    getOmniCommand xs) ∧
  (∀ xs v144.
    getOmniCommand
      (Name PlatoonLeader says prop (SOME v144)::xs) =
    getOmniCommand xs) ∧
  (∀ xs v146.
    getOmniCommand
      (Name Omni says prop (SOME (ESCc v146))::xs) =
    getOmniCommand xs) ∧
  (∀ xs v150.
    getOmniCommand
      (Name Omni says prop (SOME (SLc (PL v150)))::xs) =
    getOmniCommand xs) ∧
  (∀ xs v68 v136 v135.
    getOmniCommand (v135 meet v136 says prop v68::xs) =
    getOmniCommand xs) ∧
  (∀ xs v68 v138 v137.
    getOmniCommand (v137 quoting v138 says prop v68::xs) =
    getOmniCommand xs) ∧
  (∀ xs v69 v12.
    getOmniCommand (v12 says notf v69::xs) =
    getOmniCommand xs) ∧
  (∀ xs v71 v70 v12.
    getOmniCommand (v12 says (v70 andf v71)::xs) =
    getOmniCommand xs) ∧
  (∀ xs v73 v72 v12.
    getOmniCommand (v12 says (v72 orf v73)::xs) =
    getOmniCommand xs) ∧
  (∀ xs v75 v74 v12.
    getOmniCommand (v12 says (v74 impf v75)::xs) =
    getOmniCommand xs) ∧
  (∀ xs v77 v76 v12.
    getOmniCommand (v12 says (v76 eqf v77)::xs) =
    getOmniCommand xs) ∧
  (∀ xs v79 v78 v12.
    getOmniCommand (v12 says v78 says v79::xs) =

```

```

    getOmniCommand xs) ∧
  (∀ xs v81 v80 v12.
    getOmniCommand (v12 says v80 speaks_for v81::xs) =
    getOmniCommand xs) ∧
  (∀ xs v83 v82 v12.
    getOmniCommand (v12 says v82 controls v83::xs) =
    getOmniCommand xs) ∧
  (∀ xs v86 v85 v84 v12.
    getOmniCommand (v12 says reps v84 v85 v86::xs) =
    getOmniCommand xs) ∧
  (∀ xs v88 v87 v12.
    getOmniCommand (v12 says v87 domi v88::xs) =
    getOmniCommand xs) ∧
  (∀ xs v90 v89 v12.
    getOmniCommand (v12 says v89 eqi v90::xs) =
    getOmniCommand xs) ∧
  (∀ xs v92 v91 v12.
    getOmniCommand (v12 says v91 doms v92::xs) =
    getOmniCommand xs) ∧
  (∀ xs v94 v93 v12.
    getOmniCommand (v12 says v93 eqs v94::xs) =
    getOmniCommand xs) ∧
  (∀ xs v96 v95 v12.
    getOmniCommand (v12 says v95 eqn v96::xs) =
    getOmniCommand xs) ∧
  (∀ xs v98 v97 v12.
    getOmniCommand (v12 says v97 lte v98::xs) =
    getOmniCommand xs) ∧
  (∀ xs v99 v12 v100.
    getOmniCommand (v12 says v99 lt v100::xs) =
    getOmniCommand xs) ∧
  (∀ xs v15 v14.
    getOmniCommand (v14 speaks_for v15::xs) =
    getOmniCommand xs) ∧
  (∀ xs v17 v16.
    getOmniCommand (v16 controls v17::xs) =
    getOmniCommand xs) ∧
  (∀ xs v20 v19 v18.
    getOmniCommand (reps v18 v19 v20::xs) =
    getOmniCommand xs) ∧
  (∀ xs v22 v21.
    getOmniCommand (v21 domi v22::xs) = getOmniCommand xs) ∧
  (∀ xs v24 v23.
    getOmniCommand (v23 eqi v24::xs) = getOmniCommand xs) ∧
  (∀ xs v26 v25.
    getOmniCommand (v25 doms v26::xs) = getOmniCommand xs) ∧
  (∀ xs v28 v27.
    getOmniCommand (v27 eqs v28::xs) = getOmniCommand xs) ∧
  (∀ xs v30 v29.

```

$\text{getOmniCommand } (v_{29} \text{ eqn } v_{30}::xs) = \text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_{32} \ v_{31}.$
 $\text{getOmniCommand } (v_{31} \text{ lte } v_{32}::xs) = \text{getOmniCommand } xs) \wedge$
 $\forall xs \ v_{34} \ v_{33}.$
 $\text{getOmniCommand } (v_{33} \text{ lt } v_{34}::xs) = \text{getOmniCommand } xs$

[getOmniCommand_ind]

$\vdash \forall P.$
 $P \ [] \wedge$
 $(\forall cmd \ xs.$
 $P \ (\text{Name Omni says prop (SOME (SLc (OMNI cmd)))::xs})) \wedge$
 $(\forall xs. P \ xs \Rightarrow P \ (\text{TT::xs})) \wedge (\forall xs. P \ xs \Rightarrow P \ (\text{FF::xs})) \wedge$
 $(\forall v_2 \ xs. P \ xs \Rightarrow P \ (\text{prop } v_2::xs)) \wedge$
 $(\forall v_3 \ xs. P \ xs \Rightarrow P \ (\text{notf } v_3::xs)) \wedge$
 $(\forall v_4 \ v_5 \ xs. P \ xs \Rightarrow P \ (v_4 \text{ andf } v_5::xs)) \wedge$
 $(\forall v_6 \ v_7 \ xs. P \ xs \Rightarrow P \ (v_6 \text{ orf } v_7::xs)) \wedge$
 $(\forall v_8 \ v_9 \ xs. P \ xs \Rightarrow P \ (v_8 \text{ impf } v_9::xs)) \wedge$
 $(\forall v_{10} \ v_{11} \ xs. P \ xs \Rightarrow P \ (v_{10} \text{ eqf } v_{11}::xs)) \wedge$
 $(\forall v_{12} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says TT::xs})) \wedge$
 $(\forall v_{12} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says FF::xs})) \wedge$
 $(\forall v_{134} \ xs. P \ xs \Rightarrow P \ (\text{Name } v_{134} \text{ says prop NONE::xs})) \wedge$
 $(\forall v_{144} \ xs.$
 $P \ xs \Rightarrow$
 $P \ (\text{Name PlatoonLeader says prop (SOME } v_{144}::xs)) \wedge$
 $(\forall v_{146} \ xs.$
 $P \ xs \Rightarrow P \ (\text{Name Omni says prop (SOME (ESCc } v_{146}::xs)) \wedge$
 $(\forall v_{150} \ xs.$
 $P \ xs \Rightarrow$
 $P \ (\text{Name Omni says prop (SOME (SLc (PL } v_{150})))::xs)) \wedge$
 $(\forall v_{135} \ v_{136} \ v_{68} \ xs.$
 $P \ xs \Rightarrow P \ (v_{135} \text{ meet } v_{136} \text{ says prop } v_{68}::xs)) \wedge$
 $(\forall v_{137} \ v_{138} \ v_{68} \ xs.$
 $P \ xs \Rightarrow P \ (v_{137} \text{ quoting } v_{138} \text{ says prop } v_{68}::xs)) \wedge$
 $(\forall v_{12} \ v_{69} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says notf } v_{69}::xs)) \wedge$
 $(\forall v_{12} \ v_{70} \ v_{71} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says } (v_{70} \text{ andf } v_{71})::xs)) \wedge$
 $(\forall v_{12} \ v_{72} \ v_{73} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says } (v_{72} \text{ orf } v_{73})::xs)) \wedge$
 $(\forall v_{12} \ v_{74} \ v_{75} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says } (v_{74} \text{ impf } v_{75})::xs)) \wedge$
 $(\forall v_{12} \ v_{76} \ v_{77} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says } (v_{76} \text{ eqf } v_{77})::xs)) \wedge$
 $(\forall v_{12} \ v_{78} \ v_{79} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says } v_{78} \text{ says } v_{79}::xs)) \wedge$
 $(\forall v_{12} \ v_{80} \ v_{81} \ xs.$
 $P \ xs \Rightarrow P \ (v_{12} \text{ says } v_{80} \text{ speaks_for } v_{81}::xs)) \wedge$
 $(\forall v_{12} \ v_{82} \ v_{83} \ xs.$
 $P \ xs \Rightarrow P \ (v_{12} \text{ says } v_{82} \text{ controls } v_{83}::xs)) \wedge$
 $(\forall v_{12} \ v_{84} \ v_{85} \ v_{86} \ xs.$
 $P \ xs \Rightarrow P \ (v_{12} \text{ says reps } v_{84} \ v_{85} \ v_{86}::xs)) \wedge$
 $(\forall v_{12} \ v_{87} \ v_{88} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says } v_{87} \text{ domi } v_{88}::xs)) \wedge$
 $(\forall v_{12} \ v_{89} \ v_{90} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says } v_{89} \text{ eqi } v_{90}::xs)) \wedge$
 $(\forall v_{12} \ v_{91} \ v_{92} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says } v_{91} \text{ doms } v_{92}::xs)) \wedge$
 $(\forall v_{12} \ v_{93} \ v_{94} \ xs. P \ xs \Rightarrow P \ (v_{12} \text{ says } v_{93} \text{ eqs } v_{94}::xs)) \wedge$

$$\begin{aligned}
& (\forall v_{12} v_{95} v_{96} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{95} \text{ eqn } v_{96} :: xs)) \wedge \\
& (\forall v_{12} v_{97} v_{98} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{97} \text{ lte } v_{98} :: xs)) \wedge \\
& (\forall v_{12} v_{99} v_{100} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{99} \text{ lt } v_{100} :: xs)) \wedge \\
& (\forall v_{14} v_{15} xs. P xs \Rightarrow P (v_{14} \text{ speaks_for } v_{15} :: xs)) \wedge \\
& (\forall v_{16} v_{17} xs. P xs \Rightarrow P (v_{16} \text{ controls } v_{17} :: xs)) \wedge \\
& (\forall v_{18} v_{19} v_{20} xs. P xs \Rightarrow P (\text{reps } v_{18} v_{19} v_{20} :: xs)) \wedge \\
& (\forall v_{21} v_{22} xs. P xs \Rightarrow P (v_{21} \text{ domi } v_{22} :: xs)) \wedge \\
& (\forall v_{23} v_{24} xs. P xs \Rightarrow P (v_{23} \text{ eqi } v_{24} :: xs)) \wedge \\
& (\forall v_{25} v_{26} xs. P xs \Rightarrow P (v_{25} \text{ doms } v_{26} :: xs)) \wedge \\
& (\forall v_{27} v_{28} xs. P xs \Rightarrow P (v_{27} \text{ eqs } v_{28} :: xs)) \wedge \\
& (\forall v_{29} v_{30} xs. P xs \Rightarrow P (v_{29} \text{ eqn } v_{30} :: xs)) \wedge \\
& (\forall v_{31} v_{32} xs. P xs \Rightarrow P (v_{31} \text{ lte } v_{32} :: xs)) \wedge \\
& (\forall v_{33} v_{34} xs. P xs \Rightarrow P (v_{33} \text{ lt } v_{34} :: xs)) \Rightarrow \\
& \forall v. P v
\end{aligned}$$

[getPlCom_def]

$$\begin{aligned}
& \vdash (\text{getPlCom } [] = \text{incomplete}) \wedge \\
& (\forall xs \text{ cmd}. \text{getPlCom } (\text{SOME } (\text{SLc } (\text{PL } \text{cmd}))) :: xs = \text{cmd}) \wedge \\
& (\forall xs. \text{getPlCom } (\text{NONE} :: xs) = \text{getPlCom } xs) \wedge \\
& (\forall xs v_4. \text{getPlCom } (\text{SOME } (\text{ESCc } v_4)) :: xs = \text{getPlCom } xs) \wedge \\
& \forall xs v_9. \text{getPlCom } (\text{SOME } (\text{SLc } (\text{OMNI } v_9))) :: xs = \text{getPlCom } xs
\end{aligned}$$

[getPlCom_ind]

$$\begin{aligned}
& \vdash \forall P. \\
& P [] \wedge (\forall \text{cmd } xs. P (\text{SOME } (\text{SLc } (\text{PL } \text{cmd}))) :: xs) \wedge \\
& (\forall xs. P xs \Rightarrow P (\text{NONE} :: xs)) \wedge \\
& (\forall v_4 xs. P xs \Rightarrow P (\text{SOME } (\text{ESCc } v_4) :: xs)) \wedge \\
& (\forall v_9 xs. P xs \Rightarrow P (\text{SOME } (\text{SLc } (\text{OMNI } v_9)) :: xs)) \Rightarrow \\
& \forall v. P v
\end{aligned}$$

7 ssmPBIntegrated Theory

Built: 11 June 2018

Parent Theories: PBIntegratedDef, ssm

7.1 Theorems

[inputOK_cmd_reject_lemma]

$$\vdash \forall \text{cmd}. \neg \text{inputOK } (\text{prop } (\text{SOME } \text{cmd}))$$

[inputOK_def]

$$\begin{aligned}
& \vdash (\text{inputOK } (\text{Name PlatoonLeader says prop cmd}) \iff T) \wedge \\
& (\text{inputOK } (\text{Name Omni says prop cmd}) \iff T) \wedge \\
& (\text{inputOK TT} \iff F) \wedge (\text{inputOK FF} \iff F) \wedge \\
& (\text{inputOK } (\text{prop } v) \iff F) \wedge (\text{inputOK } (\text{notf } v_1) \iff F) \wedge \\
& (\text{inputOK } (v_2 \text{ andf } v_3) \iff F) \wedge (\text{inputOK } (v_4 \text{ orf } v_5) \iff F) \wedge \\
& (\text{inputOK } (v_6 \text{ impf } v_7) \iff F) \wedge (\text{inputOK } (v_8 \text{ eqf } v_9) \iff F) \wedge
\end{aligned}$$

$(\text{inputOK } (v_{10} \text{ says TT}) \iff F) \wedge (\text{inputOK } (v_{10} \text{ says FF}) \iff F) \wedge$
 $(\text{inputOK } (v_{133} \text{ meet } v_{134} \text{ says prop } v_{66}) \iff F) \wedge$
 $(\text{inputOK } (v_{135} \text{ quoting } v_{136} \text{ says prop } v_{66}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says notf } v_{67}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } (v_{68} \text{ andf } v_{69})) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } (v_{70} \text{ orf } v_{71})) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } (v_{72} \text{ impf } v_{73})) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } (v_{74} \text{ eqf } v_{75})) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{76} \text{ says } v_{77}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{80} \text{ controls } v_{81}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says reps } v_{82} \text{ } v_{83} \text{ } v_{84}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{85} \text{ domi } v_{86}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{87} \text{ eqi } v_{88}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{89} \text{ doms } v_{90}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{91} \text{ eqs } v_{92}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{93} \text{ eqn } v_{94}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{95} \text{ lte } v_{96}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{97} \text{ lt } v_{98}) \iff F) \wedge$
 $(\text{inputOK } (v_{12} \text{ speaks_for } v_{13}) \iff F) \wedge$
 $(\text{inputOK } (v_{14} \text{ controls } v_{15}) \iff F) \wedge$
 $(\text{inputOK } (\text{reps } v_{16} \text{ } v_{17} \text{ } v_{18}) \iff F) \wedge$
 $(\text{inputOK } (v_{19} \text{ domi } v_{20}) \iff F) \wedge$
 $(\text{inputOK } (v_{21} \text{ eqi } v_{22}) \iff F) \wedge$
 $(\text{inputOK } (v_{23} \text{ doms } v_{24}) \iff F) \wedge$
 $(\text{inputOK } (v_{25} \text{ eqs } v_{26}) \iff F) \wedge (\text{inputOK } (v_{27} \text{ eqn } v_{28}) \iff F) \wedge$
 $(\text{inputOK } (v_{29} \text{ lte } v_{30}) \iff F) \wedge (\text{inputOK } (v_{31} \text{ lt } v_{32}) \iff F)$

[inputOK_ind]

$\vdash \forall P.$

$(\forall \text{cmd}. P (\text{Name PlatoonLeader says prop cmd})) \wedge$
 $(\forall \text{cmd}. P (\text{Name Omni says prop cmd})) \wedge P \text{ TT} \wedge P \text{ FF} \wedge$
 $(\forall v. P (\text{prop } v)) \wedge (\forall v_1. P (\text{notf } v_1)) \wedge$
 $(\forall v_2 \text{ } v_3. P (v_2 \text{ andf } v_3)) \wedge (\forall v_4 \text{ } v_5. P (v_4 \text{ orf } v_5)) \wedge$
 $(\forall v_6 \text{ } v_7. P (v_6 \text{ impf } v_7)) \wedge (\forall v_8 \text{ } v_9. P (v_8 \text{ eqf } v_9)) \wedge$
 $(\forall v_{10}. P (v_{10} \text{ says TT})) \wedge (\forall v_{10}. P (v_{10} \text{ says FF})) \wedge$
 $(\forall v_{133} \text{ } v_{134} \text{ } v_{66}. P (v_{133} \text{ meet } v_{134} \text{ says prop } v_{66})) \wedge$
 $(\forall v_{135} \text{ } v_{136} \text{ } v_{66}. P (v_{135} \text{ quoting } v_{136} \text{ says prop } v_{66})) \wedge$
 $(\forall v_{10} \text{ } v_{67}. P (v_{10} \text{ says notf } v_{67})) \wedge$
 $(\forall v_{10} \text{ } v_{68} \text{ } v_{69}. P (v_{10} \text{ says } (v_{68} \text{ andf } v_{69}))) \wedge$
 $(\forall v_{10} \text{ } v_{70} \text{ } v_{71}. P (v_{10} \text{ says } (v_{70} \text{ orf } v_{71}))) \wedge$
 $(\forall v_{10} \text{ } v_{72} \text{ } v_{73}. P (v_{10} \text{ says } (v_{72} \text{ impf } v_{73}))) \wedge$
 $(\forall v_{10} \text{ } v_{74} \text{ } v_{75}. P (v_{10} \text{ says } (v_{74} \text{ eqf } v_{75}))) \wedge$
 $(\forall v_{10} \text{ } v_{76} \text{ } v_{77}. P (v_{10} \text{ says } v_{76} \text{ says } v_{77})) \wedge$
 $(\forall v_{10} \text{ } v_{78} \text{ } v_{79}. P (v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79})) \wedge$
 $(\forall v_{10} \text{ } v_{80} \text{ } v_{81}. P (v_{10} \text{ says } v_{80} \text{ controls } v_{81})) \wedge$
 $(\forall v_{10} \text{ } v_{82} \text{ } v_{83} \text{ } v_{84}. P (v_{10} \text{ says reps } v_{82} \text{ } v_{83} \text{ } v_{84})) \wedge$
 $(\forall v_{10} \text{ } v_{85} \text{ } v_{86}. P (v_{10} \text{ says } v_{85} \text{ domi } v_{86})) \wedge$
 $(\forall v_{10} \text{ } v_{87} \text{ } v_{88}. P (v_{10} \text{ says } v_{87} \text{ eqi } v_{88})) \wedge$

$$\begin{aligned}
& (\forall v_{10} v_{89} v_{90}. P (v_{10} \text{ says } v_{89} \text{ doms } v_{90})) \wedge \\
& (\forall v_{10} v_{91} v_{92}. P (v_{10} \text{ says } v_{91} \text{ eqs } v_{92})) \wedge \\
& (\forall v_{10} v_{93} v_{94}. P (v_{10} \text{ says } v_{93} \text{ eqn } v_{94})) \wedge \\
& (\forall v_{10} v_{95} v_{96}. P (v_{10} \text{ says } v_{95} \text{ lte } v_{96})) \wedge \\
& (\forall v_{10} v_{97} v_{98}. P (v_{10} \text{ says } v_{97} \text{ lt } v_{98})) \wedge \\
& (\forall v_{12} v_{13}. P (v_{12} \text{ speaks_for } v_{13})) \wedge \\
& (\forall v_{14} v_{15}. P (v_{14} \text{ controls } v_{15})) \wedge \\
& (\forall v_{16} v_{17} v_{18}. P (\text{reps } v_{16} v_{17} v_{18})) \wedge \\
& (\forall v_{19} v_{20}. P (v_{19} \text{ domi } v_{20})) \wedge \\
& (\forall v_{21} v_{22}. P (v_{21} \text{ eqi } v_{22})) \wedge \\
& (\forall v_{23} v_{24}. P (v_{23} \text{ doms } v_{24})) \wedge \\
& (\forall v_{25} v_{26}. P (v_{25} \text{ eqs } v_{26})) \wedge (\forall v_{27} v_{28}. P (v_{27} \text{ eqn } v_{28})) \wedge \\
& (\forall v_{29} v_{30}. P (v_{29} \text{ lte } v_{30})) \wedge (\forall v_{31} v_{32}. P (v_{31} \text{ lt } v_{32})) \Rightarrow \\
& \forall v. P v
\end{aligned}$$

[PBNS_def]

$$\begin{aligned}
& \vdash (\text{PBNS PLAN_PB (exec } x) = \\
& \quad \text{if getPlCom } x = \text{crossLD then MOVE_TO_ORP else PLAN_PB}) \wedge \\
& (\text{PBNS MOVE_TO_ORP (exec } x) = \\
& \quad \text{if getPlCom } x = \text{conductORP then CONDUCT_ORP} \\
& \quad \text{else MOVE_TO_ORP}) \wedge \\
& (\text{PBNS CONDUCT_ORP (exec } x) = \\
& \quad \text{if getPlCom } x = \text{moveToPB then MOVE_TO_PB else CONDUCT_ORP}) \wedge \\
& (\text{PBNS MOVE_TO_PB (exec } x) = \\
& \quad \text{if getPlCom } x = \text{conductPB then CONDUCT_PB else MOVE_TO_PB}) \wedge \\
& (\text{PBNS CONDUCT_PB (exec } x) = \\
& \quad \text{if getPlCom } x = \text{completePB then COMPLETE_PB} \\
& \quad \text{else CONDUCT_PB}) \wedge (\text{PBNS } s \text{ (trap } v_0) = s) \wedge \\
& (\text{PBNS } s \text{ (discard } v_1) = s)
\end{aligned}$$

[PBNS_ind]

$$\begin{aligned}
& \vdash \forall P. \\
& (\forall x. P \text{ PLAN_PB (exec } x)) \wedge (\forall x. P \text{ MOVE_TO_ORP (exec } x)) \wedge \\
& (\forall x. P \text{ CONDUCT_ORP (exec } x)) \wedge \\
& (\forall x. P \text{ MOVE_TO_PB (exec } x)) \wedge (\forall x. P \text{ CONDUCT_PB (exec } x)) \wedge \\
& (\forall s v_0. P s \text{ (trap } v_0)) \wedge (\forall s v_1. P s \text{ (discard } v_1)) \wedge \\
& (\forall v_6. P \text{ COMPLETE_PB (exec } v_6)) \Rightarrow \\
& \forall v v_1. P v v_1
\end{aligned}$$

[PBOut_def]

$$\begin{aligned}
& \vdash (\text{PBOut PLAN_PB (exec } x) = \\
& \quad \text{if getPlCom } x = \text{crossLD then MoveToORP else PlanPB}) \wedge \\
& (\text{PBOut MOVE_TO_ORP (exec } x) = \\
& \quad \text{if getPlCom } x = \text{conductORP then ConductORP else MoveToORP}) \wedge \\
& (\text{PBOut CONDUCT_ORP (exec } x) = \\
& \quad \text{if getPlCom } x = \text{moveToPB then MoveToORP else ConductORP}) \wedge \\
& (\text{PBOut MOVE_TO_PB (exec } x) = \\
& \quad \text{if getPlCom } x = \text{conductPB then ConductPB else MoveToPB}) \wedge
\end{aligned}$$

```

(PBOut CONDUCT_PB (exec x) =
  if getPlCom x = completePB then CompletePB else ConductPB) ∧
(PBOut s (trap v0) = unauthorized) ∧
(PBOut s (discard v1) = unauthenticated)

```

[PBOut_ind]

```

⊢ ∀ P.
  (∀ x. P PLAN_PB (exec x)) ∧ (∀ x. P MOVE_TO_ORP (exec x)) ∧
  (∀ x. P CONDUCT_ORP (exec x)) ∧
  (∀ x. P MOVE_TO_PB (exec x)) ∧ (∀ x. P CONDUCT_PB (exec x)) ∧
  (∀ s v0. P s (trap v0)) ∧ (∀ s v1. P s (discard v1)) ∧
  (∀ v6. P COMPLETE_PB (exec v6)) ⇒
  ∀ v v1. P v v1

```

[PlatoonLeader_Omni_notDiscard_slCommand_thm]

```

⊢ ∀ NS Out M Oi Os.
  ¬TR (M, Oi, Os)
  (discard
    [SOME (SLc (PL plCommand));
     SOME (SLc (OMNI omniCommand))])
  (CFG inputOK secContext secAuthorization
    ([Name Omni says prop (SOME (SLc (PL plCommand))));
     Name PlatoonLeader says
     prop (SOME (SLc (OMNI omniCommand)))]::ins) PLAN_PB
  outs)
  (CFG inputOK secContext secAuthorization ins
    (NS PLAN_PB
      (discard
        [SOME (SLc (PL plCommand));
         SOME (SLc (OMNI omniCommand))]))
    (Out PLAN_PB
      (discard
        [SOME (SLc (PL plCommand));
         SOME (SLc (OMNI omniCommand))]]::outs))

```

[PlatoonLeader_PLAN_PB_exec_justified_lemma]

```

⊢ ∀ NS Out M Oi Os.
  TR (M, Oi, Os)
  (exec
    (inputList
      [Name Omni says
       prop (SOME (SLc (OMNI ssmPlanPBComplete))));
       Name PlatoonLeader says
       prop (SOME (SLc (PL crossLD)))]))
  (CFG inputOK secContext secAuthorization
    ([Name Omni says
     prop (SOME (SLc (OMNI ssmPlanPBComplete))));
     Name PlatoonLeader says

```

```

      prop (SOME (SLc (PL crossLD))))]::ins) PLAN_PB outs)
(CFG inputOK secContext secAuthorization ins
  (NS PLAN_PB
    (exec
      (inputList
        [Name Omni says
          prop (SOME (SLc (OMNI ssmPlanPBComplete))));
          Name PlatoonLeader says
          prop (SOME (SLc (PL crossLD))))]))
  (Out PLAN_PB
    (exec
      (inputList
        [Name Omni says
          prop (SOME (SLc (OMNI ssmPlanPBComplete))));
          Name PlatoonLeader says
          prop (SOME (SLc (PL crossLD))))]::outs))  $\iff$ 
authenticationTest inputOK
  [Name Omni says
    prop (SOME (SLc (OMNI ssmPlanPBComplete))));
    Name PlatoonLeader says
    prop (SOME (SLc (PL crossLD)))]  $\wedge$ 
CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secAuthorization
    ([Name Omni says
      prop (SOME (SLc (OMNI ssmPlanPBComplete))));
      Name PlatoonLeader says
      prop (SOME (SLc (PL crossLD)))]]::ins) PLAN_PB
    outs)  $\wedge$ 
(M, Oi, Os) satList
propCommandList
  [Name Omni says
    prop (SOME (SLc (OMNI ssmPlanPBComplete))));
    Name PlatoonLeader says prop (SOME (SLc (PL crossLD)))]

```

[PlatoonLeader_PLAN_PB_exec_justified_thm]

```

 $\vdash \forall NS \text{ Out } M \text{ Oi } Os.$ 
TR (M, Oi, Os)
  (exec
    [SOME (SLc (OMNI ssmPlanPBComplete));
     SOME (SLc (PL crossLD))])
  (CFG inputOK secContext secAuthorization
    ([Name Omni says
      prop (SOME (SLc (OMNI ssmPlanPBComplete))));
      Name PlatoonLeader says
      prop (SOME (SLc (PL crossLD)))]]::ins) PLAN_PB outs)
  (CFG inputOK secContext secAuthorization ins
    (NS PLAN_PB
      (exec
        [SOME (SLc (OMNI ssmPlanPBComplete));

```



```

      SOME (SLc (PL crossLD))))))
    (Out PLAN_PB
      (exec
        [SOME (SLc (OMNI ssmPlanPBComplete));
         SOME (SLc (PL crossLD))])::outs))  $\iff$ 
authenticationTest inputOK
  [Name Omni says
   prop (SOME (SLc (OMNI ssmPlanPBComplete)))];
  Name PlatoonLeader says
  prop (SOME (SLc (PL crossLD)))]  $\wedge$ 
CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secAuthorization
    ([Name Omni says
     prop (SOME (SLc (OMNI ssmPlanPBComplete)))];
     Name PlatoonLeader says
     prop (SOME (SLc (PL crossLD)))]::ins) PLAN_PB
    outs)  $\wedge$ 
  (M, Oi, Os) satList
  [prop (SOME (SLc (OMNI ssmPlanPBComplete)))];
   prop (SOME (SLc (PL crossLD)))]

```

[PlatoonLeader_PLAN_PB_exec_lemma]

```

 $\vdash \forall M \text{ } Oi \text{ } Os.$ 
  CFGInterpret (M, Oi, Os)
    (CFG inputOK secContext secAuthorization
      ([Name Omni says
       prop (SOME (SLc (OMNI ssmPlanPBComplete)))];
       Name PlatoonLeader says
       prop (SOME (SLc (PL crossLD)))]::ins) PLAN_PB
      outs)  $\Rightarrow$ 
  (M, Oi, Os) satList
  propCommandList
  [Name Omni says
   prop (SOME (SLc (OMNI ssmPlanPBComplete)))];
   Name PlatoonLeader says prop (SOME (SLc (PL crossLD)))]

```

[PlatoonLeader_PLAN_PB_trap_justified_lemma]

```

 $\vdash \text{omniCommand} \neq \text{ssmPlanPBComplete} \Rightarrow$ 
  (s = PLAN_PB)  $\Rightarrow$ 
 $\forall NS \text{ } Out \text{ } M \text{ } Oi \text{ } Os.$ 
  TR (M, Oi, Os)
    (trap
      (inputList
        [Name Omni says
         prop (SOME (SLc (OMNI omniCommand)))];
         Name PlatoonLeader says
         prop (SOME (SLc (PL crossLD)))]))
    (CFG inputOK secContext secAuthorization
      ([Name Omni says prop (SOME (SLc (OMNI omniCommand)))];

```

```

      Name PlatoonLeader says
      prop (SOME (SLc (PL crossLD))))]::ins) PLAN_PB outs)
(CFG inputOK secContext secAuthorization ins
  (NS PLAN_PB
    (trap
      (inputList
        [Name Omni says
          prop (SOME (SLc (OMNI omniCommand))));
          Name PlatoonLeader says
          prop (SOME (SLc (PL crossLD))))]))
  (Out PLAN_PB
    (trap
      (inputList
        [Name Omni says
          prop (SOME (SLc (OMNI omniCommand))));
          Name PlatoonLeader says
          prop (SOME (SLc (PL crossLD))))]::outs))  $\iff$ 
authenticationTest inputOK
  [Name Omni says prop (SOME (SLc (OMNI omniCommand))));
   Name PlatoonLeader says
   prop (SOME (SLc (PL crossLD)))]  $\wedge$ 
CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secAuthorization
    ([Name Omni says prop (SOME (SLc (OMNI omniCommand))));
     Name PlatoonLeader says
     prop (SOME (SLc (PL crossLD)))]]::ins) PLAN_PB
  outs)  $\wedge$  (M, Oi, Os) sat prop NONE

```

[PlatoonLeader_PLAN_PB_trap_justified_thm]

```

 $\vdash$  omniCommand  $\neq$  ssmPlanPBComplete  $\Rightarrow$ 
  (s = PLAN_PB)  $\Rightarrow$ 
 $\forall$  NS Out M Oi Os.
  TR (M, Oi, Os)
    (trap
      [SOME (SLc (OMNI omniCommand));
       SOME (SLc (PL crossLD))])
    (CFG inputOK secContext secAuthorization
      ([Name Omni says prop (SOME (SLc (OMNI omniCommand))));
       Name PlatoonLeader says
       prop (SOME (SLc (PL crossLD)))]]::ins) PLAN_PB outs)
    (CFG inputOK secContext secAuthorization ins
      (NS PLAN_PB
        (trap
          [SOME (SLc (OMNI omniCommand));
           SOME (SLc (PL crossLD))]))
      (Out PLAN_PB
        (trap
          [SOME (SLc (OMNI omniCommand));
           SOME (SLc (PL crossLD))]::outs))  $\iff$ 

```

```

authenticationTest inputOK
  [Name Omni says prop (SOME (SLc (OMNI omniCommand)))];
  Name PlatoonLeader says
    prop (SOME (SLc (PL crossLD))) ] ∧
CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secAuthorization
    ([Name Omni says prop (SOME (SLc (OMNI omniCommand)))];
      Name PlatoonLeader says
        prop (SOME (SLc (PL crossLD))) ]::ins) PLAN_PB
    outs) ∧ (M, Oi, Os) sat prop NONE

```

[PlatoonLeader_PLAN_PB_trap_lemma]

```

⊢ omniCommand ≠ ssmPlanPBComplete ⇒
  (s = PLAN_PB) ⇒
  ∀ M Oi Os.
    CFGInterpret (M, Oi, Os)
      (CFG inputOK secContext secAuthorization
        ([Name Omni says prop (SOME (SLc (OMNI omniCommand)))];
          Name PlatoonLeader says
            prop (SOME (SLc (PL crossLD))) ]::ins) PLAN_PB
        outs) ⇒
      (M, Oi, Os) sat prop NONE

```

8 ssmConductORP Theory

Built: 11 June 2018

Parent Theories: ConductORPDef

8.1 Theorems

[conductORPNS_def]

```

⊢ (conductORPNS CONDUCT_ORP (exec x) =
  if getPlCom x = secure then SECURE else CONDUCT_ORP) ∧
  (conductORPNS SECURE (exec x) =
    if getPsgCom x = actionsIn then ACTIONS_IN else SECURE) ∧
  (conductORPNS ACTIONS_IN (exec x) =
    if getPlCom x = withdraw then WITHDRAW else ACTIONS_IN) ∧
  (conductORPNS WITHDRAW (exec x) =
    if getPlCom x = complete then COMPLETE else WITHDRAW) ∧
  (conductORPNS s (trap x) = s) ∧
  (conductORPNS s (discard x) = s)

```

[conductORPNS_ind]

```

⊢ ∀ P.
  (∀ x. P CONDUCT_ORP (exec x)) ∧ (∀ x. P SECURE (exec x)) ∧
  (∀ x. P ACTIONS_IN (exec x)) ∧ (∀ x. P WITHDRAW (exec x)) ∧
  (∀ s x. P s (trap x)) ∧ (∀ s x. P s (discard x)) ∧

```

$$(\forall v_5. P \text{ COMPLETE } (\text{exec } v_5)) \Rightarrow \\ \forall v \ v_1. P \ v \ v_1$$

[conductORPOut_def]

$$\vdash (\text{conductORPOut CONDUCT_ORP } (\text{exec } x) = \\ \text{if getPlCom } x = \text{secure then Secure else ConductORP}) \wedge \\ (\text{conductORPOut SECURE } (\text{exec } x) = \\ \text{if getPsgCom } x = \text{actionsIn then ActionsIn else Secure}) \wedge \\ (\text{conductORPOut ACTIONS_IN } (\text{exec } x) = \\ \text{if getPlCom } x = \text{withdraw then Withdraw else ActionsIn}) \wedge \\ (\text{conductORPOut WITHDRAW } (\text{exec } x) = \\ \text{if getPlCom } x = \text{complete then Complete else Withdraw}) \wedge \\ (\text{conductORPOut } s \ (\text{trap } x) = \text{unAuthorized}) \wedge \\ (\text{conductORPOut } s \ (\text{discard } x) = \text{unAuthenticated})$$

[conductORPOut_ind]

$$\vdash \forall P. \\ (\forall x. P \text{ CONDUCT_ORP } (\text{exec } x)) \wedge (\forall x. P \text{ SECURE } (\text{exec } x)) \wedge \\ (\forall x. P \text{ ACTIONS_IN } (\text{exec } x)) \wedge (\forall x. P \text{ WITHDRAW } (\text{exec } x)) \wedge \\ (\forall s \ x. P \ s \ (\text{trap } x)) \wedge (\forall s \ x. P \ s \ (\text{discard } x)) \wedge \\ (\forall v_5. P \text{ COMPLETE } (\text{exec } v_5)) \Rightarrow \\ \forall v \ v_1. P \ v \ v_1$$

[inputOK_cmd_reject_lemma]

$$\vdash \forall \text{cmd}. \neg \text{inputOK } (\text{prop } (\text{SOME } \text{cmd}))$$

[inputOK_def]

$$\vdash (\text{inputOK } (\text{Name PlatoonLeader says prop cmd}) \iff T) \wedge \\ (\text{inputOK } (\text{Name PlatoonSergeant says prop cmd}) \iff T) \wedge \\ (\text{inputOK } (\text{Name Omni says prop cmd}) \iff T) \wedge \\ (\text{inputOK TT} \iff F) \wedge (\text{inputOK FF} \iff F) \wedge \\ (\text{inputOK } (\text{prop } v) \iff F) \wedge (\text{inputOK } (\text{notf } v_1) \iff F) \wedge \\ (\text{inputOK } (v_2 \text{ andf } v_3) \iff F) \wedge (\text{inputOK } (v_4 \text{ orf } v_5) \iff F) \wedge \\ (\text{inputOK } (v_6 \text{ impf } v_7) \iff F) \wedge (\text{inputOK } (v_8 \text{ eqf } v_9) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says TT}) \iff F) \wedge (\text{inputOK } (v_{10} \text{ says FF}) \iff F) \wedge \\ (\text{inputOK } (v_{133} \text{ meet } v_{134} \text{ says prop } v_{66}) \iff F) \wedge \\ (\text{inputOK } (v_{135} \text{ quoting } v_{136} \text{ says prop } v_{66}) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says notf } v_{67}) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says } (v_{68} \text{ andf } v_{69})) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says } (v_{70} \text{ orf } v_{71})) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says } (v_{72} \text{ impf } v_{73})) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says } (v_{74} \text{ eqf } v_{75})) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says } v_{76} \text{ says } v_{77}) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79}) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says } v_{80} \text{ controls } v_{81}) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says reps } v_{82} \ v_{83} \ v_{84}) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says } v_{85} \text{ domi } v_{86}) \iff F) \wedge \\ (\text{inputOK } (v_{10} \text{ says } v_{87} \text{ eqi } v_{88}) \iff F) \wedge$$

$(\text{inputOK } (v_{10} \text{ says } v_{89} \text{ doms } v_{90}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{91} \text{ eqs } v_{92}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{93} \text{ eqn } v_{94}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{95} \text{ lte } v_{96}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{97} \text{ lt } v_{98}) \iff F) \wedge$
 $(\text{inputOK } (v_{12} \text{ speaks_for } v_{13}) \iff F) \wedge$
 $(\text{inputOK } (v_{14} \text{ controls } v_{15}) \iff F) \wedge$
 $(\text{inputOK } (\text{reps } v_{16} \ v_{17} \ v_{18}) \iff F) \wedge$
 $(\text{inputOK } (v_{19} \text{ domi } v_{20}) \iff F) \wedge$
 $(\text{inputOK } (v_{21} \text{ eqi } v_{22}) \iff F) \wedge$
 $(\text{inputOK } (v_{23} \text{ doms } v_{24}) \iff F) \wedge$
 $(\text{inputOK } (v_{25} \text{ eqs } v_{26}) \iff F) \wedge (\text{inputOK } (v_{27} \text{ eqn } v_{28}) \iff F) \wedge$
 $(\text{inputOK } (v_{29} \text{ lte } v_{30}) \iff F) \wedge (\text{inputOK } (v_{31} \text{ lt } v_{32}) \iff F)$

[inputOK_ind]

$\vdash \forall P.$

$(\forall \text{cmd}. P (\text{Name PlatoonLeader says prop cmd})) \wedge$
 $(\forall \text{cmd}. P (\text{Name PlatoonSergeant says prop cmd})) \wedge$
 $(\forall \text{cmd}. P (\text{Name Omni says prop cmd})) \wedge P \text{ TT} \wedge P \text{ FF} \wedge$
 $(\forall v. P (\text{prop } v)) \wedge (\forall v_1. P (\text{notf } v_1)) \wedge$
 $(\forall v_2 \ v_3. P (v_2 \text{ andf } v_3)) \wedge (\forall v_4 \ v_5. P (v_4 \text{ orf } v_5)) \wedge$
 $(\forall v_6 \ v_7. P (v_6 \text{ impf } v_7)) \wedge (\forall v_8 \ v_9. P (v_8 \text{ eqf } v_9)) \wedge$
 $(\forall v_{10}. P (v_{10} \text{ says TT})) \wedge (\forall v_{10}. P (v_{10} \text{ says FF})) \wedge$
 $(\forall v_{133} \ v_{134} \ v_{66}. P (v_{133} \text{ meet } v_{134} \text{ says prop } v_{66})) \wedge$
 $(\forall v_{135} \ v_{136} \ v_{66}. P (v_{135} \text{ quoting } v_{136} \text{ says prop } v_{66})) \wedge$
 $(\forall v_{10} \ v_{67}. P (v_{10} \text{ says notf } v_{67})) \wedge$
 $(\forall v_{10} \ v_{68} \ v_{69}. P (v_{10} \text{ says } (v_{68} \text{ andf } v_{69}))) \wedge$
 $(\forall v_{10} \ v_{70} \ v_{71}. P (v_{10} \text{ says } (v_{70} \text{ orf } v_{71}))) \wedge$
 $(\forall v_{10} \ v_{72} \ v_{73}. P (v_{10} \text{ says } (v_{72} \text{ impf } v_{73}))) \wedge$
 $(\forall v_{10} \ v_{74} \ v_{75}. P (v_{10} \text{ says } (v_{74} \text{ eqf } v_{75}))) \wedge$
 $(\forall v_{10} \ v_{76} \ v_{77}. P (v_{10} \text{ says } v_{76} \text{ says } v_{77})) \wedge$
 $(\forall v_{10} \ v_{78} \ v_{79}. P (v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79})) \wedge$
 $(\forall v_{10} \ v_{80} \ v_{81}. P (v_{10} \text{ says } v_{80} \text{ controls } v_{81})) \wedge$
 $(\forall v_{10} \ v_{82} \ v_{83} \ v_{84}. P (v_{10} \text{ says reps } v_{82} \ v_{83} \ v_{84})) \wedge$
 $(\forall v_{10} \ v_{85} \ v_{86}. P (v_{10} \text{ says } v_{85} \text{ domi } v_{86})) \wedge$
 $(\forall v_{10} \ v_{87} \ v_{88}. P (v_{10} \text{ says } v_{87} \text{ eqi } v_{88})) \wedge$
 $(\forall v_{10} \ v_{89} \ v_{90}. P (v_{10} \text{ says } v_{89} \text{ doms } v_{90})) \wedge$
 $(\forall v_{10} \ v_{91} \ v_{92}. P (v_{10} \text{ says } v_{91} \text{ eqs } v_{92})) \wedge$
 $(\forall v_{10} \ v_{93} \ v_{94}. P (v_{10} \text{ says } v_{93} \text{ eqn } v_{94})) \wedge$
 $(\forall v_{10} \ v_{95} \ v_{96}. P (v_{10} \text{ says } v_{95} \text{ lte } v_{96})) \wedge$
 $(\forall v_{10} \ v_{97} \ v_{98}. P (v_{10} \text{ says } v_{97} \text{ lt } v_{98})) \wedge$
 $(\forall v_{12} \ v_{13}. P (v_{12} \text{ speaks_for } v_{13})) \wedge$
 $(\forall v_{14} \ v_{15}. P (v_{14} \text{ controls } v_{15})) \wedge$
 $(\forall v_{16} \ v_{17} \ v_{18}. P (\text{reps } v_{16} \ v_{17} \ v_{18})) \wedge$
 $(\forall v_{19} \ v_{20}. P (v_{19} \text{ domi } v_{20})) \wedge$
 $(\forall v_{21} \ v_{22}. P (v_{21} \text{ eqi } v_{22})) \wedge$
 $(\forall v_{23} \ v_{24}. P (v_{23} \text{ doms } v_{24})) \wedge$
 $(\forall v_{25} \ v_{26}. P (v_{25} \text{ eqs } v_{26})) \wedge (\forall v_{27} \ v_{28}. P (v_{27} \text{ eqn } v_{28})) \wedge$
 $(\forall v_{29} \ v_{30}. P (v_{29} \text{ lte } v_{30})) \wedge (\forall v_{31} \ v_{32}. P (v_{31} \text{ lt } v_{32})) \Rightarrow$

$$\forall v. P \ v$$

[PlatoonLeader_ACTIONS_IN_exec_justified_lemma]

$$\vdash \forall NS \ Out \ M \ Oi \ Os.$$

$$TR \ (M, Oi, Os)$$

$$(exec$$

$$(\text{inputList}$$

$$[\text{Name Omni says}$$

$$\text{prop} \ (\text{SOME} \ (\text{SLc} \ (\text{OMNI ssmActionsInComplete})));$$

$$\text{Name PlatoonLeader says}$$

$$\text{prop} \ (\text{SOME} \ (\text{SLc} \ (\text{PL withdraw}))))]$$

$$(\text{CFG inputOK secContext secAuthorization}$$

$$([\text{Name Omni says}$$

$$\text{prop} \ (\text{SOME} \ (\text{SLc} \ (\text{OMNI ssmActionsInComplete})));$$

$$\text{Name PlatoonLeader says}$$

$$\text{prop} \ (\text{SOME} \ (\text{SLc} \ (\text{PL withdraw}))))]::ins) \ \text{ACTIONS_IN}$$

$$outs)$$

$$(\text{CFG inputOK secContext secAuthorization ins}$$

$$(NS \ \text{ACTIONS_IN}$$

$$(exec$$

$$(\text{inputList}$$

$$[\text{Name Omni says}$$

$$\text{prop}$$

$$(\text{SOME} \ (\text{SLc} \ (\text{OMNI ssmActionsInComplete})));$$

$$\text{Name PlatoonLeader says}$$

$$\text{prop} \ (\text{SOME} \ (\text{SLc} \ (\text{PL withdraw}))))]$$

$$(\text{Out ACTIONS_IN}$$

$$(exec$$

$$(\text{inputList}$$

$$[\text{Name Omni says}$$

$$\text{prop}$$

$$(\text{SOME} \ (\text{SLc} \ (\text{OMNI ssmActionsInComplete})));$$

$$\text{Name PlatoonLeader says}$$

$$\text{prop} \ (\text{SOME} \ (\text{SLc} \ (\text{PL withdraw}))))]::$$

$$outs)) \iff$$

$$\text{authenticationTest inputOK}$$

$$[\text{Name Omni says}$$

$$\text{prop} \ (\text{SOME} \ (\text{SLc} \ (\text{OMNI ssmActionsInComplete})));$$

$$\text{Name PlatoonLeader says}$$

$$\text{prop} \ (\text{SOME} \ (\text{SLc} \ (\text{PL withdraw}))))] \wedge$$

$$\text{CFGInterpret} \ (M, Oi, Os)$$

$$(\text{CFG inputOK secContext secAuthorization}$$

$$([\text{Name Omni says}$$

$$\text{prop} \ (\text{SOME} \ (\text{SLc} \ (\text{OMNI ssmActionsInComplete})));$$

$$\text{Name PlatoonLeader says}$$

$$\text{prop} \ (\text{SOME} \ (\text{SLc} \ (\text{PL withdraw}))))]::ins) \ \text{ACTIONS_IN}$$

$$outs) \wedge$$

$$(M, Oi, Os) \ \text{satList}$$

$$\text{propCommandList}$$

```

[Name Omni says
 prop (SOME (SLc (OMNI ssmActionsInComplete)));
 Name PlatoonLeader says prop (SOME (SLc (PL withdraw)))]

[PlatoonLeader_ACTIONS_IN_exec_justified_thm]
⊢ ∀ NS Out M Oi Os.
  TR (M, Oi, Os)
    (exec
      [SOME (SLc (OMNI ssmActionsInComplete));
       SOME (SLc (PL withdraw))])
    (CFG inputOK secContext secAuthorization
      ([Name Omni says
        prop (SOME (SLc (OMNI ssmActionsInComplete)));
        Name PlatoonLeader says
        prop (SOME (SLc (PL withdraw)))]::ins) ACTIONS_IN
      outs)
    (CFG inputOK secContext secAuthorization ins
      (NS ACTIONS_IN
        (exec
          [SOME (SLc (OMNI ssmActionsInComplete));
           SOME (SLc (PL withdraw))]))
      (Out ACTIONS_IN
        (exec
          [SOME (SLc (OMNI ssmActionsInComplete));
           SOME (SLc (PL withdraw))]]::outs)) ⇔
    authenticationTest inputOK
      [Name Omni says
        prop (SOME (SLc (OMNI ssmActionsInComplete)));
        Name PlatoonLeader says
        prop (SOME (SLc (PL withdraw)))] ∧
    CFGInterpret (M, Oi, Os)
      (CFG inputOK secContext secAuthorization
        ([Name Omni says
          prop (SOME (SLc (OMNI ssmActionsInComplete)));
          Name PlatoonLeader says
          prop (SOME (SLc (PL withdraw)))]::ins) ACTIONS_IN
        outs) ∧
      (M, Oi, Os) satList
      [prop (SOME (SLc (OMNI ssmActionsInComplete)));
       prop (SOME (SLc (PL withdraw)))]

```

[PlatoonLeader_ACTIONS_IN_exec_lemma]

```

⊢ ∀ M Oi Os.
  CFGInterpret (M, Oi, Os)
    (CFG inputOK secContext secAuthorization
      ([Name Omni says
        prop (SOME (SLc (OMNI ssmActionsInComplete)));
        Name PlatoonLeader says
        prop (SOME (SLc (PL withdraw)))]::ins) ACTIONS_IN

```

```

      outs)  $\Rightarrow$ 
      (M, Oi, Os) satList
      propCommandList
      [Name Omni says
       prop (SOME (SLc (OMNI ssmActionsInComplete)))];
       Name PlatoonLeader says prop (SOME (SLc (PL withdraw)))]
[PlatoonLeader_ACTIONS_IN_trap_justified_lemma]
 $\vdash$  omniCommand  $\neq$  ssmActionsInComplete  $\Rightarrow$ 
  (s = ACTIONS_IN)  $\Rightarrow$ 
 $\forall$  NS Out M Oi Os.
  TR (M, Oi, Os)
    (trap
      (inputList
        [Name Omni says
         prop (SOME (SLc (OMNI omniCommand)))];
         Name PlatoonLeader says
         prop (SOME (SLc (PL withdraw))))))
      (CFG inputOK secContext secAuthorization
        ([Name Omni says prop (SOME (SLc (OMNI omniCommand)))];
         Name PlatoonLeader says
         prop (SOME (SLc (PL withdraw)))]::ins) ACTIONS_IN
        outs)
      (CFG inputOK secContext secAuthorization ins
        (NS ACTIONS_IN
          (trap
            (inputList
              [Name Omni says
               prop (SOME (SLc (OMNI omniCommand)))];
               Name PlatoonLeader says
               prop (SOME (SLc (PL withdraw))))))
            (Out ACTIONS_IN
              (trap
                (inputList
                  [Name Omni says
                   prop (SOME (SLc (OMNI omniCommand)))];
                   Name PlatoonLeader says
                   prop (SOME (SLc (PL withdraw)))]::
                    outs))  $\iff$ 
authenticationTest inputOK
  [Name Omni says prop (SOME (SLc (OMNI omniCommand)))];
  Name PlatoonLeader says
  prop (SOME (SLc (PL withdraw)))]  $\wedge$ 
CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secAuthorization
    ([Name Omni says prop (SOME (SLc (OMNI omniCommand)))];
     Name PlatoonLeader says
     prop (SOME (SLc (PL withdraw)))]::ins) ACTIONS_IN
    outs)  $\wedge$  (M, Oi, Os) sat prop NONE

```


[PlatoonLeader_ACTIONS_IN_trap_justified_thm]

$\vdash \text{omniCommand} \neq \text{ssmActionsInComplete} \Rightarrow$
 $(s = \text{ACTIONS_IN}) \Rightarrow$
 $\forall NS \text{ Out } M \text{ } Oi \text{ } Os.$
 $\text{TR } (M, Oi, Os)$
 $(\text{trap}$
 $\quad [\text{SOME } (\text{SLc } (\text{OMNI } \text{omniCommand}))];$
 $\quad \text{SOME } (\text{SLc } (\text{PL } \text{withdraw}))])$
 $(\text{CFG inputOK secContext secAuthorization}$
 $\quad ([\text{Name Omni says prop } (\text{SOME } (\text{SLc } (\text{OMNI } \text{omniCommand}))]);$
 $\quad \text{Name PlatoonLeader says}$
 $\quad \text{prop } (\text{SOME } (\text{SLc } (\text{PL } \text{withdraw})))]::ins) \text{ ACTIONS_IN}$
 $\text{outs})$
 $(\text{CFG inputOK secContext secAuthorization ins}$
 $\quad (NS \text{ ACTIONS_IN}$
 $\quad (\text{trap}$
 $\quad \quad [\text{SOME } (\text{SLc } (\text{OMNI } \text{omniCommand}))];$
 $\quad \quad \text{SOME } (\text{SLc } (\text{PL } \text{withdraw}))])$
 $\quad (\text{Out ACTIONS_IN}$
 $\quad (\text{trap}$
 $\quad \quad [\text{SOME } (\text{SLc } (\text{OMNI } \text{omniCommand}))];$
 $\quad \quad \text{SOME } (\text{SLc } (\text{PL } \text{withdraw}))]::outs)) \iff$
 $\text{authenticationTest inputOK}$
 $[\text{Name Omni says prop } (\text{SOME } (\text{SLc } (\text{OMNI } \text{omniCommand}))]);$
 $\text{Name PlatoonLeader says}$
 $\text{prop } (\text{SOME } (\text{SLc } (\text{PL } \text{withdraw}))) \wedge$
 $\text{CFGInterpret } (M, Oi, Os)$
 $(\text{CFG inputOK secContext secAuthorization}$
 $\quad ([\text{Name Omni says prop } (\text{SOME } (\text{SLc } (\text{OMNI } \text{omniCommand}))]);$
 $\quad \text{Name PlatoonLeader says}$
 $\quad \text{prop } (\text{SOME } (\text{SLc } (\text{PL } \text{withdraw})))]::ins) \text{ ACTIONS_IN}$
 $\text{outs}) \wedge (M, Oi, Os) \text{ sat prop NONE}$

[PlatoonLeader_ACTIONS_IN_trap_lemma]

$\vdash \text{omniCommand} \neq \text{ssmActionsInComplete} \Rightarrow$
 $(s = \text{ACTIONS_IN}) \Rightarrow$
 $\forall M \text{ } Oi \text{ } Os.$
 $\text{CFGInterpret } (M, Oi, Os)$
 $(\text{CFG inputOK secContext secAuthorization}$
 $\quad ([\text{Name Omni says prop } (\text{SOME } (\text{SLc } (\text{OMNI } \text{omniCommand}))]);$
 $\quad \text{Name PlatoonLeader says}$
 $\quad \text{prop } (\text{SOME } (\text{SLc } (\text{PL } \text{withdraw})))]::ins) \text{ ACTIONS_IN}$
 $\text{outs}) \Rightarrow$
 $(M, Oi, Os) \text{ sat prop NONE}$

[PlatoonLeader_CONDUCT_ORP_exec_secure_justified_thm]

$\vdash \forall NS \text{ Out } M \text{ } Oi \text{ } Os.$
 $\text{TR } (M, Oi, Os) (\text{exec } [\text{SOME } (\text{SLc } (\text{PL } \text{secure}))])$

```

(CFG inputOK secContext secAuthorization
  ([Name PlatoonLeader says
    prop (SOME (SLc (PL secure))))]::ins) CONDUCT_ORP
  outs)
(CFG inputOK secContext secAuthorization ins
  (NS CONDUCT_ORP (exec [SOME (SLc (PL secure))]))
  (Out CONDUCT_ORP (exec [SOME (SLc (PL secure))])))::
  outs))  $\iff$ 
authenticationTest inputOK
  [Name PlatoonLeader says prop (SOME (SLc (PL secure)))]  $\wedge$ 
CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secAuthorization
    ([Name PlatoonLeader says
      prop (SOME (SLc (PL secure))))]::ins) CONDUCT_ORP
    outs)  $\wedge$ 
  (M, Oi, Os) satList [prop (SOME (SLc (PL secure)))]

```

[PlatoonLeader_CONDUCT_ORP_exec_secure_lemma]

```

 $\vdash \forall M \ Oi \ Os.$ 
  CFGInterpret (M, Oi, Os)
    (CFG inputOK secContext secAuthorization
      ([Name PlatoonLeader says
        prop (SOME (SLc (PL secure))))]::ins) CONDUCT_ORP
      outs)  $\Rightarrow$ 
  (M, Oi, Os) satList
  propCommandList
  [Name PlatoonLeader says prop (SOME (SLc (PL secure)))]

```

[PlatoonSergeant_SECURE_exec_justified_lemma]

```

 $\vdash \forall NS \ Out \ M \ Oi \ Os.$ 
  TR (M, Oi, Os)
    (exec
      (inputList
        [Name Omni says
          prop (SOME (SLc (OMNI ssmSecureComplete)));
          Name PlatoonSergeant says
          prop (SOME (SLc (PSG actionsIn)))]))
    (CFG inputOK secContext secAuthorization
      ([Name Omni says
        prop (SOME (SLc (OMNI ssmSecureComplete)));
          Name PlatoonSergeant says
          prop (SOME (SLc (PSG actionsIn)))]]::ins) SECURE
      outs)
    (CFG inputOK secContext secAuthorization ins
      (NS SECURE
        (exec
          (inputList
            [Name Omni says
              prop (SOME (SLc (OMNI ssmSecureComplete)))]

```

```

      Name PlatoonSergeant says
      prop (SOME (SLc (PSG actionsIn))))))
(Out SECURE
  (exec
    (inputList
      [Name Omni says
        prop (SOME (SLc (OMNI ssmSecureComplete)))];
      Name PlatoonSergeant says
        prop (SOME (SLc (PSG actionsIn)))))::
      outs))  $\iff$ 
authenticationTest inputOK
  [Name Omni says
    prop (SOME (SLc (OMNI ssmSecureComplete)))];
  Name PlatoonSergeant says
    prop (SOME (SLc (PSG actionsIn)))]  $\wedge$ 
CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secAuthorization
    ([Name Omni says
      prop (SOME (SLc (OMNI ssmSecureComplete)))];
      Name PlatoonSergeant says
        prop (SOME (SLc (PSG actionsIn)))]::ins) SECURE
    outs)  $\wedge$ 
(M, Oi, Os) satList
propCommandList
  [Name Omni says
    prop (SOME (SLc (OMNI ssmSecureComplete)))];
  Name PlatoonSergeant says
    prop (SOME (SLc (PSG actionsIn)))]

```

[PlatoonSergeant_SECURE_exec_justified_thm]

```

 $\vdash \forall NS \text{ Out } M \text{ Oi } Os.$ 
TR (M, Oi, Os)
  (exec
    [SOME (SLc (OMNI ssmSecureComplete));
     SOME (SLc (PSG actionsIn))])
  (CFG inputOK secContext secAuthorization
    ([Name Omni says
      prop (SOME (SLc (OMNI ssmSecureComplete)))];
      Name PlatoonSergeant says
        prop (SOME (SLc (PSG actionsIn)))]::ins) SECURE
    outs)
  (CFG inputOK secContext secAuthorization ins
    (NS SECURE
      (exec
        [SOME (SLc (OMNI ssmSecureComplete));
         SOME (SLc (PSG actionsIn))])
      (Out SECURE
        (exec
          [SOME (SLc (OMNI ssmSecureComplete));
           SOME (SLc (PSG actionsIn))])

```

```

        SOME (SLc (PSG actionsIn))]]::outs))  $\iff$ 
authenticationTest inputOK
  [Name Omni says
    prop (SOME (SLc (OMNI ssmSecureComplete)))];
    Name PlatoonSergeant says
    prop (SOME (SLc (PSG actionsIn)))]  $\wedge$ 
CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secAuthorization
    ([Name Omni says
      prop (SOME (SLc (OMNI ssmSecureComplete)))];
      Name PlatoonSergeant says
      prop (SOME (SLc (PSG actionsIn)))]::ins) SECURE
    outs)  $\wedge$ 
(M, Oi, Os) satList
[prop (SOME (SLc (OMNI ssmSecureComplete)))];
 prop (SOME (SLc (PSG actionsIn)))]

[PlatoonSergeant_SECURE_exec_lemma]

 $\vdash \forall M \text{ } Oi \text{ } Os.$ 
  CFGInterpret (M, Oi, Os)
    (CFG inputOK secContext secAuthorization
      ([Name Omni says
        prop (SOME (SLc (OMNI ssmSecureComplete)))];
        Name PlatoonSergeant says
        prop (SOME (SLc (PSG actionsIn)))]::ins) SECURE
      outs)  $\Rightarrow$ 
(M, Oi, Os) satList
propCommandList
  [Name Omni says
    prop (SOME (SLc (OMNI ssmSecureComplete)))];
    Name PlatoonSergeant says
    prop (SOME (SLc (PSG actionsIn)))]

```

9 ConductORPType Theory

Built: 11 June 2018

Parent Theories: indexedLists, patternMatches

9.1 Datatypes

```

omniCommand = ssmSecureComplete | ssmActionsInComplete
              | ssmWithdrawComplete | invalidOmniCommand

```

```

plCommand = secure | withdraw | complete | plIncomplete

```

```

psgCommand = actionsIn | psgIncomplete

```

```

slCommand =
  PL ConductORPType$plCommand
| PSG ConductORPType$psgCommand
| OMNI omniCommand

slOutput = ConductORP | Secure | ActionsIn | Withdraw | Complete
          | unAuthenticated | unAuthorized

slState = CONDUCT_ORP | SECURE | ACTIONS_IN | WITHDRAW
          | COMPLETE

stateRole = PlatoonLeader | PlatoonSergeant | Omni

```

9.2 Theorems

[omniCommand_distinct_clauses]

```

⊢ ssmSecureComplete ≠ ssmActionsInComplete ∧
  ssmSecureComplete ≠ ssmWithdrawComplete ∧
  ssmSecureComplete ≠ invalidOmniCommand ∧
  ssmActionsInComplete ≠ ssmWithdrawComplete ∧
  ssmActionsInComplete ≠ invalidOmniCommand ∧
  ssmWithdrawComplete ≠ invalidOmniCommand

```

[plCommand_distinct_clauses]

```

⊢ secure ≠ withdraw ∧ secure ≠ complete ∧
  secure ≠ plIncomplete ∧ withdraw ≠ complete ∧
  withdraw ≠ plIncomplete ∧ complete ≠ plIncomplete

```

[psgCommand_distinct_clauses]

```

⊢ actionsIn ≠ psgIncomplete

```

[slCommand_distinct_clauses]

```

⊢ (∀ a' a. PL a ≠ PSG a') ∧ (∀ a' a. PL a ≠ OMNI a') ∧
  ∀ a' a. PSG a ≠ OMNI a'

```

[slCommand_one_one]

```

⊢ (∀ a a'. (PL a = PL a') ⇔ (a = a')) ∧
  (∀ a a'. (PSG a = PSG a') ⇔ (a = a')) ∧
  ∀ a a'. (OMNI a = OMNI a') ⇔ (a = a')

```

[slOutput_distinct_clauses]

```

⊢ ConductORP ≠ Secure ∧ ConductORP ≠ ActionsIn ∧
  ConductORP ≠ Withdraw ∧ ConductORP ≠ Complete ∧
  ConductORP ≠ unAuthenticated ∧ ConductORP ≠ unAuthorized ∧
  Secure ≠ ActionsIn ∧ Secure ≠ Withdraw ∧ Secure ≠ Complete ∧
  Secure ≠ unAuthenticated ∧ Secure ≠ unAuthorized ∧
  ActionsIn ≠ Withdraw ∧ ActionsIn ≠ Complete ∧
  ActionsIn ≠ unAuthenticated ∧ ActionsIn ≠ unAuthorized ∧
  Withdraw ≠ Complete ∧ Withdraw ≠ unAuthenticated ∧
  Withdraw ≠ unAuthorized ∧ Complete ≠ unAuthenticated ∧
  Complete ≠ unAuthorized ∧ unAuthenticated ≠ unAuthorized

```

[slRole_distinct_clauses]

⊢ PlatoonLeader ≠ PlatoonSergeant ∧ PlatoonLeader ≠ Omni ∧
PlatoonSergeant ≠ Omni

[slState_distinct_clauses]

⊢ CONDUCT_ORP ≠ SECURE ∧ CONDUCT_ORP ≠ ACTIONS_IN ∧
CONDUCT_ORP ≠ WITHDRAW ∧ CONDUCT_ORP ≠ COMPLETE ∧
SECURE ≠ ACTIONS_IN ∧ SECURE ≠ WITHDRAW ∧ SECURE ≠ COMPLETE ∧
ACTIONS_IN ≠ WITHDRAW ∧ ACTIONS_IN ≠ COMPLETE ∧
WITHDRAW ≠ COMPLETE

10 ConductORPDef Theory

Built: 11 June 2018

Parent Theories: ConductORPType, ssm, OMNIType

10.1 Definitions

[secAuthorization_def]

⊢ $\forall xs. \text{secAuthorization } xs = \text{secHelper } (\text{getOmniCommand } xs)$

[secContext_def]

⊢ ($\forall xs.$
 secContext CONDUCT_ORP $xs =$
 [Name PlatoonLeader controls
 prop (SOME (SLc (PL secure))))] ∧
($\forall xs.$
 secContext SECURE $xs =$
 if getOmniCommand $xs = \text{ssmSecureComplete}$ **then**
 [prop (SOME (SLc (OMNI ssmSecureComplete))) impf
 Name PlatoonSergeant controls
 prop (SOME (SLc (PSG actionsIn)))]
 else [prop NONE]) ∧
($\forall xs.$
 secContext ACTIONS_IN $xs =$
 if getOmniCommand $xs = \text{ssmActionsInComplete}$ **then**
 [prop (SOME (SLc (OMNI ssmActionsInComplete))) impf
 Name PlatoonLeader controls
 prop (SOME (SLc (PL withdraw)))]
 else [prop NONE]) ∧
 $\forall xs.$
 secContext WITHDRAW $xs =$
 if getOmniCommand $xs = \text{ssmWithdrawComplete}$ **then**
 [prop (SOME (SLc (OMNI ssmWithdrawComplete))) impf
 Name PlatoonLeader controls
 prop (SOME (SLc (PL complete)))]
 else [prop NONE]

[secHelper_def]

$\vdash \forall cmd.$
 $\text{secHelper } cmd =$
 $[\text{Name Omni controls prop (SOME (SLc (OMNI } cmd)))]$

10.2 Theorems

[getOmniCommand_def]

$\vdash (\text{getOmniCommand } [] = \text{invalidOmniCommand}) \wedge$
 $(\forall xs \text{ cmd.}$
 getOmniCommand
 $(\text{Name Omni says prop (SOME (SLc (OMNI } cmd)))::xs) =$
 $cmd) \wedge$
 $(\forall xs. \text{getOmniCommand (TT::xs)} = \text{getOmniCommand } xs) \wedge$
 $(\forall xs. \text{getOmniCommand (FF::xs)} = \text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_2. \text{getOmniCommand (prop } v_2::xs) = \text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_3. \text{getOmniCommand (notf } v_3::xs) = \text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_5 \ v_4.$
 $\text{getOmniCommand (} v_4 \text{ andf } v_5::xs) = \text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_7 \ v_6.$
 $\text{getOmniCommand (} v_6 \text{ orf } v_7::xs) = \text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_9 \ v_8.$
 $\text{getOmniCommand (} v_8 \text{ impf } v_9::xs) = \text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_{11} \ v_{10}.$
 $\text{getOmniCommand (} v_{10} \text{ eqf } v_{11}::xs) = \text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_{12}.$
 $\text{getOmniCommand (} v_{12} \text{ says TT::xs) = getOmniCommand } xs) \wedge$
 $(\forall xs \ v_{12}.$
 $\text{getOmniCommand (} v_{12} \text{ says FF::xs) = getOmniCommand } xs) \wedge$
 $(\forall xs \ v_{134}.$
 $\text{getOmniCommand (Name } v_{134} \text{ says prop NONE::xs) =}$
 $\text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_{144}.$
 getOmniCommand
 $(\text{Name PlatoonLeader says prop (SOME } v_{144})::xs) =$
 $\text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_{144}.$
 getOmniCommand
 $(\text{Name PlatoonSergeant says prop (SOME } v_{144})::xs) =$
 $\text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_{146}.$
 getOmniCommand
 $(\text{Name Omni says prop (SOME (ESCc } v_{146}))::xs) =$
 $\text{getOmniCommand } xs) \wedge$
 $(\forall xs \ v_{150}.$
 getOmniCommand
 $(\text{Name Omni says prop (SOME (SLc (PL } v_{150}))::xs) =$
 $\text{getOmniCommand } xs) \wedge$

```

(∀ xs v151.
  getOmniCommand
    (Name Omni says prop (SOME (SLc (PSG v151))))::xs) =
  getOmniCommand xs) ∧
(∀ xs v68 v136 v135.
  getOmniCommand (v135 meet v136 says prop v68::xs) =
  getOmniCommand xs) ∧
(∀ xs v68 v138 v137.
  getOmniCommand (v137 quoting v138 says prop v68::xs) =
  getOmniCommand xs) ∧
(∀ xs v69 v12.
  getOmniCommand (v12 says notf v69::xs) =
  getOmniCommand xs) ∧
(∀ xs v71 v70 v12.
  getOmniCommand (v12 says (v70 andf v71)::xs) =
  getOmniCommand xs) ∧
(∀ xs v73 v72 v12.
  getOmniCommand (v12 says (v72 orf v73)::xs) =
  getOmniCommand xs) ∧
(∀ xs v75 v74 v12.
  getOmniCommand (v12 says (v74 impf v75)::xs) =
  getOmniCommand xs) ∧
(∀ xs v77 v76 v12.
  getOmniCommand (v12 says (v76 eqf v77)::xs) =
  getOmniCommand xs) ∧
(∀ xs v79 v78 v12.
  getOmniCommand (v12 says v78 says v79::xs) =
  getOmniCommand xs) ∧
(∀ xs v81 v80 v12.
  getOmniCommand (v12 says v80 speaks_for v81::xs) =
  getOmniCommand xs) ∧
(∀ xs v83 v82 v12.
  getOmniCommand (v12 says v82 controls v83::xs) =
  getOmniCommand xs) ∧
(∀ xs v86 v85 v84 v12.
  getOmniCommand (v12 says reps v84 v85 v86::xs) =
  getOmniCommand xs) ∧
(∀ xs v88 v87 v12.
  getOmniCommand (v12 says v87 domi v88::xs) =
  getOmniCommand xs) ∧
(∀ xs v90 v89 v12.
  getOmniCommand (v12 says v89 eqi v90::xs) =
  getOmniCommand xs) ∧
(∀ xs v92 v91 v12.
  getOmniCommand (v12 says v91 doms v92::xs) =
  getOmniCommand xs) ∧
(∀ xs v94 v93 v12.
  getOmniCommand (v12 says v93 eqs v94::xs) =
  getOmniCommand xs) ∧

```



```

(∀ xs v96 v95 v12.
  getOmniCommand (v12 says v95 eqn v96::xs) =
  getOmniCommand xs) ∧
(∀ xs v98 v97 v12.
  getOmniCommand (v12 says v97 lte v98::xs) =
  getOmniCommand xs) ∧
(∀ xs v99 v12 v100.
  getOmniCommand (v12 says v99 lt v100::xs) =
  getOmniCommand xs) ∧
(∀ xs v15 v14.
  getOmniCommand (v14 speaks_for v15::xs) =
  getOmniCommand xs) ∧
(∀ xs v17 v16.
  getOmniCommand (v16 controls v17::xs) =
  getOmniCommand xs) ∧
(∀ xs v20 v19 v18.
  getOmniCommand (reps v18 v19 v20::xs) =
  getOmniCommand xs) ∧
(∀ xs v22 v21.
  getOmniCommand (v21 domi v22::xs) = getOmniCommand xs) ∧
(∀ xs v24 v23.
  getOmniCommand (v23 eqi v24::xs) = getOmniCommand xs) ∧
(∀ xs v26 v25.
  getOmniCommand (v25 doms v26::xs) = getOmniCommand xs) ∧
(∀ xs v28 v27.
  getOmniCommand (v27 eqs v28::xs) = getOmniCommand xs) ∧
(∀ xs v30 v29.
  getOmniCommand (v29 eqn v30::xs) = getOmniCommand xs) ∧
(∀ xs v32 v31.
  getOmniCommand (v31 lte v32::xs) = getOmniCommand xs) ∧
∀ xs v34 v33.
  getOmniCommand (v33 lt v34::xs) = getOmniCommand xs

```

[getOmniCommand_ind]

```

⊢ ∀ P.
  P [] ∧
  (∀ cmd xs.
    P (Name Omni says prop (SOME (SLc (OMNI cmd))))::xs)) ∧
  (∀ xs. P xs ⇒ P (TT::xs)) ∧ (∀ xs. P xs ⇒ P (FF::xs)) ∧
  (∀ v2 xs. P xs ⇒ P (prop v2::xs)) ∧
  (∀ v3 xs. P xs ⇒ P (notf v3::xs)) ∧
  (∀ v4 v5 xs. P xs ⇒ P (v4 andf v5::xs)) ∧
  (∀ v6 v7 xs. P xs ⇒ P (v6 orf v7::xs)) ∧
  (∀ v8 v9 xs. P xs ⇒ P (v8 impf v9::xs)) ∧
  (∀ v10 v11 xs. P xs ⇒ P (v10 eqf v11::xs)) ∧
  (∀ v12 xs. P xs ⇒ P (v12 says TT::xs)) ∧
  (∀ v12 xs. P xs ⇒ P (v12 says FF::xs)) ∧
  (∀ v134 xs. P xs ⇒ P (Name v134 says prop NONE::xs)) ∧
  (∀ v144 xs.

```

$$\begin{aligned}
& P \text{ } xs \Rightarrow \\
& P (\text{Name PlatoonLeader says prop (SOME } v144)::xs)) \wedge \\
& (\forall v144 \text{ } xs. \\
& \quad P \text{ } xs \Rightarrow \\
& \quad P (\text{Name PlatoonSergeant says prop (SOME } v144)::xs)) \wedge \\
& (\forall v146 \text{ } xs. \\
& \quad P \text{ } xs \Rightarrow P (\text{Name Omni says prop (SOME (ESCC } v146)::xs)) \wedge \\
& (\forall v150 \text{ } xs. \\
& \quad P \text{ } xs \Rightarrow \\
& \quad P (\text{Name Omni says prop (SOME (SLc (PL } v150)))::xs)) \wedge \\
& (\forall v151 \text{ } xs. \\
& \quad P \text{ } xs \Rightarrow \\
& \quad P (\text{Name Omni says prop (SOME (SLc (PSG } v151)))::xs)) \wedge \\
& (\forall v135 \text{ } v136 \text{ } v68 \text{ } xs. \\
& \quad P \text{ } xs \Rightarrow P (v135 \text{ meet } v136 \text{ says prop } v68::xs)) \wedge \\
& (\forall v137 \text{ } v138 \text{ } v68 \text{ } xs. \\
& \quad P \text{ } xs \Rightarrow P (v137 \text{ quoting } v138 \text{ says prop } v68::xs)) \wedge \\
& (\forall v12 \text{ } v69 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says notf } v69::xs)) \wedge \\
& (\forall v12 \text{ } v70 \text{ } v71 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says (} v70 \text{ andf } v71)::xs)) \wedge \\
& (\forall v12 \text{ } v72 \text{ } v73 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says (} v72 \text{ orf } v73)::xs)) \wedge \\
& (\forall v12 \text{ } v74 \text{ } v75 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says (} v74 \text{ impf } v75)::xs)) \wedge \\
& (\forall v12 \text{ } v76 \text{ } v77 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says (} v76 \text{ eqf } v77)::xs)) \wedge \\
& (\forall v12 \text{ } v78 \text{ } v79 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says } v78 \text{ says } v79::xs)) \wedge \\
& (\forall v12 \text{ } v80 \text{ } v81 \text{ } xs. \\
& \quad P \text{ } xs \Rightarrow P (v12 \text{ says } v80 \text{ speaks_for } v81::xs)) \wedge \\
& (\forall v12 \text{ } v82 \text{ } v83 \text{ } xs. \\
& \quad P \text{ } xs \Rightarrow P (v12 \text{ says } v82 \text{ controls } v83::xs)) \wedge \\
& (\forall v12 \text{ } v84 \text{ } v85 \text{ } v86 \text{ } xs. \\
& \quad P \text{ } xs \Rightarrow P (v12 \text{ says reps } v84 \text{ } v85 \text{ } v86::xs)) \wedge \\
& (\forall v12 \text{ } v87 \text{ } v88 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says } v87 \text{ domi } v88::xs)) \wedge \\
& (\forall v12 \text{ } v89 \text{ } v90 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says } v89 \text{ eqi } v90::xs)) \wedge \\
& (\forall v12 \text{ } v91 \text{ } v92 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says } v91 \text{ doms } v92::xs)) \wedge \\
& (\forall v12 \text{ } v93 \text{ } v94 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says } v93 \text{ eqs } v94::xs)) \wedge \\
& (\forall v12 \text{ } v95 \text{ } v96 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says } v95 \text{ eqn } v96::xs)) \wedge \\
& (\forall v12 \text{ } v97 \text{ } v98 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says } v97 \text{ lte } v98::xs)) \wedge \\
& (\forall v12 \text{ } v99 \text{ } v100 \text{ } xs. P \text{ } xs \Rightarrow P (v12 \text{ says } v99 \text{ lt } v100::xs)) \wedge \\
& (\forall v14 \text{ } v15 \text{ } xs. P \text{ } xs \Rightarrow P (v14 \text{ speaks_for } v15::xs)) \wedge \\
& (\forall v16 \text{ } v17 \text{ } xs. P \text{ } xs \Rightarrow P (v16 \text{ controls } v17::xs)) \wedge \\
& (\forall v18 \text{ } v19 \text{ } v20 \text{ } xs. P \text{ } xs \Rightarrow P (\text{reps } v18 \text{ } v19 \text{ } v20::xs)) \wedge \\
& (\forall v21 \text{ } v22 \text{ } xs. P \text{ } xs \Rightarrow P (v21 \text{ domi } v22::xs)) \wedge \\
& (\forall v23 \text{ } v24 \text{ } xs. P \text{ } xs \Rightarrow P (v23 \text{ eqi } v24::xs)) \wedge \\
& (\forall v25 \text{ } v26 \text{ } xs. P \text{ } xs \Rightarrow P (v25 \text{ doms } v26::xs)) \wedge \\
& (\forall v27 \text{ } v28 \text{ } xs. P \text{ } xs \Rightarrow P (v27 \text{ eqs } v28::xs)) \wedge \\
& (\forall v29 \text{ } v30 \text{ } xs. P \text{ } xs \Rightarrow P (v29 \text{ eqn } v30::xs)) \wedge \\
& (\forall v31 \text{ } v32 \text{ } xs. P \text{ } xs \Rightarrow P (v31 \text{ lte } v32::xs)) \wedge \\
& (\forall v33 \text{ } v34 \text{ } xs. P \text{ } xs \Rightarrow P (v33 \text{ lt } v34::xs)) \Rightarrow \\
& \forall v. P \text{ } v
\end{aligned}$$

[getPlCom_def]

$$\begin{aligned} &\vdash (\text{getPlCom } [] = \text{plIncomplete}) \wedge \\ &(\forall xs \text{ cmd}. \text{getPlCom } (\text{SOME } (\text{SLc } (\text{PL } \text{cmd})))::xs) = \text{cmd}) \wedge \\ &(\forall xs. \text{getPlCom } (\text{NONE}::xs) = \text{getPlCom } xs) \wedge \\ &(\forall xs \ v_4. \text{getPlCom } (\text{SOME } (\text{ESCc } v_4)::xs) = \text{getPlCom } xs) \wedge \\ &(\forall xs \ v_9. \text{getPlCom } (\text{SOME } (\text{SLc } (\text{PSG } v_9)))::xs) = \text{getPlCom } xs) \wedge \\ &\forall xs \ v_{10}. \text{getPlCom } (\text{SOME } (\text{SLc } (\text{OMNI } v_{10})))::xs) = \text{getPlCom } xs \end{aligned}$$

[getPlCom_ind]

$$\begin{aligned} &\vdash \forall P. \\ &P [] \wedge (\forall \text{cmd } xs. P (\text{SOME } (\text{SLc } (\text{PL } \text{cmd})))::xs) \wedge \\ &(\forall xs. P \ xs \Rightarrow P (\text{NONE}::xs)) \wedge \\ &(\forall v_4 \ xs. P \ xs \Rightarrow P (\text{SOME } (\text{ESCc } v_4)::xs)) \wedge \\ &(\forall v_9 \ xs. P \ xs \Rightarrow P (\text{SOME } (\text{SLc } (\text{PSG } v_9)))::xs) \wedge \\ &(\forall v_{10} \ xs. P \ xs \Rightarrow P (\text{SOME } (\text{SLc } (\text{OMNI } v_{10})))::xs) \Rightarrow \\ &\forall v. P \ v \end{aligned}$$

[getPsgCom_def]

$$\begin{aligned} &\vdash (\text{getPsgCom } [] = \text{psgIncomplete}) \wedge \\ &(\forall xs \text{ cmd}. \text{getPsgCom } (\text{SOME } (\text{SLc } (\text{PSG } \text{cmd})))::xs) = \text{cmd}) \wedge \\ &(\forall xs. \text{getPsgCom } (\text{NONE}::xs) = \text{getPsgCom } xs) \wedge \\ &(\forall xs \ v_4. \text{getPsgCom } (\text{SOME } (\text{ESCc } v_4)::xs) = \text{getPsgCom } xs) \wedge \\ &(\forall xs \ v_8. \text{getPsgCom } (\text{SOME } (\text{SLc } (\text{PL } v_8)))::xs) = \text{getPsgCom } xs) \wedge \\ &\forall xs \ v_{10}. \text{getPsgCom } (\text{SOME } (\text{SLc } (\text{OMNI } v_{10})))::xs) = \text{getPsgCom } xs \end{aligned}$$

[getPsgCom_ind]

$$\begin{aligned} &\vdash \forall P. \\ &P [] \wedge (\forall \text{cmd } xs. P (\text{SOME } (\text{SLc } (\text{PSG } \text{cmd})))::xs) \wedge \\ &(\forall xs. P \ xs \Rightarrow P (\text{NONE}::xs)) \wedge \\ &(\forall v_4 \ xs. P \ xs \Rightarrow P (\text{SOME } (\text{ESCc } v_4)::xs)) \wedge \\ &(\forall v_8 \ xs. P \ xs \Rightarrow P (\text{SOME } (\text{SLc } (\text{PL } v_8)))::xs) \wedge \\ &(\forall v_{10} \ xs. P \ xs \Rightarrow P (\text{SOME } (\text{SLc } (\text{OMNI } v_{10})))::xs) \Rightarrow \\ &\forall v. P \ v \end{aligned}$$

11 ssmConductPB Theory

Built: 10 June 2018

Parent Theories: ConductPBType, ssm11, OMNIType

11.1 Definitions

[secContextConductPB_def]

$$\begin{aligned} &\vdash \forall \text{plcmd } \text{psgcmd } \text{incomplete}. \\ &\text{secContextConductPB } \text{plcmd } \text{psgcmd } \text{incomplete} = \\ &[\text{Name PlatoonLeader controls prop } (\text{SOME } (\text{SLc } (\text{PL } \text{plcmd})))]; \\ &\text{Name PlatoonSergeant controls} \\ &\text{prop } (\text{SOME } (\text{SLc } (\text{PSG } \text{psgcmd}))); \\ &\text{Name PlatoonLeader says} \end{aligned}$$

```

prop (SOME (SLc (PSG psgcmd))) impf prop NONE;
Name PlatoonSergeant says
prop (SOME (SLc (PL plcnd))) impf prop NONE]

```

[ssmConductPBStateInterp_def]

$\vdash \forall slState. \text{ssmConductPBStateInterp } slState = \text{TT}$

11.2 Theorems

[authTestConductPB_cmd_reject_lemma]

$\vdash \forall cmd. \neg \text{authTestConductPB (prop (SOME cmd))}$

[authTestConductPB_def]

$\vdash (\text{authTestConductPB (Name PlatoonLeader says prop cmd)} \iff T) \wedge$
 $(\text{authTestConductPB (Name PlatoonSergeant says prop cmd)} \iff$
 $T) \wedge (\text{authTestConductPB TT} \iff F) \wedge$
 $(\text{authTestConductPB FF} \iff F) \wedge$
 $(\text{authTestConductPB (prop } v) \iff F) \wedge$
 $(\text{authTestConductPB (notf } v_1) \iff F) \wedge$
 $(\text{authTestConductPB (} v_2 \text{ andf } v_3) \iff F) \wedge$
 $(\text{authTestConductPB (} v_4 \text{ orf } v_5) \iff F) \wedge$
 $(\text{authTestConductPB (} v_6 \text{ impf } v_7) \iff F) \wedge$
 $(\text{authTestConductPB (} v_8 \text{ eqf } v_9) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says TT)} \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says FF)} \iff F) \wedge$
 $(\text{authTestConductPB (} v_{133} \text{ meet } v_{134} \text{ says prop } v_{66}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{135} \text{ quoting } v_{136} \text{ says prop } v_{66}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says notf } v_{67}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says (} v_{68} \text{ andf } v_{69}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says (} v_{70} \text{ orf } v_{71}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says (} v_{72} \text{ impf } v_{73}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says (} v_{74} \text{ eqf } v_{75}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says } v_{76} \text{ says } v_{77}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says } v_{80} \text{ controls } v_{81}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says reps } v_{82} \text{ } v_{83} \text{ } v_{84}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says } v_{85} \text{ domi } v_{86}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says } v_{87} \text{ eqi } v_{88}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says } v_{89} \text{ doms } v_{90}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says } v_{91} \text{ eqs } v_{92}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says } v_{93} \text{ eqn } v_{94}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says } v_{95} \text{ lte } v_{96}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{10} \text{ says } v_{97} \text{ lt } v_{98}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{12} \text{ speaks_for } v_{13}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{14} \text{ controls } v_{15}) \iff F) \wedge$
 $(\text{authTestConductPB (reps } v_{16} \text{ } v_{17} \text{ } v_{18}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{19} \text{ domi } v_{20}) \iff F) \wedge$
 $(\text{authTestConductPB (} v_{21} \text{ eqi } v_{22}) \iff F) \wedge$

$$\begin{aligned}
& (\text{authTestConductPB } (v_{23} \text{ doms } v_{24}) \iff F) \wedge \\
& (\text{authTestConductPB } (v_{25} \text{ eqs } v_{26}) \iff F) \wedge \\
& (\text{authTestConductPB } (v_{27} \text{ eqn } v_{28}) \iff F) \wedge \\
& (\text{authTestConductPB } (v_{29} \text{ lte } v_{30}) \iff F) \wedge \\
& (\text{authTestConductPB } (v_{31} \text{ lt } v_{32}) \iff F)
\end{aligned}$$

[authTestConductPB_ind]

$$\begin{aligned}
& \vdash \forall P. \\
& (\forall \text{cmd}. P (\text{Name PlatoonLeader says prop cmd})) \wedge \\
& (\forall \text{cmd}. P (\text{Name PlatoonSergeant says prop cmd})) \wedge P \text{ TT} \wedge \\
& P \text{ FF} \wedge (\forall v. P (\text{prop } v)) \wedge (\forall v_1. P (\text{notf } v_1)) \wedge \\
& (\forall v_2 v_3. P (v_2 \text{ andf } v_3)) \wedge (\forall v_4 v_5. P (v_4 \text{ orf } v_5)) \wedge \\
& (\forall v_6 v_7. P (v_6 \text{ impf } v_7)) \wedge (\forall v_8 v_9. P (v_8 \text{ eqf } v_9)) \wedge \\
& (\forall v_{10}. P (v_{10} \text{ says TT})) \wedge (\forall v_{10}. P (v_{10} \text{ says FF})) \wedge \\
& (\forall v_{133} v_{134} v_{66}. P (v_{133} \text{ meet } v_{134} \text{ says prop } v_{66})) \wedge \\
& (\forall v_{135} v_{136} v_{66}. P (v_{135} \text{ quoting } v_{136} \text{ says prop } v_{66})) \wedge \\
& (\forall v_{10} v_{67}. P (v_{10} \text{ says notf } v_{67})) \wedge \\
& (\forall v_{10} v_{68} v_{69}. P (v_{10} \text{ says } (v_{68} \text{ andf } v_{69}))) \wedge \\
& (\forall v_{10} v_{70} v_{71}. P (v_{10} \text{ says } (v_{70} \text{ orf } v_{71}))) \wedge \\
& (\forall v_{10} v_{72} v_{73}. P (v_{10} \text{ says } (v_{72} \text{ impf } v_{73}))) \wedge \\
& (\forall v_{10} v_{74} v_{75}. P (v_{10} \text{ says } (v_{74} \text{ eqf } v_{75}))) \wedge \\
& (\forall v_{10} v_{76} v_{77}. P (v_{10} \text{ says } v_{76} \text{ says } v_{77})) \wedge \\
& (\forall v_{10} v_{78} v_{79}. P (v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79})) \wedge \\
& (\forall v_{10} v_{80} v_{81}. P (v_{10} \text{ says } v_{80} \text{ controls } v_{81})) \wedge \\
& (\forall v_{10} v_{82} v_{83} v_{84}. P (v_{10} \text{ says reps } v_{82} v_{83} v_{84})) \wedge \\
& (\forall v_{10} v_{85} v_{86}. P (v_{10} \text{ says } v_{85} \text{ domi } v_{86})) \wedge \\
& (\forall v_{10} v_{87} v_{88}. P (v_{10} \text{ says } v_{87} \text{ eqi } v_{88})) \wedge \\
& (\forall v_{10} v_{89} v_{90}. P (v_{10} \text{ says } v_{89} \text{ doms } v_{90})) \wedge \\
& (\forall v_{10} v_{91} v_{92}. P (v_{10} \text{ says } v_{91} \text{ eqs } v_{92})) \wedge \\
& (\forall v_{10} v_{93} v_{94}. P (v_{10} \text{ says } v_{93} \text{ eqn } v_{94})) \wedge \\
& (\forall v_{10} v_{95} v_{96}. P (v_{10} \text{ says } v_{95} \text{ lte } v_{96})) \wedge \\
& (\forall v_{10} v_{97} v_{98}. P (v_{10} \text{ says } v_{97} \text{ lt } v_{98})) \wedge \\
& (\forall v_{12} v_{13}. P (v_{12} \text{ speaks_for } v_{13})) \wedge \\
& (\forall v_{14} v_{15}. P (v_{14} \text{ controls } v_{15})) \wedge \\
& (\forall v_{16} v_{17} v_{18}. P (\text{reps } v_{16} v_{17} v_{18})) \wedge \\
& (\forall v_{19} v_{20}. P (v_{19} \text{ domi } v_{20})) \wedge \\
& (\forall v_{21} v_{22}. P (v_{21} \text{ eqi } v_{22})) \wedge \\
& (\forall v_{23} v_{24}. P (v_{23} \text{ doms } v_{24})) \wedge \\
& (\forall v_{25} v_{26}. P (v_{25} \text{ eqs } v_{26})) \wedge (\forall v_{27} v_{28}. P (v_{27} \text{ eqn } v_{28})) \wedge \\
& (\forall v_{29} v_{30}. P (v_{29} \text{ lte } v_{30})) \wedge (\forall v_{31} v_{32}. P (v_{31} \text{ lt } v_{32})) \Rightarrow \\
& \forall v. P v
\end{aligned}$$

[conductPBNS_def]

$$\begin{aligned}
& \vdash (\text{conductPBNS CONDUCT_PB (exec (PL securePB))} = \text{SECURE_PB}) \wedge \\
& (\text{conductPBNS CONDUCT_PB (exec (PL plIncompletePB))} = \\
& \text{CONDUCT_PB}) \wedge \\
& (\text{conductPBNS SECURE_PB (exec (PSG actionsInPB))} = \\
& \text{ACTIONS_IN_PB}) \wedge \\
& (\text{conductPBNS SECURE_PB (exec (PSG psgIncompletePB))} =
\end{aligned}$$

SECURE_PB) \wedge
 (conductPBNS ACTIONS_IN_PB (exec (PL withdrawPB)) =
 WITHDRAW_PB) \wedge
 (conductPBNS ACTIONS_IN_PB (exec (PL plIncompletePB)) =
 ACTIONS_IN_PB) \wedge
 (conductPBNS WITHDRAW_PB (exec (PL completePB)) =
 COMPLETE_PB) \wedge
 (conductPBNS WITHDRAW_PB (exec (PL plIncompletePB)) =
 WITHDRAW_PB) \wedge (conductPBNS s (trap (PL cmd')) = s) \wedge
 (conductPBNS s (trap (PSG cmd)) = s) \wedge
 (conductPBNS s (discard (PL cmd')) = s) \wedge
 (conductPBNS s (discard (PSG cmd)) = s)

[conductPBNS_ind]

$\vdash \forall P.$
 P CONDUCT_PB (exec (PL securePB)) \wedge
 P CONDUCT_PB (exec (PL plIncompletePB)) \wedge
 P SECURE_PB (exec (PSG actionsInPB)) \wedge
 P SECURE_PB (exec (PSG psgIncompletePB)) \wedge
 P ACTIONS_IN_PB (exec (PL withdrawPB)) \wedge
 P ACTIONS_IN_PB (exec (PL plIncompletePB)) \wedge
 P WITHDRAW_PB (exec (PL completePB)) \wedge
 P WITHDRAW_PB (exec (PL plIncompletePB)) \wedge
 ($\forall s \text{ } cmd. P \text{ } s \text{ } (trap \text{ } (PL \text{ } cmd))) \wedge$
 ($\forall s \text{ } cmd. P \text{ } s \text{ } (trap \text{ } (PSG \text{ } cmd))) \wedge$
 ($\forall s \text{ } cmd. P \text{ } s \text{ } (discard \text{ } (PL \text{ } cmd))) \wedge$
 ($\forall s \text{ } cmd. P \text{ } s \text{ } (discard \text{ } (PSG \text{ } cmd))) \wedge$
 P CONDUCT_PB (exec (PL withdrawPB)) \wedge
 P CONDUCT_PB (exec (PL completePB)) \wedge
 ($\forall v_{11}. P$ CONDUCT_PB (exec (PSG v_{11}))) \wedge
 ($\forall v_{13}. P$ SECURE_PB (exec (PL v_{13}))) \wedge
 P ACTIONS_IN_PB (exec (PL securePB)) \wedge
 P ACTIONS_IN_PB (exec (PL completePB)) \wedge
 ($\forall v_{17}. P$ ACTIONS_IN_PB (exec (PSG v_{17}))) \wedge
 P WITHDRAW_PB (exec (PL securePB)) \wedge
 P WITHDRAW_PB (exec (PL withdrawPB)) \wedge
 ($\forall v_{20}. P$ WITHDRAW_PB (exec (PSG v_{20}))) \wedge
 ($\forall v_{21}. P$ COMPLETE_PB (exec v_{21})) \Rightarrow
 $\forall v \text{ } v_1. P \text{ } v \text{ } v_1$

[conductPBOut_def]

\vdash (conductPBOut CONDUCT_PB (exec (PL securePB)) = ConductPB) \wedge
 (conductPBOut CONDUCT_PB (exec (PL plIncompletePB)) =
 ConductPB) \wedge
 (conductPBOut SECURE_PB (exec (PSG actionsInPB)) =
 SecurePB) \wedge
 (conductPBOut SECURE_PB (exec (PSG psgIncompletePB)) =
 SecurePB) \wedge
 (conductPBOut ACTIONS_IN_PB (exec (PL withdrawPB)) =

ActionsInPB) \wedge
 (conductPBOut ACTIONS_IN_PB (exec (PL plIncompletePB)) =
 ActionsInPB) \wedge
 (conductPBOut WITHDRAW_PB (exec (PL completePB)) =
 WithdrawPB) \wedge
 (conductPBOut WITHDRAW_PB (exec (PL plIncompletePB)) =
 WithdrawPB) \wedge
 (conductPBOut s (trap (PL cmd')) = unauthorized) \wedge
 (conductPBOut s (trap (PSG cmd)) = unauthorized) \wedge
 (conductPBOut s (discard (PL cmd')) = unAuthenticated) \wedge
 (conductPBOut s (discard (PSG cmd)) = unAuthenticated)

[conductPBOut_ind]

$\vdash \forall P.$
 P CONDUCT_PB (exec (PL securePB)) \wedge
 P CONDUCT_PB (exec (PL plIncompletePB)) \wedge
 P SECURE_PB (exec (PSG actionsInPB)) \wedge
 P SECURE_PB (exec (PSG psgIncompletePB)) \wedge
 P ACTIONS_IN_PB (exec (PL withdrawPB)) \wedge
 P ACTIONS_IN_PB (exec (PL plIncompletePB)) \wedge
 P WITHDRAW_PB (exec (PL completePB)) \wedge
 P WITHDRAW_PB (exec (PL plIncompletePB)) \wedge
 $(\forall s \text{ cmd}. P \ s \ (\text{trap} \ (\text{PL} \ \text{cmd}))) \wedge$
 $(\forall s \text{ cmd}. P \ s \ (\text{trap} \ (\text{PSG} \ \text{cmd}))) \wedge$
 $(\forall s \text{ cmd}. P \ s \ (\text{discard} \ (\text{PL} \ \text{cmd}))) \wedge$
 $(\forall s \text{ cmd}. P \ s \ (\text{discard} \ (\text{PSG} \ \text{cmd}))) \wedge$
 P CONDUCT_PB (exec (PL withdrawPB)) \wedge
 P CONDUCT_PB (exec (PL completePB)) \wedge
 $(\forall v_{11}. P \ \text{CONDUCT_PB} \ (\text{exec} \ (\text{PSG} \ v_{11}))) \wedge$
 $(\forall v_{13}. P \ \text{SECURE_PB} \ (\text{exec} \ (\text{PL} \ v_{13}))) \wedge$
 P ACTIONS_IN_PB (exec (PL securePB)) \wedge
 P ACTIONS_IN_PB (exec (PL completePB)) \wedge
 $(\forall v_{17}. P \ \text{ACTIONS_IN_PB} \ (\text{exec} \ (\text{PSG} \ v_{17}))) \wedge$
 P WITHDRAW_PB (exec (PL securePB)) \wedge
 P WITHDRAW_PB (exec (PL withdrawPB)) \wedge
 $(\forall v_{20}. P \ \text{WITHDRAW_PB} \ (\text{exec} \ (\text{PSG} \ v_{20}))) \wedge$
 $(\forall v_{21}. P \ \text{COMPLETE_PB} \ (\text{exec} \ v_{21})) \Rightarrow$
 $\forall v \ v_1. P \ v \ v_1$

[PlatoonLeader_exec_plCommandPB_justified_thm]

$\vdash \forall NS \ \text{Out} \ M \ O_i \ O_s.$
 TR (M, O_i, O_s) (exec (SLc (PL plCommand)))
 (CFG authTestConductPB ssmConductPBStateInterp
 (secContextConductPB plCommand psgCommand incomplete)
 (Name PlatoonLeader says
 prop (SOME (SLc (PL plCommand)))::ins) s outs)
 (CFG authTestConductPB ssmConductPBStateInterp
 (secContextConductPB plCommand psgCommand incomplete)
 ins ($NS \ s$ (exec (SLc (PL plCommand)))))

$$\begin{aligned}
& (Out\ s\ (exec\ (SLc\ (PL\ plCommand))))::outs)) \iff \\
& authTestConductPB \\
& \quad (Name\ PlatoonLeader\ says \\
& \quad \quad prop\ (SOME\ (SLc\ (PL\ plCommand)))) \wedge \\
& CFGInterpret\ (M, Oi, Os) \\
& \quad (CFG\ authTestConductPB\ ssmConductPBStateInterp \\
& \quad \quad (secContextConductPB\ plCommand\ psgCommand\ incomplete) \\
& \quad \quad (Name\ PlatoonLeader\ says \\
& \quad \quad \quad prop\ (SOME\ (SLc\ (PL\ plCommand))))::ins)\ s\ outs) \wedge \\
& (M, Oi, Os)\ sat\ prop\ (SOME\ (SLc\ (PL\ plCommand)))
\end{aligned}$$

[PlatoonLeader_plCommandPB_lemma]

$$\begin{aligned}
& \vdash CFGInterpret\ (M, Oi, Os) \\
& \quad (CFG\ authTestConductPB\ ssmConductPBStateInterp \\
& \quad \quad (secContextConductPB\ plCommand\ psgCommand\ incomplete) \\
& \quad \quad (Name\ PlatoonLeader\ says \\
& \quad \quad \quad prop\ (SOME\ (SLc\ (PL\ plCommand))))::ins)\ s\ outs) \Rightarrow \\
& (M, Oi, Os)\ sat\ prop\ (SOME\ (SLc\ (PL\ plCommand)))
\end{aligned}$$

[PlatoonSergeant_exec_psgCommandPB_justified_thm]

$$\begin{aligned}
& \vdash \forall NS\ Out\ M\ Oi\ Os. \\
& TR\ (M, Oi, Os)\ (exec\ (SLc\ (PSG\ psgCommand))) \\
& \quad (CFG\ authTestConductPB\ ssmConductPBStateInterp \\
& \quad \quad (secContextConductPB\ plCommand\ psgCommand\ incomplete) \\
& \quad \quad (Name\ PlatoonSergeant\ says \\
& \quad \quad \quad prop\ (SOME\ (SLc\ (PSG\ psgCommand))))::ins)\ s\ outs) \\
& \quad (CFG\ authTestConductPB\ ssmConductPBStateInterp \\
& \quad \quad (secContextConductPB\ plCommand\ psgCommand\ incomplete) \\
& \quad \quad \quad ins\ (NS\ s\ (exec\ (SLc\ (PSG\ psgCommand)))) \\
& \quad \quad \quad (Out\ s\ (exec\ (SLc\ (PSG\ psgCommand))))::outs)) \iff \\
& authTestConductPB \\
& \quad (Name\ PlatoonSergeant\ says \\
& \quad \quad prop\ (SOME\ (SLc\ (PSG\ psgCommand)))) \wedge \\
& CFGInterpret\ (M, Oi, Os) \\
& \quad (CFG\ authTestConductPB\ ssmConductPBStateInterp \\
& \quad \quad (secContextConductPB\ plCommand\ psgCommand\ incomplete) \\
& \quad \quad (Name\ PlatoonSergeant\ says \\
& \quad \quad \quad prop\ (SOME\ (SLc\ (PSG\ psgCommand))))::ins)\ s\ outs) \wedge \\
& (M, Oi, Os)\ sat\ prop\ (SOME\ (SLc\ (PSG\ psgCommand)))
\end{aligned}$$

[PlatoonSergeant_psgCommandPB_lemma]

$$\begin{aligned}
& \vdash CFGInterpret\ (M, Oi, Os) \\
& \quad (CFG\ authTestConductPB\ ssmConductPBStateInterp \\
& \quad \quad (secContextConductPB\ plCommand\ psgCommand\ incomplete) \\
& \quad \quad (Name\ PlatoonSergeant\ says \\
& \quad \quad \quad prop\ (SOME\ (SLc\ (PSG\ psgCommand))))::ins)\ s\ outs) \Rightarrow \\
& (M, Oi, Os)\ sat\ prop\ (SOME\ (SLc\ (PSG\ psgCommand)))
\end{aligned}$$

12 ConductPBType Theory

Built: 10 June 2018

Parent Theories: indexedLists, patternMatches

12.1 Datatypes

```
plCommandPB = securePB | withdrawPB | completePB
              | plIncompletePB

psgCommandPB = actionsInPB | psgIncompletePB

slCommand = PL plCommandPB | PSG psgCommandPB

slOutput = ConductPB | SecurePB | ActionsInPB | WithdrawPB
           | CompletePB | unAuthenticated | unAuthorized

slState = CONDUCT_PB | SECURE_PB | ACTIONS_IN_PB | WITHDRAW_PB
          | COMPLETE_PB

stateRole = PlatoonLeader | PlatoonSergeant
```

12.2 Theorems

```
[plCommandPB_distinct_clauses]
⊢ securePB ≠ withdrawPB ∧ securePB ≠ completePB ∧
  securePB ≠ plIncompletePB ∧ withdrawPB ≠ completePB ∧
  withdrawPB ≠ plIncompletePB ∧ completePB ≠ plIncompletePB

[psgCommandPB_distinct_clauses]
⊢ actionsInPB ≠ psgIncompletePB

[slCommand_distinct_clauses]
⊢ ∀ a' a. PL a ≠ PSG a'

[slCommand_one_one]
⊢ (∀ a a'. (PL a = PL a') ⇔ (a = a')) ∧
  ∀ a a'. (PSG a = PSG a') ⇔ (a = a')

[slOutput_distinct_clauses]
⊢ ConductPB ≠ SecurePB ∧ ConductPB ≠ ActionsInPB ∧
  ConductPB ≠ WithdrawPB ∧ ConductPB ≠ CompletePB ∧
  ConductPB ≠ unAuthenticated ∧ ConductPB ≠ unAuthorized ∧
  SecurePB ≠ ActionsInPB ∧ SecurePB ≠ WithdrawPB ∧
  SecurePB ≠ CompletePB ∧ SecurePB ≠ unAuthenticated ∧
  SecurePB ≠ unAuthorized ∧ ActionsInPB ≠ WithdrawPB ∧
  ActionsInPB ≠ CompletePB ∧ ActionsInPB ≠ unAuthenticated ∧
  ActionsInPB ≠ unAuthorized ∧ WithdrawPB ≠ CompletePB ∧
  WithdrawPB ≠ unAuthenticated ∧ WithdrawPB ≠ unAuthorized ∧
  CompletePB ≠ unAuthenticated ∧ CompletePB ≠ unAuthorized ∧
  unAuthenticated ≠ unAuthorized
```

[slRole_distinct_clauses]

⊢ PlatoonLeader ≠ PlatoonSergeant

[slState_distinct_clauses]

⊢ CONDUCT_PB ≠ SECURE_PB ∧ CONDUCT_PB ≠ ACTIONS_IN_PB ∧
 CONDUCT_PB ≠ WITHDRAW_PB ∧ CONDUCT_PB ≠ COMPLETE_PB ∧
 SECURE_PB ≠ ACTIONS_IN_PB ∧ SECURE_PB ≠ WITHDRAW_PB ∧
 SECURE_PB ≠ COMPLETE_PB ∧ ACTIONS_IN_PB ≠ WITHDRAW_PB ∧
 ACTIONS_IN_PB ≠ COMPLETE_PB ∧ WITHDRAW_PB ≠ COMPLETE_PB

13 ssmMoveToORP Theory

Built: 10 June 2018

Parent Theories: MoveToORPType, ssm11, OMNIType

13.1 Definitions

[secContextMoveToORP_def]

⊢ ∀ cmd.
 secContextMoveToORP cmd =
 [Name PlatoonLeader controls prop (SOME (SLc cmd))]

[ssmMoveToORPStateInterp_def]

⊢ ∀ state. ssmMoveToORPStateInterp state = TT

13.2 Theorems

[authTestMoveToORP_cmd_reject_lemma]

⊢ ∀ cmd. ¬authTestMoveToORP (prop (SOME cmd))

[authTestMoveToORP_def]

⊢ (authTestMoveToORP (Name PlatoonLeader says prop cmd) ⇔ T) ∧
 (authTestMoveToORP TT ⇔ F) ∧ (authTestMoveToORP FF ⇔ F) ∧
 (authTestMoveToORP (prop v) ⇔ F) ∧
 (authTestMoveToORP (notf v₁) ⇔ F) ∧
 (authTestMoveToORP (v₂ andf v₃) ⇔ F) ∧
 (authTestMoveToORP (v₄ orf v₅) ⇔ F) ∧
 (authTestMoveToORP (v₆ impf v₇) ⇔ F) ∧
 (authTestMoveToORP (v₈ eqf v₉) ⇔ F) ∧
 (authTestMoveToORP (v₁₀ says TT) ⇔ F) ∧
 (authTestMoveToORP (v₁₀ says FF) ⇔ F) ∧
 (authTestMoveToORP (v₁₃₃ meet v₁₃₄ says prop v₆₆) ⇔ F) ∧
 (authTestMoveToORP (v₁₃₅ quoting v₁₃₆ says prop v₆₆) ⇔ F) ∧
 (authTestMoveToORP (v₁₀ says notf v₆₇) ⇔ F) ∧
 (authTestMoveToORP (v₁₀ says (v₆₈ andf v₆₉)) ⇔ F) ∧
 (authTestMoveToORP (v₁₀ says (v₇₀ orf v₇₁)) ⇔ F) ∧

$(\text{authTestMoveToORP } (v_{10} \text{ says } (v_{72} \text{ impf } v_{73})) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } (v_{74} \text{ eqf } v_{75})) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } v_{76} \text{ says } v_{77}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } v_{80} \text{ controls } v_{81}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } \text{reps } v_{82} \ v_{83} \ v_{84}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } v_{85} \text{ domi } v_{86}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } v_{87} \text{ eqi } v_{88}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } v_{89} \text{ doms } v_{90}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } v_{91} \text{ eqs } v_{92}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } v_{93} \text{ eqn } v_{94}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } v_{95} \text{ lte } v_{96}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{10} \text{ says } v_{97} \text{ lt } v_{98}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{12} \text{ speaks_for } v_{13}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{14} \text{ controls } v_{15}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (\text{reps } v_{16} \ v_{17} \ v_{18}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{19} \text{ domi } v_{20}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{21} \text{ eqi } v_{22}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{23} \text{ doms } v_{24}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{25} \text{ eqs } v_{26}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{27} \text{ eqn } v_{28}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{29} \text{ lte } v_{30}) \iff F) \wedge$
 $(\text{authTestMoveToORP } (v_{31} \text{ lt } v_{32}) \iff F)$

[authTestMoveToORP_ind]

$\vdash \forall P.$

$(\forall \text{cmd}. P (\text{Name PlatoonLeader says prop cmd})) \wedge P \text{ TT} \wedge$
 $P \text{ FF} \wedge (\forall v. P (\text{prop } v)) \wedge (\forall v_1. P (\text{notf } v_1)) \wedge$
 $(\forall v_2 \ v_3. P (v_2 \text{ andf } v_3)) \wedge (\forall v_4 \ v_5. P (v_4 \text{ orf } v_5)) \wedge$
 $(\forall v_6 \ v_7. P (v_6 \text{ impf } v_7)) \wedge (\forall v_8 \ v_9. P (v_8 \text{ eqf } v_9)) \wedge$
 $(\forall v_{10}. P (v_{10} \text{ says TT})) \wedge (\forall v_{10}. P (v_{10} \text{ says FF})) \wedge$
 $(\forall v_{133} \ v_{134} \ v_{66}. P (v_{133} \text{ meet } v_{134} \text{ says prop } v_{66})) \wedge$
 $(\forall v_{135} \ v_{136} \ v_{66}. P (v_{135} \text{ quoting } v_{136} \text{ says prop } v_{66})) \wedge$
 $(\forall v_{10} \ v_{67}. P (v_{10} \text{ says notf } v_{67})) \wedge$
 $(\forall v_{10} \ v_{68} \ v_{69}. P (v_{10} \text{ says } (v_{68} \text{ andf } v_{69}))) \wedge$
 $(\forall v_{10} \ v_{70} \ v_{71}. P (v_{10} \text{ says } (v_{70} \text{ orf } v_{71}))) \wedge$
 $(\forall v_{10} \ v_{72} \ v_{73}. P (v_{10} \text{ says } (v_{72} \text{ impf } v_{73}))) \wedge$
 $(\forall v_{10} \ v_{74} \ v_{75}. P (v_{10} \text{ says } (v_{74} \text{ eqf } v_{75}))) \wedge$
 $(\forall v_{10} \ v_{76} \ v_{77}. P (v_{10} \text{ says } v_{76} \text{ says } v_{77})) \wedge$
 $(\forall v_{10} \ v_{78} \ v_{79}. P (v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79})) \wedge$
 $(\forall v_{10} \ v_{80} \ v_{81}. P (v_{10} \text{ says } v_{80} \text{ controls } v_{81})) \wedge$
 $(\forall v_{10} \ v_{82} \ v_{83} \ v_{84}. P (v_{10} \text{ says } \text{reps } v_{82} \ v_{83} \ v_{84})) \wedge$
 $(\forall v_{10} \ v_{85} \ v_{86}. P (v_{10} \text{ says } v_{85} \text{ domi } v_{86})) \wedge$
 $(\forall v_{10} \ v_{87} \ v_{88}. P (v_{10} \text{ says } v_{87} \text{ eqi } v_{88})) \wedge$
 $(\forall v_{10} \ v_{89} \ v_{90}. P (v_{10} \text{ says } v_{89} \text{ doms } v_{90})) \wedge$
 $(\forall v_{10} \ v_{91} \ v_{92}. P (v_{10} \text{ says } v_{91} \text{ eqs } v_{92})) \wedge$
 $(\forall v_{10} \ v_{93} \ v_{94}. P (v_{10} \text{ says } v_{93} \text{ eqn } v_{94})) \wedge$
 $(\forall v_{10} \ v_{95} \ v_{96}. P (v_{10} \text{ says } v_{95} \text{ lte } v_{96})) \wedge$
 $(\forall v_{10} \ v_{97} \ v_{98}. P (v_{10} \text{ says } v_{97} \text{ lt } v_{98})) \wedge$

$$\begin{aligned}
& (\forall v_{12} v_{13}. P (v_{12} \text{ speaks_for } v_{13})) \wedge \\
& (\forall v_{14} v_{15}. P (v_{14} \text{ controls } v_{15})) \wedge \\
& (\forall v_{16} v_{17} v_{18}. P (\text{reps } v_{16} v_{17} v_{18})) \wedge \\
& (\forall v_{19} v_{20}. P (v_{19} \text{ domi } v_{20})) \wedge \\
& (\forall v_{21} v_{22}. P (v_{21} \text{ eqi } v_{22})) \wedge \\
& (\forall v_{23} v_{24}. P (v_{23} \text{ doms } v_{24})) \wedge \\
& (\forall v_{25} v_{26}. P (v_{25} \text{ eqs } v_{26})) \wedge (\forall v_{27} v_{28}. P (v_{27} \text{ eqn } v_{28})) \wedge \\
& (\forall v_{29} v_{30}. P (v_{29} \text{ lte } v_{30})) \wedge (\forall v_{31} v_{32}. P (v_{31} \text{ lt } v_{32})) \Rightarrow \\
& \forall v. P v
\end{aligned}$$

[moveToORPNS_def]

$$\begin{aligned}
& \vdash (\text{moveToORPNS MOVE_TO_ORP (exec (SLc pltForm))} = \text{PLT_FORM}) \wedge \\
& (\text{moveToORPNS MOVE_TO_ORP (exec (SLc incomplete))} = \\
& \quad \text{MOVE_TO_ORP}) \wedge \\
& (\text{moveToORPNS PLT_FORM (exec (SLc pltMove))} = \text{PLT_MOVE}) \wedge \\
& (\text{moveToORPNS PLT_FORM (exec (SLc incomplete))} = \text{PLT_FORM}) \wedge \\
& (\text{moveToORPNS PLT_MOVE (exec (SLc pltSecureHalt))} = \\
& \quad \text{PLT_SECURE_HALT}) \wedge \\
& (\text{moveToORPNS PLT_MOVE (exec (SLc incomplete))} = \text{PLT_MOVE}) \wedge \\
& (\text{moveToORPNS PLT_SECURE_HALT (exec (SLc complete))} = \\
& \quad \text{COMPLETE}) \wedge \\
& (\text{moveToORPNS PLT_SECURE_HALT (exec (SLc incomplete))} = \\
& \quad \text{PLT_SECURE_HALT}) \wedge (\text{moveToORPNS } s \text{ (trap (SLc cmd))} = s) \wedge \\
& (\text{moveToORPNS } s \text{ (discard (SLc cmd))} = s)
\end{aligned}$$

[moveToORPNS_ind]

$$\begin{aligned}
& \vdash \forall P. \\
& \quad P \text{ MOVE_TO_ORP (exec (SLc pltForm))} \wedge \\
& \quad P \text{ MOVE_TO_ORP (exec (SLc incomplete))} \wedge \\
& \quad P \text{ PLT_FORM (exec (SLc pltMove))} \wedge \\
& \quad P \text{ PLT_FORM (exec (SLc incomplete))} \wedge \\
& \quad P \text{ PLT_MOVE (exec (SLc pltSecureHalt))} \wedge \\
& \quad P \text{ PLT_MOVE (exec (SLc incomplete))} \wedge \\
& \quad P \text{ PLT_SECURE_HALT (exec (SLc complete))} \wedge \\
& \quad P \text{ PLT_SECURE_HALT (exec (SLc incomplete))} \wedge \\
& \quad (\forall s \text{ cmd}. P s \text{ (trap (SLc cmd))}) \wedge \\
& \quad (\forall s \text{ cmd}. P s \text{ (discard (SLc cmd))}) \wedge \\
& \quad (\forall s v_6. P s \text{ (discard (ESCc } v_6 \text{))}) \wedge \\
& \quad (\forall s v_9. P s \text{ (trap (ESCc } v_9 \text{))}) \wedge \\
& \quad (\forall v_{12}. P \text{ MOVE_TO_ORP (exec (ESCc } v_{12} \text{))}) \wedge \\
& \quad P \text{ MOVE_TO_ORP (exec (SLc pltMove))} \wedge \\
& \quad P \text{ MOVE_TO_ORP (exec (SLc pltSecureHalt))} \wedge \\
& \quad P \text{ MOVE_TO_ORP (exec (SLc complete))} \wedge \\
& \quad (\forall v_{15}. P \text{ PLT_FORM (exec (ESCc } v_{15} \text{))}) \wedge \\
& \quad P \text{ PLT_FORM (exec (SLc pltForm))} \wedge \\
& \quad P \text{ PLT_FORM (exec (SLc pltSecureHalt))} \wedge \\
& \quad P \text{ PLT_FORM (exec (SLc complete))} \wedge \\
& \quad (\forall v_{18}. P \text{ PLT_MOVE (exec (ESCc } v_{18} \text{))}) \wedge \\
& \quad P \text{ PLT_MOVE (exec (SLc pltForm))} \wedge
\end{aligned}$$

$$\begin{aligned}
& P \text{ PLT_MOVE (exec (SLc pltMove)) } \wedge \\
& P \text{ PLT_MOVE (exec (SLc complete)) } \wedge \\
& (\forall v_{21}. P \text{ PLT_SECURE_HALT (exec (ESCc } v_{21}))) \wedge \\
& P \text{ PLT_SECURE_HALT (exec (SLc pltForm)) } \wedge \\
& P \text{ PLT_SECURE_HALT (exec (SLc pltMove)) } \wedge \\
& P \text{ PLT_SECURE_HALT (exec (SLc pltSecureHalt)) } \wedge \\
& (\forall v_{23}. P \text{ COMPLETE (exec } v_{23})) \Rightarrow \\
& \forall v \ v_1. P \ v \ v_1
\end{aligned}$$

[moveToORPOut_def]

$$\begin{aligned}
& \vdash (\text{moveToORPOut MOVE_TO_ORP (exec (SLc pltForm))} = \text{PLTForm}) \wedge \\
& (\text{moveToORPOut MOVE_TO_ORP (exec (SLc incomplete))} = \\
& \quad \text{MoveToORP}) \wedge \\
& (\text{moveToORPOut PLT_FORM (exec (SLc pltMove))} = \text{PLTMove}) \wedge \\
& (\text{moveToORPOut PLT_FORM (exec (SLc incomplete))} = \text{PLTForm}) \wedge \\
& (\text{moveToORPOut PLT_MOVE (exec (SLc pltSecureHalt))} = \\
& \quad \text{PLTSecureHalt}) \wedge \\
& (\text{moveToORPOut PLT_MOVE (exec (SLc incomplete))} = \text{PLTMove}) \wedge \\
& (\text{moveToORPOut PLT_SECURE_HALT (exec (SLc complete))} = \\
& \quad \text{Complete}) \wedge \\
& (\text{moveToORPOut PLT_SECURE_HALT (exec (SLc incomplete))} = \\
& \quad \text{PLTSecureHalt}) \wedge \\
& (\text{moveToORPOut } s \text{ (trap (SLc cmd))} = \text{unAuthorized}) \wedge \\
& (\text{moveToORPOut } s \text{ (discard (SLc cmd))} = \text{unAuthenticated})
\end{aligned}$$

[moveToORPOut_ind]

$$\begin{aligned}
& \vdash \forall P. \\
& P \text{ MOVE_TO_ORP (exec (SLc pltForm)) } \wedge \\
& P \text{ MOVE_TO_ORP (exec (SLc incomplete)) } \wedge \\
& P \text{ PLT_FORM (exec (SLc pltMove)) } \wedge \\
& P \text{ PLT_FORM (exec (SLc incomplete)) } \wedge \\
& P \text{ PLT_MOVE (exec (SLc pltSecureHalt)) } \wedge \\
& P \text{ PLT_MOVE (exec (SLc incomplete)) } \wedge \\
& P \text{ PLT_SECURE_HALT (exec (SLc complete)) } \wedge \\
& P \text{ PLT_SECURE_HALT (exec (SLc incomplete)) } \wedge \\
& (\forall s \text{ cmd. } P \ s \text{ (trap (SLc cmd))}) \wedge \\
& (\forall s \text{ cmd. } P \ s \text{ (discard (SLc cmd))}) \wedge \\
& (\forall s \ v_6. P \ s \text{ (discard (ESCc } v_6))) \wedge \\
& (\forall s \ v_9. P \ s \text{ (trap (ESCc } v_9))) \wedge \\
& (\forall v_{12}. P \text{ MOVE_TO_ORP (exec (ESCc } v_{12}))) \wedge \\
& P \text{ MOVE_TO_ORP (exec (SLc pltMove)) } \wedge \\
& P \text{ MOVE_TO_ORP (exec (SLc pltSecureHalt)) } \wedge \\
& P \text{ MOVE_TO_ORP (exec (SLc complete)) } \wedge \\
& (\forall v_{15}. P \text{ PLT_FORM (exec (ESCc } v_{15}))) \wedge \\
& P \text{ PLT_FORM (exec (SLc pltForm)) } \wedge \\
& P \text{ PLT_FORM (exec (SLc pltSecureHalt)) } \wedge \\
& P \text{ PLT_FORM (exec (SLc complete)) } \wedge \\
& (\forall v_{18}. P \text{ PLT_MOVE (exec (ESCc } v_{18}))) \wedge \\
& P \text{ PLT_MOVE (exec (SLc pltForm)) } \wedge
\end{aligned}$$

$$\begin{aligned}
 & P \text{ PLT_MOVE } (\text{exec } (\text{SLc pltMove})) \wedge \\
 & P \text{ PLT_MOVE } (\text{exec } (\text{SLc complete})) \wedge \\
 & (\forall v_{21}. P \text{ PLT_SECURE_HALT } (\text{exec } (\text{ESCc } v_{21}))) \wedge \\
 & P \text{ PLT_SECURE_HALT } (\text{exec } (\text{SLc pltForm})) \wedge \\
 & P \text{ PLT_SECURE_HALT } (\text{exec } (\text{SLc pltMove})) \wedge \\
 & P \text{ PLT_SECURE_HALT } (\text{exec } (\text{SLc pltSecureHalt})) \wedge \\
 & (\forall v_{23}. P \text{ COMPLETE } (\text{exec } v_{23})) \Rightarrow \\
 & \forall v \ v_1. P \ v \ v_1
 \end{aligned}$$

[PlatoonLeader_exec_slCommand_justified_thm]

$$\begin{aligned}
 & \vdash \forall NS \text{ Out } M \text{ } Oi \text{ } Os. \\
 & \quad \text{TR } (M, Oi, Os) (\text{exec } (\text{SLc slCommand})) \\
 & \quad (\text{CFG authTestMoveToORP ssmMoveToORPStateInterp} \\
 & \quad \quad (\text{secContextMoveToORP slCommand}) \\
 & \quad \quad (\text{Name PlatoonLeader says prop (SOME (SLc slCommand))} :: \\
 & \quad \quad \quad \text{ins) s outs}) \\
 & \quad (\text{CFG authTestMoveToORP ssmMoveToORPStateInterp} \\
 & \quad \quad (\text{secContextMoveToORP slCommand}) \text{ ins} \\
 & \quad \quad (NS \text{ s } (\text{exec } (\text{SLc slCommand}))) \\
 & \quad \quad (\text{Out s } (\text{exec } (\text{SLc slCommand})) :: \text{outs})) \iff \\
 & \text{authTestMoveToORP} \\
 & \quad (\text{Name PlatoonLeader says prop (SOME (SLc slCommand))}) \wedge \\
 & \text{CFGInterpret } (M, Oi, Os) \\
 & \quad (\text{CFG authTestMoveToORP ssmMoveToORPStateInterp} \\
 & \quad \quad (\text{secContextMoveToORP slCommand}) \\
 & \quad \quad (\text{Name PlatoonLeader says prop (SOME (SLc slCommand))} :: \\
 & \quad \quad \quad \text{ins) s outs}) \wedge \\
 & (M, Oi, Os) \text{ sat prop (SOME (SLc slCommand))}
 \end{aligned}$$

[PlatoonLeader_slCommand_lemma]

$$\begin{aligned}
 & \vdash \text{CFGInterpret } (M, Oi, Os) \\
 & \quad (\text{CFG authTestMoveToORP ssmMoveToORPStateInterp} \\
 & \quad \quad (\text{secContextMoveToORP slCommand}) \\
 & \quad \quad (\text{Name PlatoonLeader says prop (SOME (SLc slCommand))} :: \\
 & \quad \quad \quad \text{ins) s outs}) \Rightarrow \\
 & (M, Oi, Os) \text{ sat prop (SOME (SLc slCommand))}
 \end{aligned}$$

14 MoveToORPType Theory

Built: 10 June 2018

Parent Theories: indexedLists, patternMatches

14.1 Datatypes

$$\begin{aligned}
 \text{slCommand} &= \text{pltForm} \mid \text{pltMove} \mid \text{pltSecureHalt} \mid \text{complete} \\
 &\quad \mid \text{incomplete}
 \end{aligned}$$

```

slOutput = MoveToORP | PLTForm | PLTMove | PLTSecureHalt
          | Complete | unauthorized | unAuthenticated

slState = MOVE_TO_ORP | PLT_FORM | PLT_MOVE | PLT_SECURE_HALT
          | COMPLETE

stateRole = PlatoonLeader

```

14.2 Theorems

[slCommand_distinct_clauses]

```

⊢ pltForm ≠ pltMove ∧ pltForm ≠ pltSecureHalt ∧
  pltForm ≠ complete ∧ pltForm ≠ incomplete ∧
  pltMove ≠ pltSecureHalt ∧ pltMove ≠ complete ∧
  pltMove ≠ incomplete ∧ pltSecureHalt ≠ complete ∧
  pltSecureHalt ≠ incomplete ∧ complete ≠ incomplete

```

[slOutput_distinct_clauses]

```

⊢ MoveToORP ≠ PLTForm ∧ MoveToORP ≠ PLTMove ∧
  MoveToORP ≠ PLTSecureHalt ∧ MoveToORP ≠ Complete ∧
  MoveToORP ≠ unauthorized ∧ MoveToORP ≠ unAuthenticated ∧
  PLTForm ≠ PLTMove ∧ PLTForm ≠ PLTSecureHalt ∧
  PLTForm ≠ Complete ∧ PLTForm ≠ unauthorized ∧
  PLTForm ≠ unAuthenticated ∧ PLTMove ≠ PLTSecureHalt ∧
  PLTMove ≠ Complete ∧ PLTMove ≠ unauthorized ∧
  PLTMove ≠ unAuthenticated ∧ PLTSecureHalt ≠ Complete ∧
  PLTSecureHalt ≠ unauthorized ∧
  PLTSecureHalt ≠ unAuthenticated ∧ Complete ≠ unauthorized ∧
  Complete ≠ unAuthenticated ∧ unauthorized ≠ unAuthenticated

```

[slState_distinct_clauses]

```

⊢ MOVE_TO_ORP ≠ PLT_FORM ∧ MOVE_TO_ORP ≠ PLT_MOVE ∧
  MOVE_TO_ORP ≠ PLT_SECURE_HALT ∧ MOVE_TO_ORP ≠ COMPLETE ∧
  PLT_FORM ≠ PLT_MOVE ∧ PLT_FORM ≠ PLT_SECURE_HALT ∧
  PLT_FORM ≠ COMPLETE ∧ PLT_MOVE ≠ PLT_SECURE_HALT ∧
  PLT_MOVE ≠ COMPLETE ∧ PLT_SECURE_HALT ≠ COMPLETE

```

15 ssmMoveToPB Theory

Built: 10 June 2018

Parent Theories: MoveToPBType, ssm11, OMNIType

15.1 Definitions

[secContextMoveToPB_def]

```

⊢ ∀ cmd.
  secContextMoveToPB cmd =
    [Name PlatoonLeader controls prop (SOME (SLc cmd))]

```

[ssmMoveToPBStateInterp_def]

$\vdash \forall state. \text{ssmMoveToPBStateInterp } state = \text{TT}$

15.2 Theorems

[authTestMoveToPB_cmd_reject_lemma]

$\vdash \forall cmd. \neg \text{authTestMoveToPB } (\text{prop } (\text{SOME } cmd))$

[authTestMoveToPB_def]

$\vdash (\text{authTestMoveToPB } (\text{Name PlatoonLeader says prop } cmd) \iff \text{T}) \wedge$
 $(\text{authTestMoveToPB } \text{TT} \iff \text{F}) \wedge (\text{authTestMoveToPB } \text{FF} \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (\text{prop } v) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (\text{notf } v_1) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_2 \text{ andf } v_3) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_4 \text{ orf } v_5) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_6 \text{ impf } v_7) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_8 \text{ eqf } v_9) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says TT}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says FF}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{133} \text{ meet } v_{134} \text{ says prop } v_{66}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{135} \text{ quoting } v_{136} \text{ says prop } v_{66}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says notf } v_{67}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } (v_{68} \text{ andf } v_{69})) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } (v_{70} \text{ orf } v_{71})) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } (v_{72} \text{ impf } v_{73})) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } (v_{74} \text{ eqf } v_{75})) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } v_{76} \text{ says } v_{77}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } v_{80} \text{ controls } v_{81}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says reps } v_{82} \ v_{83} \ v_{84}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } v_{85} \text{ domi } v_{86}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } v_{87} \text{ eqi } v_{88}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } v_{89} \text{ doms } v_{90}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } v_{91} \text{ eqs } v_{92}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } v_{93} \text{ eqn } v_{94}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } v_{95} \text{ lte } v_{96}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{10} \text{ says } v_{97} \text{ lt } v_{98}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{12} \text{ speaks_for } v_{13}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{14} \text{ controls } v_{15}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (\text{reps } v_{16} \ v_{17} \ v_{18}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{19} \text{ domi } v_{20}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{21} \text{ eqi } v_{22}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{23} \text{ doms } v_{24}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{25} \text{ eqs } v_{26}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{27} \text{ eqn } v_{28}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{29} \text{ lte } v_{30}) \iff \text{F}) \wedge$
 $(\text{authTestMoveToPB } (v_{31} \text{ lt } v_{32}) \iff \text{F})$

[authTestMoveToPB_ind]

$\vdash \forall P.$

$(\forall cmd. P (\text{Name PlatoonLeader says prop } cmd)) \wedge P \text{ TT} \wedge$
 $P \text{ FF} \wedge (\forall v. P (\text{prop } v)) \wedge (\forall v_1. P (\text{notf } v_1)) \wedge$
 $(\forall v_2 v_3. P (v_2 \text{ andf } v_3)) \wedge (\forall v_4 v_5. P (v_4 \text{ orf } v_5)) \wedge$
 $(\forall v_6 v_7. P (v_6 \text{ impf } v_7)) \wedge (\forall v_8 v_9. P (v_8 \text{ eqf } v_9)) \wedge$
 $(\forall v_{10}. P (v_{10} \text{ says TT})) \wedge (\forall v_{10}. P (v_{10} \text{ says FF})) \wedge$
 $(\forall v_{133} v_{134} v_{66}. P (v_{133} \text{ meet } v_{134} \text{ says prop } v_{66})) \wedge$
 $(\forall v_{135} v_{136} v_{66}. P (v_{135} \text{ quoting } v_{136} \text{ says prop } v_{66})) \wedge$
 $(\forall v_{10} v_{67}. P (v_{10} \text{ says notf } v_{67})) \wedge$
 $(\forall v_{10} v_{68} v_{69}. P (v_{10} \text{ says } (v_{68} \text{ andf } v_{69}))) \wedge$
 $(\forall v_{10} v_{70} v_{71}. P (v_{10} \text{ says } (v_{70} \text{ orf } v_{71}))) \wedge$
 $(\forall v_{10} v_{72} v_{73}. P (v_{10} \text{ says } (v_{72} \text{ impf } v_{73}))) \wedge$
 $(\forall v_{10} v_{74} v_{75}. P (v_{10} \text{ says } (v_{74} \text{ eqf } v_{75}))) \wedge$
 $(\forall v_{10} v_{76} v_{77}. P (v_{10} \text{ says } v_{76} \text{ says } v_{77})) \wedge$
 $(\forall v_{10} v_{78} v_{79}. P (v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79})) \wedge$
 $(\forall v_{10} v_{80} v_{81}. P (v_{10} \text{ says } v_{80} \text{ controls } v_{81})) \wedge$
 $(\forall v_{10} v_{82} v_{83} v_{84}. P (v_{10} \text{ says reps } v_{82} v_{83} v_{84})) \wedge$
 $(\forall v_{10} v_{85} v_{86}. P (v_{10} \text{ says } v_{85} \text{ domi } v_{86})) \wedge$
 $(\forall v_{10} v_{87} v_{88}. P (v_{10} \text{ says } v_{87} \text{ eqi } v_{88})) \wedge$
 $(\forall v_{10} v_{89} v_{90}. P (v_{10} \text{ says } v_{89} \text{ doms } v_{90})) \wedge$
 $(\forall v_{10} v_{91} v_{92}. P (v_{10} \text{ says } v_{91} \text{ eqs } v_{92})) \wedge$
 $(\forall v_{10} v_{93} v_{94}. P (v_{10} \text{ says } v_{93} \text{ eqn } v_{94})) \wedge$
 $(\forall v_{10} v_{95} v_{96}. P (v_{10} \text{ says } v_{95} \text{ lte } v_{96})) \wedge$
 $(\forall v_{10} v_{97} v_{98}. P (v_{10} \text{ says } v_{97} \text{ lt } v_{98})) \wedge$
 $(\forall v_{12} v_{13}. P (v_{12} \text{ speaks_for } v_{13})) \wedge$
 $(\forall v_{14} v_{15}. P (v_{14} \text{ controls } v_{15})) \wedge$
 $(\forall v_{16} v_{17} v_{18}. P (\text{reps } v_{16} v_{17} v_{18})) \wedge$
 $(\forall v_{19} v_{20}. P (v_{19} \text{ domi } v_{20})) \wedge$
 $(\forall v_{21} v_{22}. P (v_{21} \text{ eqi } v_{22})) \wedge$
 $(\forall v_{23} v_{24}. P (v_{23} \text{ doms } v_{24})) \wedge$
 $(\forall v_{25} v_{26}. P (v_{25} \text{ eqs } v_{26})) \wedge (\forall v_{27} v_{28}. P (v_{27} \text{ eqn } v_{28})) \wedge$
 $(\forall v_{29} v_{30}. P (v_{29} \text{ lte } v_{30})) \wedge (\forall v_{31} v_{32}. P (v_{31} \text{ lt } v_{32})) \Rightarrow$
 $\forall v. P v$

[moveToPBNS_def]

$\vdash (\text{moveToPBNS MOVE_TO_PB (exec (SLc pltForm))} = \text{PLT_FORM}) \wedge$
 $(\text{moveToPBNS MOVE_TO_PB (exec (SLc incomplete))} =$
 $\text{MOVE_TO_PB}) \wedge$
 $(\text{moveToPBNS PLT_FORM (exec (SLc pltMove))} = \text{PLT_MOVE}) \wedge$
 $(\text{moveToPBNS PLT_FORM (exec (SLc incomplete))} = \text{PLT_FORM}) \wedge$
 $(\text{moveToPBNS PLT_MOVE (exec (SLc pltHalt))} = \text{PLT_HALT}) \wedge$
 $(\text{moveToPBNS PLT_MOVE (exec (SLc incomplete))} = \text{PLT_MOVE}) \wedge$
 $(\text{moveToPBNS PLT_HALT (exec (SLc complete))} = \text{COMPLETE}) \wedge$
 $(\text{moveToPBNS PLT_HALT (exec (SLc incomplete))} = \text{PLT_HALT}) \wedge$
 $(\text{moveToPBNS } s (\text{trap (SLc cmd)}) = s) \wedge$
 $(\text{moveToPBNS } s (\text{discard (SLc cmd)}) = s)$

[moveToPBNS_ind]

$\vdash \forall P.$
 $P \text{ MOVE_TO_PB } (\text{exec } (\text{SLc pltForm})) \wedge$
 $P \text{ MOVE_TO_PB } (\text{exec } (\text{SLc incomplete})) \wedge$
 $P \text{ PLT_FORM } (\text{exec } (\text{SLc pltMove})) \wedge$
 $P \text{ PLT_FORM } (\text{exec } (\text{SLc incomplete})) \wedge$
 $P \text{ PLT_MOVE } (\text{exec } (\text{SLc pltHalt})) \wedge$
 $P \text{ PLT_MOVE } (\text{exec } (\text{SLc incomplete})) \wedge$
 $P \text{ PLT_HALT } (\text{exec } (\text{SLc complete})) \wedge$
 $P \text{ PLT_HALT } (\text{exec } (\text{SLc incomplete})) \wedge$
 $(\forall s \text{ cmd}. P \ s \ (\text{trap } (\text{SLc cmd}))) \wedge$
 $(\forall s \text{ cmd}. P \ s \ (\text{discard } (\text{SLc cmd}))) \wedge$
 $(\forall s \ v_6. P \ s \ (\text{discard } (\text{ESCc } v_6))) \wedge$
 $(\forall s \ v_9. P \ s \ (\text{trap } (\text{ESCc } v_9))) \wedge$
 $(\forall v_{12}. P \text{ MOVE_TO_PB } (\text{exec } (\text{ESCc } v_{12}))) \wedge$
 $P \text{ MOVE_TO_PB } (\text{exec } (\text{SLc pltMove})) \wedge$
 $P \text{ MOVE_TO_PB } (\text{exec } (\text{SLc pltHalt})) \wedge$
 $P \text{ MOVE_TO_PB } (\text{exec } (\text{SLc complete})) \wedge$
 $(\forall v_{15}. P \text{ PLT_FORM } (\text{exec } (\text{ESCc } v_{15}))) \wedge$
 $P \text{ PLT_FORM } (\text{exec } (\text{SLc pltForm})) \wedge$
 $P \text{ PLT_FORM } (\text{exec } (\text{SLc pltHalt})) \wedge$
 $P \text{ PLT_FORM } (\text{exec } (\text{SLc complete})) \wedge$
 $(\forall v_{18}. P \text{ PLT_MOVE } (\text{exec } (\text{ESCc } v_{18}))) \wedge$
 $P \text{ PLT_MOVE } (\text{exec } (\text{SLc pltForm})) \wedge$
 $P \text{ PLT_MOVE } (\text{exec } (\text{SLc pltMove})) \wedge$
 $P \text{ PLT_MOVE } (\text{exec } (\text{SLc complete})) \wedge$
 $(\forall v_{21}. P \text{ PLT_HALT } (\text{exec } (\text{ESCc } v_{21}))) \wedge$
 $P \text{ PLT_HALT } (\text{exec } (\text{SLc pltForm})) \wedge$
 $P \text{ PLT_HALT } (\text{exec } (\text{SLc pltMove})) \wedge$
 $P \text{ PLT_HALT } (\text{exec } (\text{SLc pltHalt})) \wedge$
 $(\forall v_{23}. P \text{ COMPLETE } (\text{exec } v_{23})) \Rightarrow$
 $\forall v \ v_1. P \ v \ v_1$

[moveToPBOut_def]

$\vdash (\text{moveToPBOut MOVE_TO_PB } (\text{exec } (\text{SLc pltForm})) = \text{PLTForm}) \wedge$
 $(\text{moveToPBOut MOVE_TO_PB } (\text{exec } (\text{SLc incomplete})) = \text{MoveToPB}) \wedge$
 $(\text{moveToPBOut PLT_FORM } (\text{exec } (\text{SLc pltMove})) = \text{PLTMove}) \wedge$
 $(\text{moveToPBOut PLT_FORM } (\text{exec } (\text{SLc incomplete})) = \text{PLTForm}) \wedge$
 $(\text{moveToPBOut PLT_MOVE } (\text{exec } (\text{SLc pltHalt})) = \text{PLTHalt}) \wedge$
 $(\text{moveToPBOut PLT_MOVE } (\text{exec } (\text{SLc incomplete})) = \text{PLTMove}) \wedge$
 $(\text{moveToPBOut PLT_HALT } (\text{exec } (\text{SLc complete})) = \text{Complete}) \wedge$
 $(\text{moveToPBOut PLT_HALT } (\text{exec } (\text{SLc incomplete})) = \text{PLTHalt}) \wedge$
 $(\text{moveToPBOut } s \ (\text{trap } (\text{SLc cmd})) = \text{unAuthorized}) \wedge$
 $(\text{moveToPBOut } s \ (\text{discard } (\text{SLc cmd})) = \text{unAuthenticated})$

[moveToPBOut_ind]

$\vdash \forall P.$
 $P \text{ MOVE_TO_PB } (\text{exec } (\text{SLc pltForm})) \wedge$

$P \text{ MOVE_TO_PB (exec (SLc incomplete))} \wedge$
 $P \text{ PLT_FORM (exec (SLc pltMove))} \wedge$
 $P \text{ PLT_FORM (exec (SLc incomplete))} \wedge$
 $P \text{ PLT_MOVE (exec (SLc pltHalt))} \wedge$
 $P \text{ PLT_MOVE (exec (SLc incomplete))} \wedge$
 $P \text{ PLT_HALT (exec (SLc complete))} \wedge$
 $P \text{ PLT_HALT (exec (SLc incomplete))} \wedge$
 $(\forall s \text{ cmd. } P \text{ s (trap (SLc cmd))}) \wedge$
 $(\forall s \text{ cmd. } P \text{ s (discard (SLc cmd))}) \wedge$
 $(\forall s \text{ v}_6. P \text{ s (discard (ESCc v}_6\text{))}) \wedge$
 $(\forall s \text{ v}_9. P \text{ s (trap (ESCc v}_9\text{))}) \wedge$
 $(\forall v_{12}. P \text{ MOVE_TO_PB (exec (ESCc v}_{12}\text{))}) \wedge$
 $P \text{ MOVE_TO_PB (exec (SLc pltMove))} \wedge$
 $P \text{ MOVE_TO_PB (exec (SLc pltHalt))} \wedge$
 $P \text{ MOVE_TO_PB (exec (SLc complete))} \wedge$
 $(\forall v_{15}. P \text{ PLT_FORM (exec (ESCc v}_{15}\text{))}) \wedge$
 $P \text{ PLT_FORM (exec (SLc pltForm))} \wedge$
 $P \text{ PLT_FORM (exec (SLc pltHalt))} \wedge$
 $P \text{ PLT_FORM (exec (SLc complete))} \wedge$
 $(\forall v_{18}. P \text{ PLT_MOVE (exec (ESCc v}_{18}\text{))}) \wedge$
 $P \text{ PLT_MOVE (exec (SLc pltForm))} \wedge$
 $P \text{ PLT_MOVE (exec (SLc pltMove))} \wedge$
 $P \text{ PLT_MOVE (exec (SLc complete))} \wedge$
 $(\forall v_{21}. P \text{ PLT_HALT (exec (ESCc v}_{21}\text{))}) \wedge$
 $P \text{ PLT_HALT (exec (SLc pltForm))} \wedge$
 $P \text{ PLT_HALT (exec (SLc pltMove))} \wedge$
 $P \text{ PLT_HALT (exec (SLc pltHalt))} \wedge$
 $(\forall v_{23}. P \text{ COMPLETE (exec v}_{23}\text{)}) \Rightarrow$
 $\forall v \text{ v}_1. P \text{ v v}_1$

[PlatoonLeader_exec_slCommand_justified_thm]

$\vdash \forall NS \text{ Out } M \text{ Oi } Os.$

$\text{TR } (M, Oi, Os) \text{ (exec (SLc slCommand))}$
 $(\text{CFG authTestMoveToPB ssmMoveToPBStateInterp}$
 $(\text{secContextMoveToPB slCommand})$
 $(\text{Name PlatoonLeader says prop (SOME (SLc slCommand))} ::$
 $\text{ins) s outs})$
 $(\text{CFG authTestMoveToPB ssmMoveToPBStateInterp}$
 $(\text{secContextMoveToPB slCommand) ins}$
 $(NS \text{ s (exec (SLc slCommand))})$
 $(\text{Out s (exec (SLc slCommand))} :: \text{outs})) \iff$
 authTestMoveToPB
 $(\text{Name PlatoonLeader says prop (SOME (SLc slCommand))}) \wedge$
 $\text{CFGInterpret } (M, Oi, Os)$
 $(\text{CFG authTestMoveToPB ssmMoveToPBStateInterp}$
 $(\text{secContextMoveToPB slCommand})$
 $(\text{Name PlatoonLeader says prop (SOME (SLc slCommand))} ::$
 $\text{ins) s outs}) \wedge$
 $(M, Oi, Os) \text{ sat prop (SOME (SLc slCommand))}$

[PlatoonLeader_slCommand_lemma]

```

⊢ CFGInterpret (M, Oi, Os)
  (CFG authTestMoveToPB ssmMoveToPBStateInterp
   (secContextMoveToPB slCommand)
   (Name PlatoonLeader says prop (SOME (SLc slCommand)))::
    ins) s outs) ⇒
  (M, Oi, Os) sat prop (SOME (SLc slCommand))

```

16 MoveToPBType Theory

Built: 10 June 2018

Parent Theories: indexedLists, patternMatches

16.1 Datatypes

slCommand = pltForm | pltMove | pltHalt | complete | incomplete

slOutput = MoveToPB | PLTForm | PLTMove | PLTHalt | Complete
 | unauthorized | unAuthenticated

slState = MOVE_TO_PB | PLT_FORM | PLT_MOVE | PLT_HALT | COMPLETE

stateRole = PlatoonLeader

16.2 Theorems

[slCommand_distinct_clauses]

```

⊢ pltForm ≠ pltMove ∧ pltForm ≠ pltHalt ∧ pltForm ≠ complete ∧
  pltForm ≠ incomplete ∧ pltMove ≠ pltHalt ∧
  pltMove ≠ complete ∧ pltMove ≠ incomplete ∧
  pltHalt ≠ complete ∧ pltHalt ≠ incomplete ∧
  complete ≠ incomplete

```

[slOutput_distinct_clauses]

```

⊢ MoveToPB ≠ PLTForm ∧ MoveToPB ≠ PLTMove ∧
  MoveToPB ≠ PLTHalt ∧ MoveToPB ≠ Complete ∧
  MoveToPB ≠ unauthorized ∧ MoveToPB ≠ unAuthenticated ∧
  PLTForm ≠ PLTMove ∧ PLTForm ≠ PLTHalt ∧ PLTForm ≠ Complete ∧
  PLTForm ≠ unauthorized ∧ PLTForm ≠ unAuthenticated ∧
  PLTMove ≠ PLTHalt ∧ PLTMove ≠ Complete ∧
  PLTMove ≠ unauthorized ∧ PLTMove ≠ unAuthenticated ∧
  PLTHalt ≠ Complete ∧ PLTHalt ≠ unauthorized ∧
  PLTHalt ≠ unAuthenticated ∧ Complete ≠ unauthorized ∧
  Complete ≠ unAuthenticated ∧ unauthorized ≠ unAuthenticated

```

[slState_distinct_clauses]

$\vdash \text{MOVE_TO_PB} \neq \text{PLT_FORM} \wedge \text{MOVE_TO_PB} \neq \text{PLT_MOVE} \wedge$
 $\text{MOVE_TO_PB} \neq \text{PLT_HALT} \wedge \text{MOVE_TO_PB} \neq \text{COMPLETE} \wedge$
 $\text{PLT_FORM} \neq \text{PLT_MOVE} \wedge \text{PLT_FORM} \neq \text{PLT_HALT} \wedge$
 $\text{PLT_FORM} \neq \text{COMPLETE} \wedge \text{PLT_MOVE} \neq \text{PLT_HALT} \wedge$
 $\text{PLT_MOVE} \neq \text{COMPLETE} \wedge \text{PLT_HALT} \neq \text{COMPLETE}$

17 ssmPlanPB Theory

Built: 10 June 2018

Parent Theories: PlanPBDef, ssm

17.1 Theorems

[inputOK_def]

$\vdash (\text{inputOK } (\text{Name PlatoonLeader says prop } cmd) \iff T) \wedge$
 $(\text{inputOK } (\text{Name PlatoonSergeant says prop } cmd) \iff T) \wedge$
 $(\text{inputOK } TT \iff F) \wedge (\text{inputOK } FF \iff F) \wedge$
 $(\text{inputOK } (\text{prop } v) \iff F) \wedge (\text{inputOK } (\text{notf } v_1) \iff F) \wedge$
 $(\text{inputOK } (v_2 \text{ andf } v_3) \iff F) \wedge (\text{inputOK } (v_4 \text{ orf } v_5) \iff F) \wedge$
 $(\text{inputOK } (v_6 \text{ impf } v_7) \iff F) \wedge (\text{inputOK } (v_8 \text{ eqf } v_9) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } TT) \iff F) \wedge (\text{inputOK } (v_{10} \text{ says } FF) \iff F) \wedge$
 $(\text{inputOK } (v_{133} \text{ meet } v_{134} \text{ says prop } v_{66}) \iff F) \wedge$
 $(\text{inputOK } (v_{135} \text{ quoting } v_{136} \text{ says prop } v_{66}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says notf } v_{67}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } (v_{68} \text{ andf } v_{69})) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } (v_{70} \text{ orf } v_{71})) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } (v_{72} \text{ impf } v_{73})) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } (v_{74} \text{ eqf } v_{75})) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{76} \text{ says } v_{77}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{80} \text{ controls } v_{81}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says reps } v_{82} v_{83} v_{84}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{85} \text{ domi } v_{86}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{87} \text{ eqi } v_{88}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{89} \text{ doms } v_{90}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{91} \text{ eqs } v_{92}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{93} \text{ eqn } v_{94}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{95} \text{ lte } v_{96}) \iff F) \wedge$
 $(\text{inputOK } (v_{10} \text{ says } v_{97} \text{ lt } v_{98}) \iff F) \wedge$
 $(\text{inputOK } (v_{12} \text{ speaks_for } v_{13}) \iff F) \wedge$
 $(\text{inputOK } (v_{14} \text{ controls } v_{15}) \iff F) \wedge$
 $(\text{inputOK } (\text{reps } v_{16} v_{17} v_{18}) \iff F) \wedge$
 $(\text{inputOK } (v_{19} \text{ domi } v_{20}) \iff F) \wedge$
 $(\text{inputOK } (v_{21} \text{ eqi } v_{22}) \iff F) \wedge$
 $(\text{inputOK } (v_{23} \text{ doms } v_{24}) \iff F) \wedge$

$$(\text{inputOK } (v_{25} \text{ eqs } v_{26}) \iff F) \wedge (\text{inputOK } (v_{27} \text{ eqn } v_{28}) \iff F) \wedge \\ (\text{inputOK } (v_{29} \text{ lte } v_{30}) \iff F) \wedge (\text{inputOK } (v_{31} \text{ lt } v_{32}) \iff F)$$

[inputOK_ind]

$\vdash \forall P.$

$$(\forall \text{cmd}. P (\text{Name PlatoonLeader says prop cmd})) \wedge \\ (\forall \text{cmd}. P (\text{Name PlatoonSergeant says prop cmd})) \wedge P \text{ TT} \wedge \\ P \text{ FF} \wedge (\forall v. P (\text{prop } v)) \wedge (\forall v_1. P (\text{notf } v_1)) \wedge \\ (\forall v_2 v_3. P (v_2 \text{ andf } v_3)) \wedge (\forall v_4 v_5. P (v_4 \text{ orf } v_5)) \wedge \\ (\forall v_6 v_7. P (v_6 \text{ impf } v_7)) \wedge (\forall v_8 v_9. P (v_8 \text{ eqf } v_9)) \wedge \\ (\forall v_{10}. P (v_{10} \text{ says TT})) \wedge (\forall v_{10}. P (v_{10} \text{ says FF})) \wedge \\ (\forall v_{133} v_{134} v_{66}. P (v_{133} \text{ meet } v_{134} \text{ says prop } v_{66})) \wedge \\ (\forall v_{135} v_{136} v_{66}. P (v_{135} \text{ quoting } v_{136} \text{ says prop } v_{66})) \wedge \\ (\forall v_{10} v_{67}. P (v_{10} \text{ says notf } v_{67})) \wedge \\ (\forall v_{10} v_{68} v_{69}. P (v_{10} \text{ says } (v_{68} \text{ andf } v_{69}))) \wedge \\ (\forall v_{10} v_{70} v_{71}. P (v_{10} \text{ says } (v_{70} \text{ orf } v_{71}))) \wedge \\ (\forall v_{10} v_{72} v_{73}. P (v_{10} \text{ says } (v_{72} \text{ impf } v_{73}))) \wedge \\ (\forall v_{10} v_{74} v_{75}. P (v_{10} \text{ says } (v_{74} \text{ eqf } v_{75}))) \wedge \\ (\forall v_{10} v_{76} v_{77}. P (v_{10} \text{ says } v_{76} \text{ says } v_{77})) \wedge \\ (\forall v_{10} v_{78} v_{79}. P (v_{10} \text{ says } v_{78} \text{ speaks_for } v_{79})) \wedge \\ (\forall v_{10} v_{80} v_{81}. P (v_{10} \text{ says } v_{80} \text{ controls } v_{81})) \wedge \\ (\forall v_{10} v_{82} v_{83} v_{84}. P (v_{10} \text{ says reps } v_{82} v_{83} v_{84})) \wedge \\ (\forall v_{10} v_{85} v_{86}. P (v_{10} \text{ says } v_{85} \text{ domi } v_{86})) \wedge \\ (\forall v_{10} v_{87} v_{88}. P (v_{10} \text{ says } v_{87} \text{ eqi } v_{88})) \wedge \\ (\forall v_{10} v_{89} v_{90}. P (v_{10} \text{ says } v_{89} \text{ doms } v_{90})) \wedge \\ (\forall v_{10} v_{91} v_{92}. P (v_{10} \text{ says } v_{91} \text{ eqs } v_{92})) \wedge \\ (\forall v_{10} v_{93} v_{94}. P (v_{10} \text{ says } v_{93} \text{ eqn } v_{94})) \wedge \\ (\forall v_{10} v_{95} v_{96}. P (v_{10} \text{ says } v_{95} \text{ lte } v_{96})) \wedge \\ (\forall v_{10} v_{97} v_{98}. P (v_{10} \text{ says } v_{97} \text{ lt } v_{98})) \wedge \\ (\forall v_{12} v_{13}. P (v_{12} \text{ speaks_for } v_{13})) \wedge \\ (\forall v_{14} v_{15}. P (v_{14} \text{ controls } v_{15})) \wedge \\ (\forall v_{16} v_{17} v_{18}. P (\text{reps } v_{16} v_{17} v_{18})) \wedge \\ (\forall v_{19} v_{20}. P (v_{19} \text{ domi } v_{20})) \wedge \\ (\forall v_{21} v_{22}. P (v_{21} \text{ eqi } v_{22})) \wedge \\ (\forall v_{23} v_{24}. P (v_{23} \text{ doms } v_{24})) \wedge \\ (\forall v_{25} v_{26}. P (v_{25} \text{ eqs } v_{26})) \wedge (\forall v_{27} v_{28}. P (v_{27} \text{ eqn } v_{28})) \wedge \\ (\forall v_{29} v_{30}. P (v_{29} \text{ lte } v_{30})) \wedge (\forall v_{31} v_{32}. P (v_{31} \text{ lt } v_{32})) \Rightarrow \\ \forall v. P v$$

[planPBNS_def]

$\vdash (\text{planPBNS WARN0 (exec } x) =$
if
 (getRecon $x = [\text{SOME (SLc (PL recon))}] \wedge$
 (getTentativePlan $x = [\text{SOME (SLc (PL tentativePlan))}] \wedge$
 (getReport $x = [\text{SOME (SLc (PL report1))}] \wedge$
 (getInitMove $x = [\text{SOME (SLc (PSG initiateMovement))}]$)
then
 REPORT1
else WARN0) \wedge

```

(planPBNS PLAN_PB (exec x) =
  if getPlCom x = receiveMission then RECEIVE_MISSION
  else PLAN_PB) ∧
(planPBNS RECEIVE_MISSION (exec x) =
  if getPlCom x = warno then WARNO else RECEIVE_MISSION) ∧
(planPBNS REPORT1 (exec x) =
  if getPlCom x = completePlan then COMPLETE_PLAN
  else REPORT1) ∧
(planPBNS COMPLETE_PLAN (exec x) =
  if getPlCom x = opoid then OPOID else COMPLETE_PLAN) ∧
(planPBNS OPOID (exec x) =
  if getPlCom x = supervise then SUPERVISE else OPOID) ∧
(planPBNS SUPERVISE (exec x) =
  if getPlCom x = report2 then REPORT2 else SUPERVISE) ∧
(planPBNS REPORT2 (exec x) =
  if getPlCom x = complete then COMPLETE else REPORT2) ∧
(planPBNS s (trap v0) = s) ∧ (planPBNS s (discard v1) = s)

```

[planPBNS_ind]

```

⊢ ∀ P.
  (∀ x. P WARNO (exec x)) ∧ (∀ x. P PLAN_PB (exec x)) ∧
  (∀ x. P RECEIVE_MISSION (exec x)) ∧
  (∀ x. P REPORT1 (exec x)) ∧ (∀ x. P COMPLETE_PLAN (exec x)) ∧
  (∀ x. P OPOID (exec x)) ∧ (∀ x. P SUPERVISE (exec x)) ∧
  (∀ x. P REPORT2 (exec x)) ∧ (∀ s v0. P s (trap v0)) ∧
  (∀ s v1. P s (discard v1)) ∧
  (∀ v6. P TENTATIVE_PLAN (exec v6)) ∧
  (∀ v7. P INITIATE_MOVEMENT (exec v7)) ∧
  (∀ v8. P RECON (exec v8)) ∧ (∀ v9. P COMPLETE (exec v9)) ⇒
  ∀ v v1. P v v1

```

[planPBOut_def]

```

⊢ (planPBOut WARNO (exec x) =
  if
    (getRecon x = [SOME (SLc (PL recon))]) ∧
    (getTentativePlan x = [SOME (SLc (PL tentativePlan))]) ∧
    (getReport x = [SOME (SLc (PL report1))]) ∧
    (getInitMove x = [SOME (SLc (PSG initiateMovement))])
  then
    Report1
  else unauthorized) ∧
(planPBOut PLAN_PB (exec x) =
  if getPlCom x = receiveMission then ReceiveMission
  else unauthorized) ∧
(planPBOut RECEIVE_MISSION (exec x) =
  if getPlCom x = warno then Warno else unauthorized) ∧
(planPBOut REPORT1 (exec x) =
  if getPlCom x = completePlan then CompletePlan
  else unauthorized) ∧

```

```

(planPBOut COMPLETE_PLAN (exec x) =
  if getP1Com x = opoid then Opoid else unauthorized) ∧
(planPBOut OPOID (exec x) =
  if getP1Com x = supervise then Supervise
  else unauthorized) ∧
(planPBOut SUPERVISE (exec x) =
  if getP1Com x = report2 then Report2 else unauthorized) ∧
(planPBOut REPORT2 (exec x) =
  if getP1Com x = complete then Complete else unauthorized) ∧
(planPBOut s (trap v0) = unauthorized) ∧
(planPBOut s (discard v1) = unauthenticated)

```

[planPBOut_ind]

```

⊢ ∀ P.
  (∀ x. P WARNO (exec x)) ∧ (∀ x. P PLAN_PB (exec x)) ∧
  (∀ x. P RECEIVE_MISSION (exec x)) ∧
  (∀ x. P REPORT1 (exec x)) ∧ (∀ x. P COMPLETE_PLAN (exec x)) ∧
  (∀ x. P OPOID (exec x)) ∧ (∀ x. P SUPERVISE (exec x)) ∧
  (∀ x. P REPORT2 (exec x)) ∧ (∀ s v0. P s (trap v0)) ∧
  (∀ s v1. P s (discard v1)) ∧
  (∀ v6. P TENTATIVE_PLAN (exec v6)) ∧
  (∀ v7. P INITIATE_MOVEMENT (exec v7)) ∧
  (∀ v8. P RECON (exec v8)) ∧ (∀ v9. P COMPLETE (exec v9)) ⇒
  ∀ v v1. P v v1

```

[PlatoonLeader_notWARNO_notreport1_exec_plCommand_justified_lemma]

```

⊢ s ≠ WARNO ⇒
  plCommand ≠ invalidPlCommand ⇒
  plCommand ≠ report1 ⇒
  ∀ NS Out M Oi Os.
    TR (M, Oi, Os)
      (exec
        (inputList
          [Name PlatoonLeader says
            prop (SOME (SLc (PL plCommand))))]))
      (CFG inputOK secContext secContextNull
        ([Name PlatoonLeader says
          prop (SOME (SLc (PL plCommand)))]::ins) s outs)
      (CFG inputOK secContext secContextNull ins
        (NS s
          (exec
            (inputList
              [Name PlatoonLeader says
                prop (SOME (SLc (PL plCommand)))]))))
      (Out s
        (exec
          (inputList
            [Name PlatoonLeader says
              prop (SOME (SLc (PL plCommand)))])))::

```



```

outs))  $\iff$ 
authenticationTest inputOK
  [Name PlatoonLeader says
    prop (SOME (SLc (PL plCommand)))]  $\wedge$ 
CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secContextNull
    ([Name PlatoonLeader says
      prop (SOME (SLc (PL plCommand)))]::ins) s outs)  $\wedge$ 
(M, Oi, Os) satList
propCommandList
  [Name PlatoonLeader says
    prop (SOME (SLc (PL plCommand)))]

```

[PlatoonLeader_notWARNO_notreport1_exec_plCommand_justified_thm]

```

 $\vdash s \neq \text{WARNO} \Rightarrow$ 
  plCommand  $\neq$  invalidPlCommand  $\Rightarrow$ 
  plCommand  $\neq$  report1  $\Rightarrow$ 
 $\forall NS \text{ Out } M \text{ Oi } Os.$ 
  TR (M, Oi, Os) (exec [SOME (SLc (PL plCommand))])
    (CFG inputOK secContext secContextNull
      ([Name PlatoonLeader says
        prop (SOME (SLc (PL plCommand)))]::ins) s outs)
    (CFG inputOK secContext secContextNull ins
      (NS s (exec [SOME (SLc (PL plCommand))])))
    (Out s (exec [SOME (SLc (PL plCommand)))]::outs))  $\iff$ 
authenticationTest inputOK
  [Name PlatoonLeader says
    prop (SOME (SLc (PL plCommand)))]  $\wedge$ 
CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secContextNull
    ([Name PlatoonLeader says
      prop (SOME (SLc (PL plCommand)))]::ins) s outs)  $\wedge$ 
(M, Oi, Os) satList [prop (SOME (SLc (PL plCommand)))]

```

[PlatoonLeader_notWARNO_notreport1_exec_plCommand_lemma]

```

 $\vdash s \neq \text{WARNO} \Rightarrow$ 
  plCommand  $\neq$  invalidPlCommand  $\Rightarrow$ 
  plCommand  $\neq$  report1  $\Rightarrow$ 
 $\forall M \text{ Oi } Os.$ 
  CFGInterpret (M, Oi, Os)
    (CFG inputOK secContext secContextNull
      ([Name PlatoonLeader says
        prop (SOME (SLc (PL plCommand)))]::ins) s outs)  $\Rightarrow$ 
(M, Oi, Os) satList
propCommandList
  [Name PlatoonLeader says
    prop (SOME (SLc (PL plCommand)))]

```

[PlatoonLeader_psgCommand_notDiscard_thm]

$\vdash \forall NS \text{ Out } M \text{ } Oi \text{ } Os.$
 $\neg \text{TR } (M, Oi, Os) \text{ (discard [SOME (SLc (PSG psgCommand))])}$
 $(\text{CFG inputOK secContext secContextNull}$
 $([\text{Name PlatoonLeader says}$
 $\text{prop (SOME (SLc (PSG psgCommand)))]::ins) s outs)$
 $(\text{CFG inputOK secContext secContextNull ins}$
 $(NS s (\text{discard [SOME (SLc (PSG psgCommand))])})$
 $(\text{Out } s (\text{discard [SOME (SLc (PSG psgCommand))])})::$
 $outs))$

[PlatoonLeader_trap_psgCommand_justified_lemma]

$\vdash \forall NS \text{ Out } M \text{ } Oi \text{ } Os.$
 $\text{TR } (M, Oi, Os)$
 $(\text{trap}$
 $(\text{inputList}$
 $[\text{Name PlatoonLeader says}$
 $\text{prop (SOME (SLc (PSG psgCommand)))]])$
 $(\text{CFG inputOK secContext secContextNull}$
 $([\text{Name PlatoonLeader says}$
 $\text{prop (SOME (SLc (PSG psgCommand)))]::ins) s outs)$
 $(\text{CFG inputOK secContext secContextNull ins}$
 $(NS s$
 $(\text{trap}$
 $(\text{inputList}$
 $[\text{Name PlatoonLeader says}$
 $\text{prop (SOME (SLc (PSG psgCommand)))]])$
 $(\text{Out } s$
 $(\text{trap}$
 $(\text{inputList}$
 $[\text{Name PlatoonLeader says}$
 $\text{prop (SOME (SLc (PSG psgCommand)))]])::$
 $outs)) \iff$
 $\text{authenticationTest inputOK}$
 $[\text{Name PlatoonLeader says}$
 $\text{prop (SOME (SLc (PSG psgCommand)))] \wedge$
 $\text{CFGInterpret } (M, Oi, Os)$
 $(\text{CFG inputOK secContext secContextNull}$
 $([\text{Name PlatoonLeader says}$
 $\text{prop (SOME (SLc (PSG psgCommand)))]::ins) s outs) \wedge$
 $(M, Oi, Os) \text{ sat prop NONE}$

[PlatoonLeader_trap_psgCommand_lemma]

$\vdash \forall M \text{ } Oi \text{ } Os.$
 $\text{CFGInterpret } (M, Oi, Os)$
 $(\text{CFG inputOK secContext secContextNull}$
 $([\text{Name PlatoonLeader says}$
 $\text{prop (SOME (SLc (PSG psgCommand)))]::ins) s outs) \Rightarrow$
 $(M, Oi, Os) \text{ sat prop NONE}$

[PlatoonLeader_WARNO_exec_report1_justified_lemma]

$\vdash \forall NS \text{ Out } M \text{ Oi } Os.$

TR (M, Oi, Os)

(exec

(inputList

[Name PlatoonLeader says

prop (SOME (SLc (PL recon)));

Name PlatoonLeader says

prop (SOME (SLc (PL tentativePlan)));

Name PlatoonSergeant says

prop (SOME (SLc (PSG initiateMovement)));

Name PlatoonLeader says

prop (SOME (SLc (PL report1)))))]

(CFG inputOK secContext secContextNull

([Name PlatoonLeader says

prop (SOME (SLc (PL recon)));

Name PlatoonLeader says

prop (SOME (SLc (PL tentativePlan)));

Name PlatoonSergeant says

prop (SOME (SLc (PSG initiateMovement)));

Name PlatoonLeader says

prop (SOME (SLc (PL report1))))::ins) WARNO outs)

(CFG inputOK secContext secContextNull ins

(NS WARNO

(exec

(inputList

[Name PlatoonLeader says

prop (SOME (SLc (PL recon)));

Name PlatoonLeader says

prop (SOME (SLc (PL tentativePlan)));

Name PlatoonSergeant says

prop (SOME (SLc (PSG initiateMovement)));

Name PlatoonLeader says

prop (SOME (SLc (PL report1)))))]

(Out WARNO

(exec

(inputList

[Name PlatoonLeader says

prop (SOME (SLc (PL recon)));

Name PlatoonLeader says

prop (SOME (SLc (PL tentativePlan)));

Name PlatoonSergeant says

prop (SOME (SLc (PSG initiateMovement)));

Name PlatoonLeader says

prop (SOME (SLc (PL report1))))::outs)) \iff

authenticationTest inputOK

[Name PlatoonLeader says prop (SOME (SLc (PL recon)));

Name PlatoonLeader says

prop (SOME (SLc (PL tentativePlan)));

```

    Name PlatoonSergeant says
    prop (SOME (SLc (PSG initiateMovement)));
    Name PlatoonLeader says
    prop (SOME (SLc (PL report1))))]  $\wedge$ 
CFGInterpret ( $M, Oi, Os$ )
  (CFG inputOK secContext secContextNull
    ([Name PlatoonLeader says
      prop (SOME (SLc (PL recon)));
      Name PlatoonLeader says
      prop (SOME (SLc (PL tentativePlan)));
      Name PlatoonSergeant says
      prop (SOME (SLc (PSG initiateMovement)));
      Name PlatoonLeader says
      prop (SOME (SLc (PL report1))))]::ins) WARN0 outs)  $\wedge$ 
( $M, Oi, Os$ ) satList
propCommandList
  [Name PlatoonLeader says prop (SOME (SLc (PL recon)));
   Name PlatoonLeader says
   prop (SOME (SLc (PL tentativePlan)));
   Name PlatoonSergeant says
   prop (SOME (SLc (PSG initiateMovement)));
   Name PlatoonLeader says prop (SOME (SLc (PL report1)))]

[PlatoonLeader_WARN0_exec_report1_justified_thm]
 $\vdash \forall NS \text{ Out } M \text{ } Oi \text{ } Os.$ 
TR ( $M, Oi, Os$ )
  (exec
    [SOME (SLc (PL recon)); SOME (SLc (PL tentativePlan));
     SOME (SLc (PSG initiateMovement));
     SOME (SLc (PL report1))])
  (CFG inputOK secContext secContextNull
    ([Name PlatoonLeader says
      prop (SOME (SLc (PL recon)));
      Name PlatoonLeader says
      prop (SOME (SLc (PL tentativePlan)));
      Name PlatoonSergeant says
      prop (SOME (SLc (PSG initiateMovement)));
      Name PlatoonLeader says
      prop (SOME (SLc (PL report1))))]::ins) WARN0 outs)
  (CFG inputOK secContext secContextNull ins
    (NS WARN0
      (exec
        [SOME (SLc (PL recon));
         SOME (SLc (PL tentativePlan));
         SOME (SLc (PSG initiateMovement));
         SOME (SLc (PL report1))])
      (Out WARN0
        (exec
          [SOME (SLc (PL recon));

```

```

        SOME (SLc (PL tentativePlan));
        SOME (SLc (PSG initiateMovement));
        SOME (SLc (PL report1)))]::outs))  $\iff$ 
authenticationTest inputOK
  [Name PlatoonLeader says prop (SOME (SLc (PL recon)));
   Name PlatoonLeader says
   prop (SOME (SLc (PL tentativePlan)));
   Name PlatoonSergeant says
   prop (SOME (SLc (PSG initiateMovement)));
   Name PlatoonLeader says
   prop (SOME (SLc (PL report1)))]  $\wedge$ 
CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secContextNull
   ([Name PlatoonLeader says
    prop (SOME (SLc (PL recon)));
    Name PlatoonLeader says
    prop (SOME (SLc (PL tentativePlan)));
    Name PlatoonSergeant says
    prop (SOME (SLc (PSG initiateMovement)));
    Name PlatoonLeader says
    prop (SOME (SLc (PL report1)))]::ins) WARNNO outs)  $\wedge$ 
(M, Oi, Os) satList
[prop (SOME (SLc (PL recon)));
 prop (SOME (SLc (PL tentativePlan)));
 prop (SOME (SLc (PSG initiateMovement)));
 prop (SOME (SLc (PL report1)))]

```

[PlatoonLeader_WARNO_exec_report1_lemma]

$\vdash \forall M \text{ } Oi \text{ } Os.$

```

CFGInterpret (M, Oi, Os)
  (CFG inputOK secContext secContextNull
   ([Name PlatoonLeader says
    prop (SOME (SLc (PL recon)));
    Name PlatoonLeader says
    prop (SOME (SLc (PL tentativePlan)));
    Name PlatoonSergeant says
    prop (SOME (SLc (PSG initiateMovement)));
    Name PlatoonLeader says
    prop (SOME (SLc (PL report1)))]::ins) WARNNO outs)  $\Rightarrow$ 
(M, Oi, Os) satList
propCommandList
  [Name PlatoonLeader says prop (SOME (SLc (PL recon)));
   Name PlatoonLeader says
   prop (SOME (SLc (PL tentativePlan)));
   Name PlatoonSergeant says
   prop (SOME (SLc (PSG initiateMovement)));
   Name PlatoonLeader says prop (SOME (SLc (PL report1)))]

```

[PlatoonSergeant_trap_plCommand_justified_lemma]

$\vdash \forall NS \text{ Out } M \text{ } Oi \text{ } Os.$
 $\text{TR } (M, Oi, Os)$
 $(\text{trap}$
 $\quad (\text{inputList}$
 $\quad \quad [\text{Name PlatoonSergeant says}$
 $\quad \quad \quad \text{prop (SOME (SLc (PL } plCommand)))})])])$
 $(\text{CFG inputOK secContext secContextNull}$
 $\quad ([\text{Name PlatoonSergeant says}$
 $\quad \quad \text{prop (SOME (SLc (PL } plCommand))}]::ins) \text{ } s \text{ } outs)$
 $(\text{CFG inputOK secContext secContextNull } ins$
 $\quad (NS \text{ } s$
 $\quad \quad (\text{trap}$
 $\quad \quad \quad (\text{inputList}$
 $\quad \quad \quad \quad [\text{Name PlatoonSergeant says}$
 $\quad \quad \quad \quad \quad \text{prop (SOME (SLc (PL } plCommand))})])])])$
 $\quad (Out \text{ } s$
 $\quad \quad (\text{trap}$
 $\quad \quad \quad (\text{inputList}$
 $\quad \quad \quad \quad [\text{Name PlatoonSergeant says}$
 $\quad \quad \quad \quad \quad \text{prop (SOME (SLc (PL } plCommand))})])])::$
 $\quad \quad \quad outs)) \iff$
 $\text{authenticationTest inputOK}$
 $\quad [\text{Name PlatoonSergeant says}$
 $\quad \quad \text{prop (SOME (SLc (PL } plCommand))})] \wedge$
 $\text{CFGInterpret } (M, Oi, Os)$
 $\quad (\text{CFG inputOK secContext secContextNull}$
 $\quad \quad ([\text{Name PlatoonSergeant says}$
 $\quad \quad \quad \text{prop (SOME (SLc (PL } plCommand))}]::ins) \text{ } s \text{ } outs) \wedge$
 $(M, Oi, Os) \text{ sat prop NONE}$

[PlatoonSergeant_trap_plCommand_justified_thm]

$\vdash \forall NS \text{ Out } M \text{ } Oi \text{ } Os.$
 $\text{TR } (M, Oi, Os) (\text{trap } [\text{SOME (SLc (PL } plCommand))])$
 $(\text{CFG inputOK secContext secContextNull}$
 $\quad ([\text{Name PlatoonSergeant says}$
 $\quad \quad \text{prop (SOME (SLc (PL } plCommand))}]::ins) \text{ } s \text{ } outs)$
 $(\text{CFG inputOK secContext secContextNull } ins$
 $\quad (NS \text{ } s (\text{trap } [\text{SOME (SLc (PL } plCommand))])])$
 $\quad (Out \text{ } s (\text{trap } [\text{SOME (SLc (PL } plCommand))}]::outs)) \iff$
 $\text{authenticationTest inputOK}$
 $\quad [\text{Name PlatoonSergeant says}$
 $\quad \quad \text{prop (SOME (SLc (PL } plCommand))})] \wedge$
 $\text{CFGInterpret } (M, Oi, Os)$
 $\quad (\text{CFG inputOK secContext secContextNull}$
 $\quad \quad ([\text{Name PlatoonSergeant says}$
 $\quad \quad \quad \text{prop (SOME (SLc (PL } plCommand))}]::ins) \text{ } s \text{ } outs) \wedge$
 $(M, Oi, Os) \text{ sat prop NONE}$

[PlatoonSergeant_trap_plCommand_lemma]

```

⊢ ∀ M Oi Os.
  CFGInterpret (M, Oi, Os)
    (CFG inputOK secContext secContextNull
      ([Name PlatoonSergeant says
        prop (SOME (SLc (PL plCommand))))]::ins) s outs) ⇒
    (M, Oi, Os) sat prop NONE

```

18 PlanPBType Theory

Built: 10 June 2018

Parent Theories: indexedLists, patternMatches

18.1 Datatypes

```

plCommand = receiveMission | warno | tentativePlan | recon
           | report1 | completePlan | opoid | supervise | report2
           | complete | plIncomplete | invalidPlCommand

psgCommand = initiateMovement | psgIncomplete
           | invalidPsgCommand

slCommand = PL plCommand | PSG psgCommand

slOutput = PlanPB | ReceiveMission | Warno | TentativePlan
          | InitiateMovement | Recon | Report1 | CompletePlan
          | Opoid | Supervise | Report2 | Complete
          | unAuthenticated | unAuthorized

slState = PLAN_PB | RECEIVE_MISSION | WARNO | TENTATIVE_PLAN
          | INITIATE_MOVEMENT | RECON | REPORT1 | COMPLETE_PLAN
          | OPOID | SUPERVISE | REPORT2 | COMPLETE

stateRole = PlatoonLeader | PlatoonSergeant

```

18.2 Theorems

[plCommand_distinct_clauses]

```

⊢ receiveMission ≠ warno ∧ receiveMission ≠ tentativePlan ∧
  receiveMission ≠ recon ∧ receiveMission ≠ report1 ∧
  receiveMission ≠ completePlan ∧ receiveMission ≠ opoid ∧
  receiveMission ≠ supervise ∧ receiveMission ≠ report2 ∧
  receiveMission ≠ complete ∧ receiveMission ≠ plIncomplete ∧
  receiveMission ≠ invalidPlCommand ∧ warno ≠ tentativePlan ∧
  warno ≠ recon ∧ warno ≠ report1 ∧ warno ≠ completePlan ∧
  warno ≠ opoid ∧ warno ≠ supervise ∧ warno ≠ report2 ∧
  warno ≠ complete ∧ warno ≠ plIncomplete ∧
  warno ≠ invalidPlCommand ∧ tentativePlan ≠ recon ∧
  tentativePlan ≠ report1 ∧ tentativePlan ≠ completePlan ∧

```

$$\begin{aligned}
& \text{tentativePlan} \neq \text{opoid} \wedge \text{tentativePlan} \neq \text{supervise} \wedge \\
& \text{tentativePlan} \neq \text{report2} \wedge \text{tentativePlan} \neq \text{complete} \wedge \\
& \text{tentativePlan} \neq \text{plIncomplete} \wedge \\
& \text{tentativePlan} \neq \text{invalidPlCommand} \wedge \text{recon} \neq \text{report1} \wedge \\
& \text{recon} \neq \text{completePlan} \wedge \text{recon} \neq \text{opoid} \wedge \text{recon} \neq \text{supervise} \wedge \\
& \text{recon} \neq \text{report2} \wedge \text{recon} \neq \text{complete} \wedge \text{recon} \neq \text{plIncomplete} \wedge \\
& \text{recon} \neq \text{invalidPlCommand} \wedge \text{report1} \neq \text{completePlan} \wedge \\
& \text{report1} \neq \text{opoid} \wedge \text{report1} \neq \text{supervise} \wedge \text{report1} \neq \text{report2} \wedge \\
& \text{report1} \neq \text{complete} \wedge \text{report1} \neq \text{plIncomplete} \wedge \\
& \text{report1} \neq \text{invalidPlCommand} \wedge \text{completePlan} \neq \text{opoid} \wedge \\
& \text{completePlan} \neq \text{supervise} \wedge \text{completePlan} \neq \text{report2} \wedge \\
& \text{completePlan} \neq \text{complete} \wedge \text{completePlan} \neq \text{plIncomplete} \wedge \\
& \text{completePlan} \neq \text{invalidPlCommand} \wedge \text{opoid} \neq \text{supervise} \wedge \\
& \text{opoid} \neq \text{report2} \wedge \text{opoid} \neq \text{complete} \wedge \text{opoid} \neq \text{plIncomplete} \wedge \\
& \text{opoid} \neq \text{invalidPlCommand} \wedge \text{supervise} \neq \text{report2} \wedge \\
& \text{supervise} \neq \text{complete} \wedge \text{supervise} \neq \text{plIncomplete} \wedge \\
& \text{supervise} \neq \text{invalidPlCommand} \wedge \text{report2} \neq \text{complete} \wedge \\
& \text{report2} \neq \text{plIncomplete} \wedge \text{report2} \neq \text{invalidPlCommand} \wedge \\
& \text{complete} \neq \text{plIncomplete} \wedge \text{complete} \neq \text{invalidPlCommand} \wedge \\
& \text{plIncomplete} \neq \text{invalidPlCommand}
\end{aligned}$$

[psgCommand_distinct_clauses]

$$\begin{aligned}
& \vdash \text{initiateMovement} \neq \text{psgIncomplete} \wedge \\
& \quad \text{initiateMovement} \neq \text{invalidPsgCommand} \wedge \\
& \quad \text{psgIncomplete} \neq \text{invalidPsgCommand}
\end{aligned}$$

[slCommand_distinct_clauses]

$$\vdash \forall a' a. \text{PL } a \neq \text{PSG } a'$$

[slCommand_one_one]

$$\begin{aligned}
& \vdash (\forall a a'. (\text{PL } a = \text{PL } a') \iff (a = a')) \wedge \\
& \quad \forall a a'. (\text{PSG } a = \text{PSG } a') \iff (a = a')
\end{aligned}$$

[slOutput_distinct_clauses]

$$\begin{aligned}
& \vdash \text{PlanPB} \neq \text{ReceiveMission} \wedge \text{PlanPB} \neq \text{Warno} \wedge \\
& \quad \text{PlanPB} \neq \text{TentativePlan} \wedge \text{PlanPB} \neq \text{InitiateMovement} \wedge \\
& \quad \text{PlanPB} \neq \text{Recon} \wedge \text{PlanPB} \neq \text{Report1} \wedge \text{PlanPB} \neq \text{CompletePlan} \wedge \\
& \quad \text{PlanPB} \neq \text{Opoid} \wedge \text{PlanPB} \neq \text{Supervise} \wedge \text{PlanPB} \neq \text{Report2} \wedge \\
& \quad \text{PlanPB} \neq \text{Complete} \wedge \text{PlanPB} \neq \text{unAuthenticated} \wedge \\
& \quad \text{PlanPB} \neq \text{unAuthorized} \wedge \text{ReceiveMission} \neq \text{Warno} \wedge \\
& \quad \text{ReceiveMission} \neq \text{TentativePlan} \wedge \\
& \quad \text{ReceiveMission} \neq \text{InitiateMovement} \wedge \text{ReceiveMission} \neq \text{Recon} \wedge \\
& \quad \text{ReceiveMission} \neq \text{Report1} \wedge \text{ReceiveMission} \neq \text{CompletePlan} \wedge \\
& \quad \text{ReceiveMission} \neq \text{Opoid} \wedge \text{ReceiveMission} \neq \text{Supervise} \wedge \\
& \quad \text{ReceiveMission} \neq \text{Report2} \wedge \text{ReceiveMission} \neq \text{Complete} \wedge \\
& \quad \text{ReceiveMission} \neq \text{unAuthenticated} \wedge \\
& \quad \text{ReceiveMission} \neq \text{unAuthorized} \wedge \text{Warno} \neq \text{TentativePlan} \wedge \\
& \quad \text{Warno} \neq \text{InitiateMovement} \wedge \text{Warno} \neq \text{Recon} \wedge \text{Warno} \neq \text{Report1} \wedge
\end{aligned}$$

$\text{Warno} \neq \text{CompletePlan} \wedge \text{Warno} \neq \text{Opoid} \wedge \text{Warno} \neq \text{Supervise} \wedge$
 $\text{Warno} \neq \text{Report2} \wedge \text{Warno} \neq \text{Complete} \wedge$
 $\text{Warno} \neq \text{unAuthenticated} \wedge \text{Warno} \neq \text{unAuthorized} \wedge$
 $\text{TentativePlan} \neq \text{InitiateMovement} \wedge \text{TentativePlan} \neq \text{Recon} \wedge$
 $\text{TentativePlan} \neq \text{Report1} \wedge \text{TentativePlan} \neq \text{CompletePlan} \wedge$
 $\text{TentativePlan} \neq \text{Opoid} \wedge \text{TentativePlan} \neq \text{Supervise} \wedge$
 $\text{TentativePlan} \neq \text{Report2} \wedge \text{TentativePlan} \neq \text{Complete} \wedge$
 $\text{TentativePlan} \neq \text{unAuthenticated} \wedge$
 $\text{TentativePlan} \neq \text{unAuthorized} \wedge \text{InitiateMovement} \neq \text{Recon} \wedge$
 $\text{InitiateMovement} \neq \text{Report1} \wedge$
 $\text{InitiateMovement} \neq \text{CompletePlan} \wedge \text{InitiateMovement} \neq \text{Opoid} \wedge$
 $\text{InitiateMovement} \neq \text{Supervise} \wedge \text{InitiateMovement} \neq \text{Report2} \wedge$
 $\text{InitiateMovement} \neq \text{Complete} \wedge$
 $\text{InitiateMovement} \neq \text{unAuthenticated} \wedge$
 $\text{InitiateMovement} \neq \text{unAuthorized} \wedge \text{Recon} \neq \text{Report1} \wedge$
 $\text{Recon} \neq \text{CompletePlan} \wedge \text{Recon} \neq \text{Opoid} \wedge \text{Recon} \neq \text{Supervise} \wedge$
 $\text{Recon} \neq \text{Report2} \wedge \text{Recon} \neq \text{Complete} \wedge$
 $\text{Recon} \neq \text{unAuthenticated} \wedge \text{Recon} \neq \text{unAuthorized} \wedge$
 $\text{Report1} \neq \text{CompletePlan} \wedge \text{Report1} \neq \text{Opoid} \wedge$
 $\text{Report1} \neq \text{Supervise} \wedge \text{Report1} \neq \text{Report2} \wedge$
 $\text{Report1} \neq \text{Complete} \wedge \text{Report1} \neq \text{unAuthenticated} \wedge$
 $\text{Report1} \neq \text{unAuthorized} \wedge \text{CompletePlan} \neq \text{Opoid} \wedge$
 $\text{CompletePlan} \neq \text{Supervise} \wedge \text{CompletePlan} \neq \text{Report2} \wedge$
 $\text{CompletePlan} \neq \text{Complete} \wedge \text{CompletePlan} \neq \text{unAuthenticated} \wedge$
 $\text{CompletePlan} \neq \text{unAuthorized} \wedge \text{Opoid} \neq \text{Supervise} \wedge$
 $\text{Opoid} \neq \text{Report2} \wedge \text{Opoid} \neq \text{Complete} \wedge$
 $\text{Opoid} \neq \text{unAuthenticated} \wedge \text{Opoid} \neq \text{unAuthorized} \wedge$
 $\text{Supervise} \neq \text{Report2} \wedge \text{Supervise} \neq \text{Complete} \wedge$
 $\text{Supervise} \neq \text{unAuthenticated} \wedge \text{Supervise} \neq \text{unAuthorized} \wedge$
 $\text{Report2} \neq \text{Complete} \wedge \text{Report2} \neq \text{unAuthenticated} \wedge$
 $\text{Report2} \neq \text{unAuthorized} \wedge \text{Complete} \neq \text{unAuthenticated} \wedge$
 $\text{Complete} \neq \text{unAuthorized} \wedge \text{unAuthenticated} \neq \text{unAuthorized}$

[slRole_distinct_clauses]

$\vdash \text{PlatoonLeader} \neq \text{PlatoonSergeant}$

[slState_distinct_clauses]

$\vdash \text{PLAN_PB} \neq \text{RECEIVE_MISSION} \wedge \text{PLAN_PB} \neq \text{WARNO} \wedge$
 $\text{PLAN_PB} \neq \text{TENTATIVE_PLAN} \wedge \text{PLAN_PB} \neq \text{INITIATE_MOVEMENT} \wedge$
 $\text{PLAN_PB} \neq \text{RECON} \wedge \text{PLAN_PB} \neq \text{REPORT1} \wedge$
 $\text{PLAN_PB} \neq \text{COMPLETE_PLAN} \wedge \text{PLAN_PB} \neq \text{OPOID} \wedge$
 $\text{PLAN_PB} \neq \text{SUPERVISE} \wedge \text{PLAN_PB} \neq \text{REPORT2} \wedge$
 $\text{PLAN_PB} \neq \text{COMPLETE} \wedge \text{RECEIVE_MISSION} \neq \text{WARNO} \wedge$
 $\text{RECEIVE_MISSION} \neq \text{TENTATIVE_PLAN} \wedge$
 $\text{RECEIVE_MISSION} \neq \text{INITIATE_MOVEMENT} \wedge$
 $\text{RECEIVE_MISSION} \neq \text{RECON} \wedge \text{RECEIVE_MISSION} \neq \text{REPORT1} \wedge$
 $\text{RECEIVE_MISSION} \neq \text{COMPLETE_PLAN} \wedge \text{RECEIVE_MISSION} \neq \text{OPOID} \wedge$
 $\text{RECEIVE_MISSION} \neq \text{SUPERVISE} \wedge \text{RECEIVE_MISSION} \neq \text{REPORT2} \wedge$
 $\text{RECEIVE_MISSION} \neq \text{COMPLETE} \wedge \text{WARNO} \neq \text{TENTATIVE_PLAN} \wedge$

```

WARNO ≠ INITIATE_MOVEMENT ∧ WARNO ≠ RECON ∧ WARNO ≠ REPORT1 ∧
WARNO ≠ COMPLETE_PLAN ∧ WARNO ≠ OPOID ∧ WARNO ≠ SUPERVISE ∧
WARNO ≠ REPORT2 ∧ WARNO ≠ COMPLETE ∧
TENTATIVE_PLAN ≠ INITIATE_MOVEMENT ∧ TENTATIVE_PLAN ≠ RECON ∧
TENTATIVE_PLAN ≠ REPORT1 ∧ TENTATIVE_PLAN ≠ COMPLETE_PLAN ∧
TENTATIVE_PLAN ≠ OPOID ∧ TENTATIVE_PLAN ≠ SUPERVISE ∧
TENTATIVE_PLAN ≠ REPORT2 ∧ TENTATIVE_PLAN ≠ COMPLETE ∧
INITIATE_MOVEMENT ≠ RECON ∧ INITIATE_MOVEMENT ≠ REPORT1 ∧
INITIATE_MOVEMENT ≠ COMPLETE_PLAN ∧
INITIATE_MOVEMENT ≠ OPOID ∧ INITIATE_MOVEMENT ≠ SUPERVISE ∧
INITIATE_MOVEMENT ≠ REPORT2 ∧ INITIATE_MOVEMENT ≠ COMPLETE ∧
RECON ≠ REPORT1 ∧ RECON ≠ COMPLETE_PLAN ∧ RECON ≠ OPOID ∧
RECON ≠ SUPERVISE ∧ RECON ≠ REPORT2 ∧ RECON ≠ COMPLETE ∧
REPORT1 ≠ COMPLETE_PLAN ∧ REPORT1 ≠ OPOID ∧
REPORT1 ≠ SUPERVISE ∧ REPORT1 ≠ REPORT2 ∧
REPORT1 ≠ COMPLETE ∧ COMPLETE_PLAN ≠ OPOID ∧
COMPLETE_PLAN ≠ SUPERVISE ∧ COMPLETE_PLAN ≠ REPORT2 ∧
COMPLETE_PLAN ≠ COMPLETE ∧ OPOID ≠ SUPERVISE ∧
OPOID ≠ REPORT2 ∧ OPOID ≠ COMPLETE ∧ SUPERVISE ≠ REPORT2 ∧
SUPERVISE ≠ COMPLETE ∧ REPORT2 ≠ COMPLETE

```

19 PlanPBDef Theory

Built: 10 June 2018

Parent Theories: PlanPBType, acfFoundation, OMNIType

19.1 Definitions

[PL_notWARNO_Auth_def]

```

⊢ ∀ cmd.
  PL_notWARNO_Auth cmd =
    if cmd = report1 then prop NONE
    else
      Name PlatoonLeader says prop (SOME (SLc (PL cmd))) impf
      Name PlatoonLeader controls prop (SOME (SLc (PL cmd)))

```

[PL_WARNO_Auth_def]

```

⊢ PL_WARNO_Auth =
  prop (SOME (SLc (PL recon))) impf
  prop (SOME (SLc (PL tentativePlan))) impf
  prop (SOME (SLc (PSG initiateMovement))) impf
  Name PlatoonLeader controls prop (SOME (SLc (PL report1)))

```

[secContext_def]

```

⊢ ∀ s x.
  secContext s x =
    if s = WARNO then

```



```

getInitMove
  (Name PlatoonSergeant says prop (SOME (ESCc v146)))::
    xs) =
getInitMove xs) ∧
(∀ xs v150.
  getInitMove
    (Name PlatoonSergeant says prop (SOME (SLc (PL v150))))::
      xs) =
getInitMove xs) ∧
(∀ xs.
  getInitMove
    (Name PlatoonSergeant says
      prop (SOME (SLc (PSG psgIncomplete))))::xs) =
getInitMove xs) ∧
(∀ xs.
  getInitMove
    (Name PlatoonSergeant says
      prop (SOME (SLc (PSG invalidPsgCommand))))::xs) =
getInitMove xs) ∧
(∀ xs v68 v136 v135.
  getInitMove (v135 meet v136 says prop v68::xs) =
getInitMove xs) ∧
(∀ xs v68 v138 v137.
  getInitMove (v137 quoting v138 says prop v68::xs) =
getInitMove xs) ∧
(∀ xs v69 v12.
  getInitMove (v12 says notf v69::xs) = getInitMove xs) ∧
(∀ xs v71 v70 v12.
  getInitMove (v12 says (v70 andf v71)::xs) =
getInitMove xs) ∧
(∀ xs v73 v72 v12.
  getInitMove (v12 says (v72 orf v73)::xs) =
getInitMove xs) ∧
(∀ xs v75 v74 v12.
  getInitMove (v12 says (v74 impf v75)::xs) =
getInitMove xs) ∧
(∀ xs v77 v76 v12.
  getInitMove (v12 says (v76 eqf v77)::xs) =
getInitMove xs) ∧
(∀ xs v79 v78 v12.
  getInitMove (v12 says v78 says v79::xs) =
getInitMove xs) ∧
(∀ xs v81 v80 v12.
  getInitMove (v12 says v80 speaks_for v81::xs) =
getInitMove xs) ∧
(∀ xs v83 v82 v12.
  getInitMove (v12 says v82 controls v83::xs) =
getInitMove xs) ∧
(∀ xs v86 v85 v84 v12.

```

```

    getInitMove (v12 says reps v84 v85 v86::xs) =
    getInitMove xs) ∧
  (∀ xs v88 v87 v12.
    getInitMove (v12 says v87 domi v88::xs) =
    getInitMove xs) ∧
  (∀ xs v90 v89 v12.
    getInitMove (v12 says v89 eqi v90::xs) = getInitMove xs) ∧
  (∀ xs v92 v91 v12.
    getInitMove (v12 says v91 doms v92::xs) =
    getInitMove xs) ∧
  (∀ xs v94 v93 v12.
    getInitMove (v12 says v93 eqs v94::xs) = getInitMove xs) ∧
  (∀ xs v96 v95 v12.
    getInitMove (v12 says v95 eqn v96::xs) = getInitMove xs) ∧
  (∀ xs v98 v97 v12.
    getInitMove (v12 says v97 lte v98::xs) = getInitMove xs) ∧
  (∀ xs v99 v12 v100.
    getInitMove (v12 says v99 lt v100::xs) = getInitMove xs) ∧
  (∀ xs v15 v14.
    getInitMove (v14 speaks_for v15::xs) = getInitMove xs) ∧
  (∀ xs v17 v16.
    getInitMove (v16 controls v17::xs) = getInitMove xs) ∧
  (∀ xs v20 v19 v18.
    getInitMove (reps v18 v19 v20::xs) = getInitMove xs) ∧
  (∀ xs v22 v21.
    getInitMove (v21 domi v22::xs) = getInitMove xs) ∧
  (∀ xs v24 v23.
    getInitMove (v23 eqi v24::xs) = getInitMove xs) ∧
  (∀ xs v26 v25.
    getInitMove (v25 doms v26::xs) = getInitMove xs) ∧
  (∀ xs v28 v27.
    getInitMove (v27 eqs v28::xs) = getInitMove xs) ∧
  (∀ xs v30 v29.
    getInitMove (v29 eqn v30::xs) = getInitMove xs) ∧
  (∀ xs v32 v31.
    getInitMove (v31 lte v32::xs) = getInitMove xs) ∧
  ∀ xs v34 v33. getInitMove (v33 lt v34::xs) = getInitMove xs

```

[getInitMove_ind]

```

⊢ ∀ P.
  P [] ∧
  (∀ xs.
    P
      (Name PlatoonSergeant says
        prop (SOME (SLc (PSG initiateMovement)))::xs)) ∧
  (∀ xs. P xs ⇒ P (TT::xs)) ∧ (∀ xs. P xs ⇒ P (FF::xs)) ∧
  (∀ v2 xs. P xs ⇒ P (prop v2::xs)) ∧
  (∀ v3 xs. P xs ⇒ P (notf v3::xs)) ∧
  (∀ v4 v5 xs. P xs ⇒ P (v4 andf v5::xs)) ∧

```

$$\begin{aligned}
& (\forall v_6 v_7 xs. P xs \Rightarrow P (v_6 \text{ orf } v_7 :: xs)) \wedge \\
& (\forall v_8 v_9 xs. P xs \Rightarrow P (v_8 \text{ impf } v_9 :: xs)) \wedge \\
& (\forall v_{10} v_{11} xs. P xs \Rightarrow P (v_{10} \text{ eqf } v_{11} :: xs)) \wedge \\
& (\forall v_{12} xs. P xs \Rightarrow P (v_{12} \text{ says TT} :: xs)) \wedge \\
& (\forall v_{12} xs. P xs \Rightarrow P (v_{12} \text{ says FF} :: xs)) \wedge \\
& (\forall v_{134} xs. P xs \Rightarrow P (\text{Name } v_{134} \text{ says prop NONE} :: xs)) \wedge \\
& (\forall v_{144} xs. \\
& \quad P xs \Rightarrow \\
& \quad P (\text{Name PlatoonLeader says prop (SOME } v_{144}) :: xs)) \wedge \\
& (\forall v_{146} xs. \\
& \quad P xs \Rightarrow \\
& \quad P \\
& \quad (\text{Name PlatoonSergeant says prop (SOME (ESCc } v_{146})) :: xs)) \wedge \\
& (\forall v_{150} xs. \\
& \quad P xs \Rightarrow \\
& \quad P \\
& \quad (\text{Name PlatoonSergeant says} \\
& \quad \text{prop (SOME (SLc (PL } v_{150})) :: xs)) \wedge \\
& (\forall xs. \\
& \quad P xs \Rightarrow \\
& \quad P \\
& \quad (\text{Name PlatoonSergeant says} \\
& \quad \text{prop (SOME (SLc (PSG psgIncomplete)) :: xs)) \wedge \\
& (\forall xs. \\
& \quad P xs \Rightarrow \\
& \quad P \\
& \quad (\text{Name PlatoonSergeant says} \\
& \quad \text{prop (SOME (SLc (PSG invalidPsgCommand)) :: xs)) \wedge \\
& (\forall v_{135} v_{136} v_{68} xs. \\
& \quad P xs \Rightarrow P (v_{135} \text{ meet } v_{136} \text{ says prop } v_{68} :: xs)) \wedge \\
& (\forall v_{137} v_{138} v_{68} xs. \\
& \quad P xs \Rightarrow P (v_{137} \text{ quoting } v_{138} \text{ says prop } v_{68} :: xs)) \wedge \\
& (\forall v_{12} v_{69} xs. P xs \Rightarrow P (v_{12} \text{ says notf } v_{69} :: xs)) \wedge \\
& (\forall v_{12} v_{70} v_{71} xs. P xs \Rightarrow P (v_{12} \text{ says (} v_{70} \text{ andf } v_{71}) :: xs)) \wedge \\
& (\forall v_{12} v_{72} v_{73} xs. P xs \Rightarrow P (v_{12} \text{ says (} v_{72} \text{ orf } v_{73}) :: xs)) \wedge \\
& (\forall v_{12} v_{74} v_{75} xs. P xs \Rightarrow P (v_{12} \text{ says (} v_{74} \text{ impf } v_{75}) :: xs)) \wedge \\
& (\forall v_{12} v_{76} v_{77} xs. P xs \Rightarrow P (v_{12} \text{ says (} v_{76} \text{ eqf } v_{77}) :: xs)) \wedge \\
& (\forall v_{12} v_{78} v_{79} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{78} \text{ says } v_{79} :: xs)) \wedge \\
& (\forall v_{12} v_{80} v_{81} xs. \\
& \quad P xs \Rightarrow P (v_{12} \text{ says } v_{80} \text{ speaks_for } v_{81} :: xs)) \wedge \\
& (\forall v_{12} v_{82} v_{83} xs. \\
& \quad P xs \Rightarrow P (v_{12} \text{ says } v_{82} \text{ controls } v_{83} :: xs)) \wedge \\
& (\forall v_{12} v_{84} v_{85} v_{86} xs. \\
& \quad P xs \Rightarrow P (v_{12} \text{ says reps } v_{84} v_{85} v_{86} :: xs)) \wedge \\
& (\forall v_{12} v_{87} v_{88} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{87} \text{ domi } v_{88} :: xs)) \wedge \\
& (\forall v_{12} v_{89} v_{90} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{89} \text{ eqi } v_{90} :: xs)) \wedge \\
& (\forall v_{12} v_{91} v_{92} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{91} \text{ doms } v_{92} :: xs)) \wedge \\
& (\forall v_{12} v_{93} v_{94} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{93} \text{ eqs } v_{94} :: xs)) \wedge
\end{aligned}$$

$$\begin{aligned}
& (\forall v_{12} v_{95} v_{96} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{95} \text{ eqn } v_{96} :: xs)) \wedge \\
& (\forall v_{12} v_{97} v_{98} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{97} \text{ lte } v_{98} :: xs)) \wedge \\
& (\forall v_{12} v_{99} v_{100} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{99} \text{ lt } v_{100} :: xs)) \wedge \\
& (\forall v_{14} v_{15} xs. P xs \Rightarrow P (v_{14} \text{ speaks_for } v_{15} :: xs)) \wedge \\
& (\forall v_{16} v_{17} xs. P xs \Rightarrow P (v_{16} \text{ controls } v_{17} :: xs)) \wedge \\
& (\forall v_{18} v_{19} v_{20} xs. P xs \Rightarrow P (\text{reps } v_{18} v_{19} v_{20} :: xs)) \wedge \\
& (\forall v_{21} v_{22} xs. P xs \Rightarrow P (v_{21} \text{ domi } v_{22} :: xs)) \wedge \\
& (\forall v_{23} v_{24} xs. P xs \Rightarrow P (v_{23} \text{ eqi } v_{24} :: xs)) \wedge \\
& (\forall v_{25} v_{26} xs. P xs \Rightarrow P (v_{25} \text{ doms } v_{26} :: xs)) \wedge \\
& (\forall v_{27} v_{28} xs. P xs \Rightarrow P (v_{27} \text{ eqs } v_{28} :: xs)) \wedge \\
& (\forall v_{29} v_{30} xs. P xs \Rightarrow P (v_{29} \text{ eqn } v_{30} :: xs)) \wedge \\
& (\forall v_{31} v_{32} xs. P xs \Rightarrow P (v_{31} \text{ lte } v_{32} :: xs)) \wedge \\
& (\forall v_{33} v_{34} xs. P xs \Rightarrow P (v_{33} \text{ lt } v_{34} :: xs)) \Rightarrow \\
& \forall v. P v
\end{aligned}$$

[getPlCom_def]

$$\begin{aligned}
& \vdash (\text{getPlCom } [] = \text{invalidPlCommand}) \wedge \\
& (\forall xs \text{ cmd.} \\
& \quad \text{getPlCom} \\
& \quad \quad (\text{Name PlatoonLeader says prop (SOME (SLc (PL cmd)))}) :: \\
& \quad \quad \quad xs) = \\
& \quad \quad \text{cmd}) \wedge (\forall xs. \text{getPlCom (TT :: xs)} = \text{getPlCom } xs) \wedge \\
& (\forall xs. \text{getPlCom (FF :: xs)} = \text{getPlCom } xs) \wedge \\
& (\forall xs v_2. \text{getPlCom (prop } v_2 :: xs) = \text{getPlCom } xs) \wedge \\
& (\forall xs v_3. \text{getPlCom (notf } v_3 :: xs) = \text{getPlCom } xs) \wedge \\
& (\forall xs v_5 v_4. \text{getPlCom (v}_4 \text{ andf v}_5 :: xs) = \text{getPlCom } xs) \wedge \\
& (\forall xs v_7 v_6. \text{getPlCom (v}_6 \text{ orf v}_7 :: xs) = \text{getPlCom } xs) \wedge \\
& (\forall xs v_9 v_8. \text{getPlCom (v}_8 \text{ impf v}_9 :: xs) = \text{getPlCom } xs) \wedge \\
& (\forall xs v_{11} v_{10}. \text{getPlCom (v}_{10} \text{ eqf v}_{11} :: xs) = \text{getPlCom } xs) \wedge \\
& (\forall xs v_{12}. \text{getPlCom (v}_{12} \text{ says TT :: xs)} = \text{getPlCom } xs) \wedge \\
& (\forall xs v_{12}. \text{getPlCom (v}_{12} \text{ says FF :: xs)} = \text{getPlCom } xs) \wedge \\
& (\forall xs v_{134}. \\
& \quad \text{getPlCom (Name v}_{134} \text{ says prop NONE :: xs)} = \text{getPlCom } xs) \wedge \\
& (\forall xs v_{146}. \\
& \quad \text{getPlCom} \\
& \quad \quad (\text{Name PlatoonLeader says prop (SOME (ESCc v}_{146})}) :: xs) = \\
& \quad \quad \text{getPlCom } xs) \wedge \\
& (\forall xs v_{151}. \\
& \quad \text{getPlCom} \\
& \quad \quad (\text{Name PlatoonLeader says prop (SOME (SLc (PSG v}_{151})}) :: xs) = \\
& \quad \quad \quad xs) = \\
& \quad \quad \text{getPlCom } xs) \wedge \\
& (\forall xs v_{144}. \\
& \quad \text{getPlCom} \\
& \quad \quad (\text{Name PlatoonSergeant says prop (SOME v}_{144}) :: xs) = \\
& \quad \quad \text{getPlCom } xs) \wedge \\
& (\forall xs v_{68} v_{136} v_{135}. \\
& \quad \text{getPlCom (v}_{135} \text{ meet v}_{136} \text{ says prop v}_{68} :: xs) = \\
& \quad \text{getPlCom } xs) \wedge
\end{aligned}$$

$(\forall xs \ v_{68} \ v_{138} \ v_{137}.$
 $\quad \text{getPlCom } (v_{137} \text{ quoting } v_{138} \text{ says prop } v_{68}::xs) =$
 $\quad \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{69} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says notf } v_{69}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{71} \ v_{70} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } (v_{70} \text{ andf } v_{71})::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{73} \ v_{72} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } (v_{72} \text{ orf } v_{73})::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{75} \ v_{74} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } (v_{74} \text{ impf } v_{75})::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{77} \ v_{76} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } (v_{76} \text{ eqf } v_{77})::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{79} \ v_{78} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } v_{78} \text{ says } v_{79}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{81} \ v_{80} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } v_{80} \text{ speaks_for } v_{81}::xs) =$
 $\quad \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{83} \ v_{82} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } v_{82} \text{ controls } v_{83}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{86} \ v_{85} \ v_{84} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says reps } v_{84} \ v_{85} \ v_{86}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{88} \ v_{87} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } v_{87} \text{ domi } v_{88}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{90} \ v_{89} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } v_{89} \text{ eqi } v_{90}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{92} \ v_{91} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } v_{91} \text{ doms } v_{92}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{94} \ v_{93} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } v_{93} \text{ eqs } v_{94}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{96} \ v_{95} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } v_{95} \text{ eqn } v_{96}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{98} \ v_{97} \ v_{12}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } v_{97} \text{ lte } v_{98}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{99} \ v_{12} \ v_{100}.$
 $\quad \text{getPlCom } (v_{12} \text{ says } v_{99} \text{ lt } v_{100}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{15} \ v_{14}.$
 $\quad \text{getPlCom } (v_{14} \text{ speaks_for } v_{15}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{17} \ v_{16}.$
 $\quad \text{getPlCom } (v_{16} \text{ controls } v_{17}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{20} \ v_{19} \ v_{18}.$
 $\quad \text{getPlCom } (\text{reps } v_{18} \ v_{19} \ v_{20}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{22} \ v_{21}.$ $\text{getPlCom } (v_{21} \text{ domi } v_{22}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{24} \ v_{23}.$ $\text{getPlCom } (v_{23} \text{ eqi } v_{24}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{26} \ v_{25}.$ $\text{getPlCom } (v_{25} \text{ doms } v_{26}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{28} \ v_{27}.$ $\text{getPlCom } (v_{27} \text{ eqs } v_{28}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{30} \ v_{29}.$ $\text{getPlCom } (v_{29} \text{ eqn } v_{30}::xs) = \text{getPlCom } xs) \wedge$
 $(\forall xs \ v_{32} \ v_{31}.$ $\text{getPlCom } (v_{31} \text{ lte } v_{32}::xs) = \text{getPlCom } xs) \wedge$
 $\forall xs \ v_{34} \ v_{33}.$ $\text{getPlCom } (v_{33} \text{ lt } v_{34}::xs) = \text{getPlCom } xs$

[getPlCom_ind]

$$\begin{aligned}
& \vdash \forall P. \\
& \quad P \square \wedge \\
& \quad (\forall cmd \ xs. \\
& \quad \quad P \\
& \quad \quad \quad (\text{Name PlatoonLeader says prop (SOME (SLc (PL cmd)))}) :: \\
& \quad \quad \quad \quad xs)) \wedge (\forall xs. P \ xs \Rightarrow P \ (\text{TT} :: xs)) \wedge \\
& \quad (\forall xs. P \ xs \Rightarrow P \ (\text{FF} :: xs)) \wedge \\
& \quad (\forall v_2 \ xs. P \ xs \Rightarrow P \ (\text{prop } v_2 :: xs)) \wedge \\
& \quad (\forall v_3 \ xs. P \ xs \Rightarrow P \ (\text{notf } v_3 :: xs)) \wedge \\
& \quad (\forall v_4 \ v_5 \ xs. P \ xs \Rightarrow P \ (v_4 \ \text{andf } v_5 :: xs)) \wedge \\
& \quad (\forall v_6 \ v_7 \ xs. P \ xs \Rightarrow P \ (v_6 \ \text{orf } v_7 :: xs)) \wedge \\
& \quad (\forall v_8 \ v_9 \ xs. P \ xs \Rightarrow P \ (v_8 \ \text{impf } v_9 :: xs)) \wedge \\
& \quad (\forall v_{10} \ v_{11} \ xs. P \ xs \Rightarrow P \ (v_{10} \ \text{eqf } v_{11} :: xs)) \wedge \\
& \quad (\forall v_{12} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says TT} :: xs)) \wedge \\
& \quad (\forall v_{12} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says FF} :: xs)) \wedge \\
& \quad (\forall v_{134} \ xs. P \ xs \Rightarrow P \ (\text{Name } v_{134} \ \text{says prop NONE} :: xs)) \wedge \\
& \quad (\forall v_{146} \ xs. \\
& \quad \quad P \ xs \Rightarrow \\
& \quad \quad \quad P \\
& \quad \quad \quad \quad (\text{Name PlatoonLeader says prop (SOME (ESCc } v_{146})) :: \\
& \quad \quad \quad \quad \quad xs)) \wedge \\
& \quad (\forall v_{151} \ xs. \\
& \quad \quad P \ xs \Rightarrow \\
& \quad \quad \quad P \\
& \quad \quad \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \quad \quad \quad \text{prop (SOME (SLc (PSG } v_{151}))) :: xs)) \wedge \\
& \quad (\forall v_{144} \ xs. \\
& \quad \quad P \ xs \Rightarrow \\
& \quad \quad \quad P \ (\text{Name PlatoonSergeant says prop (SOME } v_{144}) :: xs)) \wedge \\
& \quad (\forall v_{135} \ v_{136} \ v_{68} \ xs. \\
& \quad \quad P \ xs \Rightarrow P \ (v_{135} \ \text{meet } v_{136} \ \text{says prop } v_{68} :: xs)) \wedge \\
& \quad (\forall v_{137} \ v_{138} \ v_{68} \ xs. \\
& \quad \quad P \ xs \Rightarrow P \ (v_{137} \ \text{quoting } v_{138} \ \text{says prop } v_{68} :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{69} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says notf } v_{69} :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{70} \ v_{71} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } (v_{70} \ \text{andf } v_{71}) :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{72} \ v_{73} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } (v_{72} \ \text{orf } v_{73}) :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{74} \ v_{75} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } (v_{74} \ \text{impf } v_{75}) :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{76} \ v_{77} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } (v_{76} \ \text{eqf } v_{77}) :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{78} \ v_{79} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } v_{78} \ \text{says } v_{79} :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{80} \ v_{81} \ xs. \\
& \quad \quad P \ xs \Rightarrow P \ (v_{12} \ \text{says } v_{80} \ \text{speaks_for } v_{81} :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{82} \ v_{83} \ xs. \\
& \quad \quad P \ xs \Rightarrow P \ (v_{12} \ \text{says } v_{82} \ \text{controls } v_{83} :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{84} \ v_{85} \ v_{86} \ xs. \\
& \quad \quad P \ xs \Rightarrow P \ (v_{12} \ \text{says reps } v_{84} \ v_{85} \ v_{86} :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{87} \ v_{88} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } v_{87} \ \text{domi } v_{88} :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{89} \ v_{90} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } v_{89} \ \text{eqi } v_{90} :: xs)) \wedge \\
& \quad (\forall v_{12} \ v_{91} \ v_{92} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } v_{91} \ \text{doms } v_{92} :: xs)) \wedge
\end{aligned}$$

$$\begin{aligned}
& (\forall v_{12} v_{93} v_{94} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{93} \text{ eqs } v_{94} :: xs)) \wedge \\
& (\forall v_{12} v_{95} v_{96} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{95} \text{ eqn } v_{96} :: xs)) \wedge \\
& (\forall v_{12} v_{97} v_{98} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{97} \text{ lte } v_{98} :: xs)) \wedge \\
& (\forall v_{12} v_{99} v_{100} xs. P xs \Rightarrow P (v_{12} \text{ says } v_{99} \text{ lt } v_{100} :: xs)) \wedge \\
& (\forall v_{14} v_{15} xs. P xs \Rightarrow P (v_{14} \text{ speaks_for } v_{15} :: xs)) \wedge \\
& (\forall v_{16} v_{17} xs. P xs \Rightarrow P (v_{16} \text{ controls } v_{17} :: xs)) \wedge \\
& (\forall v_{18} v_{19} v_{20} xs. P xs \Rightarrow P (\text{reps } v_{18} v_{19} v_{20} :: xs)) \wedge \\
& (\forall v_{21} v_{22} xs. P xs \Rightarrow P (v_{21} \text{ domi } v_{22} :: xs)) \wedge \\
& (\forall v_{23} v_{24} xs. P xs \Rightarrow P (v_{23} \text{ eqi } v_{24} :: xs)) \wedge \\
& (\forall v_{25} v_{26} xs. P xs \Rightarrow P (v_{25} \text{ doms } v_{26} :: xs)) \wedge \\
& (\forall v_{27} v_{28} xs. P xs \Rightarrow P (v_{27} \text{ eqs } v_{28} :: xs)) \wedge \\
& (\forall v_{29} v_{30} xs. P xs \Rightarrow P (v_{29} \text{ eqn } v_{30} :: xs)) \wedge \\
& (\forall v_{31} v_{32} xs. P xs \Rightarrow P (v_{31} \text{ lte } v_{32} :: xs)) \wedge \\
& (\forall v_{33} v_{34} xs. P xs \Rightarrow P (v_{33} \text{ lt } v_{34} :: xs)) \Rightarrow \\
& \forall v. P v
\end{aligned}$$

[getPsgCom_def]

$$\begin{aligned}
& \vdash (\text{getPsgCom } [] = \text{invalidPsgCommand}) \wedge \\
& (\forall xs \text{ cmd.} \\
& \quad \text{getPsgCom} \\
& \quad \quad (\text{Name PlatoonSergeant says prop (SOME (SLc (PSG cmd)))}) :: \\
& \quad \quad \quad xs) = \\
& \quad \quad \text{cmd}) \wedge (\forall xs. \text{getPsgCom (TT :: xs)} = \text{getPsgCom xs}) \wedge \\
& (\forall xs. \text{getPsgCom (FF :: xs)} = \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_2. \text{getPsgCom (prop } v_2 :: xs) = \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_3. \text{getPsgCom (notf } v_3 :: xs) = \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_5 \ v_4. \text{getPsgCom (v}_4 \text{ andf } v_5 :: xs) = \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_7 \ v_6. \text{getPsgCom (v}_6 \text{ orf } v_7 :: xs) = \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_9 \ v_8. \text{getPsgCom (v}_8 \text{ impf } v_9 :: xs) = \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_{11} \ v_{10}. \text{getPsgCom (v}_{10} \text{ eqf } v_{11} :: xs) = \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_{12}. \text{getPsgCom (v}_{12} \text{ says TT :: xs)} = \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_{12}. \text{getPsgCom (v}_{12} \text{ says FF :: xs)} = \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_{134}. \\
& \quad \text{getPsgCom (Name v}_{134} \text{ says prop NONE :: xs)} = \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_{144}. \\
& \quad \text{getPsgCom (Name PlatoonLeader says prop (SOME v}_{144}) :: xs) =} \\
& \quad \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_{146}. \\
& \quad \text{getPsgCom} \\
& \quad \quad (\text{Name PlatoonSergeant says prop (SOME (ESCc v}_{146}) ::} \\
& \quad \quad \quad xs) = \\
& \quad \quad \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_{150}. \\
& \quad \text{getPsgCom} \\
& \quad \quad (\text{Name PlatoonSergeant says prop (SOME (SLc (PL v}_{150})) ::} \\
& \quad \quad \quad xs) = \\
& \quad \quad \text{getPsgCom xs}) \wedge \\
& (\forall xs \ v_{68} \ v_{136} \ v_{135}. \\
& \quad \text{getPsgCom (v}_{135} \text{ meet v}_{136} \text{ says prop v}_{68} :: xs) =}
\end{aligned}$$

```

    getPsgCom xs) ∧
  (∀ xs v68 v138 v137.
    getPsgCom (v137 quoting v138 says prop v68::xs) =
    getPsgCom xs) ∧
  (∀ xs v69 v12.
    getPsgCom (v12 says notf v69::xs) = getPsgCom xs) ∧
  (∀ xs v71 v70 v12.
    getPsgCom (v12 says (v70 andf v71)::xs) = getPsgCom xs) ∧
  (∀ xs v73 v72 v12.
    getPsgCom (v12 says (v72 orf v73)::xs) = getPsgCom xs) ∧
  (∀ xs v75 v74 v12.
    getPsgCom (v12 says (v74 impf v75)::xs) = getPsgCom xs) ∧
  (∀ xs v77 v76 v12.
    getPsgCom (v12 says (v76 eqf v77)::xs) = getPsgCom xs) ∧
  (∀ xs v79 v78 v12.
    getPsgCom (v12 says v78 says v79::xs) = getPsgCom xs) ∧
  (∀ xs v81 v80 v12.
    getPsgCom (v12 says v80 speaks_for v81::xs) =
    getPsgCom xs) ∧
  (∀ xs v83 v82 v12.
    getPsgCom (v12 says v82 controls v83::xs) =
    getPsgCom xs) ∧
  (∀ xs v86 v85 v84 v12.
    getPsgCom (v12 says reps v84 v85 v86::xs) =
    getPsgCom xs) ∧
  (∀ xs v88 v87 v12.
    getPsgCom (v12 says v87 domi v88::xs) = getPsgCom xs) ∧
  (∀ xs v90 v89 v12.
    getPsgCom (v12 says v89 eqi v90::xs) = getPsgCom xs) ∧
  (∀ xs v92 v91 v12.
    getPsgCom (v12 says v91 doms v92::xs) = getPsgCom xs) ∧
  (∀ xs v94 v93 v12.
    getPsgCom (v12 says v93 eqs v94::xs) = getPsgCom xs) ∧
  (∀ xs v96 v95 v12.
    getPsgCom (v12 says v95 eqn v96::xs) = getPsgCom xs) ∧
  (∀ xs v98 v97 v12.
    getPsgCom (v12 says v97 lte v98::xs) = getPsgCom xs) ∧
  (∀ xs v99 v12 v100.
    getPsgCom (v12 says v99 lt v100::xs) = getPsgCom xs) ∧
  (∀ xs v15 v14.
    getPsgCom (v14 speaks_for v15::xs) = getPsgCom xs) ∧
  (∀ xs v17 v16.
    getPsgCom (v16 controls v17::xs) = getPsgCom xs) ∧
  (∀ xs v20 v19 v18.
    getPsgCom (reps v18 v19 v20::xs) = getPsgCom xs) ∧
  (∀ xs v22 v21. getPsgCom (v21 domi v22::xs) = getPsgCom xs) ∧
  (∀ xs v24 v23. getPsgCom (v23 eqi v24::xs) = getPsgCom xs) ∧
  (∀ xs v26 v25. getPsgCom (v25 doms v26::xs) = getPsgCom xs) ∧
  (∀ xs v28 v27. getPsgCom (v27 eqs v28::xs) = getPsgCom xs) ∧

```

$$\begin{aligned}
& (\forall xs \ v_{30} \ v_{29}. \text{getPsgCom } (v_{29} \text{ eqn } v_{30}::xs) = \text{getPsgCom } xs) \wedge \\
& (\forall xs \ v_{32} \ v_{31}. \text{getPsgCom } (v_{31} \text{ lte } v_{32}::xs) = \text{getPsgCom } xs) \wedge \\
& \forall xs \ v_{34} \ v_{33}. \text{getPsgCom } (v_{33} \text{ lt } v_{34}::xs) = \text{getPsgCom } xs
\end{aligned}$$

[getPsgCom_ind]

$\vdash \forall P.$

$P \ [] \wedge$

$(\forall cmd \ xs.$

P

$(\text{Name PlatoonSergeant says}$

$\text{prop (SOME (SLc (PSG cmd)))::xs)) \wedge$

$(\forall xs. P \ xs \Rightarrow P \ (\text{TT}::xs)) \wedge (\forall xs. P \ xs \Rightarrow P \ (\text{FF}::xs)) \wedge$

$(\forall v_2 \ xs. P \ xs \Rightarrow P \ (\text{prop } v_2::xs)) \wedge$

$(\forall v_3 \ xs. P \ xs \Rightarrow P \ (\text{notf } v_3::xs)) \wedge$

$(\forall v_4 \ v_5 \ xs. P \ xs \Rightarrow P \ (v_4 \ \text{andf } v_5::xs)) \wedge$

$(\forall v_6 \ v_7 \ xs. P \ xs \Rightarrow P \ (v_6 \ \text{orf } v_7::xs)) \wedge$

$(\forall v_8 \ v_9 \ xs. P \ xs \Rightarrow P \ (v_8 \ \text{impf } v_9::xs)) \wedge$

$(\forall v_{10} \ v_{11} \ xs. P \ xs \Rightarrow P \ (v_{10} \ \text{eqf } v_{11}::xs)) \wedge$

$(\forall v_{12} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says TT}::xs)) \wedge$

$(\forall v_{12} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says FF}::xs)) \wedge$

$(\forall v_{134} \ xs. P \ xs \Rightarrow P \ (\text{Name } v_{134} \ \text{says prop NONE}::xs)) \wedge$

$(\forall v_{144} \ xs.$

$P \ xs \Rightarrow$

$P \ (\text{Name PlatoonLeader says prop (SOME } v_{144})::xs)) \wedge$

$(\forall v_{146} \ xs.$

$P \ xs \Rightarrow$

P

$(\text{Name PlatoonSergeant says prop (SOME (ESCc } v_{146}))::$

$xs)) \wedge$

$(\forall v_{150} \ xs.$

$P \ xs \Rightarrow$

P

$(\text{Name PlatoonSergeant says}$

$\text{prop (SOME (SLc (PL } v_{150})))::xs)) \wedge$

$(\forall v_{135} \ v_{136} \ v_{68} \ xs.$

$P \ xs \Rightarrow P \ (v_{135} \ \text{meet } v_{136} \ \text{says prop } v_{68}::xs)) \wedge$

$(\forall v_{137} \ v_{138} \ v_{68} \ xs.$

$P \ xs \Rightarrow P \ (v_{137} \ \text{quoting } v_{138} \ \text{says prop } v_{68}::xs)) \wedge$

$(\forall v_{12} \ v_{69} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says notf } v_{69}::xs)) \wedge$

$(\forall v_{12} \ v_{70} \ v_{71} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } (v_{70} \ \text{andf } v_{71})::xs)) \wedge$

$(\forall v_{12} \ v_{72} \ v_{73} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } (v_{72} \ \text{orf } v_{73})::xs)) \wedge$

$(\forall v_{12} \ v_{74} \ v_{75} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } (v_{74} \ \text{impf } v_{75})::xs)) \wedge$

$(\forall v_{12} \ v_{76} \ v_{77} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } (v_{76} \ \text{eqf } v_{77})::xs)) \wedge$

$(\forall v_{12} \ v_{78} \ v_{79} \ xs. P \ xs \Rightarrow P \ (v_{12} \ \text{says } v_{78} \ \text{says } v_{79}::xs)) \wedge$

$(\forall v_{12} \ v_{80} \ v_{81} \ xs.$

$P \ xs \Rightarrow P \ (v_{12} \ \text{says } v_{80} \ \text{speaks_for } v_{81}::xs)) \wedge$

$(\forall v_{12} \ v_{82} \ v_{83} \ xs.$

$P \ xs \Rightarrow P \ (v_{12} \ \text{says } v_{82} \ \text{controls } v_{83}::xs)) \wedge$

$(\forall v_{12} \ v_{84} \ v_{85} \ v_{86} \ xs.$

$$\begin{aligned}
& P \text{ } xs \Rightarrow P \text{ } (v_{12} \text{ says reps } v_{84} \text{ } v_{85} \text{ } v_{86} :: xs)) \wedge \\
& (\forall v_{12} \text{ } v_{87} \text{ } v_{88} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{12} \text{ says } v_{87} \text{ domi } v_{88} :: xs)) \wedge \\
& (\forall v_{12} \text{ } v_{89} \text{ } v_{90} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{12} \text{ says } v_{89} \text{ eqi } v_{90} :: xs)) \wedge \\
& (\forall v_{12} \text{ } v_{91} \text{ } v_{92} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{12} \text{ says } v_{91} \text{ doms } v_{92} :: xs)) \wedge \\
& (\forall v_{12} \text{ } v_{93} \text{ } v_{94} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{12} \text{ says } v_{93} \text{ eqs } v_{94} :: xs)) \wedge \\
& (\forall v_{12} \text{ } v_{95} \text{ } v_{96} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{12} \text{ says } v_{95} \text{ eqn } v_{96} :: xs)) \wedge \\
& (\forall v_{12} \text{ } v_{97} \text{ } v_{98} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{12} \text{ says } v_{97} \text{ lte } v_{98} :: xs)) \wedge \\
& (\forall v_{12} \text{ } v_{99} \text{ } v_{100} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{12} \text{ says } v_{99} \text{ lt } v_{100} :: xs)) \wedge \\
& (\forall v_{14} \text{ } v_{15} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{14} \text{ speaks_for } v_{15} :: xs)) \wedge \\
& (\forall v_{16} \text{ } v_{17} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{16} \text{ controls } v_{17} :: xs)) \wedge \\
& (\forall v_{18} \text{ } v_{19} \text{ } v_{20} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (reps \text{ } v_{18} \text{ } v_{19} \text{ } v_{20} :: xs)) \wedge \\
& (\forall v_{21} \text{ } v_{22} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{21} \text{ domi } v_{22} :: xs)) \wedge \\
& (\forall v_{23} \text{ } v_{24} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{23} \text{ eqi } v_{24} :: xs)) \wedge \\
& (\forall v_{25} \text{ } v_{26} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{25} \text{ doms } v_{26} :: xs)) \wedge \\
& (\forall v_{27} \text{ } v_{28} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{27} \text{ eqs } v_{28} :: xs)) \wedge \\
& (\forall v_{29} \text{ } v_{30} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{29} \text{ eqn } v_{30} :: xs)) \wedge \\
& (\forall v_{31} \text{ } v_{32} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{31} \text{ lte } v_{32} :: xs)) \wedge \\
& (\forall v_{33} \text{ } v_{34} \text{ } xs. P \text{ } xs \Rightarrow P \text{ } (v_{33} \text{ lt } v_{34} :: xs)) \Rightarrow \\
& \forall v. P \text{ } v
\end{aligned}$$

[getRecon_def]

$$\begin{aligned}
& \vdash (\text{getRecon } [] = [\text{NONE}]) \wedge \\
& (\forall xs. \\
& \quad \text{getRecon} \\
& \quad \quad (\text{Name PlatoonLeader says prop (SOME (SLc (PL recon)))) ::} \\
& \quad \quad \quad xs) = \\
& \quad \quad [\text{SOME (SLc (PL recon))}] \wedge \\
& (\forall xs. \text{getRecon } (\text{TT} :: xs) = \text{getRecon } xs) \wedge \\
& (\forall xs. \text{getRecon } (\text{FF} :: xs) = \text{getRecon } xs) \wedge \\
& (\forall xs \text{ } v_2. \text{getRecon } (\text{prop } v_2 :: xs) = \text{getRecon } xs) \wedge \\
& (\forall xs \text{ } v_3. \text{getRecon } (\text{notf } v_3 :: xs) = \text{getRecon } xs) \wedge \\
& (\forall xs \text{ } v_5 \text{ } v_4. \text{getRecon } (v_4 \text{ andf } v_5 :: xs) = \text{getRecon } xs) \wedge \\
& (\forall xs \text{ } v_7 \text{ } v_6. \text{getRecon } (v_6 \text{ orf } v_7 :: xs) = \text{getRecon } xs) \wedge \\
& (\forall xs \text{ } v_9 \text{ } v_8. \text{getRecon } (v_8 \text{ impf } v_9 :: xs) = \text{getRecon } xs) \wedge \\
& (\forall xs \text{ } v_{11} \text{ } v_{10}. \text{getRecon } (v_{10} \text{ eqf } v_{11} :: xs) = \text{getRecon } xs) \wedge \\
& (\forall xs \text{ } v_{12}. \text{getRecon } (v_{12} \text{ says TT} :: xs) = \text{getRecon } xs) \wedge \\
& (\forall xs \text{ } v_{12}. \text{getRecon } (v_{12} \text{ says FF} :: xs) = \text{getRecon } xs) \wedge \\
& (\forall xs \text{ } v_{134}. \\
& \quad \text{getRecon } (\text{Name } v_{134} \text{ says prop NONE} :: xs) = \text{getRecon } xs) \wedge \\
& (\forall xs \text{ } v_{146}. \\
& \quad \text{getRecon} \\
& \quad \quad (\text{Name PlatoonLeader says prop (SOME (ESCc } v_{146})) :: xs) = \\
& \quad \quad \text{getRecon } xs) \wedge \\
& (\forall xs. \\
& \quad \text{getRecon} \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \quad \text{prop (SOME (SLc (PL receiveMission)))) :: xs} = \\
& \quad \quad \text{getRecon } xs) \wedge \\
& (\forall xs.
\end{aligned}$$

```

getRecon
  (Name PlatoonLeader says prop (SOME (SLc (PL warno))))::
    xs) =
getRecon xs) ∧
(∀ xs.
  getRecon
    (Name PlatoonLeader says
      prop (SOME (SLc (PL tentativePlan))))::xs) =
getRecon xs) ∧
(∀ xs.
  getRecon
    (Name PlatoonLeader says
      prop (SOME (SLc (PL report1))))::xs) =
getRecon xs) ∧
(∀ xs.
  getRecon
    (Name PlatoonLeader says
      prop (SOME (SLc (PL completePlan))))::xs) =
getRecon xs) ∧
(∀ xs.
  getRecon
    (Name PlatoonLeader says prop (SOME (SLc (PL opoid))))::
      xs) =
getRecon xs) ∧
(∀ xs.
  getRecon
    (Name PlatoonLeader says
      prop (SOME (SLc (PL supervise))))::xs) =
getRecon xs) ∧
(∀ xs.
  getRecon
    (Name PlatoonLeader says
      prop (SOME (SLc (PL report2))))::xs) =
getRecon xs) ∧
(∀ xs.
  getRecon
    (Name PlatoonLeader says
      prop (SOME (SLc (PL complete))))::xs) =
getRecon xs) ∧
(∀ xs.
  getRecon
    (Name PlatoonLeader says
      prop (SOME (SLc (PL plIncomplete))))::xs) =
getRecon xs) ∧
(∀ xs.
  getRecon
    (Name PlatoonLeader says
      prop (SOME (SLc (PL invalidPlCommand))))::xs) =
getRecon xs) ∧

```

```

(∀ xs v151.
  getRecon
    (Name PlatoonLeader says prop (SOME (SLc (PSG v151))))::
      xs) =
  getRecon xs) ∧
(∀ xs v144.
  getRecon
    (Name PlatoonSergeant says prop (SOME v144)::xs) =
  getRecon xs) ∧
(∀ xs v68 v136 v135.
  getRecon (v135 meet v136 says prop v68::xs) =
  getRecon xs) ∧
(∀ xs v68 v138 v137.
  getRecon (v137 quoting v138 says prop v68::xs) =
  getRecon xs) ∧
(∀ xs v69 v12.
  getRecon (v12 says notf v69::xs) = getRecon xs) ∧
(∀ xs v71 v70 v12.
  getRecon (v12 says (v70 andf v71)::xs) = getRecon xs) ∧
(∀ xs v73 v72 v12.
  getRecon (v12 says (v72 orf v73)::xs) = getRecon xs) ∧
(∀ xs v75 v74 v12.
  getRecon (v12 says (v74 impf v75)::xs) = getRecon xs) ∧
(∀ xs v77 v76 v12.
  getRecon (v12 says (v76 eqf v77)::xs) = getRecon xs) ∧
(∀ xs v79 v78 v12.
  getRecon (v12 says v78 says v79::xs) = getRecon xs) ∧
(∀ xs v81 v80 v12.
  getRecon (v12 says v80 speaks_for v81::xs) =
  getRecon xs) ∧
(∀ xs v83 v82 v12.
  getRecon (v12 says v82 controls v83::xs) = getRecon xs) ∧
(∀ xs v86 v85 v84 v12.
  getRecon (v12 says reps v84 v85 v86::xs) = getRecon xs) ∧
(∀ xs v88 v87 v12.
  getRecon (v12 says v87 domi v88::xs) = getRecon xs) ∧
(∀ xs v90 v89 v12.
  getRecon (v12 says v89 eqi v90::xs) = getRecon xs) ∧
(∀ xs v92 v91 v12.
  getRecon (v12 says v91 doms v92::xs) = getRecon xs) ∧
(∀ xs v94 v93 v12.
  getRecon (v12 says v93 eqs v94::xs) = getRecon xs) ∧
(∀ xs v96 v95 v12.
  getRecon (v12 says v95 eqn v96::xs) = getRecon xs) ∧
(∀ xs v98 v97 v12.
  getRecon (v12 says v97 lte v98::xs) = getRecon xs) ∧
(∀ xs v99 v12 v100.
  getRecon (v12 says v99 lt v100::xs) = getRecon xs) ∧
(∀ xs v15 v14.

```

```

    getRecon (v14 speaks_for v15::xs) = getRecon xs) ∧
  (∀ xs v17 v16.
    getRecon (v16 controls v17::xs) = getRecon xs) ∧
  (∀ xs v20 v19 v18.
    getRecon (reps v18 v19 v20::xs) = getRecon xs) ∧
  (∀ xs v22 v21. getRecon (v21 domi v22::xs) = getRecon xs) ∧
  (∀ xs v24 v23. getRecon (v23 eqi v24::xs) = getRecon xs) ∧
  (∀ xs v26 v25. getRecon (v25 doms v26::xs) = getRecon xs) ∧
  (∀ xs v28 v27. getRecon (v27 eqs v28::xs) = getRecon xs) ∧
  (∀ xs v30 v29. getRecon (v29 eqn v30::xs) = getRecon xs) ∧
  (∀ xs v32 v31. getRecon (v31 lte v32::xs) = getRecon xs) ∧
  ∀ xs v34 v33. getRecon (v33 lt v34::xs) = getRecon xs

```

[getRecon_ind]

```

⊢ ∀ P.
  P [] ∧
  (∀ xs.
    P
      (Name PlatoonLeader says
        prop (SOME (SLc (PL recon)))::xs)) ∧
    (∀ xs. P xs ⇒ P (TT::xs)) ∧ (∀ xs. P xs ⇒ P (FF::xs)) ∧
    (∀ v2 xs. P xs ⇒ P (prop v2::xs)) ∧
    (∀ v3 xs. P xs ⇒ P (notf v3::xs)) ∧
    (∀ v4 v5 xs. P xs ⇒ P (v4 andf v5::xs)) ∧
    (∀ v6 v7 xs. P xs ⇒ P (v6 orf v7::xs)) ∧
    (∀ v8 v9 xs. P xs ⇒ P (v8 impf v9::xs)) ∧
    (∀ v10 v11 xs. P xs ⇒ P (v10 eqf v11::xs)) ∧
    (∀ v12 xs. P xs ⇒ P (v12 says TT::xs)) ∧
    (∀ v12 xs. P xs ⇒ P (v12 says FF::xs)) ∧
    (∀ v134 xs. P xs ⇒ P (Name v134 says prop NONE::xs)) ∧
    (∀ v146 xs.
      P xs ⇒
      P
        (Name PlatoonLeader says prop (SOME (ESCc v146))::
          xs)) ∧
    (∀ xs.
      P xs ⇒
      P
        (Name PlatoonLeader says
          prop (SOME (SLc (PL receiveMission)))::xs)) ∧
    (∀ xs.
      P xs ⇒
      P
        (Name PlatoonLeader says
          prop (SOME (SLc (PL warno)))::xs)) ∧
    (∀ xs.
      P xs ⇒
      P
        (Name PlatoonLeader says

```


$$\begin{aligned}
& \text{prop (SOME (SLc (PL tentativePlan)))::xs))} \wedge \\
(\forall xs. & \\
& P \ xs \Rightarrow \\
& P \\
& \text{(Name PlatoonLeader says} \\
& \text{prop (SOME (SLc (PL report1)))::xs))} \wedge \\
(\forall xs. & \\
& P \ xs \Rightarrow \\
& P \\
& \text{(Name PlatoonLeader says} \\
& \text{prop (SOME (SLc (PL completePlan)))::xs))} \wedge \\
(\forall xs. & \\
& P \ xs \Rightarrow \\
& P \\
& \text{(Name PlatoonLeader says} \\
& \text{prop (SOME (SLc (PL opoid)))::xs))} \wedge \\
(\forall xs. & \\
& P \ xs \Rightarrow \\
& P \\
& \text{(Name PlatoonLeader says} \\
& \text{prop (SOME (SLc (PL supervise)))::xs))} \wedge \\
(\forall xs. & \\
& P \ xs \Rightarrow \\
& P \\
& \text{(Name PlatoonLeader says} \\
& \text{prop (SOME (SLc (PL report2)))::xs))} \wedge \\
(\forall xs. & \\
& P \ xs \Rightarrow \\
& P \\
& \text{(Name PlatoonLeader says} \\
& \text{prop (SOME (SLc (PL complete)))::xs))} \wedge \\
(\forall xs. & \\
& P \ xs \Rightarrow \\
& P \\
& \text{(Name PlatoonLeader says} \\
& \text{prop (SOME (SLc (PL plIncomplete)))::xs))} \wedge \\
(\forall xs. & \\
& P \ xs \Rightarrow \\
& P \\
& \text{(Name PlatoonLeader says} \\
& \text{prop (SOME (SLc (PL invalidPlCommand)))::xs))} \wedge \\
(\forall v151 \ xs. & \\
& P \ xs \Rightarrow \\
& P \\
& \text{(Name PlatoonLeader says} \\
& \text{prop (SOME (SLc (PSG v151)))::xs))} \wedge \\
(\forall v144 \ xs. & \\
& P \ xs \Rightarrow \\
& P \text{ (Name PlatoonSergeant says prop (SOME v144)::xs))} \wedge
\end{aligned}$$

$$\begin{aligned}
& (\forall v135 \ v136 \ v68 \ xs. \\
& \quad P \ xs \Rightarrow P \ (v135 \ \text{meet} \ v136 \ \text{says} \ \text{prop} \ v68 :: xs)) \wedge \\
& (\forall v137 \ v138 \ v68 \ xs. \\
& \quad P \ xs \Rightarrow P \ (v137 \ \text{quoting} \ v138 \ \text{says} \ \text{prop} \ v68 :: xs)) \wedge \\
& (\forall v12 \ v69 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ \text{notf} \ v69 :: xs)) \wedge \\
& (\forall v12 \ v70 \ v71 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ (v70 \ \text{andf} \ v71) :: xs)) \wedge \\
& (\forall v12 \ v72 \ v73 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ (v72 \ \text{orf} \ v73) :: xs)) \wedge \\
& (\forall v12 \ v74 \ v75 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ (v74 \ \text{impf} \ v75) :: xs)) \wedge \\
& (\forall v12 \ v76 \ v77 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ (v76 \ \text{eqf} \ v77) :: xs)) \wedge \\
& (\forall v12 \ v78 \ v79 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ v78 \ \text{says} \ v79 :: xs)) \wedge \\
& (\forall v12 \ v80 \ v81 \ xs. \\
& \quad P \ xs \Rightarrow P \ (v12 \ \text{says} \ v80 \ \text{speaks_for} \ v81 :: xs)) \wedge \\
& (\forall v12 \ v82 \ v83 \ xs. \\
& \quad P \ xs \Rightarrow P \ (v12 \ \text{says} \ v82 \ \text{controls} \ v83 :: xs)) \wedge \\
& (\forall v12 \ v84 \ v85 \ v86 \ xs. \\
& \quad P \ xs \Rightarrow P \ (v12 \ \text{says} \ \text{reps} \ v84 \ v85 \ v86 :: xs)) \wedge \\
& (\forall v12 \ v87 \ v88 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ v87 \ \text{domi} \ v88 :: xs)) \wedge \\
& (\forall v12 \ v89 \ v90 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ v89 \ \text{eqi} \ v90 :: xs)) \wedge \\
& (\forall v12 \ v91 \ v92 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ v91 \ \text{doms} \ v92 :: xs)) \wedge \\
& (\forall v12 \ v93 \ v94 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ v93 \ \text{eqs} \ v94 :: xs)) \wedge \\
& (\forall v12 \ v95 \ v96 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ v95 \ \text{eqn} \ v96 :: xs)) \wedge \\
& (\forall v12 \ v97 \ v98 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ v97 \ \text{lte} \ v98 :: xs)) \wedge \\
& (\forall v12 \ v99 \ v100 \ xs. P \ xs \Rightarrow P \ (v12 \ \text{says} \ v99 \ \text{lt} \ v100 :: xs)) \wedge \\
& (\forall v14 \ v15 \ xs. P \ xs \Rightarrow P \ (v14 \ \text{speaks_for} \ v15 :: xs)) \wedge \\
& (\forall v16 \ v17 \ xs. P \ xs \Rightarrow P \ (v16 \ \text{controls} \ v17 :: xs)) \wedge \\
& (\forall v18 \ v19 \ v20 \ xs. P \ xs \Rightarrow P \ (\text{reps} \ v18 \ v19 \ v20 :: xs)) \wedge \\
& (\forall v21 \ v22 \ xs. P \ xs \Rightarrow P \ (v21 \ \text{domi} \ v22 :: xs)) \wedge \\
& (\forall v23 \ v24 \ xs. P \ xs \Rightarrow P \ (v23 \ \text{eqi} \ v24 :: xs)) \wedge \\
& (\forall v25 \ v26 \ xs. P \ xs \Rightarrow P \ (v25 \ \text{doms} \ v26 :: xs)) \wedge \\
& (\forall v27 \ v28 \ xs. P \ xs \Rightarrow P \ (v27 \ \text{eqs} \ v28 :: xs)) \wedge \\
& (\forall v29 \ v30 \ xs. P \ xs \Rightarrow P \ (v29 \ \text{eqn} \ v30 :: xs)) \wedge \\
& (\forall v31 \ v32 \ xs. P \ xs \Rightarrow P \ (v31 \ \text{lte} \ v32 :: xs)) \wedge \\
& (\forall v33 \ v34 \ xs. P \ xs \Rightarrow P \ (v33 \ \text{lt} \ v34 :: xs)) \Rightarrow \\
& \forall v. P \ v
\end{aligned}$$

[getReport_def]

$$\begin{aligned}
& \vdash (\text{getReport} \ [] = [\text{NONE}]) \wedge \\
& (\forall xs. \\
& \quad \text{getReport} \\
& \quad \quad (\text{Name} \ \text{PlatoonLeader} \ \text{says} \\
& \quad \quad \quad \text{prop} \ (\text{SOME} \ (\text{SLc} \ (\text{PL} \ \text{report1})))) :: xs = \\
& \quad \quad [\text{SOME} \ (\text{SLc} \ (\text{PL} \ \text{report1}))]) \wedge \\
& (\forall xs. \text{getReport} \ (\text{TT} :: xs) = \text{getReport} \ xs) \wedge \\
& (\forall xs. \text{getReport} \ (\text{FF} :: xs) = \text{getReport} \ xs) \wedge \\
& (\forall xs \ v2. \text{getReport} \ (\text{prop} \ v2 :: xs) = \text{getReport} \ xs) \wedge \\
& (\forall xs \ v3. \text{getReport} \ (\text{notf} \ v3 :: xs) = \text{getReport} \ xs) \wedge \\
& (\forall xs \ v5 \ v4. \text{getReport} \ (v4 \ \text{andf} \ v5 :: xs) = \text{getReport} \ xs) \wedge \\
& (\forall xs \ v7 \ v6. \text{getReport} \ (v6 \ \text{orf} \ v7 :: xs) = \text{getReport} \ xs) \wedge \\
& (\forall xs \ v9 \ v8. \text{getReport} \ (v8 \ \text{impf} \ v9 :: xs) = \text{getReport} \ xs) \wedge
\end{aligned}$$

```

(∀ xs v11 v10. getReport (v10 eqf v11::xs) = getReport xs) ∧
(∀ xs v12. getReport (v12 says TT::xs) = getReport xs) ∧
(∀ xs v12. getReport (v12 says FF::xs) = getReport xs) ∧
(∀ xs v134.
  getReport (Name v134 says prop NONE::xs) = getReport xs) ∧
(∀ xs v146.
  getReport
    (Name PlatoonLeader says prop (SOME (ESCc v146))::xs) =
  getReport xs) ∧
(∀ xs.
  getReport
    (Name PlatoonLeader says
      prop (SOME (SLc (PL receiveMission)))::xs) =
  getReport xs) ∧
(∀ xs.
  getReport
    (Name PlatoonLeader says prop (SOME (SLc (PL warno)))::
      xs) =
  getReport xs) ∧
(∀ xs.
  getReport
    (Name PlatoonLeader says
      prop (SOME (SLc (PL tentativePlan)))::xs) =
  getReport xs) ∧
(∀ xs.
  getReport
    (Name PlatoonLeader says prop (SOME (SLc (PL recon)))::
      xs) =
  getReport xs) ∧
(∀ xs.
  getReport
    (Name PlatoonLeader says
      prop (SOME (SLc (PL completePlan)))::xs) =
  getReport xs) ∧
(∀ xs.
  getReport
    (Name PlatoonLeader says prop (SOME (SLc (PL opoid)))::
      xs) =
  getReport xs) ∧
(∀ xs.
  getReport
    (Name PlatoonLeader says
      prop (SOME (SLc (PL supervise)))::xs) =
  getReport xs) ∧
(∀ xs.
  getReport
    (Name PlatoonLeader says
      prop (SOME (SLc (PL report2)))::xs) =
  getReport xs) ∧

```

```

(∀ xs.
  getReport
    (Name PlatoonLeader says
      prop (SOME (SLc (PL complete))))::xs) =
  getReport xs) ∧
(∀ xs.
  getReport
    (Name PlatoonLeader says
      prop (SOME (SLc (PL plIncomplete))))::xs) =
  getReport xs) ∧
(∀ xs.
  getReport
    (Name PlatoonLeader says
      prop (SOME (SLc (PL invalidPlCommand))))::xs) =
  getReport xs) ∧
(∀ xs v151.
  getReport
    (Name PlatoonLeader says prop (SOME (SLc (PSG v151))))::
    xs) =
  getReport xs) ∧
(∀ xs v144.
  getReport
    (Name PlatoonSergeant says prop (SOME v144))::xs) =
  getReport xs) ∧
(∀ xs v68 v136 v135.
  getReport (v135 meet v136 says prop v68::xs) =
  getReport xs) ∧
(∀ xs v68 v138 v137.
  getReport (v137 quoting v138 says prop v68::xs) =
  getReport xs) ∧
(∀ xs v69 v12.
  getReport (v12 says notif v69::xs) = getReport xs) ∧
(∀ xs v71 v70 v12.
  getReport (v12 says (v70 andf v71)::xs) = getReport xs) ∧
(∀ xs v73 v72 v12.
  getReport (v12 says (v72 orf v73)::xs) = getReport xs) ∧
(∀ xs v75 v74 v12.
  getReport (v12 says (v74 impf v75)::xs) = getReport xs) ∧
(∀ xs v77 v76 v12.
  getReport (v12 says (v76 eqf v77)::xs) = getReport xs) ∧
(∀ xs v79 v78 v12.
  getReport (v12 says v78 says v79::xs) = getReport xs) ∧
(∀ xs v81 v80 v12.
  getReport (v12 says v80 speaks_for v81::xs) =
  getReport xs) ∧
(∀ xs v83 v82 v12.
  getReport (v12 says v82 controls v83::xs) =
  getReport xs) ∧
(∀ xs v86 v85 v84 v12.

```

```

    getReport (v12 says reps v84 v85 v86::xs) =
    getReport xs) ∧
  (∀ xs v88 v87 v12.
    getReport (v12 says v87 domi v88::xs) = getReport xs) ∧
  (∀ xs v90 v89 v12.
    getReport (v12 says v89 eqi v90::xs) = getReport xs) ∧
  (∀ xs v92 v91 v12.
    getReport (v12 says v91 doms v92::xs) = getReport xs) ∧
  (∀ xs v94 v93 v12.
    getReport (v12 says v93 eqs v94::xs) = getReport xs) ∧
  (∀ xs v96 v95 v12.
    getReport (v12 says v95 eqn v96::xs) = getReport xs) ∧
  (∀ xs v98 v97 v12.
    getReport (v12 says v97 lte v98::xs) = getReport xs) ∧
  (∀ xs v99 v12 v100.
    getReport (v12 says v99 lt v100::xs) = getReport xs) ∧
  (∀ xs v15 v14.
    getReport (v14 speaks_for v15::xs) = getReport xs) ∧
  (∀ xs v17 v16.
    getReport (v16 controls v17::xs) = getReport xs) ∧
  (∀ xs v20 v19 v18.
    getReport (reps v18 v19 v20::xs) = getReport xs) ∧
  (∀ xs v22 v21. getReport (v21 domi v22::xs) = getReport xs) ∧
  (∀ xs v24 v23. getReport (v23 eqi v24::xs) = getReport xs) ∧
  (∀ xs v26 v25. getReport (v25 doms v26::xs) = getReport xs) ∧
  (∀ xs v28 v27. getReport (v27 eqs v28::xs) = getReport xs) ∧
  (∀ xs v30 v29. getReport (v29 eqn v30::xs) = getReport xs) ∧
  (∀ xs v32 v31. getReport (v31 lte v32::xs) = getReport xs) ∧
  ∀ xs v34 v33. getReport (v33 lt v34::xs) = getReport xs

```

[getReport_ind]

```

⊢ ∀ P.
  P [] ∧
  (∀ xs.
    P
      (Name PlatoonLeader says
        prop (SOME (SLc (PL report1))))::xs)) ∧
  (∀ xs. P xs ⇒ P (TT::xs)) ∧ (∀ xs. P xs ⇒ P (FF::xs)) ∧
  (∀ v2 xs. P xs ⇒ P (prop v2::xs)) ∧
  (∀ v3 xs. P xs ⇒ P (notf v3::xs)) ∧
  (∀ v4 v5 xs. P xs ⇒ P (v4 andf v5::xs)) ∧
  (∀ v6 v7 xs. P xs ⇒ P (v6 orf v7::xs)) ∧
  (∀ v8 v9 xs. P xs ⇒ P (v8 impf v9::xs)) ∧
  (∀ v10 v11 xs. P xs ⇒ P (v10 eqf v11::xs)) ∧
  (∀ v12 xs. P xs ⇒ P (v12 says TT::xs)) ∧
  (∀ v12 xs. P xs ⇒ P (v12 says FF::xs)) ∧
  (∀ v134 xs. P xs ⇒ P (Name v134 says prop NONE::xs)) ∧
  (∀ v146 xs.
    P xs ⇒

```

$$\begin{aligned}
& P \\
& \quad (\text{Name PlatoonLeader says prop (SOME (ESCc v146))} :: \\
& \quad \quad xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL receiveMission)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL warno)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL tentativePlan)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL recon)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL completePlan)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL opoid)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL supervise)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL report2)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL complete)))} :: xs)) \wedge \\
& (\forall xs.
\end{aligned}$$

```

P xs ⇒
P
(Name PlatoonLeader says
 prop (SOME (SLc (PL plIncomplete)))::xs)) ∧
(∀ xs.
 P xs ⇒
 P
 (Name PlatoonLeader says
  prop (SOME (SLc (PL invalidPlCommand)))::xs)) ∧
(∀ v151 xs.
 P xs ⇒
 P
 (Name PlatoonLeader says
  prop (SOME (SLc (PSG v151)))::xs)) ∧
(∀ v144 xs.
 P xs ⇒
 P (Name PlatoonSergeant says prop (SOME v144)::xs)) ∧
(∀ v135 v136 v68 xs.
 P xs ⇒ P (v135 meet v136 says prop v68::xs)) ∧
(∀ v137 v138 v68 xs.
 P xs ⇒ P (v137 quoting v138 says prop v68::xs)) ∧
(∀ v12 v69 xs. P xs ⇒ P (v12 says notf v69::xs)) ∧
(∀ v12 v70 v71 xs. P xs ⇒ P (v12 says (v70 andf v71)::xs)) ∧
(∀ v12 v72 v73 xs. P xs ⇒ P (v12 says (v72 orf v73)::xs)) ∧
(∀ v12 v74 v75 xs. P xs ⇒ P (v12 says (v74 impf v75)::xs)) ∧
(∀ v12 v76 v77 xs. P xs ⇒ P (v12 says (v76 eqf v77)::xs)) ∧
(∀ v12 v78 v79 xs. P xs ⇒ P (v12 says v78 says v79::xs)) ∧
(∀ v12 v80 v81 xs.
 P xs ⇒ P (v12 says v80 speaks_for v81::xs)) ∧
(∀ v12 v82 v83 xs.
 P xs ⇒ P (v12 says v82 controls v83::xs)) ∧
(∀ v12 v84 v85 v86 xs.
 P xs ⇒ P (v12 says reps v84 v85 v86::xs)) ∧
(∀ v12 v87 v88 xs. P xs ⇒ P (v12 says v87 domi v88::xs)) ∧
(∀ v12 v89 v90 xs. P xs ⇒ P (v12 says v89 eqi v90::xs)) ∧
(∀ v12 v91 v92 xs. P xs ⇒ P (v12 says v91 doms v92::xs)) ∧
(∀ v12 v93 v94 xs. P xs ⇒ P (v12 says v93 eqs v94::xs)) ∧
(∀ v12 v95 v96 xs. P xs ⇒ P (v12 says v95 eqn v96::xs)) ∧
(∀ v12 v97 v98 xs. P xs ⇒ P (v12 says v97 lte v98::xs)) ∧
(∀ v12 v99 v100 xs. P xs ⇒ P (v12 says v99 lt v100::xs)) ∧
(∀ v14 v15 xs. P xs ⇒ P (v14 speaks_for v15::xs)) ∧
(∀ v16 v17 xs. P xs ⇒ P (v16 controls v17::xs)) ∧
(∀ v18 v19 v20 xs. P xs ⇒ P (reps v18 v19 v20::xs)) ∧
(∀ v21 v22 xs. P xs ⇒ P (v21 domi v22::xs)) ∧
(∀ v23 v24 xs. P xs ⇒ P (v23 eqi v24::xs)) ∧
(∀ v25 v26 xs. P xs ⇒ P (v25 doms v26::xs)) ∧
(∀ v27 v28 xs. P xs ⇒ P (v27 eqs v28::xs)) ∧
(∀ v29 v30 xs. P xs ⇒ P (v29 eqn v30::xs)) ∧
(∀ v31 v32 xs. P xs ⇒ P (v31 lte v32::xs)) ∧

```

$$(\forall v_{33} v_{34} xs. P xs \Rightarrow P (v_{33} \text{ lt } v_{34} :: xs)) \Rightarrow \\ \forall v. P v$$

[getTentativePlan_def]

```

⊢ (getTentativePlan [] = [NONE]) ∧
(∀ xs.
  getTentativePlan
    (Name PlatoonLeader says
      prop (SOME (SLc (PL tentativePlan))))::xs) =
    [SOME (SLc (PL tentativePlan))]) ∧
(∀ xs. getTentativePlan (TT::xs) = getTentativePlan xs) ∧
(∀ xs. getTentativePlan (FF::xs) = getTentativePlan xs) ∧
(∀ xs v2.
  getTentativePlan (prop v2::xs) = getTentativePlan xs) ∧
(∀ xs v3.
  getTentativePlan (notf v3::xs) = getTentativePlan xs) ∧
(∀ xs v5 v4.
  getTentativePlan (v4 andf v5::xs) = getTentativePlan xs) ∧
(∀ xs v7 v6.
  getTentativePlan (v6 orf v7::xs) = getTentativePlan xs) ∧
(∀ xs v9 v8.
  getTentativePlan (v8 impf v9::xs) = getTentativePlan xs) ∧
(∀ xs v11 v10.
  getTentativePlan (v10 eqf v11::xs) = getTentativePlan xs) ∧
(∀ xs v12.
  getTentativePlan (v12 says TT::xs) = getTentativePlan xs) ∧
(∀ xs v12.
  getTentativePlan (v12 says FF::xs) = getTentativePlan xs) ∧
(∀ xs v134.
  getTentativePlan (Name v134 says prop NONE::xs) =
    getTentativePlan xs) ∧
(∀ xs v146.
  getTentativePlan
    (Name PlatoonLeader says prop (SOME (ESCc v146))::xs) =
    getTentativePlan xs) ∧
(∀ xs.
  getTentativePlan
    (Name PlatoonLeader says
      prop (SOME (SLc (PL receiveMission))))::xs) =
    getTentativePlan xs) ∧
(∀ xs.
  getTentativePlan
    (Name PlatoonLeader says prop (SOME (SLc (PL warno))))::
      xs) =
    getTentativePlan xs) ∧
(∀ xs.
  getTentativePlan
    (Name PlatoonLeader says prop (SOME (SLc (PL recon))))::
      xs) =

```

```

    getTenativePlan xs) ∧
  (∀ xs.
    getTenativePlan
      (Name PlatoonLeader says
        prop (SOME (SLc (PL report1))))::xs) =
    getTenativePlan xs) ∧
  (∀ xs.
    getTenativePlan
      (Name PlatoonLeader says
        prop (SOME (SLc (PL completePlan))))::xs) =
    getTenativePlan xs) ∧
  (∀ xs.
    getTenativePlan
      (Name PlatoonLeader says prop (SOME (SLc (PL opoid))))::
        xs) =
    getTenativePlan xs) ∧
  (∀ xs.
    getTenativePlan
      (Name PlatoonLeader says
        prop (SOME (SLc (PL supervise))))::xs) =
    getTenativePlan xs) ∧
  (∀ xs.
    getTenativePlan
      (Name PlatoonLeader says
        prop (SOME (SLc (PL report2))))::xs) =
    getTenativePlan xs) ∧
  (∀ xs.
    getTenativePlan
      (Name PlatoonLeader says
        prop (SOME (SLc (PL complete))))::xs) =
    getTenativePlan xs) ∧
  (∀ xs.
    getTenativePlan
      (Name PlatoonLeader says
        prop (SOME (SLc (PL plIncomplete))))::xs) =
    getTenativePlan xs) ∧
  (∀ xs.
    getTenativePlan
      (Name PlatoonLeader says
        prop (SOME (SLc (PL invalidPlCommand))))::xs) =
    getTenativePlan xs) ∧
  (∀ xs v151.
    getTenativePlan
      (Name PlatoonLeader says prop (SOME (SLc (PSG v151))))::
        xs) =
    getTenativePlan xs) ∧
  (∀ xs v144.
    getTenativePlan
      (Name PlatoonSergeant says prop (SOME v144))::xs) =

```

```

    getTenativePlan xs) ∧
(∀ xs v68 v136 v135.
  getTenativePlan (v135 meet v136 says prop v68::xs) =
  getTenativePlan xs) ∧
(∀ xs v68 v138 v137.
  getTenativePlan (v137 quoting v138 says prop v68::xs) =
  getTenativePlan xs) ∧
(∀ xs v69 v12.
  getTenativePlan (v12 says notf v69::xs) =
  getTenativePlan xs) ∧
(∀ xs v71 v70 v12.
  getTenativePlan (v12 says (v70 andf v71)::xs) =
  getTenativePlan xs) ∧
(∀ xs v73 v72 v12.
  getTenativePlan (v12 says (v72 orf v73)::xs) =
  getTenativePlan xs) ∧
(∀ xs v75 v74 v12.
  getTenativePlan (v12 says (v74 impf v75)::xs) =
  getTenativePlan xs) ∧
(∀ xs v77 v76 v12.
  getTenativePlan (v12 says (v76 eqf v77)::xs) =
  getTenativePlan xs) ∧
(∀ xs v79 v78 v12.
  getTenativePlan (v12 says v78 says v79::xs) =
  getTenativePlan xs) ∧
(∀ xs v81 v80 v12.
  getTenativePlan (v12 says v80 speaks_for v81::xs) =
  getTenativePlan xs) ∧
(∀ xs v83 v82 v12.
  getTenativePlan (v12 says v82 controls v83::xs) =
  getTenativePlan xs) ∧
(∀ xs v86 v85 v84 v12.
  getTenativePlan (v12 says reps v84 v85 v86::xs) =
  getTenativePlan xs) ∧
(∀ xs v88 v87 v12.
  getTenativePlan (v12 says v87 domi v88::xs) =
  getTenativePlan xs) ∧
(∀ xs v90 v89 v12.
  getTenativePlan (v12 says v89 eqi v90::xs) =
  getTenativePlan xs) ∧
(∀ xs v92 v91 v12.
  getTenativePlan (v12 says v91 doms v92::xs) =
  getTenativePlan xs) ∧
(∀ xs v94 v93 v12.
  getTenativePlan (v12 says v93 eqs v94::xs) =
  getTenativePlan xs) ∧
(∀ xs v96 v95 v12.
  getTenativePlan (v12 says v95 eqn v96::xs) =
  getTenativePlan xs) ∧

```

```

(∀ xs v98 v97 v12.
  getTentativePlan (v12 says v97 lte v98::xs) =
  getTentativePlan xs) ∧
(∀ xs v99 v12 v100.
  getTentativePlan (v12 says v99 lt v100::xs) =
  getTentativePlan xs) ∧
(∀ xs v15 v14.
  getTentativePlan (v14 speaks_for v15::xs) =
  getTentativePlan xs) ∧
(∀ xs v17 v16.
  getTentativePlan (v16 controls v17::xs) =
  getTentativePlan xs) ∧
(∀ xs v20 v19 v18.
  getTentativePlan (reps v18 v19 v20::xs) =
  getTentativePlan xs) ∧
(∀ xs v22 v21.
  getTentativePlan (v21 domi v22::xs) = getTentativePlan xs) ∧
(∀ xs v24 v23.
  getTentativePlan (v23 eqi v24::xs) = getTentativePlan xs) ∧
(∀ xs v26 v25.
  getTentativePlan (v25 doms v26::xs) = getTentativePlan xs) ∧
(∀ xs v28 v27.
  getTentativePlan (v27 eqs v28::xs) = getTentativePlan xs) ∧
(∀ xs v30 v29.
  getTentativePlan (v29 eqn v30::xs) = getTentativePlan xs) ∧
(∀ xs v32 v31.
  getTentativePlan (v31 lte v32::xs) = getTentativePlan xs) ∧
∀ xs v34 v33.
  getTentativePlan (v33 lt v34::xs) = getTentativePlan xs

```

[getTentativePlan_ind]

```

⊢ ∀ P.
  P [] ∧
  (∀ xs.
    P
      (Name PlatoonLeader says
        prop (SOME (SLc (PL tentativePlan)))::xs)) ∧
  (∀ xs. P xs ⇒ P (TT::xs)) ∧ (∀ xs. P xs ⇒ P (FF::xs)) ∧
  (∀ v2 xs. P xs ⇒ P (prop v2::xs)) ∧
  (∀ v3 xs. P xs ⇒ P (notf v3::xs)) ∧
  (∀ v4 v5 xs. P xs ⇒ P (v4 andf v5::xs)) ∧
  (∀ v6 v7 xs. P xs ⇒ P (v6 orf v7::xs)) ∧
  (∀ v8 v9 xs. P xs ⇒ P (v8 impf v9::xs)) ∧
  (∀ v10 v11 xs. P xs ⇒ P (v10 eqf v11::xs)) ∧
  (∀ v12 xs. P xs ⇒ P (v12 says TT::xs)) ∧
  (∀ v12 xs. P xs ⇒ P (v12 says FF::xs)) ∧
  (∀ v134 xs. P xs ⇒ P (Name v134 says prop NONE::xs)) ∧
  (∀ v146 xs.
    P xs ⇒

```

$$\begin{aligned}
& P \\
& \quad (\text{Name PlatoonLeader says prop (SOME (ESCc v146))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL receiveMission)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL warno)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL recon)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL report1)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL completePlan)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL opoid)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL supervise)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL report2)))} :: xs)) \wedge \\
& (\forall xs. \\
& \quad P \quad xs \Rightarrow \\
& \quad P \\
& \quad \quad (\text{Name PlatoonLeader says} \\
& \quad \quad \text{prop (SOME (SLc (PL complete)))} :: xs)) \wedge \\
& (\forall xs.
\end{aligned}$$

```

P xs ⇒
P
(Name PlatoonLeader says
 prop (SOME (SLc (PL plIncomplete)))::xs)) ∧
(∀ xs.
 P xs ⇒
 P
 (Name PlatoonLeader says
  prop (SOME (SLc (PL invalidPlCommand)))::xs)) ∧
(∀ v151 xs.
 P xs ⇒
 P
 (Name PlatoonLeader says
  prop (SOME (SLc (PSG v151)))::xs)) ∧
(∀ v144 xs.
 P xs ⇒
 P (Name PlatoonSergeant says prop (SOME v144)::xs)) ∧
(∀ v135 v136 v68 xs.
 P xs ⇒ P (v135 meet v136 says prop v68::xs)) ∧
(∀ v137 v138 v68 xs.
 P xs ⇒ P (v137 quoting v138 says prop v68::xs)) ∧
(∀ v12 v69 xs. P xs ⇒ P (v12 says notf v69::xs)) ∧
(∀ v12 v70 v71 xs. P xs ⇒ P (v12 says (v70 andf v71)::xs)) ∧
(∀ v12 v72 v73 xs. P xs ⇒ P (v12 says (v72 orf v73)::xs)) ∧
(∀ v12 v74 v75 xs. P xs ⇒ P (v12 says (v74 impf v75)::xs)) ∧
(∀ v12 v76 v77 xs. P xs ⇒ P (v12 says (v76 eqf v77)::xs)) ∧
(∀ v12 v78 v79 xs. P xs ⇒ P (v12 says v78 says v79::xs)) ∧
(∀ v12 v80 v81 xs.
 P xs ⇒ P (v12 says v80 speaks_for v81::xs)) ∧
(∀ v12 v82 v83 xs.
 P xs ⇒ P (v12 says v82 controls v83::xs)) ∧
(∀ v12 v84 v85 v86 xs.
 P xs ⇒ P (v12 says reps v84 v85 v86::xs)) ∧
(∀ v12 v87 v88 xs. P xs ⇒ P (v12 says v87 domi v88::xs)) ∧
(∀ v12 v89 v90 xs. P xs ⇒ P (v12 says v89 eqi v90::xs)) ∧
(∀ v12 v91 v92 xs. P xs ⇒ P (v12 says v91 doms v92::xs)) ∧
(∀ v12 v93 v94 xs. P xs ⇒ P (v12 says v93 eqs v94::xs)) ∧
(∀ v12 v95 v96 xs. P xs ⇒ P (v12 says v95 eqn v96::xs)) ∧
(∀ v12 v97 v98 xs. P xs ⇒ P (v12 says v97 lte v98::xs)) ∧
(∀ v12 v99 v100 xs. P xs ⇒ P (v12 says v99 lt v100::xs)) ∧
(∀ v14 v15 xs. P xs ⇒ P (v14 speaks_for v15::xs)) ∧
(∀ v16 v17 xs. P xs ⇒ P (v16 controls v17::xs)) ∧
(∀ v18 v19 v20 xs. P xs ⇒ P (reps v18 v19 v20::xs)) ∧
(∀ v21 v22 xs. P xs ⇒ P (v21 domi v22::xs)) ∧
(∀ v23 v24 xs. P xs ⇒ P (v23 eqi v24::xs)) ∧
(∀ v25 v26 xs. P xs ⇒ P (v25 doms v26::xs)) ∧
(∀ v27 v28 xs. P xs ⇒ P (v27 eqs v28::xs)) ∧
(∀ v29 v30 xs. P xs ⇒ P (v29 eqn v30::xs)) ∧
(∀ v31 v32 xs. P xs ⇒ P (v31 lte v32::xs)) ∧

```

$$\begin{array}{l}
(\forall v_{33} \ v_{34} \ xs. \ P \ xs \Rightarrow P \ (v_{33} \ \text{lt} \ v_{34} :: xs)) \Rightarrow \\
\forall v. \ P \ v
\end{array}$$

Index

ConductORPDef Theory, 46

Definitions, 46

secAuthorization_def, 46

secContext_def, 46

secHelper_def, 47

Theorems, 47

getOmniCommand_def, 47

getOmniCommand_ind, 49

getPlCom_def, 50

getPlCom_ind, 51

getPsgCom_def, 51

getPsgCom_ind, 51

ConductORPType Theory, 44

Datatypes, 44

Theorems, 45

omniCommand_distinct_clauses, 45

plCommand_distinct_clauses, 45

psgCommand_distinct_clauses, 45

slCommand_distinct_clauses, 45

slCommand_one_one, 45

slOutput_distinct_clauses, 45

slRole_distinct_clauses, 46

slState_distinct_clauses, 46

ConductPBType Theory, 57

Datatypes, 57

Theorems, 57

plCommandPB_distinct_clauses, 57

psgCommandPB_distinct_clauses, 57

slCommand_distinct_clauses, 57

slCommand_one_one, 57

slOutput_distinct_clauses, 57

slRole_distinct_clauses, 58

slState_distinct_clauses, 58

MoveToORPType Theory, 62

Datatypes, 62

Theorems, 63

slCommand_distinct_clauses, 63

slOutput_distinct_clauses, 63

slState_distinct_clauses, 63

MoveToPBType Theory, 68

Datatypes, 68

Theorems, 68

slCommand_distinct_clauses, 68

slOutput_distinct_clauses, 68

slState_distinct_clauses, 69

OMNIType Theory, 3

Datatypes, 3

Theorems, 3

command_distinct_clauses, 3

command_one_one, 3

escCommand_distinct_clauses, 3

escOutput_distinct_clauses, 3

escState_distinct_clauses, 3

output_distinct_clauses, 4

output_one_one, 4

principal_one_one, 4

state_distinct_clauses, 4

state_one_one, 4

PBIntegratedDef Theory, 23

Definitions, 23

secAuthorization_def, 23

secContext_def, 23

secHelper_def, 24

Theorems, 24

getOmniCommand_def, 24

getOmniCommand_ind, 27

getPlCom_def, 28

getPlCom_ind, 28

PBTypeIntegrated Theory, 21

Datatypes, 21

Theorems, 22

omniCommand_distinct_clauses, 22

plCommand_distinct_clauses, 22

slCommand_distinct_clauses, 22

slCommand_one_one, 22

slOutput_distinct_clauses, 23

slState_distinct_clauses, 23

stateRole_distinct_clauses, 23

PlanPBDef Theory, 82

- Definitions, 82
 - PL_notWARNO_Auth_def, 82
 - PL_WARNO_Auth_def, 82
 - secContext_def, 82
 - secContextNull_def, 83
- Theorems, 83
 - getInitMove_def, 83
 - getInitMove_ind, 85
 - getPlCom_def, 87
 - getPlCom_ind, 89
 - getPsgCom_def, 90
 - getPsgCom_ind, 92
 - getRecon_def, 93
 - getRecon_ind, 96
 - getReport_def, 98
 - getReport_ind, 101
 - getTenativePlan_def, 104
 - getTenativePlan_ind, 107
- PlanPBType Theory**, 79
 - Datatypes, 79
 - Theorems, 79
 - plCommand_distinct_clauses, 79
 - psgCommand_distinct_clauses, 80
 - slCommand_distinct_clauses, 80
 - slCommand_one_one, 80
 - slOutput_distinct_clauses, 80
 - slRole_distinct_clauses, 81
 - slState_distinct_clauses, 81
- satList Theory**, 21
 - Definitions, 21
 - satList_def, 21
 - Theorems, 21
 - satList_conj, 21
 - satList_CONS, 21
 - satList_nil, 21
- ssm Theory**, 11
 - Datatypes, 11
 - Definitions, 12
 - authenticationTest_def, 12
 - commandList_def, 12
 - inputList_def, 12
 - propCommandList_def, 12
 - TR_def, 12
 - Theorems, 13
 - CFGInterpret_def, 13
 - CFGInterpret_ind, 13
 - configuration_one_one, 13
 - extractCommand_def, 13
 - extractCommand_ind, 13
 - extractInput_def, 14
 - extractInput_ind, 14
 - extractPropCommand_def, 15
 - extractPropCommand_ind, 15
 - TR_cases, 16
 - TR_discard_cmd_rule, 17
 - TR_EQ_rules_thm, 17
 - TR_exec_cmd_rule, 17
 - TR_ind, 18
 - TR_rules, 18
 - TR_strongind, 19
 - TR_trap_cmd_rule, 20
 - TRrule0, 20
 - TRrule1, 20
 - trType_distinct_clauses, 20
 - trType_one_one, 21
- ssm11 Theory**, 4
 - Datatypes, 4
 - Definitions, 4
 - TR_def, 4
 - Theorems, 5
 - CFGInterpret_def, 5
 - CFGInterpret_ind, 6
 - configuration_one_one, 6
 - order_distinct_clauses, 6
 - order_one_one, 6
 - TR_cases, 6
 - TR_discard_cmd_rule, 7
 - TR_EQ_rules_thm, 7
 - TR_exec_cmd_rule, 8
 - TR_ind, 8
 - TR_rules, 9
 - TR_strongind, 9
 - TR_trap_cmd_rule, 10
 - TRrule0, 10
 - TRrule1, 11
 - trType_distinct_clauses, 11

trType_one_one, 11

ssmConductORP Theory, 35

Theorems, 35

- conductORPNS_def, 35
- conductORPNS_ind, 35
- conductORPOut_def, 36
- conductORPOut_ind, 36
- inputOK_cmd_reject_lemma, 36
- inputOK_def, 36
- inputOK_ind, 37
- PlatoonLeader_ACTIONS_IN_exec_justified_lemma, 38
- PlatoonLeader_ACTIONS_IN_exec_justified.thm, 39
- PlatoonLeader_ACTIONS_IN_exec_lemma, 39
- PlatoonLeader_ACTIONS_IN_trap_justified_lemma, 40
- PlatoonLeader_ACTIONS_IN_trap_justified.thm, 41
- PlatoonLeader_ACTIONS_IN_trap_lemma, 41
- PlatoonLeader_CONDUCT_ORP_exec_secure_justified.thm, 41
- PlatoonLeader_CONDUCT_ORP_exec_secure_lemma, 42
- PlatoonSergeant_SECURE_exec_justified_lemma, 42
- PlatoonSergeant_SECURE_exec_justified.thm, 43
- PlatoonSergeant_SECURE_exec_lemma, 44

ssmConductPB Theory, 51

Definitions, 51

- secContextConductPB_def, 51
- ssmConductPBStateInterp_def, 52

Theorems, 52

- authTestConductPB_cmd_reject_lemma, 52
- authTestConductPB_def, 52
- authTestConductPB_ind, 53
- conductPBNS_def, 53
- conductPBNS_ind, 54
- conductPBOut_def, 54
- conductPBOut_ind, 55
- PlatoonLeader_exec_plCommandPB_justified.thm, 55
- PlatoonLeader_plCommandPB_lemma, 56
- PlatoonSergeant_exec_psgCommandPB_justified.thm, 56
- PlatoonSergeant_psgCommandPB_lemma, 56

ssmMoveToORP Theory, 58

Definitions, 58

- secContextMoveToORP_def, 58
- ssmMoveToORPStateInterp_def, 58

Theorems, 58

- authTestMoveToORP_cmd_reject_lemma, 58
- authTestMoveToORP_def, 58
- authTestMoveToORP_ind, 59
- moveToORPNS_def, 60
- moveToORPNS_ind, 60
- moveToORPOut_def, 61
- moveToORPOut_ind, 61
- PlatoonLeader_exec_slCommand_justified.thm, 62
- PlatoonLeader_slCommand_lemma, 62

ssmMoveToPB Theory, 63

Definitions, 63

- secContextMoveToPB_def, 63
- ssmMoveToPBStateInterp_def, 64

Theorems, 64

- authTestMoveToPB_cmd_reject_lemma, 64
- authTestMoveToPB_def, 64
- authTestMoveToPB_ind, 65
- moveToPBNS_def, 65
- moveToPBNS_ind, 66
- moveToPBOut_def, 66
- moveToPBOut_ind, 66
- PlatoonLeader_exec_slCommand_justified.thm, 67
- PlatoonLeader_slCommand_lemma, 68

ssmPBIntegrated Theory, 28

- Theorems, 28
 - inputOK_cmd_reject_lemma, 28
 - inputOK_def, 28
 - inputOK_ind, 29
 - PBNS_def, 30
 - PBNS_ind, 30
 - PBOut_def, 30
 - PBOut_ind, 31
 - PlatoonLeader_Omni_notDiscard_slCom-
mand_thm, 31
 - PlatoonLeader_PLAN_PB_exec_justi-
fied_lemma, 31
 - PlatoonLeader_PLAN_PB_exec_justi-
fied_thm, 32
 - PlatoonLeader_PLAN_PB_exec_lemma,
33
 - PlatoonLeader_PLAN_PB_trap_justi-
fied_lemma, 33
 - PlatoonLeader_PLAN_PB_trap_justi-
fied_thm, 34
 - PlatoonLeader_PLAN_PB_trap_lemma,
35
- ssmPlanPB Theory**, 69
 - Theorems, 69
 - inputOK_def, 69
 - inputOK_ind, 70
 - planPBNS_def, 70
 - planPBNS_ind, 71
 - planPBOut_def, 71
 - planPBOut_ind, 72
 - PlatoonLeader_notWARNO_notreport1_-
exec_plCommand_justified_lemma, 72
 - PlatoonLeader_notWARNO_notreport1_-
exec_plCommand_justified_thm, 73
 - PlatoonLeader_notWARNO_notreport1_-
exec_plCommand_lemma, 73
 - PlatoonLeader_psgCommand_notDis-
card_thm, 74
 - PlatoonLeader_trap_psgCommand_jus-
tified_lemma, 74
 - PlatoonLeader_trap_psgCommand_lemma,
74
 - PlatoonLeader_WARNO_exec_report1_-
justified_lemma, 75
 - PlatoonLeader_WARNO_exec_report1_-
justified_thm, 76
 - PlatoonLeader_WARNO_exec_report1_-
lemma, 77
 - PlatoonSergeant_trap_plCommand_jus-
tified_lemma, 77
 - PlatoonSergeant_trap_plCommand_jus-
tified_thm, 78
 - PlatoonSergeant_trap_plCommand_lemma,
78