

Contents

1	Title head * TAB	1
1.1	sub title * * TAB or * TAB * 	1
2	Plain Lists + TAB or - TAB	1
3	Links [[]]	2

1 Title head | * TAB |

1.1 sub title | * * TAB or * TAB * |

3.1 Built-in Table Editor

Org makes it easy to format tables in plain ASCII. Any line with `'|'` as the first non-whitespace character is considered part of a table. `'|'` is also the column separator^{[12](#)}. Moreover, a line starting with `'| - '` is a horizontal rule. It separates rows explicitly. Rows before the first horizontal rule are header lines. A table might look like this:

	Name		Phone		Age	
	-----+		-----+		-----	
	Peter		1234		17	
	Anna		4321		25	

A table is re-aligned automatically each time you press `TAB`, `RET` or `C-c C-c` inside the table. `TAB` also moves to the next field—`RET` to the next row—and creates new table rows at the end of the table or before horizontal lines. The indentation of the table is set by the first line. Horizontal rules are automatically expanded on every re-align to span the whole table width. So, to create the above table, you would only type

	Name		Phone		Age	
	-					

Figure 1: How to make Built-in Table

from <https://orgmode.org/org.html>

Table 1: Insert caption

Name	phone	age
peter	1234	17
Anna	4321	25

2 Plain Lists | + TAB or - TAB |

- link1_test
- is it working well?

- .

3 Links | [] |

- https `https://sryuauos.github.io/Manuals/`
- file `file:///home/Manuals/Manuals/Map.org`
 - `file:///home/Manuals/Manuals/Map.org`