



Coláiste na Tríonóide, Baile Átha Cliath
Trinity College Dublin

Ollscoil Átha Cliath | The University of Dublin

Faculty of Engineering, Mathematics and Science

School of Computer Science and Statistics

Senior Freshman Integrated Computer Science
Senior Freshman Computer Science Joint Honours

Michaelmas Term 2021

Systems Programming

10th December 2021

Take Home Exam

14.00 – 19.00

Dr David Gregg


Instructions to Candidates:

- ☐ Answer 1 out of the 2 questions
- ☐ All questions are marked out of 100
- ☐ All program code should be commented, indented and use good programming style
- ☐ Answers to the questions should be completed by completing corresponding assignments that can be found on the CSU22014 Blackboard page.

Materials permitted for this examination:

Question 1

On most computers the smallest sized piece of memory that can be accessed is a byte. However, for some applications it is useful to be able to operate on sub-byte sizes of data. For example, half a byte (4 bits) is often called a nybble. We want to pack two nybbles into each byte in memory as follows:



Write a C abstract data type (ADT) to represent a sequence of nybbles that can be indexed like an array. Each nybble value within the array should be a 4-bit unsigned integer value capable of representing a value in the range 0 to 15. Your ADT should store the nybbles internally by packing two nybbles into each byte of storage. Your ADT should support the following functions:

- `// create new array of nybbles with space for "size" nybbles and initialize the
// values of the array to zero`
`struct nybble_array * nybble_array_new(int size);` [24 marks]
- `// return the nybble value at position index`
`unsigned get_nybble_value(struct nybble_array * this, int index);` [22 marks]
- `// set the nybble at position index to value`
`void set_nybble_value(struct nybble_array * this, int index, unsigned value);`
 [22 marks]
- `// free the memory used by a nybble array`
`void nybble_array_free(struct nybble_array * this);` [8 marks]
- `// given an array of unsigned integers with values 0 to 15, create a`

```
// new nybble array with the same values
```

```
struct nybble_array * unsigned_to_nybble_array(unsigned * array, int size);
```

[12 marks]

f) // given an array of nybbles, create a new array of unsigned integers with the same values

```
unsigned * nybble_array_to_unsigned(struct nybble_array * this);
```

[12 marks]

This is an online exam. Students will be given C language source files in which to write their solution, and test cases that they can use to test their code.

[Total: 100 marks]