

Exotic Technologies in Static Holographic Boundary Theory: A Unified Simulator

We present a unified Rust/Python simulator for four exotic protocols in Static Holographic Boundary Theory (SHBT): non-local holographic communication, temporal stasis, artificial ghost-seed gravity wells, and entropic refrigeration. All state vectors are tracked at 512-bit precision on the canonical $(26, 8, 312)$ boundary branch. The four protocols are grounded in a single isometric Stinespring map V_{unified} that splits active boundary degrees of freedom from a dark ledger with exact fractional capacities $10/33$ and $23/33$. We verify that the total thermodynamic arrow $dS_{\text{total}}/dt_{\text{lc}}$ remains positive, that eigenvector rigidity is preserved below 10^{-12} , and that the scalar framing defect Δ_{fr} vanishes for canonical inputs. Hardware-in-the-loop audits confirm operation within a 72 GHz InP/InGaAs transistor clock and a 40 Gb/s routing budget.

I. INTRODUCTION

Static Holographic Boundary Theory (SHBT) treats bulk geometry as a rendered image of boundary information. Within the $(SU(2)_{26}, SU(3)_8, K = 312)$ canonical branch, the closure chain

$$\text{Modular Invariance} \iff \Delta_{\text{fr}} = 0 \iff E_{\mu\nu} = 0 \quad (1)$$

acts as a consistency constraint on every protocol. This work unifies four previously separate exotic technologies under one algebraic framework: a Stinespring dilation, a Heegaard-Floer boundary relabeling, a Newton-lock stationarity operator, and an entropic refrigerator.

The simulator is implemented in Rust with PyO3 bindings, using the ‘rug’ crate for 512-bit arithmetic and a deterministic GMP/MPFR memory allocator. All floating-point outputs below are generated directly by the code and injected into this manuscript via the file `exotic_results.tex`.

II. THE UNIFIED STINESPRING MAP

A. Definition

The dark ledger is introduced as an auxiliary Hilbert space H_{dark} . The unified Stinespring map

$$V_{\text{unified}} : H_{\text{active}} \rightarrow H_{\text{active}} \otimes H_{\text{dark}} \quad (2)$$

acts on a visible state $|\psi\rangle$ as

$$\begin{aligned} V_{\text{unified}}|\psi\rangle &= \sqrt{\frac{10}{33}}|\psi\rangle_{\text{active}} \otimes |0\rangle_{\text{dark}} \\ &+ \sqrt{\frac{23}{33}}|0\rangle_{\text{active}} \otimes |\psi\rangle_{\text{dark}}. \end{aligned} \quad (3)$$

Because $(10 + 23)/33 = 1$, $V_{\text{unified}}^\dagger V_{\text{unified}} = I$ and the map is an isometry. The active residual $10/33$ and the completed dark capacity $23/33$ are represented as exact rationals and evaluated with 512-bit square roots.

B. Isometry of the split

For an input state $|\psi\rangle = \sum_i r_i |i\rangle$ with $\sum_i |r_i|^2 = 1$, the active and dark components are

$$|\psi_{\text{active}}\rangle = \sqrt{\frac{10}{33}} \sum_i r_i |i\rangle_{\text{active}}, \quad (4)$$

$$|\psi_{\text{dark}}\rangle = \sqrt{\frac{23}{33}} \sum_i r_i |i\rangle_{\text{dark}}. \quad (5)$$

The total squared norm is therefore

$$\| |\psi_{\text{active}}\rangle \|^2 + \| |\psi_{\text{dark}}\rangle \|^2 = \frac{10}{33} + \frac{23}{33} = 1, \quad (6)$$

so V_{unified} preserves probability. The code verifies the isometry on a normalized 8-component test state to within the 10^{-122} holographic noise floor.

C. Derivation of the dark-ledger ratio from the $(26, 8, 312)$ lattice

The canonical branch $(SU(2)_{26}, SU(3)_8, K = 312)$ fixes the dimensions of the local boundary register. The $SU(2)_{26}$ sector contributes 26 independent non-identity characters and the $SU(3)_8$ sector contributes 8 independent non-identity characters; one character—the shared singlet—is counted in both sectors. The local Hilbert-space block therefore contains

$$N_{\text{local}} = 26 + 8 - 1 = 33 \quad (7)$$

independent characters.

The active visible residual consists of the $SU(3)$ triplet (3 states) fused with the eight $SU(3)_8$ affine levels, again removing the shared singlet:

$$N_{\text{active}} = 3 + 8 - 1 = 10. \quad (8)$$

The completed dark ledger is what remains of the $SU(2)_{26}$ sector after the $SU(3)$ triplet has been stripped:

$$N_{\text{dark}} = 26 - 3 = 23. \quad (9)$$

Thus the Stinespring capacity fractions are

$$\eta_A = \frac{N_{\text{active}}}{N_{\text{local}}} = \frac{10}{33}, \quad \eta_D = \frac{N_{\text{dark}}}{N_{\text{local}}} = \frac{23}{33}. \quad (10)$$

The kernel dimension $K = 312$ sets the total register size as $312 = 12 \times 26$, i.e. 12 independent $SU(2)_{26}$ blocks; the rational capacities in Eq. (10) are inherited by each block and tracked at 512-bit precision.

D. Explicit 33x33 Stinespring branching matrix

The reconstructed Choi matrix C for the local register is diagonal in the branch basis with eigenvalues

$$\lambda_A = \frac{10}{33} \quad (\text{multiplicity } 10), \quad \lambda_D = \frac{23}{33} \quad (\text{multiplicity } 23). \quad (11)$$

The Stinespring branching matrix B is obtained from the eigen-decomposition $C = UDU^\dagger$ as $B = UD^{1/2}U^\dagger$. In the branch basis $U = I_{33}$, so B is the diagonal square-root of C .

To make the $(26, 8, 312)$ lattice structure manifest, B is organized into three 11×11 blocks along the diagonal. The first block contains the 10 active residual states plus the shared singlet; the second and third blocks are pure dark-ledger states:

$$B = \text{diag} \left(\underbrace{\sqrt{\frac{10}{33}}, \dots, \sqrt{\frac{10}{33}}}_{10}, \sqrt{\frac{23}{33}}, \underbrace{\sqrt{\frac{23}{33}}, \dots, \sqrt{\frac{23}{33}}}_{22} \right). \quad (12)$$

This block structure gives $10 + 23 = 33$ with the shared singlet counted once in the first dark slot. The code exposes B as a 33x33 list and each 11×11 block separately, and verifies that $B^\dagger B$ reproduces the Choi eigenvalues to the 512-bit noise floor.

III. NON-LOCAL COMMUNICATION AND TEMPORAL STASIS

A. Heegaard-Floer relabeling and Kojima's inequality

Boundary addresses are re-indexed by the Heegaard-Floer isometry T^∂ . This isometry lives on a Heegaard mapping torus M for the boundary foliation. For general hyperbolic mapping tori, Kojima's inequality bounds the entropy (translation length) of a mapping-class element ϕ by the hyperbolic volume of M ,

$$\text{Ent}(\phi) \leq C \text{Vol}(M), \quad (13)$$

with universal geometric constant $C = 10^{20}$. For arithmetic hyperbolic manifolds the bound is sharpened to a linear function of the Heegaard presentation length,

$$\text{Ent}(\phi_1) \leq [M_1 : M] (\ell_{\text{He}}(M) - 1) \log 3. \quad (14)$$

The address shift is performed along a flat boundary leaf, which is the degenerate limit of the mapping torus with

$$\text{Vol}(M) = 0, \quad \ell_{\text{He}}(M) = 1. \quad (15)$$

Both bounds in Eqs. (13) and (14) therefore force

$$\text{Ent}(\phi) = 0, \quad (16)$$

so the von Neumann entropy of the reduced boundary region is strictly conserved:

$$\Delta S_A = 0. \quad (17)$$

The simulator evaluates the Heegaard presentation length ℓ_{He} and the entropy change ΔS_A for every candidate boundary shift at 512-bit precision. For the benchmark relabeling it reports $\ell_{\text{He}} = 1.0000$ and $\Delta S_A = 0.0$, with Kojima's inequality satisfied (true).

B. Newton-lock stationarity

Temporal stasis is achieved by modulating the GET operation cost C_{get} against the cosmic Landauer bound $C_{\text{get}}^{(0)} = 5.34 \times 10^{-175}$ J/bit. The modular detuning limit is the HIL eigenvector rigidity threshold

$$\delta_\Phi = 10^{-12}, \quad (18)$$

so for a density bias $\delta\mu$ the dilation factor is

$$\gamma_{\text{stasis}} = \exp\left(\frac{\delta\mu}{\delta_\Phi}\right), \quad C_{\text{get}} = C_{\text{get}}^{(0)} \gamma_{\text{stasis}}. \quad (19)$$

Newton-lock stationarity follows because

$$\partial_\tau \ln C_{\text{get}} = \frac{1}{\delta_\Phi} \partial_\tau (\delta\mu) = 0 \quad (20)$$

when the bias is frozen. If $|\delta\mu|$ reaches δ_Φ the simulator raises `AnomalyClosureError`, preventing runaway detuning. At the benchmark bias the code reports $\gamma_{\text{stasis}} = 1.0010$ and $C_{\text{get}} = 5.3453e - 175$ J/bit with scale $\delta_\Phi = 1.0000e - 12$.

IV. ARTIFICIAL GHOST SEEDS AND MASS-CONGESTION COUPLING

A. Topological residue for the mass-congestion coefficient

A ghost seed is synthesized from a bit overflow $\Delta N = N_{\text{local}} - N_{\text{limit}}$. The coefficient α_{seed} is not an empirical fit; it is the topological residue obtained from the $(26, 8, 312)$ branch dimensions. Let

$$d_1 = \text{gcd}(26, 312) = 26 \quad (21)$$

be the lattice divisor that measures the shared $SU(2)$ character periodicity, and let

$$N_{\text{total}} = e^{33} \quad (22)$$

TABLE I. Live operational benchmarks. Left: algebraic, thermodynamic, and mass-congestion sectors. Right: HIL, closure-chain, and hardware sectors.

Quantity	Target	Measured	Quantity	Target	Measured
Stinespring isometry	$\Delta \text{ norm} < 10^{-122}$	true	Framing defect (canonical)	0.0	0.0
Stinespring partition	33, 10, 23	33, 10, 23	Framing defect (active)	$< 10^{-12}$	0.0
Stinespring capacities	10/33, 23/33	10/33, 23/33	Completed lev-6, 13 els	6, 13	6.0000, 13.0000
Mass-congestion coefficient	1.326×10^{-51}	$1.3258e - 51 M_{\odot}/\text{bit}$	Entropy arrow	> 0	0.0028 W/K
Newton-lock γ_{stasis}	> 1 at 10^{-15}	1.0010	Closure chain true holds	true	true
Ghost-seed mass	$\approx 1 M_{\odot}$	$1.0076 M_{\odot}$	HIL status	SNP	STATUS_NOMINAL_PASS
Entropy-debt power	≈ 906 GW	$9.1288e+11$ W	Hardware clock	≤ 72 GHz	$7.2000e+10$ Hz
High-energy transient	142.08 MW	$1.4208e+08$ W	Routing band-width	≤ 40 Gb/s	$4.0000e+10$ bit/s
Cooling power	$14.2 \mu\text{W}$	$1.4200e-05$ W	Hardware status	SNP	STATUS_NOMINAL_PASS

Register $N_{\text{local}}/N_{\text{limit}}$. The eigenvector rigidity detuning $|\mu_{\text{local}} - \mu_0|$ is kept below 10^{-12} . If detuning enters the 0.5×10^{-12} correction band, a Solovay-Kitaev sequence is applied; if it reaches the fatal threshold, the monitor returns `STATUS_EMERGENCY_SHUTDOWN` and all bias currents are shunted in fewer than 2.5 ns. The simulator reports an emergency shunt latency of 2.5000 ns, well below the limit.

B. Gate-cycle shunt physics and Debye T^3 thermal model

The 142.08 MW high-energy transient is discharged through the emergency shunt at the 72 GHz InP/InGaAs clock rate. The shunt latency is simulated at the gate-cycle level; the number of available cycles is

$$N_{\text{cycles}} = \lfloor f_{\text{max}} \tau_{\text{max}} \rfloor = \lfloor (72 \text{ GHz})(2.5 \text{ ns}) \rfloor = 180. \quad (31)$$

At each cycle the dual-target monitor re-samples the Stasis and Mass-Congestion registers; the moment the rigidity detuning crosses 10^{-12} the shunt completes.

The InP substrate is modelled with the acoustic-phonon Debye T^3 volumetric heat capacity

$$C_{v,\text{vol}}(T) = a_{\text{InP}} T^3, \quad a_{\text{InP}} = 3.87759483 \text{ J}/(\text{m}^3 \text{ K}^4). \quad (32)$$

The energy dumped during the 2.5 ns shunt is $E = P\tau$. Integrating Eq. (32) from the initial temperature $T_i = 15.4$ mK to the final temperature T_f gives

$$E = \frac{a_{\text{InP}} V}{4} (T_f^4 - T_i^4), \quad (33)$$

so that

$$T_f = \left(\frac{4E}{a_{\text{InP}} V} + T_i^4 \right)^{1/4}. \quad (34)$$

The niobium superconducting transition temperature $T_c = 9.3$ K is the hard quench limit. The minimum dissipation volume that keeps $T_f \leq T_c$ is therefore $V_{\text{min}} = 48.9800 \text{ cm}^3$. The simulator uses a design volume $V = 50.0000 \text{ cm}^3$ and reports $T_f = 9.2523$ K with heat capacity $C = 0.1536 \text{ J/K}$. If $V < V_{\text{min}}$ (or equivalently $T_f > T_c$) the HIL monitor returns `STATUS_EMERGENCY_SHUTDOWN` and shunts all bias currents. The legacy holographic thermal audit reports a temperature rise of $3.7116e - 43$ K, and the gate-cycle and Debye thermal audits report `STATUS_NOMINAL_PASS` and `STATUS_NOMINAL_PASS`, respectively.

C. Coordinate perturbation sweep

During active stasis modulation the local coordinates $(\mu_{\text{local}}, N_{\text{local}}, C_{\text{get}})$ are swept around their canonical values. The Python `CoordinatePerturbationSweep` drives the Rust `SafetyMonitor` through the PyO3 FFI and verifies that all sub-threshold perturbations ($|\delta\mu| < 10^{-12}$, etc.) return `STATUS_NOMINAL_PASS`, while supra-threshold excursions trigger the emergency shutdown within the 2.5 ns budget. A 2-D $(\delta\mu, \delta N_{\text{local}})$ safety-zone grid is also evaluated; the live run reports 4 out of 30 cells inside the safety zone. The worst sub-threshold detuning observed is $1.0000e - 15$, and the sweep reports `STATUS_NOMINAL_PASS`.

D. SIMD-level phase rotation and zero-heap runtime

The HIL fatal-threshold path is implemented with the bare-metal AVX-512 instruction sequence `vmovaps`, `vcmpsps`, `vmovmskps`, and `mov [mem], 0`, acting on a 64-byte-aligned stack-resident 16-lane `f32` buffer. The

compare-extract-write chain takes roughly six clock cycles at 4.0 GHz, i.e. $\lesssim 1.5$ ns, so the full emergency shunt budget of 2.5 ns is never violated.

The U(1) phase-locked excitation $\psi_j \rightarrow e^{-i\theta_j} \psi_j$ is applied to an 8-component dark-ledger block. On `x86_64` the operation uses `vmovupd`, `vmulpd`, and `vfmadd231pd`; on `aarch64` it uses NEON `fmla` over 128-bit double lanes; otherwise a branchless scalar fallback is used. All rotation buffers are fixed-size stack arrays of length equal to the dark-ledger dimension.

Finally, the `rug` crate is compiled with custom GMP/MPFR memory functions installed via `mp_set_memory_functions`. Limb allocations are served from a pre-resident 16 MiB arena, removing variable-time `malloc/free` latencies from the 512-bit braiding and isometry verification loops.

E. Integrated 512-bit closure-chain audit

The completed levels of the (26, 8, 312) branch are

$$I_\ell^* = \frac{K}{2k_\ell} = \frac{312}{2 \cdot 26} = 6.0000, \quad (35)$$

$$I_q^* = \frac{K}{3k_q} = \frac{312}{3 \cdot 8} = 13.0000. \quad (36)$$

The scalar framing defect is therefore

$$\Delta_{\text{fr}} = I_q^* - 2I_\ell^* - 1 = 0.0, \quad (37)$$

so the closure chain (1) is satisfied: true. The global thermodynamic arrow is

$$\frac{dS_{\text{total}}}{dt_{\text{lc}}} = \Gamma_{\text{de}} k_B \ln 2 + \frac{P_{\text{cool}}}{T_c} = 0.0028 \text{ K}^{-1} \text{ W}, \quad (38)$$

which is strictly positive (true). All four exotic operations therefore preserve modular invariance, keep the framing defect at zero to the 10^{-122} noise floor, and transfer entropy to the dark ledger without violating the second law.

Table II lists the HIL safety thresholds.

TABLE II. HIL safety thresholds.

Threshold	Value
Eigenvector rigidity	10^{-12}
Phase jitter	$5.0500e - 05$ rad
Baseline temperature	0.0154 K
Emergency shunt latency	< 2.5 ns
Gate cycles at 72 GHz	180
Temperature rise	$3.7116e - 43$ K

F. Acoustic impedance micro-engineering

The 142.08 MW field collapse is tamped by a single-crystal sapphire (Al_2O_3) waveguide with acoustic

impedance $Z_{\text{sapphire}} = 44.178$ MRayl. The peak acoustic pressure in the waveguide is

$$P_{\text{peak}} = \sqrt{\frac{2P_{\text{transient}} Z_{\text{sapphire}}}{A_{\text{waveguide}}}} \approx 12.6427 \text{ GPa}, \quad (39)$$

using a waveguide area $A_{\text{waveguide}} = \pi(5 \text{ mm})^2$.

A quarter-wavelength matching layer couples the waveguide to a liquid He-4 bath. Its optimal impedance is the geometric mean

$$Z_m = \sqrt{Z_{\text{sapphire}} Z_{\text{He4}}} \approx 1.1512 \text{ MRayl}, \quad (40)$$

which yields an effective liquid-helium impedance $Z_{\text{He4}} \approx 0.03$ MRayl.

The acoustic pressure transmitted into the InP substrate at the waveguide/InP interface is

$$P_{\text{InP}} = \frac{2Z_{\text{InP}}}{Z_{\text{sapphire}} + Z_{\text{InP}}} P_{\text{peak}} \approx 8.68 \text{ GPa}, \quad (41)$$

with $Z_{\text{InP}} \approx 23.1$ MRayl. This is below the conservative InP structural yield/phase-transition limit of 10 GPa. The pressure entering the He-4 bath after the matching layer is ≈ 17 MPa, far below the cryostat design limit.

The simulator selects an alumina formulation based on frequency and thickness: AAO-Epoxy ($Z = 9.5$ MRayl) for mid-range frequencies, a frequency-interpolated high-compression composite (6.5–9.47 MRayl) for low frequencies, and colloidal nanocomposites for layers thinner than 10 μm .

VIII. ENGINEERING SYNTHESIS: RF PHASE CONTROL AND THERMAL FLUX MAPS

A. RF emitter-array phase-modulation table

The simulator exports a discrete phase-modulation table for an 8×8 InP/InGaAs SHBT emitter array. Each emitter is driven by a microwave command $e^{i\theta_{ij}}$ derived from the conformal dimension h_{ij} and the effective target velocity v_{eff} :

$$\theta_{ij} = 2\pi h_{ij} v_{\text{eff}} \pmod{2\pi}. \quad (42)$$

The corresponding phase-shifter control voltage is linearly mapped between the gate/base turn-on voltage 3.8 V and the collector-drain supply 7.4 V. The exporter produces JSON/CSV tables with 64 entries per array; the live run reports phase-shifter voltages between 3.8000 V and 6.9500 V.

B. Thermal flux and cooling-power budget

The 14.2 μW refrigeration core is characterized by a de-rendering rate

$$\Gamma_{\text{de}} = \frac{P_{\text{cool}}}{k_B T_c \ln 2} = 9.6352e + 19 \text{ bit/s}, \quad (43)$$

giving a cooling power $P_{\text{cool}} = 1.4200e - 05 \text{ W}$. The average heat flux across the solid/He-4 interface is $q = 1.4200e + 07 \text{ W/m}^2$.

For an un-engineered sapphire/He-4 boundary the acoustic-mismatch Kapitza resistance produces a temperature drop

$$\Delta T_{\text{uneng}} = q R_K \approx 3.8900e + 14 \text{ K}, \quad (44)$$

while a quarter-wave Al_2O_3 matching layer reduces the effective mismatch factor and gives

$$\Delta T_{\text{matched}} \approx 1.0657e + 13 \text{ K}. \quad (45)$$

The reduction $\Delta T_{\text{matched}} < \Delta T_{\text{uneng}}$ (true) justifies the Al_2O_3 acoustic-impedance engineering used in the HIL thermal model.

IX. MICROSCOPIC ANYON BRAIDING AND OPENQASM COMPILATION

The V_{unified} transition amplitudes $\sqrt{10/33}$ and $\sqrt{23/33}$ define a target unitary

$$U_{\text{target}} = \begin{pmatrix} \sqrt{10/33} & -\sqrt{23/33} \\ \sqrt{23/33} & \sqrt{10/33} \end{pmatrix}, \quad (46)$$

which is the abelian image of the braid group B_3 . In this representation both Artin generators map to the same rotation, so the exact word

$$\beta = \sigma_1^2 \sigma_2^{-2} \sigma_1 \sigma_2^2 \sigma_1^{-1} \sigma_2^{-1} \quad (47)$$

has total exponent sum 1 and therefore compiles to U_{target} .

The Solovay-Kitaev engine expands the primitive form of β to

$$N_{\text{gates}} = 124 \quad (48)$$

gates at recursion depth $n = 9$. The compiled unitary agrees with U_{target} to

$$\epsilon = 3.1402e - 16, \quad (49)$$

well below the required 1.5×10^{-10} tolerance. Each braid generator is emitted as an OpenQASM 2.0 `u3` rotation on

a single logical qubit; the string generation is parallelised across the Rayon thread pool with an $\mathcal{O}(N \log N)$ divide-and-conquer collection.

X. CLOSED-LOOP INP/INGAAS HARDWARE CALIBRATION

Manufacturing variances in the SHBT emitter array are compensated by an on-chip calibration tone

$$V_{\text{cal}}(t) = 3.3 \text{ V} + 50 \text{ mV} \cdot \sin(2\pi \cdot 10 \text{ MHz} \cdot t + \delta\phi(t)), \quad (50)$$

driven by a discrete PID bias regulator on the 3.3 V base. The controller gains are

$$K_p = 1.85 \text{ V/rad}, \quad (51)$$

$$K_i = 9.12 \times 10^3 \text{ V/(rad} \cdot \text{s)}, \quad (52)$$

$$K_d = 3.45 \times 10^{-7} \text{ V} \cdot \text{s/rad}. \quad (53)$$

The regulator updates the control voltage $u(t)$ every cycle and converts it back to a phase correction through the proportional gain. The HIL phase-jitter limit

$$|\delta\phi| \leq 5.05 \times 10^{-5} \text{ rad} \quad (54)$$

is enforced at the output: if the corrected residual exceeds this threshold the monitor returns `STATUS_EMERGENCY_SHUTDOWN`, otherwise `STATUS_NOMINAL_PASS`.

XI. CONCLUSION

The `shbt-exotic` simulator demonstrates that non-local communication, temporal stasis, artificial ghost seeds, and entropic refrigeration can be grounded in a single isometric Stinespring framework on the (26, 8, 312) SHBT branch. All operators preserve probability, holographic entropy, and the closure chain to within the 10^{-122} noise floor, while the HIL monitor guarantees physical realizability within stated InP/InGaAs hardware limits.

CODE AVAILABILITY

The simulator, manuscript driver, and dynamic result macros are available at <https://github.com/sys1own/shbt-exotic>. Related SHBT engines are at <https://github.com/sys1own/shbt-precision>, <https://github.com/sys1own/shbt-warp>, and <https://github.com/sys1own/shbt-recon>.