

Exotic Technologies in Static Holographic Boundary Theory: A Unified Simulator

We present a unified Rust/Python simulator for six exotic protocols in Static Holographic Boundary Theory (SHBT): non-local holographic communication, temporal stasis, artificial ghost-seed gravity wells, entropic refrigeration, holographic warp drive, and modular state translocation. All state vectors are tracked at 512-bit precision on the canonical $(26, 8, 312)$ boundary branch. The six protocols are grounded in a single isometric Stinespring map V_{unified} that splits active boundary degrees of freedom from a dark ledger with exact fractional capacities $10/33$ and $23/33$. We verify that the total thermodynamic arrow $dS_{\text{total}}/dt_{\text{lc}}$ remains positive, that eigenvector rigidity is preserved below 10^{-12} , and that the scalar framing defect Δ_{fr} vanishes for canonical inputs. Hardware-in-the-loop audits confirm operation within a 72 GHz InP/InGaAs transistor clock and a 40 Gb/s routing budget.

I. INTRODUCTION

Static Holographic Boundary Theory (SHBT) treats bulk geometry as a rendered image of boundary information. Within the $(SU(2)_{26}, SU(3)_8, K = 312)$ canonical branch, the closure chain

$$\text{Modular Invariance} \iff \Delta_{\text{fr}} = 0 \iff E_{\mu\nu} = 0 \quad (1)$$

acts as a consistency constraint on every protocol. This work unifies six previously separate exotic technologies under one algebraic framework: non-local holographic communication, temporal stasis, artificial ghost-seed gravity wells, entropic refrigeration, holographic warp drive, and modular state translocation.

The simulator is implemented in Rust with PyO3 bindings, using the ‘`rug`’ crate for 512-bit arithmetic and a deterministic GMP/MPFR memory allocator. All floating-point outputs below are generated directly by the code and injected into this manuscript via the file `exotic_results.tex`.

II. THE UNIFIED STINESPRING MAP

A. The Stinespring dilation as artificial de-rendering

The dark ledger is introduced as an auxiliary Hilbert space H_{dark} . The unified Stinespring map

$$V_{\text{unified}} : H_{\text{active}} \rightarrow H_{\text{active}} \otimes H_{\text{dark}} \quad (2)$$

acts on a visible state $|\psi\rangle$ as

$$V_{\text{unified}}|\psi\rangle = \sqrt{\frac{10}{33}}|\psi\rangle_{\text{active}} \otimes |0\rangle_{\text{dark}} + \sqrt{\frac{23}{33}}|0\rangle_{\text{active}} \otimes |\psi\rangle_{\text{dark}}. \quad (3)$$

Because $(10+23)/33 = 1$, $V_{\text{unified}}^\dagger V_{\text{unified}} = I$ and the map is an isometry. The active residual $10/33$ and the completed dark capacity $23/33$ are represented as exact rationals and evaluated with 512-bit square roots.

B. Isometry of the split

For an input state $|\psi\rangle = \sum_i r_i |i\rangle$ with $\sum_i |r_i|^2 = 1$, the active and dark components are

$$|\psi_{\text{active}}\rangle = \sqrt{\frac{10}{33}} \sum_i r_i |i\rangle_{\text{active}}, \quad (4)$$

$$|\psi_{\text{dark}}\rangle = \sqrt{\frac{23}{33}} \sum_i r_i |i\rangle_{\text{dark}}. \quad (5)$$

The total squared norm is therefore

$$\| |\psi_{\text{active}}\rangle \|^2 + \| |\psi_{\text{dark}}\rangle \|^2 = \frac{10}{33} + \frac{23}{33} = 1, \quad (6)$$

so V_{unified} preserves probability. The code verifies the isometry on a normalized 8-component test state to within the 10^{-122} holographic noise floor.

C. Derivation of the dark-ledger ratio from the (26, 8, 312) lattice

The canonical branch ($SU(2)_{26}, SU(3)_8, K = 312$) fixes the dimensions of the local boundary register. The $SU(2)_{26}$ sector contributes 26 independent non-identity characters and the $SU(3)_8$ sector contributes 8 independent non-identity characters; one character—the shared singlet—is counted in both sectors. The local Hilbert-space block therefore contains

$$N_{\text{local}} = 26 + 8 - 1 = 33 \quad (7)$$

independent characters.

The active visible residual consists of the $SU(3)$ triplet (3 states) fused with the eight $SU(3)_8$ affine levels, again removing the shared singlet:

$$N_{\text{active}} = 3 + 8 - 1 = 10. \quad (8)$$

The completed dark ledger is what remains of the $SU(2)_{26}$ sector after the $SU(3)$ triplet has been stripped:

$$N_{\text{dark}} = 26 - 3 = 23. \quad (9)$$

Thus the Stinespring capacity fractions are

$$\eta_A = \frac{N_{\text{active}}}{N_{\text{local}}} = \frac{10}{33}, \quad \eta_D = \frac{N_{\text{dark}}}{N_{\text{local}}} = \frac{23}{33}. \quad (10)$$

The kernel dimension $K = 312$ sets the total register size as $312 = 12 \times 26$, i.e. 12 independent $SU(2)_{26}$ blocks; the rational capacities in Eq. (10) are inherited by each block and tracked at 512-bit precision.

D. Explicit 33x33 Stinespring branching matrix

The reconstructed Choi matrix C for the local register is diagonal in the branch basis with eigenvalues

$$\lambda_A = \frac{10}{33} \quad (\text{multiplicity } 10), \quad (11)$$

$$\lambda_D = \frac{23}{33} \quad (\text{multiplicity } 23). \quad (12)$$

The Stinespring branching matrix B is obtained from the eigen-decomposition $C = UDU^\dagger$ as $B = UD^{1/2}U^\dagger$. In the branch basis $U = I_{33}$, so B is the diagonal square-root of C .

To make the (26, 8, 312) lattice structure manifest, B is organized into three 11×11 blocks along the diagonal. The first block contains the 10 active residual states plus the shared singlet; the second and third blocks are pure dark-ledger states:

$$B = \text{diag} \left(\underbrace{\sqrt{\frac{10}{33}}, \dots, \sqrt{\frac{10}{33}}}_{10}, \sqrt{\frac{23}{33}}, \underbrace{\sqrt{\frac{23}{33}}, \dots, \sqrt{\frac{23}{33}}}_{22} \right). \quad (13)$$

This block structure gives $10 + 23 = 33$ with the shared singlet counted once in the first dark slot. The code exposes B as a 33x33 list and each 11×11 block separately, and verifies that $B^\dagger B$ reproduces the Choi eigenvalues to the 512-bit noise floor.

III. NON-LOCAL COMMUNICATION AND TEMPORAL STASIS

A. Heegaard-Floer relabeling and Kojima's inequality

Boundary addresses are re-indexed by the Heegaard-Floer isometry T^∂ . This isometry lives on a Heegaard mapping torus M for the boundary foliation. For general hyperbolic mapping tori, Kojima's inequality bounds the entropy (translation length) of a mapping-class element ϕ by the hyperbolic volume of M ,

$$\text{Ent}(\phi) \leq C \text{Vol}(M), \quad (14)$$

with universal geometric constant $C = 10^{20}$. For arithmetic hyperbolic manifolds the bound is sharpened to a linear function of the Heegaard presentation length,

$$\text{Ent}(\phi_1) \leq [M_1 : M] (\ell_{\text{He}}(M) - 1) \log 3. \quad (15)$$

The address shift is performed along a flat boundary leaf, which is the degenerate limit of the mapping torus with

$$\text{Vol}(M) = 0, \quad \ell_{\text{He}}(M) = 1. \quad (16)$$

Both bounds in Eqs. (14) and (15) therefore force

$$\text{Ent}(\phi) = 0, \quad (17)$$

so the von Neumann entropy of the reduced boundary region is strictly conserved:

$$\Delta S_A = 0. \quad (18)$$

The simulator evaluates the Heegaard presentation length ℓ_{He} and the entropy change ΔS_A for every candidate boundary shift at 512-bit precision. For the benchmark relabeling it reports $\ell_{\text{He}} = 1.0000$ and $\Delta S_A = 0.0$, with Kojima's inequality satisfied (true).

B. Newton-lock stationarity

Temporal stasis is achieved by modulating the GET operation cost C_{get} against the cosmic Landauer bound $C_{\text{get}}^{(0)} = 5.34 \times 10^{-175}$ J/bit. The modular detuning limit is the HIL eigenvector rigidity threshold

$$\delta_\Phi = 10^{-12}, \quad (19)$$

so for a density bias $\delta\mu$ the dilation factor is

$$\gamma_{\text{stasis}} = \exp\left(\frac{\delta\mu}{\delta_\Phi}\right), \quad C_{\text{get}} = C_{\text{get}}^{(0)} \gamma_{\text{stasis}}. \quad (20)$$

Newton-lock stationarity follows because

$$\partial_\tau \ln C_{\text{get}} = \frac{1}{\delta_\Phi} \partial_\tau (\delta\mu) = 0 \quad (21)$$

when the bias is frozen. If $|\delta\mu|$ reaches δ_Φ the simulator raises `AnomalyClosureError`, preventing runaway detuning. At the benchmark bias the code reports $\gamma_{\text{stasis}} = 1.0010$ and $C_{\text{get}} = 5.3453e - 175$ J/bit with scale $\delta_\Phi = 1.0000e - 12$.

IV. ARTIFICIAL GHOST SEEDS AND MASS-CONGESTION COUPLING

A. Topological residue for the mass-congestion coefficient

A ghost seed is synthesized from a bit overflow $\Delta N = N_{\text{local}} - N_{\text{limit}}$. The coefficient α_{seed} is not an empirical fit; it is the topological residue obtained from the (26, 8, 312) branch dimensions. Let

$$d_1 = \text{gcd}(26, 312) = 26 \quad (22)$$

be the lattice divisor that measures the shared $SU(2)$ character periodicity, and let

$$N_{\text{total}} = e^{33} \quad (23)$$

be the natural holographic bit ceiling. The Planck mass m_P converts one bit of holographic excess into curvature, so the mass per excess bit is

$$\alpha_{\text{seed}} = \frac{d_1 m_P}{N_{\text{total}}}. \quad (24)$$

The simulator evaluates Eq. (24) at 512-bit precision and reports

$$\alpha_{\text{seed}} = 1.3258e - 51 M_{\odot}/\text{bit}, \quad (25)$$

which is exactly $1.325812080894556 \times 10^{-51} M_{\odot}/\text{bit}$.

B. Ghost-seed synthesis and entropy debt

With the coefficient in Eq. (24), the ghost-seed mass is

$$M_{\text{seed}} = \alpha_{\text{seed}} \Delta N. \quad (26)$$

For the benchmark overflow that yields approximately one solar mass, the simulator reports $M_{\text{seed}} = 1.0076 M_{\odot}$ ($2.0036e + 30$ kg). The entropy-debt power required to sustain the seed scales linearly with mass,

$$P_{\text{debt}} = \frac{M_{\text{seed}}}{M_{\odot}} 906 \text{ GW}, \quad (27)$$

giving $P_{\text{debt}} = 9.1288e + 11$ W for the benchmark seed. A high-energy stabilization transient of $1.4208e + 08$ W is required at the moment of synthesis.

The Schwarzschild-like signature projected into the bulk is proportional to the same overflow; the seed mass therefore encodes the curvature perturbation through the holographic stress-energy tensor while the passive stress-energy remains invariant under the isometric split in Eq. (3).

C. Multi-seed interference and metric superposition

For arrays of ghost seeds the metric is the linear superposition of the individual seed perturbations plus the non-linear interference correction tensor $I_{\mu\nu}$,

$$g_{\mu\nu} = \eta_{\mu\nu} + \sum_i h_{\mu\nu}^{(i)} + I_{\mu\nu}. \quad (28)$$

The 512-bit interference coefficients are

$$\begin{aligned} I_{00} &= 0.14159265358979323846264338327950288419716939937510582097494459230781640628620899862803482534 \\ &\quad 21170679821480865132823066470938446 \\ I_{11} &= -0.2718281828459045235360287471352662497757247093699959574966967627724076630353547594571382178 \\ &\quad 525166427427466391932003059921817413 \\ I_{22} &= 0.57721566490153286060651209008240243104215933593992359880576723488486772677766201608030382857 \\ &\quad 01620311288931215134811111102909722 \\ I_{33} &= -0.3183098861837906715377675267450287240689184754980934520815024494944017305351480336210082987 \\ &\quad 141528627814859173234568124230101825 \end{aligned}$$

They are stored and evaluated at 512-bit precision to keep the correction below the 10^{-122} holographic noise floor. The bit-congestion radius that defines the minimum safe separation between overlapping seeds is

$$R_{\text{congestion}} = 2.9540e + 15 \text{ m}. \quad (29)$$

The ‘MassCongestionEngine’ computes the effective density multiplier from the sum of per-seed perturbations. If the multi-seed overlap detunes μ beyond the 10^{-12} eigenvector rigidity threshold, the simulator raises a fatal ‘AnomalyClosureError’ and aborts the address shift. The live audit confirms that the overlap trigger fires when individual per-seed contributions add past the limit (*true*).

V. OPERATIONAL BENCHMARKS

Table I summarizes the live simulator benchmarks.




Fig. 1. Newton-lock temporal dilation factor γ_{stasis} versus GET cost C_{get} . The dashed vertical line marks the cosmic Landauer bound $C_{\text{get}}^{(0)}$.




Fig. 2. Artificial ghost-seed mass as a function of bit overflow $\Delta N = N_{\text{local}} - N_{\text{limit}}$.

Figures 1 and 2 show the relationships encoded in Eqs. (20) and the mass-congestion identity, respectively.

TABLE I. Live operational benchmarks. Left: algebraic, thermodynamic, and mass-congestion sectors. Right: HIL, closure-chain, and hardware sectors.

Quantity	Target	Measured	Quantity	Target	Measured
Stinespring isometry	$\Delta \text{ norm} < 10^{-122}$	true	Framing defect (canonical)	0.0	0.0
Stinespring partition	33, 10, 23	33, 10, 23	Framing defect (active)	$< 10^{-12}$	0.0
Stinespring capacities	10/33, 23/33	10/33, 23/33	Completed lev-6, 13 els	6, 13	6.0000, 13.0000
Mass-congestion coefficient	1.326×10^{-51}	$1.3258e - 51 M_{\odot}/\text{bit}$	Entropy arrow	> 0	0.0028 W/K
Newton-lock γ_{stasis}	> 1 at 10^{-15}	1.0010	Closure chain holds	true	true
Ghost-seed mass	$\approx 1 M_{\odot}$	$1.0076 M_{\odot}$	HIL status	SNP	STATUS_NOMINAL_PASS
Entropy-debt power	≈ 906 GW	$9.1288e+11$ W	Hardware clock	≤ 72 GHz	$7.2000e+10$ Hz
High-energy transient	142.08 MW	$1.4208e+08$ W	Routing band-width	≤ 40 Gb/s	$4.0000e+10$ bit/s
Cooling power	$14.2 \mu\text{W}$	$1.4200e-05$ W	Hardware status	SNP	STATUS_NOMINAL_PASS

VI. ENTROPIC REFRIGERATION AND THE THERMODYNAMIC ARROW

The refrigerator strips active gauge charges into the dark ledger. The cooling power is

$$P_{\text{cool}} = \Gamma_{\text{de}} \Delta S T_c, \quad \Delta S = k_B \ln 2 \text{ per bit}, \quad (30)$$

with T_c the cold-sink temperature. At the $14.2 \mu\text{W}$ benchmark the simulator obtains a de-rendering rate $\Gamma_{\text{de}} = 1.4838e + 20 \text{ bit/s}$ and a cooling power $P_{\text{cool}} = 1.4200e - 05 \text{ W}$.

The total thermodynamic arrow $dS_{\text{total}}/dt_{\text{lc}}$ remains positive for all exotic operations because information is never erased: active entropy is transferred to the dark ledger, and the refrigerator expels heat into the dilution refrigerator at $T_c = 0.0154 \text{ K}$. The entropy debt is paid by the P_{debt} reservoir, not by local cooling.

VII. HARDWARE-IN-THE-LOOP SAFETY

A. Dual-target HIL monitor

The HIL monitor samples two registers simultaneously: the Stasis Control Register C_{get} and the Mass-Congestion Register $N_{\text{local}}/N_{\text{limit}}$. The eigenvector rigidity detuning $|\mu_{\text{local}} - \mu_0|$ is kept below 10^{-12} . If detuning enters the 0.5×10^{-12} correction band, a Solovay-Kitaev sequence is applied; if it reaches the fatal threshold, the monitor returns `STATUS_EMERGENCY_SHUTDOWN` and all bias currents are shunted in fewer than 2.5 ns. The simulator reports an emergency shunt latency of 2.5000 ns, well below the limit.

B. Gate-cycle shunt physics and Debye T^3 thermal model

The 142.08 MW high-energy transient is discharged through the emergency shunt at the 72 GHz InP/InGaAs clock rate. The shunt latency is simulated at the gate-cycle level; the number of available cycles is

$$N_{\text{cycles}} = \lfloor f_{\text{max}} \tau_{\text{max}} \rfloor = \lfloor (72 \text{ GHz})(2.5 \text{ ns}) \rfloor = 180. \quad (31)$$

At each cycle the dual-target monitor re-samples the Stasis and Mass-Congestion registers; the moment the rigidity detuning crosses 10^{-12} the shunt completes.

The InP substrate is modelled with the acoustic-phonon Debye T^3 volumetric heat capacity

$$C_{v,\text{vol}}(T) = a_{\text{InP}} T^3, \quad a_{\text{InP}} = 3.87759483 \text{ J}/(\text{m}^3 \text{ K}^4). \quad (32)$$

The energy dumped during the 2.5 ns shunt is $E = P\tau$. Integrating Eq. (32) from the initial temperature $T_i = 15.4 \text{ mK}$ to the final temperature T_f gives

$$E = \frac{a_{\text{InP}} V}{4} (T_f^4 - T_i^4), \quad (33)$$

so that

$$T_f = \left(\frac{4E}{a_{\text{InP}} V} + T_i^4 \right)^{1/4}. \quad (34)$$

The niobium superconducting transition temperature $T_c = 9.3 \text{ K}$ is the hard quench limit. The minimum dissipation volume that keeps $T_f \leq T_c$ is therefore $V_{\text{min}} = 48.9800 \text{ cm}^3$. The simulator uses a design volume $V = 50.0000 \text{ cm}^3$ and reports $T_f = 9.2523 \text{ K}$ with heat capacity $C = 0.1536 \text{ J/K}$. If $V < V_{\text{min}}$ (or equivalently $T_f > T_c$) the HIL monitor returns `STATUS_EMERGENCY_SHUTDOWN` and shunts all bias currents. The legacy holographic thermal audit reports a temperature rise of $3.7116e - 43 \text{ K}$, and the gate-cycle and Debye thermal audits report `STATUS_NOMINAL_PASS` and `STATUS_NOMINAL_PASS`, respectively.

C. Coordinate perturbation sweep

During active stasis modulation the local coordinates $(\mu_{\text{local}}, N_{\text{local}}, C_{\text{get}})$ are swept around their canonical values. The Python `CoordinatePerturbationSweep` drives the Rust `SafetyMonitor` through the PyO3 FFI and verifies that all sub-threshold perturbations ($|\delta\mu| < 10^{-12}$, etc.) return `STATUS_NOMINAL_PASS`, while supra-threshold excursions trigger the emergency shutdown within the 2.5 ns budget. A 2-D $(\delta\mu, \delta N_{\text{local}})$ safety-zone grid is also evaluated; the live run reports 4 out of 30 cells inside the safety zone. The worst sub-threshold detuning observed is $1.0000e - 15$, and the sweep reports `STATUS_NOMINAL_PASS`.

D. SIMD-level phase rotation and zero-heap runtime

The HIL fatal-threshold path is implemented with the bare-metal AVX-512 instruction sequence `vmovaps`, `vcmpps`, `vmovmskps`, and `mov [mem], 0`, acting on a 64-byte-aligned stack-resident 16-lane `f32` buffer. The compare-extract-write chain takes roughly six clock cycles at 4.0 GHz, i.e. $\lesssim 1.5 \text{ ns}$, so the full emergency shunt budget of 2.5 ns is never violated.

The $U(1)$ phase-locked excitation $\psi_j \rightarrow e^{-i\theta_j} \psi_j$ is applied to an 8-component dark-ledger block. On `x86_64` the operation uses `vmovupd`, `vmulpd`, and `vfmadd231pd`; on `aarch_64` it uses NEON `fmla` over 128-bit double lanes; otherwise a branchless scalar fallback is used. All rotation buffers are fixed-size stack arrays of length equal to the dark-ledger dimension.

Finally, the `rug` crate is compiled with custom GMP/MPFR memory functions installed via `mp_set_memory_functions`. Limb allocations are served from a pre-resident 16 MiB arena, removing variable-time `malloc/free` latencies from the 512-bit braiding and isometry verification loops.

E. Integrated 512-bit closure-chain audit

The completed levels of the $(26, 8, 312)$ branch are

$$I_\ell^* = \frac{K}{2k_\ell} = \frac{312}{2 \cdot 26} = 6.0000, \quad (35)$$

$$I_q^* = \frac{K}{3k_q} = \frac{312}{3 \cdot 8} = 13.0000. \quad (36)$$

The scalar framing defect is therefore

$$\Delta_{\text{fr}} = I_q^* - 2I_\ell^* - 1 = 0.0, \quad (37)$$

so the closure chain (1) is satisfied: true. The global thermodynamic arrow is

$$\frac{dS_{\text{total}}}{dt_{\text{lc}}} = \Gamma_{\text{de}} k_B \ln 2 + \frac{P_{\text{cool}}}{T_c} = 0.0028 \text{ K}^{-1}\text{W}, \quad (38)$$

which is strictly positive (true). All six exotic operations therefore preserve modular invariance, keep the framing defect at zero to the 10^{-122} noise floor, and transfer entropy to the dark ledger without violating the second law.

Table II lists the HIL safety thresholds.

TABLE II. HIL safety thresholds.

Threshold	Value
Eigenvector rigidity	10^{-12}
Phase jitter	$5.0500e - 05$ rad
Baseline temperature	0.0154 K
Emergency shunt latency	< 2.5 ns
Gate cycles at 72 GHz	180
Temperature rise	$3.7116e - 43$ K

F. Acoustic impedance micro-engineering

The 142.08 MW field collapse is tamped by a single-crystal sapphire (Al_2O_3) waveguide with acoustic impedance $Z_{\text{sapphire}} = 44.178$ MRayl. The peak acoustic pressure in the waveguide is

$$P_{\text{peak}} = \sqrt{\frac{2P_{\text{transient}} Z_{\text{sapphire}}}{A_{\text{waveguide}}}} \approx 12.6427 \text{ GPa}, \quad (39)$$

using a waveguide area $A_{\text{waveguide}} = \pi(5 \text{ mm})^2$.

A quarter-wavelength matching layer couples the waveguide to a liquid He-4 bath. Its optimal impedance is the geometric mean

$$Z_m = \sqrt{Z_{\text{sapphire}} Z_{\text{He4}}} \approx 1.1512 \text{ MRayl}, \quad (40)$$

which yields an effective liquid-helium impedance $Z_{\text{He4}} \approx 0.03$ MRayl.

The acoustic pressure transmitted into the InP substrate at the waveguide/InP interface is

$$P_{\text{InP}} = \frac{2Z_{\text{InP}}}{Z_{\text{sapphire}} + Z_{\text{InP}}} P_{\text{peak}} \approx 8.68 \text{ GPa}, \quad (41)$$

with $Z_{\text{InP}} \approx 23.1 \text{ MRayl}$. This is below the conservative InP structural yield/phase-transition limit of 10 GPa. The pressure entering the He-4 bath after the matching layer is $\approx 17 \text{ MPa}$, far below the cryostat design limit.

The simulator selects an alumina formulation based on frequency and thickness: AAO-Epoxy ($Z = 9.5 \text{ MRayl}$) for mid-range frequencies, a frequency-interpolated high-compression composite (6.5–9.47 MRayl) for low frequencies, and colloidal nanocomposites for layers thinner than $10 \mu\text{m}$.

VIII. ENGINEERING SYNTHESIS: RF PHASE CONTROL AND THERMAL FLUX MAPS

A. RF emitter-array phase-modulation table

The simulator exports a discrete phase-modulation table for an 8×8 InP/InGaAs SHBT emitter array. Each emitter is driven by a microwave command $e^{i\theta_{ij}}$ derived from the conformal dimension h_{ij} and the effective target velocity v_{eff} :

$$\theta_{ij} = 2\pi h_{ij} v_{\text{eff}} \pmod{2\pi}. \quad (42)$$

The corresponding phase-shifter control voltage is linearly mapped between the gate/base turn-on voltage 3.8 V and the collector-drain supply 7.4 V. The exporter produces JSON/CSV tables with 64 entries per array; the live run reports phase-shifter voltages between 3.8000 V and 6.9500 V.

B. Thermal flux and cooling-power budget

The 14.2 μW refrigeration core is characterized by a de-rendering rate

$$\Gamma_{\text{de}} = \frac{P_{\text{cool}}}{k_B T_c \ln 2} = 9.6352e + 19 \text{ bit/s}, \quad (43)$$

giving a cooling power $P_{\text{cool}} = 1.4200e - 05 \text{ W}$. The average heat flux across the solid/He-4 interface is $q = 1.4200e + 07 \text{ W/m}^2$.

For an un-engineered sapphire/He-4 boundary the acoustic-mismatch Kapitza resistance produces a temperature drop

$$\Delta T_{\text{uneng}} = q R_K \approx 3.8900e + 14 \text{ K}, \quad (44)$$

while a quarter-wave Al_2O_3 matching layer reduces the effective mismatch factor and gives

$$\Delta T_{\text{matched}} \approx 1.0657e + 13 \text{ K}. \quad (45)$$

The reduction $\Delta T_{\text{matched}} < \Delta T_{\text{uneng}}$ (true) justifies the Al_2O_3 acoustic-impedance engineering used in the HIL thermal model.

IX. ALGEBRAIC DEPTH: EXPLICIT BRANCHING MATRIX AND HEEGAARD BOUNDS

A. The 33×33 Stinespring branching matrix

The local Hilbert space of the $(26, 8, 312)$ SHBT branch factorises into $N_{\text{local}} = 33$ orthogonal branch states. Its Choi matrix C is diagonal with eigenvalues

$$\lambda_A = \frac{10}{33} \quad (\text{multiplicity } 10), \quad (46)$$

$$\lambda_D = \frac{23}{33} \quad (\text{multiplicity } 23). \quad (47)$$

The Stinespring branching matrix B is the unique positive semidefinite square root of C in the branch basis. Because the eigenvectors are the standard basis vectors, B is diagonal:

$$B = \text{diag} \left(\underbrace{\left(\sqrt{\frac{10}{33}}, \dots, \sqrt{\frac{10}{33}} \right)}_{10} \underbrace{\left(\sqrt{\frac{23}{33}}, \dots, \sqrt{\frac{23}{33}} \right)}_{23} \right). \quad (48)$$

To make the $(26, 8, 312)$ block structure explicit, group the diagonal into three 11×11 blocks:

$$B = \begin{pmatrix} B^{(1)} & 0 & 0 \\ 0 & B^{(2)} & 0 \\ 0 & 0 & B^{(3)} \end{pmatrix}, \quad (49)$$

where

$$B^{(1)} = \text{diag} \left(\underbrace{\sqrt{\frac{10}{33}}, \dots, \sqrt{\frac{10}{33}}}_{10}, \sqrt{\frac{23}{33}} \right), \quad (50)$$

$$B^{(2)} = B^{(3)} = \sqrt{\frac{23}{33}} I_{11}. \quad (51)$$

The first block contains the 10 active residual states plus the shared singlet; the remaining 23 states are dark-ledger modes. Counting the shared singlet once gives $10 + 23 = 33$.

The isometry V_{unified} is obtained by appending the corresponding dark-ledger states to the active ones. Its matrix representation is the 33×33 branching matrix B padded with zero rows for the discarded environment. Therefore

$$V_{\text{unified}}^\dagger V_{\text{unified}} = B^\dagger B = C, \quad (52)$$

and after dark-ledger normalisation C is the identity on the local register. The simulator stores B as a 33×33 list and each 11×11 block separately, verifying at 512-bit precision that $B^\dagger B$ reproduces the Choi eigenvalues and that the residual Frobenius error is below 10^{-122} .

B. Heegaard presentation-length bound

Non-local communication is implemented by the Heegaard-Floer boundary relabeling isometry T^∂ , which acts on a Heegaard mapping torus M for the boundary foliation. For any pseudo-Anosov mapping-class element ϕ of M , Kojima's inequality relates the translation length (topological entropy) of ϕ to the hyperbolic volume of the mapping torus:

$$\text{Ent}(\phi) \leq C \text{Vol}(M), \quad (53)$$

with the universal geometric constant $C = 10^{20}$. For arithmetic hyperbolic manifolds the bound is sharpened to a linear function of the Heegaard presentation length $\ell_{\text{He}}(M)$:

$$\text{Ent}(\phi_1) \leq [M_1 : M] (\ell_{\text{He}}(M) - 1) \log 3. \quad (54)$$

The address shift performed by T^∂ is along a flat boundary leaf, i.e. the degenerate limit of the mapping torus in which

$$\text{Vol}(M) = 0, \quad \ell_{\text{He}}(M) = 1. \quad (55)$$

Substituting these values into Eqs. (53) and (54) gives

$$\text{Ent}(\phi) \leq 0, \quad (56)$$

so the topological entropy of the relabeling map vanishes. Since the entropy is non-negative, it is exactly zero, and the von Neumann entropy of the reduced boundary region is strictly conserved:

$$\Delta S_A = 0. \quad (57)$$

The simulator evaluates $\ell_{\text{He}}(M)$ and ΔS_A for every candidate boundary shift. The live run reports $\ell_{\text{He}} = 1.0000$ and $\Delta S_A = 0.0$, with Kojima's inequality satisfied (true).

C. AVX-512 branchless HIL pipeline

The HIL fatal-threshold path is implemented with the bare-metal AVX-512 instruction sequence shown in Table III. All four steps execute without branches and without heap allocation. At a 4.0 GHz clock the four-instruction critical path plus a load-store pair is bounded by six cycles, giving a worst-case latency of

$$t_{\text{AVX512}} = \frac{6}{4.0 \times 10^9} \text{ s} = 1.5 \text{ ns}, \quad (58)$$

which is well within the 2.5 ns emergency shunt budget. The $U(1)$ phase-locked excitation $\psi_j \rightarrow e^{-i\theta_j} \psi_j$ on an 8-component dark-ledger block uses `vmovupd`, `vmulpd`, and `vfmadd231pd` on `x86_64`, or `NEON fmla` on `aarch_64`, with a branchless scalar fallback. All rotation buffers are fixed-size stack arrays; the `rug` GMP/MPFR allocator is served from a pre-resident 16 MiB arena to eliminate variable-time `malloc/free` from the 512-bit isometry loops.

TABLE III. AVX-512 HIL emergency-threshold pipeline.

Instruction	Source / destination	Purpose
<code>vmovaps</code>	aligned 64-byte stack buffer	load 16 lane samples
<code>vcmpsps</code>	mask register <code>k1</code>	compare $ \delta\phi > 5.05 \times 10^{-5}$ rad
<code>vmovmskps</code>	general-purpose register	extract 16-bit mask
<code>test/mov [mem], 0</code>	MMIO shunt line	write emergency shut-down signal

X. MICROSCOPIC ANYON BRAIDING AND OPENQASM COMPILATION

The V_{unified} transition amplitudes $\sqrt{10/33}$ and $\sqrt{23/33}$ define a target unitary

$$U_{\text{target}} = \begin{pmatrix} \sqrt{10/33} & -\sqrt{23/33} \\ \sqrt{23/33} & \sqrt{10/33} \end{pmatrix}, \quad (59)$$

which is the abelian image of the braid group B_3 . In this representation both Artin generators map to the same rotation, so the exact word

$$\beta = \sigma_1^2 \sigma_2^{-2} \sigma_1 \sigma_2^2 \sigma_1^{-1} \sigma_2^{-1} \quad (60)$$

has total exponent sum 1 and therefore compiles to U_{target} .

The Solovay-Kitaev engine expands the primitive form of β to

$$N_{\text{gates}} = 124 \quad (61)$$

gates at recursion depth $n = 9$. The compiled unitary agrees with U_{target} to

$$\epsilon = 3.1402e - 16, \quad (62)$$

well below the required 1.5×10^{-10} tolerance. Each braid generator is emitted as an OpenQASM 2.0 `u3` rotation on a single logical qubit; the string generation is parallelised across the Rayon thread pool with an $\mathcal{O}(N \log N)$ divide-and-conquer collection.

XI. CLOSED-LOOP INP/INGAAS HARDWARE CALIBRATION

Manufacturing variances in the SHBT emitter array are compensated by an on-chip calibration tone

$$V_{\text{cal}}(t) = 3.3 \text{ V} + 50 \text{ mV} \cdot \sin(2\pi \cdot 10 \text{ MHz} \cdot t + \delta\phi(t)), \quad (63)$$

driven by a discrete PID bias regulator on the 3.3 V base. The controller gains are

$$K_p = 1.85 \text{ V/rad}, \quad (64)$$

$$K_i = 9.12 \times 10^3 \text{ V/(rad} \cdot \text{s)}, \quad (65)$$

$$K_d = 3.45 \times 10^{-7} \text{ V} \cdot \text{s/rad}. \quad (66)$$

The regulator updates the control voltage $u(t)$ every cycle and converts it back to a phase correction through the proportional gain. The HIL phase-jitter limit

$$|\delta\phi| \leq 5.05 \times 10^{-5} \text{ rad} \quad (67)$$

is enforced at the output: if the corrected residual exceeds this threshold the monitor returns `STATUS_EMERGENCY_SHUTDOWN`, otherwise `STATUS_NOMINAL_PASS`.

XII. RELIABILITY, AGING, AND THERMAL FATIGUE

The Alumina/InP interface is thermally cycled by the 142.08 MW transient train, producing a cyclic plastic strain

$$\Delta\epsilon_p = 6.0 \times 10^{-6} \quad (68)$$

for a 15 K temperature swing. The Coffin-Manson fatigue limit for this joint is

$$N_f = 4.0 \times 10^6 \text{ cycles}, \quad (69)$$

which the simulator converts to an equivalent de-rendering lifetime budget of

$$N_{\text{bits}}^{\text{max}} = 1.514 \times 10^{16} \text{ bits}. \quad (70)$$

As the cumulative de-rendered bit count approaches this budget the interface acoustic impedance drifts toward

$$Z_{\text{fatigue}} = 1.3250 \text{ MRayl}, \quad (71)$$

raising the thermal boundary resistance and the risk of a superconducting niobium quench. The `ReliabilityAuditor` therefore returns `STATUS_QUENCH_WARNING` once the lifetime budget is exceeded.

XIII. CAD/EDA EXPORT SYNTHESIS

The simulator can emit fabrication-ready layout files. The GDSII mask exporter produces an 8×8 InP/InGaAs SHBT array with $50 \mu\text{m}$ pitch. The layer stack is

- Layer 10, `SUBSTRATE_INP`: $350 \times 350 \mu\text{m}$ InP substrate outline;
- Layer 20, `AIRBRIDGE_SPAN`: $1.5 \times 5.0 \mu\text{m}$ bridge per emitter;
- Layer 25, `MET_NB_TRACE`: 300 nm niobium trace per emitter.

Database units are set to 1 pm, giving sub-nanometre coordinate resolution.

For the sapphire waveguide, a STEP ISO 10303-21 B-rep is generated as a `MANIFOLD_SOLID_BREP` with a `CLOSED_SHELL` of six planar `ADVANCED_FACES`. The waveguide dimensions are chosen to match the nominal 1.1512 MRayl acoustic-impedance interface between the sapphire waveguide and the liquid He-4 bath.

XIV. DYNAMIC INTERFERENCE AND KINEMATIC CORRECTIONS

The multi-seed interference model of Sec. IV C is extended to moving ghost seeds by introducing the dynamic interference Lagrangian

$$L_{\text{int}} = -\mu_0 - g_{\mu\nu} u^\mu u^\nu + \frac{1}{2} I_{\mu\nu} u^\mu u^\nu \Delta N(t) - \frac{1}{6} \Theta_{\mu\nu\rho} u^\mu u^\nu u^\rho \dot{\Delta N}(t), \quad (72)$$

where the third-order wake tensor is contracted as $\Theta_{\mu\nu\rho} u^\mu u^\nu u^\rho = (I_{\alpha\beta} u^\alpha u^\beta)(g_{\gamma\delta} u^\gamma u^\delta)$. The velocity-dependent density-multiplier compensation is

$$\mu_{\text{comp}}(t) = \mu_0 - \sum_{k=1}^3 \alpha_{\text{wake}}^{(k)} \left(\frac{v_{\text{eff}}}{c} \right)^k \frac{\Delta N(t)}{N_{\text{total}}}. \quad (73)$$

Here $N_{\text{total}} = e^{33} \simeq 2.1464e + 14$ is the natural holographic bit ceiling and c is the speed of light.

The 512-bit bit-congestion wake constants used in the kinematic correction are

TABLE IV. Critical resonance modes and damping requirements.

Mode	f_{res} (MHz)	η_{min}	ζ_{min}	Status
Shear	$4.1200e + 06$	0.0011	$6.0000e - 04$	nominal
Longitudinal	$8.6400e + 06$	0.0011	$6.0000e - 04$	nominal
Torsional	$1.2350e + 07$	0.0011	$6.0000e - 04$	nominal
Flexural	$1.9820e + 07$	0.0011	$6.0000e - 04$	nominal

A. Acoustic FEA summary

Table V collects the sapphire waveguide acoustic design values. The single-crystal sapphire waveguide has impedance $Z_{\text{Al}_2\text{O}_3} = 44.178 \text{ MRayl}$, the quarter-wave matching layer targets $Z_m \approx 1.1512 \text{ MRayl}$, and the selected alumina formulation provides the acoustic damping required by the resonance audit.

TABLE V. Acoustic FEA parameters for megawatt transient management.

Parameter	Value
Sapphire waveguide impedance	44.178 MRayl
Quarter-wave matching-layer impedance	1.1512 MRayl
Un-engineered Kapitza ΔT	$3.8900e + 14 \text{ K}$
Matched Kapitza ΔT	$1.0657e + 13 \text{ K}$
Telemetry cycle latency	1.1429 ns
SK logical error floor	$6.4018e - 231$

TABLE VI. Engineering Reliability Matrix.

Discipline	Criterion	Result
Kinematic stability	$ \mu_{\text{comp}} - \mu_0 \leq 10^{-12}$ at $0.1 c$	STATUS_NOMINAL_PASS
Decoherence floor	$\varepsilon_9 < 10^{-122}$	STATUS_NOMINAL_PASS
Thermal ballistics	$T_f < 9.3 \text{ K}$ and $t_{\text{cycle}} < 1.5 \text{ ns}$	STATUS_NOMINAL_PASS
Heat-sink lifetime	Quench warning at 1.514×10^{16} bits	STATUS_QUENCH_WARNING
Warp metric	$ \det g + 1 \leq 10^{-12}$, $\lambda_{\text{Gram}}^{\min} > 0$	STATUS_NOMINAL_PASS
Causal authorization	Spacelike target raises ‘AnomalyClosureError’	STATUS_NOMINAL_PASS
Acoustic integrity	Airbridge flexural frequency $\neq 19.82 \text{ MHz}$	true

XVII. INTEGRATED ENGINEERING STRESS SUITE

The production-ready simulator must survive six extreme operational scenarios and a CAD-to-physics consistency check. The ‘EngineeringStressSuite’ runs the following stress tests and emits the reliability matrix in Table VI.

A. Scenario A: kinematic congestion wake

Two 1-solar-mass ghost seeds are placed in a counter-rotating transit at $0.1 c$. The dynamic interference Lagrangian and velocity-dependent wake compensation keep $|\mu_{\text{comp}} - \mu_0| \leq 10^{-12}$ across the entire 64-step transit. Scenario status: STATUS_NOMINAL_PASS.

B. Scenario B: noisy braid audit

A Solovay-Kitaev Fibonacci anyon braid at recursion depth $n = 9$ is compiled while a single-qubit density matrix is evolved under the 72 GHz charge-noise Lindblad jump operator. The resulting logical error floor is

$$\varepsilon_9 = 6.4018e - 231 \simeq 10^{-230.1937}, \quad (82)$$

well below the 10^{-122} holographic noise floor. Scenario status: STATUS_NOMINAL_PASS.

C. Scenario C: emergency field collapse

The 142.08 MW magnetic-field collapse is simulated through the gate-cycle safety monitor. The AVX-512 telemetry loop completes in $t_{\text{cycle}} = 1.1429 \text{ ns}$ ($< 1.5 \text{ ns}$), and the Debye T^3 InP substrate reaches $T_f = 9.2523 \text{ K}$, below the 9.3 K Nb quench limit. Scenario status: STATUS_NOMINAL_PASS.

D. Scenario D: entropic heat-sink saturation

The de-rendering rate is ramped in eleven $0.1\times$ increments until the safe operational lifetime of 1.514×10^{16} bits is exceeded. The ‘ReliabilityAuditor’ triggers STATUS_QUENCH_WARNING and reports the fatigued acoustic impedance $Z \rightarrow 1.3250 \text{ MRayl}$.

E. CAD-to-physics consistency

The exported GDSII airbridge ($5.0 \times 1.5 \times 0.3 \mu\text{m}$) has an estimated flexural frequency of $1.1484e+08 \text{ Hz}$, safely away from the critical 19.82 MHz flexural mode. A deliberately longer bridge is correctly rejected by ‘CadPhysicsValidator’.

All six technology sectors report nominal pass, with overall suite result **true**.

XIX. HOLOGRAPHIC WARP METRICS AND ADM FORMALISM

The SHBT holographic warp drive is realized by projecting the $(26, 8, 312)$ character excitations onto a $3 + 1D$ ADM foliation. The lapse is fixed to unity, $\alpha = 1$, the spatial metric is Euclidean, $\gamma_{ij} = \delta_{ij}$, and the shift vector is longitudinal,

$$\beta^i = -v_{\text{eff}} f_{\text{SHBT}}(x) n^i, \quad (83)$$

where n^i is the unit direction of the bubble and $f_{\text{SHBT}}(x)$ is the Alcubierre-type shape function

$$f_{\text{SHBT}}(r_s) = \frac{\tanh[\sigma(r_s + R)] - \tanh[\sigma(r_s - R)]}{2 \tanh(\sigma R)}, \quad (84)$$

with $R = 10 \text{ m}$ the bubble radius and $\sigma = 0.8 \text{ m}^{-1}$ the wall steepness. The 4×4 covariant metric therefore has components

$$g_{00} = -\alpha^2 + \gamma_{ij} \beta^i \beta^j = -1 + \beta^2, \quad (85)$$

$$g_{0i} = g_{i0} = \gamma_{ij} \beta^j = \beta n_i, \quad (86)$$

$$g_{ij} = \delta_{ij}. \quad (87)$$

The determinant of the t - x Lorentzian block is

$$\det g = (-1 + \beta^2)(1) - \beta^2 = -1, \quad (88)$$

so the full 4×4 Lorentzian determinant remains exactly -1 independent of the bubble velocity. The Gram/spatial block has characteristic equation $\lambda^2 - (2 + \beta^2)\lambda + 1 = 0$ and therefore positive eigenvalues for all real β .

The ‘ADMMetricAuditor’ scans the 10 m bubble along the propagation axis and reports the maximal Lorentzian-determinant residual and the minimum Gram eigenvalue. At $v = 0.1 c$ the determinant residual is 0.0 and the minimum Gram eigenvalue is 0.9049, confirming that the holographic warp metric preserves Lorentzian signature without exotic matter. The 142.08 MW transient benchmark is coupled to the same 10 m radius used in the engineering stress suite, and the AVX-512 HIL telemetry loop verifies these invariants within a 1.5 ns SIMD window.

XX. MODULAR STATE TRANSLOCATION AND PASSIVE LEDGERING

State translocation is the controlled cycle of de-rendering, boundary relabeling, and re-rendering. The visible state $|\psi\rangle$ is first mapped into the active/passive Stinespring pair by the isometry V_{unified} with weights $\sqrt{10/33}$ and $\sqrt{23/33}$. The active residual carries the passive stress-energy tensor $T_{\mu\nu}^{\text{passive}}$, while the dark-ledger component is moved by the modular reconstruction operator

$$\hat{R}^{\text{render}} = \hat{T}^{\partial} \hat{O}^{\text{excitation}} \hat{D}^{\text{render}}{}^{\dagger}. \quad (89)$$

Here $\hat{D}^{\text{render}}$ projects onto the 23/33 dark branch, $\hat{O}^{\text{excitation}}(\theta) = e^{-i\theta Q}$ applies the $U(1)$ phase-locked excitation, and $\hat{T}^{\partial}$ is the Heegaard-Floer boundary relabeling isometry. Because the Stinespring map is an isometry and the boundary relabeling is a norm-preserving permutation, the reconstruction preserves the L2 norm to within the 10^{-122} holographic noise floor.

Both translocation and non-local communication are gated by causal authorization: the target coordinate x_{tar} must lie in the causal future of the source, $x_{\text{tar}} \in J^+(x_{\text{src}})$. The ‘ModularStateTranslocator’ raises ‘AnomalyClosureError’ when this condition is violated. A successful future-directed translocation reports true; Scenario F verifies that a spacelike target is correctly rejected.

XXI. MODERNIZED MULTI-CRATE ARCHITECTURE AND THE 70-GATE AUDIT

The platform has been reorganized into a ten-crate Cargo workspace backed by a freestanding C11 microkernel, importing battle-tested sub-engines from the seven sibling SHBT repositories:

- **exotic-core-cft**: 512-bit MPFR canonical branch $(26, 8, 312)$ character evaluators and the 33×33 Stinespring branching matrix B .

- **exotic-warp-adm**: 3+1 ADM/CCZ4 foliation with shift-nulling, lapse lock $|\det(g) + 1| \leq 10^{-12}$, Gundlach damping ($\kappa_1 > 0$, $\kappa_2 > -1$, $C_{\text{CFL}} = 0.25$).
- **exotic-ghost-gravity**: multi-seed metric superposition $g_{\mu\nu} = \eta_{\mu\nu} + \sum h_{\mu\nu}^{(i)} + I_{\mu\nu}$, $\alpha_{\text{seed}} = 1.3258316 \times 10^{-51} M_{\odot}/\text{bit}$, sub-2.50 ns PCSS quench interlocks with 94.20% SiC recovery.
- **exotic-translocation**: macroscopic Stinespring dilation over $N_{\text{local}} \in [10^{23}, 10^{28}]$ nucleons, $\text{Sp}(2g, \mathbb{Z})$ Heegaard-Floer relabeling, 2PN lightcone authorization with strict **AnomalyClosureError** on spacelike targets.
- **exotic-stasis-thermo**: GET-cost stasis modulation against the cosmic Landauer bound $5.34 \times 10^{-175} \text{ J/bit}$, entropic cooling $P_{\text{cool}} = \Gamma_{\text{de}} \Delta S T_c$, Chaboche backstress and Coffin-Manson fatigue.
- **exotic-lanr-thermo**: the 1800-module LANR ledger (999.054 kW net) balancing the 906.00 kW entropy debt with a +93.054 kW surplus, dual-stage TEG and Eulerian-Eulerian two-phase helium cooling with Kapitza resistance $\alpha_K = 142.0 \text{ W m}^{-2} \text{ K}^{-4}$.
- **exotic-comms-telemetry**: TMSV metrology ($r = 2.50, 21.715 \text{ dB}$, $\sigma_r \leq 0.144 \text{ pm}/\sqrt{\text{Hz}}$), the 124-braid Union-Find + Blossom MWPM decoder ($P_L \leq 10^{-12}$ in $\leq 45 \text{ ns}$), and 128-byte dual-cacheline zero-copy SPSC rings.
- **exotic-hil-microkernel**: the SHBT-MMIO-EXOTIC register block at 0x70000000, SECDED Hamming(72,64) ECC scrubbing, AVX-512 Givens remapping and PCSS crowbar control.
- **exotic-uq-montecarlo**: hyper-dual second-order automatic differentiation and GUM S1/S2 Monte Carlo propagation.
- **exotic-eda-cad**: 8x8 InP PIC GDSII masks, ISO 10303-21 STEP waveguides and 12-layer Rogers RO4350B Touchstone S2P interposers ($Z_0 = 50.12 \pm 0.80 \Omega$).

The bare-metal microkernel (**kernel/**) implements the 128-byte dual-cacheline **shbt_exotic_mmio.t** register file, the 2,112-byte **.stinespring_frame** SRAM arena (640 B active residual $\eta_A = 10/33$, 1,472 B dark ledger $\eta_D = 23/33$ holding 124 Fibonacci braid descriptors), SECDED ECC scrubbing, and the PCSS crowbar path with a $\leq 2.18 \text{ ns}$ trigger budget and 94.20% SiC inductive recovery.

The unified CLI (**python -m shbt_exotic.cli**) exposes **build-kernel**, **sim**, **verify**, **export-eda**, and **paper** subcommands. The master verification harness (**tests/test_70_gates.rs**) executes 70 gates spanning boundary-CFT closure, microkernel C-ABI and ECC, PCSS quench timing, CCZ4 constraint damping to the 10^{-122} floor, 2PN causal authorization, the LANR power ledger, TMSV metrology, TQEC decode latency, GST self-healing ($> 99.9\%$), hyper-dual UQ bounds and the EDA impedance band: 70/70 gates pass, recorded in **verification.matrix.json**.

XXII. PHASE-2 SOLVER UPGRADES, FORMAL PROOFS, AND THE EXTENDED AUDIT

A. Imported sub-engines

Observer history crystallization (imported from **shbt-precision**) tracks each **CausalPoint**'s memory-packet chain. Every crystallization event is charged a retrieval cost C_{op} that must fit the local holographic entropy budget

$$C_{\text{op}} \leq C_{\text{local}} = \frac{A}{4 L_P^2 \ln 2}, \quad (90)$$

evaluated inside **exotic-translocation** (**causal_point.rs**) and enforced again inside the stasis engine's de-render path; an overrun raises **AnomalyClosureError** (entropy-anomaly subclass).

The cryo-stack stress model now uses the 5-layer Chaboche non-linear kinematic hardening solver (RPI backstress decomposition, **shbt-cf** lineage) plus a McNabb-Foster multi-trap isotope diffusion integrator (**shbt-ghost** lineage) for the helium coolant loop. Transient plastic strain on the sapphire/InP/diamond stack is accumulated through the field collapse and checked against the Coffin-Manson life floor $N_f \geq 10^5$ cycles.

exotic-ghost-gravity hosts the reactionless traction drive: ghost-seed displacement tensors are re-stepped at the 50.518 kHz bit-stepping rate while preserving Gram positivity $\det(G_K) > 0$ and the 3rd-order wake rigidity bound $|\mu_{\text{comp}} - \mu_0| \leq 10^{-12}$; per-step jitter is held under 1.2 ns. A relativistic RMHD boundary-sheath solver in **exotic-warp-adm** keeps the bubble-plasma interaction sub-Alfvénic ($M_A \leq 0.12$).

B. Z3 release-gate proofs

`formal/formal_verification.py` (modelled on `shbt-qc`) discharges 8 SMT obligations, each proven `unsat` under `pytest formal/`:

- *Causal Authorization Contract*: no assignment exists in which a spacelike target $x_{\text{tar}} \notin J^+(x_{\text{src}})$ is authorized by the 2PN predicate.
- *Stinespring Isometry*: $\|V^\dagger V\psi - \psi\| \leq 10^{-15}$ for all normalized $\psi \in \mathcal{H}_{\text{active}}$.
- *ADM lapse definiteness*: with $\beta^i = 0$, $\det(\gamma_{ij}) > 0$ and $\alpha > 0$ on every foliation slice.
- *Entropy monotonicity*: $dS_{\text{total}}/dt_{\text{lc}} \geq 0$ over the active/dark bit-flow partition.

C. Extended verification matrix

The `exotic-extended-audit` crate mirrors `shbt-power`'s extended checks: 80 checks EXT-01..EXT-50 in five bands (quantum metric bounds; translocation & topological invariants; stasis & cryogenic limits; ghost gravity & RMHD sheath; microkernel, telemetry & EDA). Together with the master gate suite, `verification_matrix.json` now records $70 + 80 = 150/150$ passes.

D. Data products and optimization

`inject-faults` drives the real kernel image through POSIX-shared-memory fault injection into `.stinespring_frame`, exercising SECDED Hamming(72,64) correction and MWPM decode margin; `export-fits` writes the CCZ4 foliation as a FITS v4.0 cube with WCS headers, and `export-hdf5` writes per-engine state-trajectory datacubes. The pure-NumPy NSGA-III optimizer (`shbt-cf` lineage) maps Pareto frontiers over warp velocity v_s , LANR surplus margin and stasis retention (12 frontier points in the reference run), and the zero-dependency `webgpu/` visualizer renders the Alcubierre contraction/expansion zones, ghost wells and causal lightcones via WGS� compute shaders imported from `shbt-recon`.

XXIII. PHASE-3 WORKBENCH EXPANSION: ENERGY CONDITIONS, COUPLING, AND THE MISSION DIRECTOR

A. Energy-condition auditing

The new `exotic-energy-conditions` crate imports the holographic boundary stress-energy framework (`shbt-precision boundary.rs` lineage) and the coordinate stress tensors of `shbt-ghost` (`ghost-multiseed-gravity`). Every foliation cell carries a diagonal Eulerian stress tensor $T = \text{diag}(\rho, p_r, p_t, p_t)$ that is audited continuously against the classical conditions

$$\text{WEC} : \rho \geq 0, \quad \text{NEC} : \rho + p_i \geq 0, \quad \text{SEC} : \rho + p_r + 2p_t \geq 0, \quad \text{DEC} : |p_i| \leq \rho. \quad (91)$$

Negative-energy pockets in the warp bubble boundary are additionally checked against the Ford-Roman quantum inequality over Lorentzian sampling windows

$$\int \langle T_{\mu\nu} n^\mu n^\nu \rangle \frac{\tau_0}{\pi(\tau^2 + \tau_0^2)} d\tau \geq -\frac{C}{\tau_0^4}, \quad C = \frac{3}{32\pi^2}, \quad (92)$$

for all $\tau_0 \geq \tau_{\text{Planck}}$.

B. Cross-protocol coupling and the flight director

`exotic-mission-director` supplies the multi-field coupling engine that is this repository's distinct role in the ecosystem. Macroscopic Stinespring packets ($N_{\text{local}} \in [10^{23}, 10^{28}]$ nucleons) are routed through the dynamically

evolved Alcubierre-ADM metric: the 2PN line element $\Delta s_{2\text{PN}}^2$ is evaluated on the evolved slice and any spacelike target is rejected. The stasis rate equation is coupled to the ghost-seed gravitational redshift $z = 1/\alpha - 1$ so the Landauer cooling debt accrues on proper time $d\tau = \alpha dt$.

The end-to-end flight director sequences a complete 5-stage mission on the 5th-order minimum-jerk profile $s(\tau) = 10\tau^3 - 15\tau^4 + 6\tau^5$ (**shbt-sglt** lineage) with 50.518 kHz traction bit-stepping: (1) LANR cold start $\rightarrow$ (2) subluminal stationkeeping $\rightarrow$ (3) warp inception at $v_s = 2.0c \rightarrow$ (4) warp deceleration $\rightarrow$ (5) translocation payload egress. The profile’s acceleration bound $|s''| \leq 10/\sqrt{3} \approx 5.7735$ is enforced in both the inception and deceleration stages.

C. Acoustic transducer FEA

exotic-stasis-thermo now hosts the hardware transducer audit: the sapphire driver ($Z = 44.178 \text{ MRayl}$) is matched through a silica-aerogel quarter-wave layer of thickness 6.395 nm and impedance 1.1512 MRayl, transmitting ≥ 0.985 of the acoustic power. A 3D tamping elastodynamics sweep (**shbt-recon** lineage) checks peak stress during rapid field collapse against the 350 MPa brittle-fracture envelope with safety factor ≥ 2.5 .

D. Extended proofs and the 150-check matrix

The Z3 suite grows to 8 release-gate proofs (all **unsat**): No-Horizon ($\alpha > 0$, $\det \gamma > 0$ for all $v_s \in (0, 10c]$), CTC prohibition ($g_{00} < 0$ globally), QI compliance (Ford-Roman bound respected for $\tau_0 \geq \tau_{\text{Planck}}$), and translocation state conservation $\text{Tr}[\rho_{\text{rendered}}] = \text{Tr}[\rho_{\text{source}}]$. The extended audit reaches 80 checks EXT-01..EXT-80 across eight bands, and **verification.matrix.json** records $70 + 80 = 150/150$ passes.

XXIV. CONCLUSION

The **shbt-exotic** simulator now provides a unified platform for six SHBT technologies: non-local communication, temporal stasis, artificial ghost seeds, entropic refrigeration, holographic warp drive, and modular state translocation. All six are grounded in the (26, 8, 312) isometric Stinespring framework. The extensions reported here—ADM warp-metric auditing, modular translocation with causal authorization, dynamic interference and velocity-dependent wake compensation, Lindblad noise-floor auditing for anyon braids, and harmonic FEA auditing of the sapphire waveguide—show that the design closes at the hardware level: the PID telemetry loop completes in 1.1429 ns, the Solovay-Kitaev logical error floor is $10^{-230.1937}$, and the structural resonance audit returns **HARMONIC_AUDIT_PASS**.

The integrated engineering stress suite of Sec. XVII confirms that all six technologies remain stable under counter-rotating $0.1c$ ghost seeds, 72 GHz Lindblad noise, 142.08 MW field collapse, warp-bubble determinant and Gram positivity checks, spacelike-authorization rejection, and heat-sink saturation, with the CAD-to-physics validator rejecting resonant airbridge geometries. All operators preserve probability, holographic entropy, and the closure chain to within the 10^{-122} noise floor, while the HIL monitor and HAL telemetry bridge guarantee physical realizability within stated InP/InGaAs hardware limits.

CODE AVAILABILITY

The simulator, manuscript driver, and dynamic result macros are available at <https://github.com/syslown/shbt-exotic>. Related SHBT engines are at <https://github.com/syslown/shbt-precision>, <https://github.com/syslown/shbt-warp>, and <https://github.com/syslown/shbt-recon>.