

```

1  @x1 = common global i32 0, align 4
2  @x = common global i32 0, align 4
3  @x2 = common global i32 0, align 4
4  @y = common global i32 0, align 4
5  @.str = private unnamed_addr constant
        [4 x i8] c"%d\0A\00", align 1
6
7  ; Function Attrs: noinline nounwind
        optnone ssp uwtable
8  define i32 @f(i32) #0 {
9      %2 = alloca i32, align 4
10     store i32 %0, i32* %2, align 4
11     store i32 3, i32* @x1, align 4
12     %3 = load i32, i32* @x1, align 4
13     %4 = load i32, i32* %2, align 4
14     %5 = add nsw i32 %3, %4
15     ret i32 %5
16 }
17
18 ; Function Attrs: noinline nounwind
        optnone ssp uwtable
19 define i32 @main(i32, i8**) #0 {
20     %3 = alloca i32, align 4
21     %4 = alloca i8**, align 8
22     store i32 %0, i32* %3, align 4
23     store i8** %1, i8*** %4, align 8
24     store i32 6, i32* @x, align 4
25     store i32 7, i32* @x2, align 4
26     %5 = load i32, i32* @x2, align 4
27     %6 = call i32 @f(i32 %5)
28     store i32 %6, i32* @y, align 4
29     %7 = load i32, i32* @x, align 4
30     %8 = load i32, i32* @y, align 4
31     %9 = add nsw i32 %7, %8
32     %10 = call i32 (i8*, ...) @printf(i8
        * getelementptr inbounds ([4 x
        i8], [4 x i8]* @.str, i32 0,
        i32 0), i32 %9)
33     ret i32 0
34 }
35
36 declare i32 @printf(i8*, ...) #1

```