Apache Ranger Public REST APIs

Date of Publish: 2018-07-15



Contents

| Apache Ranger Public REST APIs | 3 |
|---|----|
| Service Definition APIs | 4 |
| Get Service Definition by ID | |
| Get Service Definition by Name | |
| Create Service Definition | |
| Update Service Definition by ID | |
| Update Service Definition by Name | |
| Delete Service Definition by ID | |
| Delete Service Definition by Name | |
| Search Service Definitions. | |
| | |
| Service APIs | 13 |
| Get Service by ID | 13 |
| Get Service by Name | |
| Create Service | |
| Update Service by ID | |
| Update Service by Name | |
| Delete Service by ID | |
| Delete Service by Name | 16 |
| Search Services | |
| | |
| Policy APIs | 19 |
| Get Policy by ID | |
| Get Policy by Service Name and Policy Name | 21 |
| Create Policy | 23 |
| Update Policy by ID | 25 |
| Update Policy by Service Name and Policy Name | |
| Delete Policy by ID | 29 |
| Delete Policy by Service Name and Policy Name | 29 |
| Search Policies in a Service | 29 |

Apache Ranger Public REST APIs

Reference for the Apache Ranger REST APIs.

Service Definition APIs

Reference for the Apache Ranger REST Service Definition APIs.

Get Service Definition by ID

 $Reference\ information\ for\ the\ Ranger\ REST\ API\ service/public/v2/api/servicedef/\{id\}.$

| API Name | Get Service Definition |
|--------------|---------------------------------------|
| Request Type | GET |
| Request URL | service/public/v2/api/servicedef/{id} |

```
API Name
                                          Get Service Definition
Request Params
Response
                                           {
                                               "accessTypes": [
                                                        "impliedGrants": [],
                                                        "itemId": 1,
                                                        "label": "Read",
                                                        "name": "read"
                                                        "impliedGrants": [],
                                                        "itemId": 2,
                                                        "label": "Write",
                                                        "name": "write"
                                                        "impliedGrants": [],
                                                        "itemId": 3,
                                                        "label": "Execute",
                                                        "name": "execute"
                                               "configs": [
                                                    {
                                                        "itemId": 1,
                                                        "label": "Username",
                                                        "mandatory": true,
                                                        "name": "username",
                                                        "subType": "",
                                                        "type": "string",
                                                        "uiHint": "",
                                                        "validationMessage": "",
                                                        "validationRegEx": ""
                                                        "itemId": 2,
                                                        "label": "Password",
                                                        "mandatory": true,
                                                        "name": "password",
                                                        "subType": "",
                                                        "type": "password",
                                                        "uiHint": "",
                                                        "validationMessage": "",
                                                        "validationRegEx": ""
                                                        "itemId": 3,
                                                        "label": "Namenode URL",
                                                        "mandatory": true,
                                                        "name":
                                            "fs.default.name",
                                                        "subType": "",
                                                        "type": "string",
                                                        "uiHint": "",
                                                        "validationMessage": "",
                                                        "validationRegEx": ""
                                                        "defaultValue": "false",
                                                        "itemId": 4,
                                                        "label": "Authorization
                                            Enabled",
                                                        "mandatory": true,
                                                        "name":
                                            "hadoop.security.authorization",
                                                        "subType":
```

Get Service Definition by Name

 $Reference\ information\ for\ the\ Ranger\ REST\ API\ service/public/v2/api/servicedef/name/\{name\}.$

| API Name | Get Service Definition |
|--------------|--|
| Request Type | GET |
| Request URL | service/public/v2/api/servicedef/name/{name} |

```
API Name
                                          Get Service Definition
Request Params
Response
                                           {
                                                "accessTypes": [
                                                        "impliedGrants": [],
                                                        "itemId": 1,
                                                        "label": "select",
                                                        "name": "select"
                                                        "impliedGrants": [],
                                                        "itemId": 2,
                                                        "label": "update",
                                                        "name": "update"
                                                        "impliedGrants": [],
                                                        "itemId": 3,
                                                        "label": "Create",
                                                        "name": "create"
                                                        "impliedGrants": [],
                                                        "itemId": 4,
                                                        "label": "Drop",
                                                        "name": "drop"
                                                        "impliedGrants": [],
                                                        "itemId": 5,
                                                        "label": "Alter",
                                                        "name": "alter"
                                                        "impliedGrants": [],
                                                        "itemId": 6,
                                                        "label": "Index",
                                                        "name": "index"
                                                        "impliedGrants": [],
                                                        "itemId": 7,
                                                        "label": "Lock",
                                                        "name": "lock"
                                                         "impliedGrants": [
                                                             "select",
                                                             "update",
                                                             "create",
                                                             "drop",
                                                             "alter",
                                                             "index",
                                                             "lock"
                                                         "itemId": 8,
                                                        "label": "All",
                                                        "name": "all"
                                                "configs": [
                                                         "itemId": 1,
                                                         "label": "Username",
                                                         "mandatory": true,
                                                         "name": "username"
```

Create Service Definition

Reference information for the Ranger REST API service/public/v2/api/servicedef.

| API Name | Create Service Definition |
|--------------|---------------------------|
| Request Type | Post |

```
API Name
                                           Create Service Definition
Request URL
                                           service/public/v2/api/servicedef
Request Params
                                            {
                                                 "accessTypes": [
                                                         "impliedGrants": [],
                                                         "itemId": 1,
                                                         "label": "select",
                                                         "name": "select"
                                                         "impliedGrants": [],
                                                         "itemId": 2,
                                                         "label": "update",
                                                         "name": "update"
                                                         "impliedGrants": [],
                                                         "itemId": 3,
                                                         "label": "Create",
                                                         "name": "create"
                                                         "impliedGrants": [],
                                                         "itemId": 4,
                                                         "label": "Drop",
                                                         "name": "drop"
                                                         "impliedGrants": [
                                                              "select",
                                                              "update",
                                                              "create",
                                                              "drop"
                                                         "itemId": 5,
                                                         "label": "All",
                                                         "name": "all"
                                                 ],
                                                 "configs": [
                                                         "itemId": 1,
                                                         "label": "Username",
                                                         "mandatory": true,
                                                         "name": "username",
                                                         "type": "string",
                                                         "uiHint": "",
                                                         "validationMessage": "",
                                                         "validationRegEx": ""
                                                         "itemId": 2,
                                                         "label": "Password",
                                                         "mandatory": true,
                                                         "name": "password",
                                                         "type": "password",
                                                         "uiHint": "",
                                                         "validationMessage": "",
                                                         "validationRegEx": ""
                                                 "contextEnrichers": [],
                                                 "description": "Test Component",
                                                 "enums": [],
                                                 "implClass":
                                             "org.apache.ranger.services.test.RangerService'
```

Update Service Definition by ID

 $Reference\ information\ for\ the\ Ranger\ REST\ API\ service/public/v2/api/servicedef/\{id\}.$

| API Name | Update Service Definition |
|--------------|---------------------------|
| Request Type | PUT |

| API Name | Update Service Definition |
|-------------|--|
| Request URL | service/public/v2/api/servicedef/{id} |
| | <pre># service/public/2/api/servicedef/(id) {</pre> |
| | <pre></pre> |
| | "name": "password", "type": "password", "uiHint": "", "validationMessage": "", "validationRegEx": "" |

Update Service Definition by Name

 $Reference\ information\ for\ the\ Ranger\ REST\ API\ service/public/v2/api/servicedef/\{name\}.$

| API Name | Update Service Definition |
|----------------|---|
| Request Type | PUT |
| Request URL | service/public/v2/api/servicedef/{name} |
| Request Params | Application/json • Example: |
| Response | 200-Application/json |

Delete Service Definition by ID

Reference information for the Ranger REST API service/public/v2/api/servicedef/{id}.

| API Name | Delete Service Definition |
|---------------|---------------------------------------|
| Request Type | DELETE |
| Request URL | service/public/v2/api/servicedef/{id} |
| Request Param | |
| Response | 204-No Content |

Delete Service Definition by Name

Reference information for the Ranger REST API service/public/v2/api/servicedef/name/{name}.

| API Name | Delete Service Definition |
|---------------|--|
| Request Type | DELETE |
| Request URL | service/public/v2/api/servicedef/name/{name} |
| Request Param | |
| Response | 204-No Content |

Search Service Definitions

Reference information for the Ranger REST API service/public/v2/api/servicedef.

| API Name | Search Service Definitions |
|--------------|----------------------------------|
| Request Type | GET |
| Request URL | service/public/v2/api/servicedef |

| API Name | Search Service Definitions |
|----------------|---|
| Request Params | Query Params |
| | pageSize int The page size required |
| | startIndex int The start record index |
| | serviceType string The service definition names("hdfs","hive","hbase","knox","storm", "solr", "kafka","yarn") |
| | isEnabled boolean The enabled status : true if enabled; false otherwise |
| | Example: |
| | pageSize=25&startIndex=0 |
| Response | |
| | [] |
| | { |
| | "accessTypes": [{ |
| | "impliedGrants": [], "itemId": 1, |
| | "label": "Read", |
| | "name": "read" }, |
| | } , { |
| | <pre>"impliedGrants": [], "itemId": 2,</pre> |
| | "label": "Write", |
| | "name": "write" |
| | }, |
| | "impliedGrants": [], |
| | "itemId": 3, |
| | "label": "Execute", "name": "execute" |
| | } |
| |], "configs": [|
| | Conrigs : [|
| | "itemId": 1, |
| | "label": "Username", "mandatory": true, |
| | "name": "username", |
| | "subType": "", |
| | "type": "string", "uiHint": "", |
| | "validationMessage": |
| | "", |
| | "validationRegEx": |
| | }, |
| | "description": "Sub |
| | Resource for Test Component", "excludesSupported": |
| | true, |
| | "itemId": 2, |
| | "label": "Test sub resource", |
| | "level": 20, |
| | "lookupSupported": true, |
| | "mandatory": true, |
| | "matcher": |
| | <pre>"org.apache.ranger.plugin.resourcematcher.Rang</pre> |
| 12 | "ignoreCase": |
| | "true", |
| | "wildCard": "true" |
| | 1 |

Service APIs

Reference for the Apache Ranger REST Service APIs.

Get Service by ID

Reference information for the Ranger REST API service/public/v2/api/service/{id}.

| API Name | Get Service |
|----------------|--|
| Request Type | GET |
| Request URL | service/public/v2/api/service/{id} |
| Request Params | |
| Response | <pre>{ "configs": { "fs.default.name": "hdfs://akulkarni-etp-real- final-1.novalocal:8020", "hadoop.security.auth_to_local": "DEFAULT", "hadoop.security.authentication": "simple", "hadoop.security.authorization": "false", "password": "*****", "username": "hadoop" }, "createTime": 1450757397000, "createdBy": "amb_ranger_admin", "description": "hdfs repo", "guid": "ec082eea-0c22-43b8-84e0-129422f689b9 "id": 1, "isEnabled": true, "name": "cl1_hadoop", "policyUpdateTime": 1450757398000, "policyVersion": 2, "tagVersion": 1, "type": "hdfs", "updateTime": 1450757398000, "updatedBy": "amb_ranger_admin", "version": 3 }</pre> |

Get Service by Name

 $Reference\ information\ for\ the\ Ranger\ REST\ API\ service/public/v2/api/service/name/\{name\}.$

| API Name | Get Service |
|--------------|-------------|
| Request Type | GET |

| API Name | Get Service |
|----------------|---|
| Request URL | service/public/v2/api/service/name/{name} |
| Request Params | |
| Response | <pre>{ "configs": { "jdbc.driverClassName": "org.apache.hive.jdbc.HiveDriver", "jdbc.url": "jdbc:hive2://akulkarni-etp-real- final-1.novalocal:10000", "password": "*****", "username": "hive" }, "createTime": 1450757992000, "createdBy": "amb_ranger_admin", "description": "hive repo", "guid": "2bca8f98-4859-43c3- a8f4-d31a15f28793", "id": 3, "isEnabled": true, "name": "cl1_hive", "policyUpdateTime": 1450757995000, "policyVersion": 4, "tagUpdateTime": 1450916660000, "tagVersion": 74, "type": "hive", "updateTime": 1450757995000, "updatedBy": "amb_ranger_admin", "version": 78 }</pre> |

Create Service

Reference information for the Ranger REST API service/public/v2/api/service.

| API Name | Create Service |
|--------------|----------------|
| Request Type | Post |

| API Name | Create Service |
|----------------|--|
| Request URL | service/public/v2/api/service |
| Request Params | <pre>{ "configs": {</pre> |
| Response | <pre>{ "configs": { "password": "*****", "username": "hadoop" }, "createTime": 1451348710255, "createdBy": "Admin", "description": "test service", "guid": "e72cb64d-66d7-4632- b5ae-c6966cb52105", "id": 6, "isEnabled": true, "name": "cll_test", "tagVersion": 1, "type": "test", "updateTime": 1451348710256, "updatedBy": "Admin", "version": 1 }</pre> |

Update Service by ID

Reference information for the Ranger REST API service/public/v2/api/service/{id}.

| API Name | Update Service |
|----------------|------------------------------------|
| Request Type | PUT |
| Request URL | service/public/v2/api/service/{id} |
| Request Params | Application/json • Example: |
| Response | 200-Application/json |

Update Service by Name

Reference information for the Ranger REST API service/public/v2/api/service/name/{name}.

| API Name | Update Service |
|--------------|----------------|
| Request Type | PUT |

| API Name | Update Service |
|----------------|--|
| Request URL | service/public/v2/api/service/name/{name} |
| Request Params | <pre>{ "configs": {</pre> |
| Response | <pre>{ "configs": { "password": "*****", "username": "admin" }, "createTime": 1451348710000, "createdBy": "Admin", "description": "test service", "guid": "e72cb64d-66d7-4632- b5ae-c6966cb52105", "id": 6, "isEnabled": true, "name": "cl1_test", "policyUpdateTime": 1451351474000, "policyVersion": 3, "tagVersion": 1, "type": "test", "updateTime": 1451352016713, "updatedBy": "Admin", "version": 5 }</pre> |

Delete Service by ID

Reference information for the Ranger REST API service/public/v2/api/service/{id}.

| API Name | Delete Service |
|---------------|------------------------------------|
| Request Type | DELETE |
| Request URL | service/public/v2/api/service/{id} |
| Request Param | |
| Response | 204-No Content |

Delete Service by Name

 $Reference\ information\ for\ the\ Ranger\ REST\ API\ service/public/v2/api/service/name/\{name\}.$

| API Name | Delete Service |
|--------------|----------------|
| Request Type | DELETE |

| API Name | Delete Service |
|---------------|---|
| Request URL | service/public/v2/api/service/name/{name} |
| Request Param | |
| Response | 204-No Content |

Search Services

Reference information for the Ranger REST API service/public/v2/api/service.

| API Name | Search Services |
|--------------|-------------------------------|
| Request Type | GET |
| Request URL | service/public/v2/api/service |

| API Name | Search Services |
|----------------|--|
| Request Params | Query Parameters: |
| | pageSize int The page size required |
| | startIndex int The start record index |
| | serviceName stringThe service name |
| | serviceNamePartial string Partial service name |
| | serviceType string The service types(such as "hdfs", "hive", "hbase", "knox", "storm") |
| | isEnabled boolean The enabled status (true/false): true is enabled, false otherwise |
| | Example: |
| | pageSize=25&startIndex=0 |
| Response | |
| | [|
| | "fs.default.name": "hdfs://akulkarni-etp-real- final-1.novalocal:8020", |
| | "hadoop.security.auth_to_local": "DEFAULT", |
| | "hadoop.security.authentication": "simple", |
| | "hadoop.security.authorization": "false", |
| | "password": "****", |
| | "createTime": 1450757397000, "createdBy": |
| | <pre>"amb_ranger_admin",</pre> |
| | "ec082eea-0c22-43b8-84e0-129422f689b9 "id": 1, |
| | "isEnabled": true, "name": "cll_hadoop", |
| | "policyUpdateTime": 1450757398000, "policyVersion": 2, |
| | "tagVersion": 1, "type": "hdfs", |
| | "updateTime": 1450757398000, "updatedBy": |
| | <pre>"amb_ranger_admin",</pre> |
| | {' |
| | "password": "*****, "username": "yarn", |
| | "yarn.url": "http://akulkarni-etp-real- final-1.novalocal:8088" |
| | }, |
| | "createTime": 1450757747000, "createdBy": "amb_ranger_admin", |
| | 18 "amb_ranger_admin", |
| | "080970a9-2216-4660-962e-2b48046bf87e "id": 2, |

Policy APIs

Reference for the Apache Ranger REST Policy APIs.

Get Policy by ID

Reference information for the Ranger REST API service/public/v2/api/policy/{id}.

| API Name | Get Policy |
|--------------|-----------------------------------|
| Request Type | Get |
| Request URL | service/public/v2/api/policy/{id} |

```
API Name
                                          Get Policy
Request Params
Response
                                           {
                                               "allowExceptions": [],
                                               "createTime": 1450757397000,
                                               "createdBy": "amb_ranger_admin",
                                               "denyExceptions": [],
                                               "denyPolicyItems": [],
                                               "description": "Default Policy
                                            for Service: cl1_hadoop",
                                               "guid":
                                            "4c2f7afb-23fa-45e9-9b41-29bdc7423b65",
                                               "id": 1,
                                               "isAuditEnabled": true,
                                               "isEnabled": true,
                                               "name":
                                            "cl1_hadoop-1-20151222040957",
                                               "policyItems": [
                                                        "accesses": [
                                                            {
                                                                 "isAllowed":
                                            true,
                                                                 "type": "read"
                                                                 "isAllowed":
                                            true,
                                                                 "type": "write"
                                                                 "isAllowed":
                                            true,
                                                                 "type":
                                            "execute"
                                                        "conditions": [],
                                                        "delegateAdmin": true,
                                                        "groups": [],
                                                        "users": [
                                                            "ambari-qa"
                                               "resourceSignature":
                                            "6f956063401eda656f1eae8870c1afac",
                                               "resources": {
                                                    "path": {
                                                        "isExcludes": false,
                                                        "isRecursive": true,
                                                        "values": [
                                               "service": "cl1_hadoop",
                                               "updateTime": 1450757398000,
                                               "updatedBy": "amb_ranger_admin",
                                               "version": 2
                                           }
```

Get Policy by Service Name and Policy Name

 $Reference\ information\ for\ the\ Ranger\ REST\ API\ service/public/v2/api/service/\{service-name\}/policy/\{policy-name\}.$

| API Name | Get Policy |
|--------------|---|
| Request Type | Get |
| Request URL | service/public/v2/api/service/{service-name}/policy/{policy-name} |

| API Name | Get Policy | Get Policy | |
|----------------|--|---|--|
| Request Params | | | |
| Response | (| | |
| | "cre "cre "der "der for Ser "gui "d62181 "id" "is# "is# "is# "ram | 120-1b66-43e6-9fef-9c917a8e9e25 : 4, AuditEnabled": true, Enabled": true, | |
| | | { "accesses": [| |
| | | { | |
| | true, | "isAllowed": "type": "select" }, | |
| | true, | { "isAllowed": "type": "update" | |
| | | }, { "isAllowed": | |
| | true, | "type": "create" }, | |
| | true, | <pre>"isAllowed": "type": "drop" },</pre> | |
| | true, | { "isAllowed": "type": "alter" | |
| | true, | }, { "isAllowed": "type": "index" | |
| | true, | }, { "isAllowed": "type": "lock" | |
| | true, | }, { "isAllowed": | |
| | | "type": "all" }], "conditions": [], "delegateAdmin": true, | |
| | 22 | "groups": [], "users": ["ambari-qa" | |

Create Policy

Reference information for the Ranger REST API service/public/v2/api/policy.

| API name | Create Policy |
|--------------|---------------|
| Request Type | POST |

| API name | Create Policy |
|-------------|---|
| Request URL | service/public/v2/api/policy |
| | |
| | <pre></pre> |
| | <pre>"type": "create"</pre> |
| | "isRecursive": false, "isRecursive": false, "values": [|

Update Policy by ID

Reference information for the Ranger REST API service/public/v2/api/policy/{id}.

| API Name | update policy |
|--------------|---------------|
| Request Type | PUT |

| API Name | update policy |
|----------------|---|
| Request URL | service/public/v2/api/policy/{id} |
| Request Params | <pre>{ "id": 8, "allowExceptions": [], "denyExceptions": [], "denyPolicyItems": [</pre> |
| | <pre>"isAllowed": true,</pre> |
| | <pre>{ "accesses": [</pre> |
| | true, "type": "create' }, { "isAllowed": true, |
| | <pre>"type": "drop" }],</pre> |
| | "isRecursive": false, "values": ["abc"] |

Update Policy by Service Name and Policy Name

 $Reference\ information\ for\ the\ Ranger\ REST\ API\ service/public/v2/api/service/\{service-name\}/policy/\{policy-name\}.$

| API Name | update policy |
|--------------|---------------|
| Request Type | PUT |

| API Name | update policy | update policy | |
|-----------------------------|---|---|--|
| Request URL | service/public/v2/api/service/{service-name}/policy/{p | service/public/v2/api/service/{service-name}/policy/{policy-name} | |
| Request URL Request Params | <pre>{ "allowExceptions": [], "denyExceptions": [], "denyPolicyItems": [</pre> | ed": "drop" , true, | |
| | <pre>"description": "Policy for Service: cl1_test", "isAuditEnabled": true, "isEnabled": true, "name": "cl1_test-1", "policyItems": [</pre> | ed": "select" ed": | |
| | true, "isAllowe"; " true, "type"; " , "isAllowe"; " | "create" | |
| | "isAllowed true, "type": " | "drop" , true, ic"], | |
| | "isRecursive": for "values": [| | |

Delete Policy by ID

Reference information for the Ranger REST API service/public/v2/api/policy/{id}.

| API Name | Delete Policy |
|----------------|-----------------------------------|
| Request Type | DELETE |
| Request URL | service/public/v2/api/policy/{id} |
| Request Params | |
| Response | 204 - No Content |

Delete Policy by Service Name and Policy Name

Reference information for the Ranger REST API service/public/v2/api/policy.

| API Name | Delete Policy |
|----------------|--|
| Request Type | DELETE |
| Request URL | service/public/v2/api/policy |
| Request Params | Query Parameters: servicename string The name of service policyname string The name of policy Example: servicename=service-name&policyname=policy-name |
| Response | 204 - No Content |

Search Policies in a Service

Reference information for the Ranger REST API service/public/v2/api/service/{service-name}/policy.

| API Name | Search Policies in a Service |
|--------------|---|
| API Name | Search Policies in a Service |
| Request Type | GET |
| Request URL | service/public/v2/api/service/{service-name}/policy |

| API Name | Search Policies in a Service |
|----------------|---|
| API Name | Search Policies in a Service |
| Request Params | Query Parameters: |
| | pageSize int The page size required |
| | startIndex int The start record index |
| | policyName string The Exact Name of the policy |
| | policyNamePartial string The Partial Name of the policy |
| | policyId string The policy ID |
| | polResource string The policy resource value |
| | resource:resource-type string The policy resource value for given resource-type |
| | user stringThe user name |
| | group string The group name |
| | isRecursive boolean The isRecursive property ("true" or "false") |
| | isEnabled boolean The enable/disabled property ("true" or "false") |
| | Example = |
| | pageSize=25&startIndex=0&resource:database=finance |
| Response | |
| | <pre>[</pre> |
| | "type": "select" }, { |
| | "isAllowed": true, |
| | "type": "update" |
| | |
| | }, { |
| | "isAllowed": true, |
| | "type": |
| | "create" |
| | }, |
| | "isAllowed": |
| 30 | true, |
| | "type": "drop" |
| | }, |