

**Lecture**

# **Documenting Classes**





## Documenting Classes

The docstring for a class should summarize its behavior and list the public methods and instance variables. If the class is intended to be subclassed, and has an additional interface for subclasses, this interface should be listed separately (in the docstring). The class constructor should be documented in the docstring for its `__init__` method. Individual methods should be documented by their own docstring.



## Documenting Classes

The docstring for a class should summarize its behavior and list the public methods and instance variables. If the class is intended to be subclassed, and has an additional interface for subclasses, this interface should be listed separately (in the docstring). The class constructor should be documented in the docstring for its `__init__` method. Individual methods should be documented by their own docstring.



## Documenting Classes

The docstring for a class should summarize its behavior and list the public methods and instance variables. If the class is intended to be subclassed, and has an additional interface for subclasses, this interface should be listed separately (in the docstring). The class constructor should be documented in the docstring for its `__init__` method. Individual methods should be documented by their own docstring.



## Documenting Classes

The docstring for a class should summarize its behavior and list the public methods and instance variables. If the class is intended to be subclassed, and has an additional interface for subclasses, this interface should be listed separately (in the docstring). The class constructor should be documented in the docstring for its `__init__` method. Individual methods should be documented by their own docstring.



## Documenting Classes

```
class TissueSample:
    """Class that represents a tissue sample.

    Attributes:
        patient (Patient): the patient associated with the tissue sample.
        organ (str): the organ associated with tissue sample.
        code (str): a unique alphanumeric sequence that identifies the tissue sample.
        diagnosis (str): the diagnosis associated with this tissue sample. By default,
            it is initialized to None when the instance is created.

    Methods:
        show_data(): displays the four main properties of the tissue sample
            in a human-readable format.
    """

    def __init__(self, patient, organ, code):
        """Initialize the values of the instance attributes of an instance of TissueSample.

        Args:
            patient (Patient): the patient associated with the tissue sample.
            organ (str): the organ associated with tissue sample.
            code (str): a unique alphanumeric sequence that identifies the tissue sample.
        """
        self.patient = patient
        self.organ = organ
        self._code = code
        self._diagnosis = None
```



## Documenting Classes

```
class TissueSample:
    """Class that represents a tissue sample.

    Attributes:
        patient (Patient): the patient associated with the tissue sample.
        organ (str): the organ associated with tissue sample.
        code (str): a unique alphanumeric sequence that identifies the tissue sample.
        diagnosis (str): the diagnosis associated with this tissue sample. By default,
            it is initialized to None when the instance is created.

    Methods:
        show_data(): displays the four main properties of the tissue sample
            in a human-readable format.
    """

    def __init__(self, patient, organ, code):
        """Initialize the values of the instance attributes of an instance of TissueSample.

        Args:
            patient (Patient): the patient associated with the tissue sample.
            organ (str): the organ associated with tissue sample.
            code (str): a unique alphanumeric sequence that identifies the tissue sample.
        """
        self.patient = patient
        self.organ = organ
        self._code = code
        self._diagnosis = None
```



## Documenting Classes

```
"""Class that represents a tissue sample.

Attributes:
    patient (Patient): the patient associated with the tissue sample.
    organ (str): the organ associated with tissue sample.
    code (str): a unique alphanumeric sequence that identifies the tissue sample.
    diagnosis (str): the diagnosis associated with this tissue sample. By default,
        it is initialized to None when the instance is created.

Methods:
    show_data(): displays the four main properties of the tissue sample
        in a human-readable format.

"""
```





## Documenting Classes

```
"""Class that represents a tissue sample.
```

```
Attributes:
```

```
    patient (Patient): the patient associated with the tissue sample.  
    organ (str): the organ associated with tissue sample.  
    code (str): a unique alphanumeric sequence that identifies the tissue sample.  
    diagnosis (str): the diagnosis associated with this tissue sample. By default,  
        it is initialized to None when the instance is created.
```

```
Methods:
```

```
    show_data(): displays the four main properties of the tissue sample  
        in a human-readable format.
```

```
"""
```





## Documenting Classes

```
"""Class that represents a tissue sample.
```

```
Attributes:
```

```
    patient (Patient): the patient associated with the tissue sample.  
    organ (str): the organ associated with tissue sample.  
    code (str): a unique alphanumeric sequence that identifies the tissue sample.  
    diagnosis (str): the diagnosis associated with this tissue sample. By default,  
        it is initialized to None when the instance is created.
```

```
Methods:
```

```
    show_data(): displays the four main properties of the tissue sample  
        in a human-readable format.
```

```
"""
```





## Documenting Classes

```
"""Class that represents a tissue sample.
```

```
Attributes:
```

```
    patient (Patient): the patient associated with the tissue sample.  
    organ (str): the organ associated with tissue sample.  
    code (str): a unique alphanumeric sequence that identifies the tissue sample.  
    diagnosis (str): the diagnosis associated with this tissue sample. By default,  
        it is initialized to None when the instance is created.
```

```
Methods:
```

```
    show_data(): displays the four main properties of the tissue sample  
        in a human-readable format.
```

```
"""
```





## Documenting Classes

```
"""Class that represents a tissue sample.
```

```
Attributes:
```

```
    patient (Patient): the patient associated with the tissue sample.  
    organ (str): the organ associated with tissue sample.  
    code (str): a unique alphanumeric sequence that identifies the tissue sample.  
    diagnosis (str): the diagnosis associated with this tissue sample. By default,  
        it is initialized to None when the instance is created.
```

```
Methods:
```

```
    show_data(): displays the four main properties of the tissue sample  
        in a human-readable format.
```

```
"""
```





## Documenting Classes

```
"""Class that represents a tissue sample.
```

```
Attributes:
```

```
    patient (Patient): the patient associated with the tissue sample.  
    organ (str): the organ associated with tissue sample.  
    code (str): a unique alphanumeric sequence that identifies the tissue sample.  
    diagnosis (str): the diagnosis associated with this tissue sample. By default,  
        it is initialized to None when the instance is created.
```

```
Methods:
```

```
    show_data(): displays the four main properties of the tissue sample  
        in a human-readable format.
```

```
"""
```





## Documenting Classes

```
"""Class that represents a tissue sample.
```

```
Attributes:
```

```
    patient (Patient): the patient associated with the tissue sample.  
    organ (str): the organ associated with tissue sample.  
    code (str): a unique alphanumeric sequence that identifies the tissue sample.  
    diagnosis (str): the diagnosis associated with this tissue sample. By default,  
        it is initialized to None when the instance is created.
```

```
Methods:
```

```
    show_data(): displays the four main properties of the tissue sample  
        in a human-readable format.
```

```
"""
```



## Documenting Classes

```
class TissueSample:
    """Class that represents a tissue sample.

    Attributes:
        patient (Patient): the patient associated with the tissue sample.
        organ (str): the organ associated with tissue sample.
        code (str): a unique alphanumeric sequence that identifies the tissue sample.
        diagnosis (str): the diagnosis associated with this tissue sample. By default,
            it is initialized to None when the instance is created.

    Methods:
        show_data(): displays the four main properties of the tissue sample
            in a human-readable format.
    """

    def __init__(self, patient, organ, code):
        """Initialize the values of the instance attributes of an instance of TissueSample.

        Args:
            patient (Patient): the patient associated with the tissue sample.
            organ (str): the organ associated with tissue sample.
            code (str): a unique alphanumeric sequence that identifies the tissue sample.
        """
        self.patient = patient
        self.organ = organ
        self._code = code
        self._diagnosis = None
```



## Documenting Classes

```
class TissueSample:
    """Class that represents a tissue sample.

    Attributes:
        patient (Patient): the patient associated with the tissue sample.
        organ (str): the organ associated with tissue sample.
        code (str): a unique alphanumeric sequence that identifies the tissue sample.
        diagnosis (str): the diagnosis associated with this tissue sample. By default,
            it is initialized to None when the instance is created.

    Methods:
        show_data(): displays the four main properties of the tissue sample
            in a human-readable format.
    """

    def __init__(self, patient, organ, code):
        """Initialize the values of the instance attributes of an instance of TissueSample.

        Args:
            patient (Patient): the patient associated with the tissue sample.
            organ (str): the organ associated with tissue sample.
            code (str): a unique alphanumeric sequence that identifies the tissue sample.
        """
        self.patient = patient
        self.organ = organ
        self._code = code
        self._diagnosis = None
```





## Documenting Classes

```
"""Initialize the values of the instance attributes of an instance of TissueSample.  
Args:  
    patient (Patient): the patient associated with the tissue sample.  
    organ (str): the organ associated with tissue sample.  
    code (str): a unique alphanumeric sequence that identifies the tissue sample.  
"""
```



## Documenting Classes

```
"""Initialize the values of the instance attributes of an instance of TissueSample.  
Args:  
    patient (Patient): the patient associated with the tissue sample.  
    organ (str): the organ associated with tissue sample.  
    code (str): a unique alphanumeric sequence that identifies the tissue sample.  
"""
```



## Documenting Classes

```
"""Initialize the values of the instance attributes of an instance of TissueSample.
```

```
Args:
```

```
    patient (Patient): the patient associated with the tissue sample.
```

```
    organ (str): the organ associated with tissue sample.
```

```
    code (str): a unique alphanumeric sequence that identifies the tissue sample.
```

```
"""
```





## Documenting Classes

```
"""Initialize the values of the instance attributes of an instance of TissueSample.  
Args:  
    patient (Patient): the patient associated with the tissue sample.  
    organ (str): the organ associated with tissue sample.  
    code (str): a unique alphanumeric sequence that identifies the tissue sample.  
"""
```



## Documenting Classes

```
"""Initialize the values of the instance attributes of an instance of TissueSample.
```

```
Args:
```

```
    patient (Patient): the patient associated with the tissue sample.
```

```
    organ (str): the organ associated with tissue sample.
```

```
    code (str): a unique alphanumeric sequence that identifies the tissue sample.
```

```
"""
```





## Documenting Classes

```
"""Initialize the values of the instance attributes of an instance of TissueSample.
```

```
Args:
```

```
    patient (Patient): the patient associated with the tissue sample.  
    organ (str): the organ associated with tissue sample.  
    code (str): a unique alphanumeric sequence that identifies the tissue sample.
```

```
"""
```



## Documenting Classes

### ◆ For properties:

- Only document the **getters**.

```
@property
def diagnosis(self):
    """Diagnosis associated with the tissue sample."""
    return self._diagnosis


@diagnosis.setter
def diagnosis(self, diagnosis):
    self._diagnosis = diagnosis
```



## Documenting Classes

### ◆ For properties:

- Only document the getters.



```
@property
def diagnosis(self):
    """Diagnosis associated with the tissue sample."""
    return self._diagnosis

@diagnosis.setter
def diagnosis(self, diagnosis):
    self._diagnosis = diagnosis
```





\_\_doc\_\_

