Lecture

“Rich Comparison” Methods

“Rich Comparison” Methods

`__lt__()`	<	Less than
`__le__()`	<=	Less Than or Equal to
`__eq__()`	==	Equal to
`__ne__()`	!=	Not equal to
`__gt__()`	>	Greater than
`__ge__()`	>=	Greater than or Equal to

“Rich Comparison” Methods

```
class Point:

    def __init__(self, x, y):
        self.x = x
        self.y = y
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
Traceback (most recent call last):
  File "<pyshell#2>", line 1, in <module>
    point1 < point2
TypeError: '<' not supported between instances of 'Point' and 'Point'
>>> point1 == point2
False
>>> point1 >= point2
Traceback (most recent call last):
  File "<pyshell#4>", line 1, in <module>
    point1 >= point2
TypeError: '>=' not supported between instances of 'Point' and 'Point'
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
Traceback (most recent call last):
  File "<pyshell#2>", line 1, in <module>
    point1 < point2
TypeError: '<' not supported between instances of 'Point' and 'Point'
>>> point1 == point2
False
>>> point1 >= point2
Traceback (most recent call last):
  File "<pyshell#4>", line 1, in <module>
    point1 >= point2
TypeError: '>=' not supported between instances of 'Point' and 'Point'
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
Traceback (most recent call last):
  File "<pyshell#2>", line 1, in <module>
    point1 < point2
TypeError: '<' not supported between instances of 'Point' and 'Point'
>>> point1 == point2
False
>>> point1 >= point2
Traceback (most recent call last):
  File "<pyshell#4>", line 1, in <module>
    point1 >= point2
TypeError: '>=' not supported between instances of 'Point' and 'Point'
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
Traceback (most recent call last):
  File "<pyshell#2>", line 1, in <module>
    point1 < point2
TypeError: '<' not supported between instances of 'Point' and 'Point'
>>> point1 == point2
False
>>> point1 >= point2
Traceback (most recent call last):
  File "<pyshell#4>", line 1, in <module>
    point1 >= point2
TypeError: '>=' not supported between instances of 'Point' and 'Point'
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
Traceback (most recent call last):
  File "<pyshell#2>", line 1, in <module>
    point1 < point2
TypeError: '<' not supported between instances of 'Point' and 'Point'
>>> point1 == point2
False
>>> point1 >= point2
Traceback (most recent call last):
  File "<pyshell#4>", line 1, in <module>
    point1 >= point2
TypeError: '>=' not supported between instances of 'Point' and 'Point'
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
Traceback (most recent call last):
  File "<pyshell#2>", line 1, in <module>
    point1 < point2
TypeError: '<' not supported between instances of 'Point' and 'Point'
>>> point1 == point2
False
>>> point1 >= point2
Traceback (most recent call last):
  File "<pyshell#4>", line 1, in <module>
    point1 >= point2
TypeError: '>=' not supported between instances of 'Point' and 'Point'
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
Traceback (most recent call last):
  File "<pyshell#2>", line 1, in <module>
    point1 < point2
TypeError: '<' not supported between instances of 'Point' and 'Point'
>>> point1 == point2
False
>>> point1 >= point2
Traceback (most recent call last):
  File "<pyshell#4>", line 1, in <module>
    point1 >= point2
TypeError: '>=' not supported between instances of 'Point' and 'Point'
```

```
class Point:

    def __init__(self, x, y):
        self.x = x
        self.y = y

    def __lt__(self, other):
        return self.x < other.x

    def __le__(self, other):
        return self.x <= other.x

    def __eq__(self, other):
        return (self.x == other.x) and (self.y == other.y)

    def __ne__(self, other):
        return (self.x != other.x) or (self.y != other.y)

    def __gt__(self, other):
        return self.x > other.x

    def __ge__(self, other):
        return self.x >= other.x
```

```
class Point:

    def __init__(self, x, y):
        self.x = x
        self.y = y

    def __lt__(self, other):
        return self.x < other.x

    def __le__(self, other):
        return self.x <= other.x

    def __eq__(self, other):
        return (self.x == other.x) and (self.y == other.y)

    def __ne__(self, other):
        return (self.x != other.x) or (self.y != other.y)

    def __gt__(self, other):
        return self.x > other.x

    def __ge__(self, other):
        return self.x >= other.x
```

```
class Point:

    def __init__(self, x, y):
        self.x = x
        self.y = y

    def __lt__(self, other):
        return self.x < other.x

    def __le__(self, other):
        return self.x <= other.x

    def __eq__(self, other):
        return (self.x == other.x) and (self.y == other.y)

    def __ne__(self, other):
        return (self.x != other.x) or (self.y != other.y)

    def __gt__(self, other):
        return self.x > other.x

    def __ge__(self, other):
        return self.x >= other.x
```

```
class Point:

    def __init__(self, x, y):
        self.x = x
        self.y = y

    def __lt__(self, other):
        return self.x < other.x

    def __le__(self, other):
        return self.x <= other.x

    def __eq__(self, other):
        return (self.x == other.x) and (self.y == other.y)

    def __ne__(self, other):
        return (self.x != other.x) or (self.y != other.y)

    def __gt__(self, other):
        return self.x > other.x

    def __ge__(self, other):
        return self.x >= other.x
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
True
>>> point1 <= point2
True
>>> point1 == point2
False
>>> point1 != point2
True
>>> point1 > point2
False
>>> point1 >= point2
False
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
True
>>> point1 <= point2
True
>>> point1 == point2
False
>>> point1 != point2
True
>>> point1 > point2
False
>>> point1 >= point2
False
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
True
>>> point1 <= point2
True
>>> point1 == point2
False
>>> point1 != point2
True
>>> point1 > point2
False
>>> point1 >= point2
False
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
True
>>> point1 <= point2
True
>>> point1 == point2
False
>>> point1 != point2
True
>>> point1 > point2
False
>>> point1 >= point2
False
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
True
>>> point1 <= point2
True
>>> point1 == point2
False
>>> point1 != point2
True
>>> point1 > point2
False
>>> point1 >= point2
False
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
True
>>> point1 <= point2
True
>>> point1 == point2
False
>>> point1 != point2
True
>>> point1 > point2
False
>>> point1 >= point2
False
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
True
>>> point1 <= point2
True
>>> point1 == point2
False
>>> point1 != point2
True
>>> point1 > point2
False
>>> point1 >= point2
False
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
True
>>> point1 <= point2
True
>>> point1 == point2
False
>>> point1 != point2
True
>>> point1 > point2
False
>>> point1 >= point2
False
```

“Rich Comparison” Methods

```
>>> point1 = Point(-53, 34)
>>> point2 = Point(56, 23)
>>> point1 < point2
True
>>> point1 <= point2
True
>>> point1 == point2
False
>>> point1 != point2
True
>>> point1 > point2
False
>>> point1 >= point2
False
```