

Smart Fleet Platform - API Documentation

Environment

Service	URL	Swagger
Identity Service	http://localhost:5057	http://localhost:5057/swagger
Fleet Service	http://localhost:5081	http://localhost:5081/swagger
API Gateway	http://localhost:5000	http://localhost:5000/swagger
Kafka UI	http://localhost:8080	N/A
Seq Dashboard	http://localhost:5341	N/A

Identity Service

Base URL:

http://localhost:5057/api

Register User

Endpoint

POST /Auth/register

Request

```
{
  "firstName": "Yusuf",
  "lastName": "Sayed",
  "email": "yusuf@test.com",
  "password": "Password123!",
  "confirmPassword": "Password123!"
}
```

Response

```
{
  "message": "User registered successfully"
}
```

Login

Endpoint

POST /Auth/login

Request

```
{
  "email": "yusuf@test.com",
  "password": "Password123!"
}
```

Response

```
{
  "token": "eyJhbGciOiJIUzI1NiIs... ",
  "email": "yusuf@test.com",
  "expiresAt": "2026-12-31T23:59:59Z"
}
```

cURL

```
curl -X POST "http://localhost:5057/api/Auth/login"
-H "Content-Type: application/json"
-d '{
  "email": "yusuf@test.com",
  "password": "Password123!"
}'
```

Fleet Service

Base URL:

http://localhost:5081/api

Get All Vehicles

Endpoint

GET /vehicles

Request

No request body required.

Response

```
[
  {
    "id": 1,
    "registrationNumber": "MH01AB1234",
    "manufacturer": "Tata",
    "model": "Ace",
    "year": 2024
  }
]
```

Get Vehicle By Id

Endpoint

GET /vehicles/{id}

Example

```
GET /vehicles/1
```

Response

```
{
  "id": 1,
  "registrationNumber": "MH01AB1234",
  "manufacturer": "Tata",
  "model": "Ace",
  "year": 2024
}
```

```
"year": 2024
}
```

Create Vehicle

Endpoint

POST /vehicles

Request

```
{
  "registrationNumber": "MH01AB1234",
  "manufacturer": "Tata",
  "model": "Ace Gold",
  "year": 2024,
  "fuelType": "Diesel",
  "status": "Active"
}
```

Response

```
{
  "id": 1,
  "registrationNumber": "MH01AB1234",
  "manufacturer": "Tata",
  "model": "Ace Gold",
  "year": 2024,
  "fuelType": "Diesel",
  "status": "Active"
}
```

Update Vehicle

Endpoint

PUT /vehicles/{id}

Example

```
PUT /vehicles/1
```

Request

```
{
  "registrationNumber": "MH01AB1234",
  "manufacturer": "Tata",
  "model": "Ace Updated",
  "year": 2025,
  "fuelType": "Diesel",
  "status": "Active"
}
```

Response

```
{
  "message": "Vehicle updated successfully"
}
```

Delete Vehicle

Endpoint

DELETE /vehicles/{id}

Example

```
DELETE /vehicles/1
```

Response

```
{
  "message": "Vehicle deleted successfully"
}
```

Kafka Topics

Vehicle Created

Topic:

```
vehicle-created
```

Sample Event

```
{
  "vehicleId": 1,
  "registrationNumber": "MH01AB1234",
  "createdAt": "2026-06-16T13:00:00Z"
}
```

SQL Server

Connection String

```
Server=localhost,1433;
Database=SmartFleetIdentityDb;
User Id=sa;
Password=YourStrong@Passw0rd;
TrustServerCertificate=True;
```

Health Check URLs

Identity Service

```
http://localhost:5057/swagger
```

Fleet Service

http://localhost:5081/swagger

Kafka UI

http://localhost:8080

Seq Dashboard

http://localhost:5341

Default Test User

Email

yusuf@test.com

Password

Password123!