Substrate

River

Kitties-003

Tracking All Kitties

https://substrate.dev/substrate-collectables-workshop/#/2/tracking-all-kitties



1- Creating a List

在运行时开发中,列表迭代通常是危险的。我们将使用mapping和计数器来模拟列表。

```
people列表
decl_storage! {
  trait Store for Module<T: Trait> as Example {
    AllPeopleArray get(person): map u32 => T::Accountld;
    AllPeopleCount get(num_of_people): u32;
count 3
PeopleArray
[0,0001], [1,0002],[2,0003]
```



```
3- Updating our List in Storage
people列表
fn add_person(origin, new_person: T::AccountId) -> Result {
  let sender = ensure_signed(origin)?;
  let all_people_count = Self::num_of_friends();
  let new_all_people_count =
all_people_count.checked_add(1).ok_or("Overflow adding a new person")?;
  <ali><ali><ali><ali>peopleCount<a><ali><ali>people_count</a>);</a>
  Ok(())
+1
count 4
PeopleArray
[0,0001], [1,0002],[2,0003],[3,0003]
```



- 1- 创建了kitty的数量
- 2- 查询创建的Kitty的记录: index和kitty_id的对应关系
- 3- Kitty_id和index的关系



2- Checking for Overflow/Underflow

```
AllPeopleCount

checked_add()

checked_sub()
```

```
let all_people_count = Self::num_of_people();
let new_all_people_count = all_people_count.checked_add(1).ok_or("Overflow adding a new person")?;
```

```
let new_all_people_count = match all_people_count.checked_add(1) {
    Some (c) => c,
    None => return Err("Overflow adding a new person"),
};
```



```
1- Storage
     // ACTION: Create new storage items to globally track all kitties:
            - `AllKittiesArray` which is a `map` from `u64` to `T::Hash`, add a getter function for this
            - `AllKittiesCount` which is a `u64`, add a getter function for this
            - `AllKittiesIndex` which is a `map` from `T::Hash` to `u64`
2- create_kitty
       // ACTION: Get the current `AllKittiesCount` value and store it in `all kitties count`
       // ACTION: Create a `new_all_kitties_count` by doing a `checked_add()` to increment
'all kitties count'
             REMINDER: Return an `Err()` if there is an overflow
3- create_kitty
       // ACTION: Update the storage for the global kitty tracking
               - `AllKittiesArray` should use the `all_kitties_count` (remember `index` is `count - 1`)
               - `AllKittiesCount` should use `new all kitties count`
               - `AllKittiesIndex` should use `all kitties count`
```

Substrate

River

Thanks