

# Supporting Document

## Mandatory Technical Document



PP-Module for WLAN Clients

Version: 1.0

2019-08-28

National Information Assurance Partnership

## Foreword

This is a Supporting Document (SD), intended to complement the Common Criteria version 3 and the associated Common Evaluation Methodology for Information Technology Security Evaluation.

SDs may be “Guidance Documents”, that highlight specific approaches and application of the standard to areas where no mutual recognition of its application is required, and as such, are not of normative nature, or “Mandatory Technical Documents”, whose application is mandatory for evaluations whose scope is covered by that of the SD. The usage of the latter class is not only mandatory, but certificates issued as a result of their application are recognized under the CCRA.

### Technical Editor:

National Information Assurance Partnership (NIAP)

### Document history:

Version	Date	Comment
1.0	2019-08-28	Initial Release

### General Purpose:

The purpose of this SD is to define evaluation methods for the functional behavior of PP-Module for Wireless LAN Clients products.

### Acknowledgements:

This SD was developed with support from NIAP WLAN Clients Technical Community members, with representatives from industry, Government agencies, Common Criteria Test Laboratories, and members of academia.

## Table of Contents

- 1 Introduction
  - 1.1 Technology Area and Scope of Supporting Document
  - 1.2 Structure of the Document
  - 1.3 Terms
- 2 Evaluation Activities for SFRs
  - 2.1 General Purpose Operating Systems Protection Profile
    - 2.1.1 Modified SFRs
      - 2.1.1.1 Cryptographic Support (FCS)
  - 2.2 Mobile Device Fundamentals Protection Profile
    - 2.2.1 Modified SFRs
      - 2.2.1.1 Cryptographic Support (FCS)
    - 2.2.2 TOE SFR Evaluation Activities

2.2.3	Security Audit (FAU)
2.2.4	Cryptographic Support (FCS)
2.2.5	Identification and Authentication (FIA)
2.2.6	Security Management (FMT)
2.2.7	Protection of the TSF (FPT)
2.2.8	TOE Access (FTA)
2.2.9	Trusted Path/Channels (FTP)
3	Evaluation Activities for Optional SFRs
3.1	Identification and Authentication (FIA)
4	Evaluation Activities for Selection-Based SFRs
4.1	Cryptographic Support (FCS)
5	Evaluation Activities for Objective SFRs
6	Evaluation Activities for SARs
7	Required Supplementary Information
Appendix A -	References

# 1 Introduction

## 1.1 Technology Area and Scope of Supporting Document

The scope of the WLAN Clients PP-Module is to describe the security functionality of a PP-Module for Wireless LAN Clients in terms of [CC] and to define functional and assurance requirements for them. The PP-Module is intended for use with the following Base-PPs:

- [General Purpose Operating Systems, Version 4.2.1](#)
- [Mobile Device Fundamentals, Version 3.1](#)

This SD is mandatory for evaluations of TOEs that claim conformance to a PP-Configuration that includes the PP-Module for WLAN Clients, Version 1.0. Although Evaluation Activities are defined mainly for the evaluators to follow, in general they also help Developers to prepare for evaluation by identifying specific requirements for their TOE. The specific requirements in Evaluation Activities may in some cases clarify the meaning of Security Functional Requirements (SFR), and may identify particular requirements for the content of Security Targets (ST) (especially the TOE Summary Specification), user guidance documentation, and possibly supplementary information (e.g. for entropy analysis or cryptographic key management architecture).

## 1.2 Structure of the Document

Evaluation Activities can be defined for both SFRs and Security Assurance Requirements (SAR), which are themselves defined in separate sections of the SD.

If any Evaluation Activity cannot be successfully completed in an evaluation then the overall verdict for the evaluation is a 'fail'. In rare cases there may be acceptable reasons why an Evaluation Activity may be modified or deemed not applicable for a particular TOE, but this must be approved by the Certification Body for the evaluation.

In general, if all Evaluation Activities (for both SFRs and SARs) are successfully completed in an evaluation then it would be expected that the overall verdict for the evaluation is a 'pass'. To reach a 'fail' verdict when the Evaluation Activities have been successfully completed would require a specific justification from the evaluator as to why the Evaluation Activities were not sufficient for that TOE.

Similarly, at the more granular level of Assurance Components, if the Evaluation Activities for an Assurance Component and all of its related SFR Evaluation Activities are successfully completed in an evaluation then it would be expected that the verdict for the Assurance Component is a 'pass'. To reach a 'fail' verdict for the Assurance Component when these Evaluation Activities have been successfully completed would require a specific justification from the evaluator as to why the Evaluation Activities were not sufficient for that TOE.

## 1.3 Terms

### Common Criteria Terms

The following definitions are for Common Criteria terms used in this document:

Base Protection Profile (Base-PP)	Protection Profile used to build a PP-Configuration.
Common Criteria (CC)	Common Criteria for Information Technology Security Evaluation (International Standard ISO/IEC 15408).

Common Criteria Testing Laboratory	Within the context of the Common Criteria Evaluation and Validation Scheme (CCEVS), an IT security evaluation facility, accredited by the National Voluntary Laboratory Accreditation Program (NVLAP) and approved by the NIAP Validation Body to conduct Common Criteria-based evaluations.
Common Evaluation Methodology (CEM)	Common Evaluation Methodology for Information Technology Security Evaluation.
Protection Profile (PP)	An implementation-independent set of security requirements for a category of products.
Protection Profile Configuration (PP-Configuration)	A comprehensive set of security requirements for a product type that consists of at least one Base-PP and at least one PP-Module.
Protection Profile Module (PP-Module)	An implementation-independent statement of security needs for a TOE type complementary to one or more Base Protection Profiles.
Security Functional Requirement (SFR)	A requirement for security enforcement by the TOE.
Security Target (ST)	A set of implementation-dependent security requirements for a specific product.
Target of Evaluation (TOE)	The product under evaluation.
TOE Security Functionality (TSF)	The security functionality of the product under evaluation.
TOE Summary Specification (TSS)	A description of how a TOE satisfies the Security Functional Requirements (SFRs) in a Security Target (ST).

## Technical Terms

The following definitions define Technical terms used in this document:

AP (Access Point)	A device that provides the network interface that enables wireless client hosts to access a wired network. Once authenticated as trusted nodes on the wired infrastructure, the APs provide the encryption service on the wireless network between the wireless client and the radio frequency (RF) interface of the AP.
Administrator	A user that has administrative privilege to configure the TOE.
Authentication Server	A server on the wired network that receives authentication credentials from wireless clients and determines their validity.
Authentication Credentials	The information the system uses to verify that the user or administrator is authorized to access the TOE or network. Credentials can exist in various forms, such as username/password or digital certificates.
Critical Security Parameter	Security related information, e.g. secret and private cryptographic keys, and authentication data such as passwords and Personal Identification Numbers (PINs), whose disclosure or modification can compromise the security of a cryptographic module.
Entropy Source	A cryptographic function that provides a seed for a random number generator by accumulating the outputs from one or more noise sources. The functionality includes a measure of the minimum work required to guess a given output and tests to ensure that the noise sources are operating properly.
Extensible Authentication Protocol	An authentication framework, used in wireless networks, that uses Public Key Infrastructure (PKI) to authenticate both the authentication server and the wireless client.
FIPS-Approved Cryptographic	A cryptographic operation that is specified for use by FIPS 140.

Function	
IEEE 802.1X	A standard for port-based network access control that defines an authentication mechanism for WLAN Clients to attach to a wired network.
Unauthorized User	A user that has not been granted the ability to use the TOE.

## 2 Evaluation Activities for SFRs

The EAs presented in this section capture the actions the evaluator performs to address technology specific aspects covering specific SARs (e.g. ASE\_TSS.1, ADV\_FSP.1, AGD\_OPE.1, and ATE\_IND.1) – this is in addition to the CEM work units that are performed in [6 Evaluation Activities for SARs](#).

Regarding design descriptions (designated by the subsections labelled TSS, as well as any required supplementary material that may be treated as proprietary), the evaluator must ensure there is specific information that satisfies the EA. For findings regarding the TSS section, the evaluator's verdicts will be associated with the CEM work unit ASE\_TSS.1-1. Evaluator verdicts associated with the supplementary evidence will also be associated with ASE\_TSS.1-1, since the requirement to provide such evidence is specified in ASE in the cPP.

For ensuring the guidance documentation provides sufficient information for the administrators/users as it pertains to SFRs, the evaluator's verdicts will be associated with CEM work units ADV\_FSP.1-7, AGD\_OPE.1-4, and AGD\_OPE.1-5.

Finally, the subsection labelled Tests is where the authors have determined that testing of the product in the context of the associated SFR is necessary. While the evaluator is expected to develop tests, there may be instances where it is more practical for the developer to construct tests, or where the developer may have existing tests. Therefore, it is acceptable for the evaluator to witness developer-generated tests in lieu of executing the tests. In this case, the evaluator must ensure the developer's tests are executing both in the manner declared by the developer and as mandated by the EA. The CEM work units that are associated with the EAs specified in this section are: ATE\_IND.1-3, ATE\_IND.1-4, ATE\_IND.1-5, ATE\_IND.1-6, and ATE\_IND.1-7.

### 2.1 General Purpose Operating Systems Protection Profile

The EAs defined in this section are only applicable in cases where the TOE claims conformance to a PP-Configuration that includes the GPOS PP.

#### 2.1.1 Modified SFRs

##### 2.1.1.1 Cryptographic Support (FCS)

FCS\_CKM\_EXT.4 Cryptographic Key Destruction

FCS\_COP.1 Cryptographic Operation

FCS\_RBG\_EXT.1 Random Bit Generation

### 2.2 Mobile Device Fundamentals Protection Profile

The EAs defined in this section are only applicable in cases where the TOE claims conformance to a PP-Configuration that includes the MDF PP.

#### 2.2.1 Modified SFRs

##### 2.2.1.1 Cryptographic Support (FCS)

FCS\_CKM\_EXT.4 Key Destruction

FCS\_COP.1 Cryptographic Operation

FCS\_RBG\_EXT.1 Random Bit Generation

#### 2.2.2 TOE SFR Evaluation Activities

##### 2.2.3 Security Audit (FAU)

FAU\_GEN.1/WLAN Audit Data Generation (Wireless LAN)

## **TSS**

The evaluator shall check the TSS and ensure it provides a format for audit records. Each audit record format type must be covered, along with a brief description of each field.

If "invoke platform-provided functionality" is selected, the evaluator shall examine the TSS to verify it describes (for each supported platform) how this functionality is invoked (it should be noted that this may be through a mechanism that is not implemented by the WLAN Client; however, that mechanism will be identified in the TSS as part of this evaluation activity).

## **Guidance**

The evaluator shall check the operational guidance and ensure it lists all of the auditable events and provides a format for audit records. Each audit record format type must be covered, along with a brief description of each field. The evaluator shall check to make sure that every audit event type mandated by the PP-Module is described and that the description of the fields contains the information required in FAU\_GEN.1.2/WLAN, and the additional information specified in the Auditable Events table.

The evaluator shall in particular ensure that the operational guidance is clear in relation to the contents for failed cryptographic events. In the Auditable Events table, information detailing the cryptographic mode of operation and a name or identifier for the object being encrypted is required. The evaluator shall ensure that name or identifier is sufficient to allow an administrator reviewing the audit log to determine the context of the cryptographic operation (for example, performed during a key negotiation exchange, performed when encrypting data for transit) as well as the non-TOE endpoint of the connection for cryptographic failures relating to communications with other IT systems.

The evaluator shall also make a determination of the administrative actions that are relevant in the context of this PP-Module. The TOE may contain functionality that is not evaluated in the context of this PP-Module because the functionality is not specified in an SFR. This functionality may have administrative aspects that are described in the operational guidance. Since such administrative actions will not be performed in an evaluated configuration of the TOE, the evaluator shall examine the operational guidance and make a determination of which administrative commands, including subcommands, scripts, and configuration files, are related to the configuration (including enabling or disabling) of the mechanisms implemented in the TOE that are necessary to enforce the requirements specified in the PP-Module, which thus form the set of "all administrative actions". The evaluator may perform this activity as part of the activities associated with ensuring the AGD\_OPE guidance satisfies the requirements.

## **Tests**

The evaluator shall test the TOE's ability to correctly generate audit records by having the TOE generate audit records in accordance with the assurance activities associated with the functional requirements in this PP-Module. When verifying the test results, the evaluator shall ensure the audit records generated during testing match the format specified in the administrative guide, and that the fields in each audit record have the proper entries.

Note that the testing here can be accomplished in conjunction with the testing of the security mechanisms directly. For example, testing performed to ensure that the administrative guidance provided is correct verifies that AGD\_OPE.1 is satisfied and should address the invocation of the administrative actions that are needed to verify the audit records are generated as expected.

## **2.2.4 Cryptographic Support (FCS)**

### **FCS\_CKM.1/WLAN Cryptographic Key Generation (Symmetric Keys for WPA2 Connections)**

## **TSS**

The evaluator shall verify that the TSS describes how the primitives defined and implemented by this PP-Module are used by the TOE in establishing and maintaining secure connectivity to the wireless clients. The TSS shall also provide a description of the developer's method(s) of assuring that their implementation conforms to the cryptographic standards; this includes not only testing done by the developing organization, but also any third-party testing that is performed.

## **Guidance**

There are no guidance evaluation activities for this component.

## **Tests**

The evaluator shall perform the following tests:

- **Test 1:** The evaluator shall configure the access point so the cryptoperiod of the session key is 1 hour. The evaluator shall successfully connect the TOE to the access point and maintain the connection for a length of time that is greater than the configured cryptoperiod. The evaluator shall use a packet capture tool to determine that after the configured cryptoperiod, a re-negotiation is initiated to establish a new session key. Finally, the evaluator shall determine that the renegotiation has been successful and the client continues communication with the access point.
- **Test 2:** The evaluator shall perform the following test using a packet sniffing tool to collect frames between the TOE and a wireless LAN access point:

Step 1: The evaluator shall configure the access point to an unused channel and configure the WLAN sniffer to sniff only on that channel (i.e., lock the sniffer on the selected channel). The sniffer should also be configured to filter on the MAC address of the TOE and/or access point.

Step 2: The evaluator shall configure the TOE to communicate with a WLAN access point using IEEE 802.11-2016 and a 256-bit (64 hex values 0-f) pre-shared key. The pre-shared key is only used for testing.

Step 3: The evaluator shall start the sniffing tool, initiate a connection between the TOE and the access point, and allow the TOE to authenticate, associate, and successfully complete the 4-way handshake with the client.

Step 4: The evaluator shall set a timer for 1 minute, at the end of which the evaluator shall disconnect the TOE from the wireless network and stop the sniffer.

Step 5: The evaluator shall identify the 4-way handshake frames (denoted EAPOL-key in Wireshark captures) and derive the PTK from the 4-way handshake frames and preshared key as specified in IEEE 802.11-2016.

Step 6: The evaluator shall select the first data frame from the captured packets that was sent between the TOE and access point after the 4-way handshake successfully completed, and without the frame control value 0x4208 (the first 2 bytes are 08 42). The evaluator shall use the PTK to decrypt the data portion of the packet as specified in IEEE 802.11-2016, and shall verify that the decrypted data contains ASCII-readable text.

Step 7: The evaluator shall repeat Step 6 for the next 2 data frames between the TOE and access point and without frame control value 0x4208.

## **FCS\_CKM.2/WLAN Cryptographic Key Distribution (Group Temporal Key for WLAN)**

### **TSS**

The evaluator shall check the TSS to ensure that it describes how the GTK is unwrapped prior to being installed for use on the TOE using the AES implementation specified in this PP-Module.

### **Guidance**

There are no guidance evaluation activities for this component.

### **Tests**

The evaluator shall perform the following test using a packet sniffing tool to collect frames between the TOE and a wireless access point (which may be performed in conjunction with the assurance activity for FCS\_CKM.1.1/WLAN).

Step 1: The evaluator shall configure the access point to an unused channel and configure the WLAN sniffer to sniff only on that channel (i.e., lock the sniffer on the selected channel). The sniffer should also be configured to filter on the MAC address of the TOE and/or access point.

Step 2: The evaluator shall configure the TOE to communicate with the access point using IEEE 802.11-2016 and a 256-bit (64 hex values 0-f) pre-shared key, setting up the connections as described in the operational guidance. The pre-shared key is only used for testing.

Step 3: The evaluator shall start the sniffing tool, initiate a connection between the TOE and access point, and allow the TOE to authenticate, associate, and successfully complete the 4-way handshake with the TOE.

Step 4: The evaluator shall set a timer for 1 minute, at the end of which the evaluator shall disconnect the TOE from the access point and stop the sniffer.

Step 5: The evaluator shall identify the 4-way handshake frames (denoted EAPOL-key in Wireshark captures) and derive the PTK and GTK from the 4-way handshake frames and preshared key as specified in IEEE 802.11-2016.

Step 6: The evaluator shall select the first data frame from the captured packets that was sent between the TOE and access point after the 4-way handshake successfully completed, and with the frame control value 0x4208 (the first 2 bytes are 08 42). The evaluator shall use the GTK to decrypt the data portion of the selected packet as specified in IEEE 802.11-2016, and shall verify that the decrypted data contains ASCII-readable text.

Step 7: The evaluator shall repeat Step 6 for the next 2 data frames with frame control value 0x4208.

## **FCS\_TLSC\_EXT.1/WLAN TLS Client Protocol (EAP-TLS for WLAN)**

### **TSS**

The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that the cipher suites supported are specified. The evaluator shall check the TSS to ensure that the cipher suites specified include those listed for this component.

### **Guidance**

The evaluator shall check the operational guidance to ensure that it contains instructions on configuring the TOE so that TLS conforms to the description in the TSS (for instance, the set of cipher suites advertised by the TOE may have to be restricted to meet the requirements).

The evaluator shall check that the guidance contains instructions for the administrator to configure the list of Certificate Authorities that are allowed to sign certificates used by the authentication server that will be accepted by the TOE in the EAP-TLS exchange, and instructions on how to specify the algorithm suites that will be proposed and accepted by the TOE during the EAP-TLS exchange.

### **Tests**

The evaluator shall write, or the TOE developer shall provide, an application for the purposes of testing TLS.

The evaluator shall perform the following tests:

- **Test 1:** The evaluator shall establish a TLS connection using each of the cipher suites specified by the requirement. This connection may be established as part of the establishment of a higher-level protocol, e.g., as part of an EAP session. It is sufficient to observe the successful negotiation of a cipher suite to satisfy the intent of the test; it is not necessary to examine the characteristics of the encrypted traffic in an attempt to discern the cipher suite being used (for example, that the cryptographic algorithm is 128-bit AES and not 256-bit AES).
- **Test 2:** The evaluator shall attempt to establish the connection using a server with a server certificate that contains the Server Authentication purpose in the extendedKeyUsage field and verify that a connection is established. The evaluator will then verify that the client rejects an otherwise valid server certificate that lacks the Server Authentication purpose in the extendedKeyUsage field and a connection is not established. Ideally, the two certificates should be identical except for the extendedKeyUsage field.
- **Test 3:** The evaluator shall send a server certificate in the TLS connection that does not match the server-selected cipher suite (for example, send a ECDSA certificate while using the TLS\_RSA\_WITH\_AES\_128\_CBC\_SHA cipher suite or send a RSA certificate while using one of the ECDSA cipher suites.) The evaluator shall verify that the TOE disconnects after receiving the server's Certificate handshake message.
- **Test 4:** The evaluator shall configure the server to select the TLS\_NULL\_WITH\_NULL\_NULL cipher suite and verify that the client denies the connection.
- **Test 5:** The evaluator shall perform the following modifications to the traffic:
  - Change the TLS version selected by the server in the Server Hello to a nonsupported TLS version (for example 1.5 represented by the two bytes 03 06) and verify that the client rejects the connection.
  - Modify at least one byte in the server's nonce in the Server Hello handshake message, and verify that the client rejects the Server Key Exchange handshake message (if using a DHE or ECDHE cipher suite) or that the server denies the client's Finished handshake message.
  - Modify the server's selected cipher suite in the Server Hello handshake message to be a cipher suite not presented in the Client Hello handshake message. The evaluator shall verify that the client rejects the connection after receiving the Server Hello.
  - [conditional: the TOE supports at least one cipher suite that uses DHE or ECDHE for key exchange] Modify the signature block in the Server's Key Exchange handshake message, and verify that the client rejects the connection after receiving the Server Key Exchange message. This test does not apply to cipher suites using RSA key exchange.
  - Modify a byte in the Server Finished handshake message, and verify that the client sends an Encrypted Message followed by a FIN and ACK message. This is sufficient to deduce that the TOE responded with a Fatal Alert and no further data would be sent.
  - Send a garbled message from the server after the server has issued the ChangeCipherSpec message and verify that the client denies the connection.

## 2.2.5 Identification and Authentication (FIA)

### FIA\_PAE\_EXT.1 Port Access Entity Authentication

#### TSS

There are no TSS evaluation activities for this component.

#### Guidance

There are no guidance evaluation activities for this component.

#### Tests

The evaluator shall perform the following tests:

- **Test 1:** The evaluator shall demonstrate that the TOE has no access to the test network. After successfully authenticating with an authentication server through a wireless access system, the evaluator shall demonstrate that the TOE does have access to the test network.
- **Test 2:** The evaluator shall demonstrate that the TOE has no access to the test network. The evaluator shall attempt to authenticate using an invalid client certificate, such that the EAP-TLS negotiation fails. This should result in the TOE still being unable to access the test network.
- **Test 3:** The evaluator shall demonstrate that the TOE has no access to the test network. The evaluator shall attempt to authenticate using an invalid authentication server certificate, such that the EAP-TLS negotiation fails. This should result in the TOE still being unable to access the test network.

### FIA\_X509\_EXT.2/WLAN X.509 Certificate Authentication (EAP-TLS for WLAN)

#### TSS

The evaluator shall check the TSS to ensure that it describes how the TOE chooses which certificates to use, and any necessary instructions in the administrative guidance for configuring the operational environment so that the TOE can use the certificates.

The evaluator shall examine the TSS to confirm that it describes the behavior of the TOE when a connection cannot be established during the validity check of a certificate used in establishing a trusted channel. The evaluator shall verify that any distinctions between trusted channels are described. If the requirement that the administrator is able to specify the default action, then the evaluator shall ensure that the operational guidance contains instructions on how this configuration action is performed.

### **Guidance**

The evaluator shall check the administrative guidance to ensure that it describes how the TOE chooses which certificates to use, and any necessary instructions for configuring the operating environment so that the TOE can use the certificates.

### **Tests**

The evaluator shall perform the following test:

- **Test 1:** The evaluator shall demonstrate using a valid certificate that requires certificate validation checking to be performed in at least some part by communicating with a non-TOE IT entity. The evaluator shall then manipulate the environment so that the TOE is unable to verify the validity of the certificate, and observe that the action selected in FIA\_X509\_EXT.2.2 is performed. If the selected action is administrator-configurable, then the evaluator shall follow the operational guidance to determine that all supported administrator-configurable options behave in their documented manner.

## **2.2.6 Security Management (FMT)**

### **FMT\_SMF.1/WLAN Specification of Management Functions (WLAN Client)**

#### **TSS**

There are no TSS evaluation activities for this component.

#### **Guidance**

The evaluator shall check the operational guidance to verify that every management function claimed by the TOE is described there. The evaluator shall also verify that these descriptions include the information required to perform the management duties associated with the function.

#### **Tests**

The evaluator shall test the TOE's ability to provide the management functions by configuring the TOE and performing the management activities associated with each function claimed in the SFR.

Note that this may be accomplished in conjunction with the testing of other requirements, such as FCS\_TLSC\_EXT.1/WLAN and FTA\_WSE\_EXT.1.

## **2.2.7 Protection of the TSF (FPT)**

### **FPT\_TST\_EXT.1/WLAN TSF Cryptographic Functionality Testing (WLAN Client)**

#### **TSS**

The evaluator shall examine the TSS to ensure that it details the self tests that are run by the TSF on start-up; this description should include an outline of what the tests are actually doing (e.g., rather than saying "memory is tested", a description similar to "memory is tested by writing a value to each memory location and reading it back to ensure it is identical to what was written" shall be used). The evaluator shall ensure that the TSS makes an argument that the tests are sufficient to demonstrate that the TSF is operating correctly.

The evaluator shall examine the TSS to ensure that it describes how to verify the integrity of stored TSF executable code when it is loaded for execution. The evaluator shall ensure that the TSS makes an argument that the tests are sufficient to demonstrate that the integrity of stored TSF executable code has not been compromised. The evaluator also ensures that the TSS (or the operational guidance) describes the actions that take place for successful (e.g. hash verified) and unsuccessful (e.g., hash not verified) cases.

#### **Guidance**

The evaluator shall ensure that the operational guidance describes the actions that take place for successful (e.g. hash verified) and unsuccessful (e.g., hash not verified) cases.

#### **Tests**

The evaluator shall perform the following tests:

- **Test 1:** The evaluator shall perform the integrity check on a known good TSF executable and verify that the check is successful.
- **Test 2:** The evaluator shall modify the TSF executable, perform the integrity check on the modified TSF executable, and verify that the check fails.

## **2.2.8 TOE Access (FTA)**

### **FTA\_WSE\_EXT.1 Wireless Network Access**

#### **TSS**

The evaluator shall examine the TSS to determine that all of the attributes that can be used to specify acceptable networks (access points) are specifically defined.

#### **Guidance**

The evaluator shall examine the operational guidance to determine that it contains guidance for configuring each of the



attributes identified in the TSS.

#### **Tests**

The evaluator shall perform the following tests for each attribute:

- **Test 1:** The evaluator shall configure the TOE to allow a connection with a specific access point. The evaluator shall also configure the test environment such that the allowed access point and an access point that is not allowed are both “visible” to the TOE. The evaluator shall demonstrate that they can successfully establish a session with the allowed access point. The evaluator shall then attempt to establish a session with the disallowed access point and observe that the access attempt fails.
- **Test 2:** The evaluator shall configure the TOE to allow a connection with a specific access point using EAP-TLS authentication (not only will the valid SSID be configured, but the TOE will also be provided with certificates to complete the EAP-TLS authentication). The evaluator shall also configure the test environment such that an access point broadcasts the SSID the TOE has been configured to connect to but the authentication server does not have valid credentials. The evaluator shall then attempt to establish a session with the valid SSID/invalid authentication server and observe that the access attempt fails.

### **2.2.9 Trusted Path/Channels (FTP)**

#### **FTP\_ITC\_EXT.1/WLAN Trusted Channel Communication (Wireless LAN)**

##### **TSS**

The evaluator shall examine the TSS to determine that it describes the details of the TOE connecting to an access point in terms of the cryptographic protocols specified in the requirement, along with TOE-specific options or procedures that might not be reflected in the specification. The evaluator shall also confirm that all protocols listed in the TSS are specified and included in the requirements in the ST.

##### **Guidance**

The evaluator shall confirm that the operational guidance includes instructions for establishing the connection to the access point and that it includes recovery instructions should a connection be unintentionally broken.

##### **Tests**

The evaluator shall perform the following tests:

- **Test 1:** The evaluator shall ensure that the TOE is able to initiate communications with an access point using the protocols specified in the requirement by setting up the connections as described in the operational guidance and ensuring that communications are successful.
- **Test 2:** The evaluator shall ensure, for each communication channel with an authorized IT entity, the channel data is not sent in plaintext.
- **Test 3:** The evaluator shall ensure, for each communication channel with an authorized IT entity, modification of the channel data is detected by the TOE.
- **Test 4:** The evaluators shall physically interrupt the connection from the TOE to the access point (e.g., moving the TOE host out of range of the access point, turning the access point off). The evaluators shall ensure that subsequent communications are appropriately protected, at a minimum in the case of any attempts to automatically resume the connection or connect to a new access point.

Further evaluation activities are associated with the specific protocols.

## **3 Evaluation Activities for Optional SFRs**

ST

### **3.1 Identification and Authentication (FIA)**

#### **FIA\_X509\_EXT.4 X.509 Certificate Storage and Management**

##### **TSS**

The evaluator shall examine the TSS to determine that it describes all certificate stores implemented that contain certificates used to meet the requirements of this PP-Module. This description shall contain information pertaining to how certificates are loaded into the store, and how the store is protected from unauthorized access.

##### **Guidance**

The evaluator shall check the administrative guidance to ensure that it describes how to load X.509 certificates into the TOE's certificate store.

##### **Tests**

The evaluator shall perform the following test for each TOE function that requires the use of certificates:

- **Test 1:** The evaluator shall demonstrate that using a certificate without a valid certification path results in the function failing. The evaluator shall then load any certificates needed to validate the certificate to be used in the function and demonstrate that the function succeeds. The evaluator then shall delete one of these dependent certificates and show

that the function fails.

## 4 Evaluation Activities for Selection-Based SFRs

### 4.1 Cryptographic Support (FCS)

#### FCS\_TLSC\_EXT.2/WLAN TLS Client Support for Supported Groups Extension (EAP-TLS for WLAN)

##### TSS

The evaluator shall verify that the TSS describes the Supported Groups extension and whether the required behavior is performed by default or may be configured.

##### Guidance

If the TSS indicates that the Supported Groups extension must be configured to meet the requirement, the evaluator shall verify that the operational guidance includes instructions for configuration of this extension.

##### Tests

The evaluator shall perform the following test:

- **Test 1:** The evaluator shall configure a server to perform ECDHE key exchange using each of the TOE's supported curves and shall verify that the TOE successfully connects to the server.

## 5 Evaluation Activities for Objective SFRs

The PP-Module does not define any objective requirements.

## 6 Evaluation Activities for SARs

The PP-Module does not define any SARs beyond those defined within the base-PP to which it must claim conformance. It is important to note that a TOE that is evaluated against the PP-Module is inherently evaluated against the Base-PP as well. The Base-PP includes a number of Evaluation Activities associated with both SFRs and SARs. Additionally, the PP-Module includes a number of SFR-based Evaluation Activities that similarly refine the SARs of the Base-PPs. The evaluation laboratory will evaluate the TOE against the chosen Base-PP and supplement that evaluation with the necessary SFRs that are taken from the PP-Module.

## 7 Required Supplementary Information

This Supporting Document has no required supplementary information beyond the ST, operational guidance, and testing.

## Appendix A - References

Identifier	Title
[CC]	Common Criteria for Information Technology Security Evaluation - <ul style="list-style-type: none"><li>• <a href="#">Part 1: Introduction and General Model</a>, CCMB-2017-04-001, Version 3.1 Revision 5, April 2017.</li><li>• <a href="#">Part 2: Security Functional Components</a>, CCMB-2017-04-002, Version 3.1 Revision 5, April 2017.</li><li>• <a href="#">Part 3: Security Assurance Components</a>, CCMB-2017-04-003, Version 3.1 Revision 5, April 2017.</li></ul>
[CEM]	<a href="#">Common Evaluation Methodology for Information Technology Security - Evaluation Methodology</a> , CCMB-2017-04-004, Version 3.1, Revision 5, April 2017.
[GPOS]	<a href="#">Protection Profile for General Purpose Operating Systems, Version 4.2.1</a>
[MDF]	<a href="#">Protection Profile for Mobile Device Fundamentals, Version 3.1</a>
[802.11-2016]	<a href="#">802.11-2016 - IEEE Standard for Information technology—Telecommunications and information exchange between systems Local and metropolitan area networks—Specific requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications</a>
[802.11-2016]	<a href="#">802.1X-2010 - IEEE Standard for Local and metropolitan area networks--Port-Based Network Access Control</a>
[RFC 3394]	<a href="#">RFC 3394 - Advanced Encryption Standard (AES) Key Wrap Algorithm</a>

[RFC 4346]	<a href="#">RFC 4346 - The Transport Layer Security (TLS) Protocol Version 1.1</a>
[RFC 5216]	<a href="#">RFC 5216 - The EAP-TLS Authentication Protocol</a>
[RFC 5246]	<a href="#">RFC 5246 - The Transport Layer Security (TLS) Protocol Version 1.2</a>
[RFC 5280]	<a href="#">RFC 5280 - Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile</a>